# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY CX122 S1, Intel Xeon E5606, 2.13 GHz

SPECint®_rate2006 = 163

SPECint_rate_base2006 = 154

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Jan-2011




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5606 |
| CPU Characteristics: | |
| CPU MHz: | 2133 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 8 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 96 GB (12 x 8 GB 2Rx4 PC3-10600R-9, ECC, running at 1067 MHz and CL7) |
| Disk Subsystem: | 1 x SATA, 160 GB, 5400 RPM |
| Other Hardware: | -- |

## Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 (x86_64) with SP1, Kernel 2.6.32.12-0.7-default |
| Compiler: | Intel C++ Compiler XE for applications running on IA-32 Version 12.0.1.116 Build 20101116 |
| Auto Parallel: | No |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Microquill SmartHeap V9.01 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY CX122 S1, Intel Xeon E5606, 2.13 GHz

SPECint_rate2006 = 163

SPECint_rate_base2006 = 154

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Jan-2011

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 8 | 633 | 124 | 632 | 124 | **633** | **124** | 8 | **528** | **148** | 528 | 148 | 527 | 148 |
| 401.bzip2 | 8 | **952** | **81.1** | 951 | 81.2 | 955 | 80.8 | 8 | 869 | 88.9 | **870** | **88.8** | 870 | 88.7 |
| 403.gcc | 8 | 541 | 119 | 544 | 118 | **541** | **119** | 8 | 541 | 119 | 544 | 118 | **541** | **119** |
| 429.mcf | 8 | 368 | 198 | **367** | **199** | 363 | 201 | 8 | 352 | 207 | **342** | **214** | 340 | 214 |
| 445.gobmk | 8 | 686 | 122 | **686** | **122** | 684 | 123 | 8 | 663 | 126 | **665** | **126** | 665 | 126 |
| 456.hmmer | 8 | 366 | 204 | 361 | 207 | **365** | **204** | 8 | **304** | **246** | 304 | 246 | 304 | 245 |
| 458.sjeng | 8 | **755** | **128** | 755 | 128 | 754 | 128 | 8 | 712 | 136 | **712** | **136** | 713 | 136 |
| 462.libquantum | 8 | 221 | 751 | **221** | **751** | 221 | 749 | 8 | 221 | 751 | **221** | **751** | 221 | 749 |
| 464.h264ref | 8 | 839 | 211 | **837** | **211** | 837 | 211 | 8 | 824 | 215 | **825** | **215** | 826 | 214 |
| 471.omnetpp | 8 | 490 | 102 | 490 | 102 | **490** | **102** | 8 | 452 | 111 | 452 | 111 | **452** | **111** |
| 473.astar | 8 | 610 | 92.0 | **610** | **92.0** | 609 | 92.2 | 8 | 610 | 92.0 | **610** | **92.0** | 609 | 92.2 |
| 483.xalancbmk | 8 | **351** | **157** | 352 | 157 | 351 | 157 | 8 | **351** | **157** | 352 | 157 | 351 | 157 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
 numactl was used to bind copies to the cores
```

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
Hugepages were not configured on the system
```

## Platform Notes

```
BIOS configuration:
Data Reuse Optimization = Disable
```

## General Notes

```
For information about Fujitsu please visit: http://www.fujitsu.com
Binaries were compiled on RHEL5.5 with binutils-2.17.50.0.6-14.el5
```

## Base Compiler Invocation

C benchmarks:

```
icc  -m32
```

Continued on next page

## Base Compiler Invocation (Continued)

C++ benchmarks:
icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/smartheap -lsmartheap
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:
icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-opt-prefetch -auto-ilp32 -ansi-alias
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

403.gcc: basepeak = yes

429.mcf: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -auto-ilp32

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
-ansi-alias -auto-ilp32

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll4 -auto-ilp32
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
-L/smartheap -lsmartheap

Continued on next page

## Peak Optimization Flags (Continued)

473.astar: `basepeak = yes`

483.xalancbmk: `basepeak = yes`

## Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.html`
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.xml`
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.xml`


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 16:33:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 March 2011.