



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp®\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55


Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011



### Hardware

CPU Name: Intel Xeon E5607  
 CPU Characteristics:  
 CPU MHz: 2267  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86\_64), Kernel 2.6.32.12-0.7-default  
 Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116  
 Auto Parallel: No  
 File System: ext3  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55

Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011

L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC, downclocked to 1066 MHz)  
Disk Subsystem: 1 x 146 GB 15000 RPM SAS  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binaries compiled on RHEL5.5 with binutils-2.17.50.0.6-14.el5

## Results Table

| Benchmark     | Base   |             |             |             |             |            |            | Peak   |             |            |             |             |            |             |
|---------------|--------|-------------|-------------|-------------|-------------|------------|------------|--------|-------------|------------|-------------|-------------|------------|-------------|
|               | Copies | Seconds     | Ratio       | Seconds     | Ratio       | Seconds    | Ratio      | Copies | Seconds     | Ratio      | Seconds     | Ratio       | Seconds    | Ratio       |
| 410.bwaves    | 8      | 847         | 128         | 849         | 128         | <b>848</b> | <b>128</b> | 8      | <b>847</b>  | <b>128</b> | 845         | 129         | 848        | 128         |
| 416.gamess    | 8      | <b>1071</b> | <b>146</b>  | 1072        | 146         | 1071       | 146        | 8      | 1042        | 150        | <b>1042</b> | <b>150</b>  | 1040       | 151         |
| 433.milc      | 8      | <b>552</b>  | <b>133</b>  | 550         | 133         | 552        | 133        | 8      | 545         | 135        | <b>546</b>  | <b>135</b>  | 546        | 135         |
| 434.zeusmp    | 8      | 489         | 149         | <b>489</b>  | <b>149</b>  | 500        | 146        | 8      | 489         | 149        | <b>489</b>  | <b>149</b>  | 500        | 146         |
| 435.gromacs   | 8      | 451         | 127         | 452         | 126         | <b>452</b> | <b>126</b> | 8      | 451         | 127        | 452         | 126         | <b>452</b> | <b>126</b>  |
| 436.cactusADM | 8      | 652         | 147         | 659         | 145         | <b>655</b> | <b>146</b> | 8      | 652         | 147        | 659         | 145         | <b>655</b> | <b>146</b>  |
| 437.leslie3d  | 8      | 828         | 90.9        | <b>825</b>  | <b>91.2</b> | 822        | 91.4       | 8      | 812         | 92.6       | 814         | 92.4        | <b>812</b> | <b>92.6</b> |
| 444.namd      | 8      | <b>607</b>  | <b>106</b>  | 606         | 106         | 607        | 106        | 8      | 598         | 107        | 598         | 107         | <b>598</b> | <b>107</b>  |
| 447.dealII    | 8      | 494         | 185         | 482         | 190         | <b>485</b> | <b>189</b> | 8      | 494         | 185        | 482         | 190         | <b>485</b> | <b>189</b>  |
| 450.soplex    | 8      | <b>685</b>  | <b>97.4</b> | 685         | 97.4        | 684        | 97.6       | 8      | 647         | 103        | 648         | 103         | <b>648</b> | <b>103</b>  |
| 453.povray    | 8      | 253         | 168         | <b>253</b>  | <b>168</b>  | 252        | 169        | 8      | 201         | 212        | <b>202</b>  | <b>211</b>  | 202        | 211         |
| 454.calculix  | 8      | 386         | 171         | 387         | 171         | <b>387</b> | <b>171</b> | 8      | 386         | 171        | 387         | 171         | <b>387</b> | <b>171</b>  |
| 459.GemsFDTD  | 8      | 1004        | 84.5        | <b>1009</b> | <b>84.1</b> | 1009       | 84.1       | 8      | 1004        | 84.5       | <b>1009</b> | <b>84.1</b> | 1009       | 84.1        |
| 465.tonto     | 8      | <b>537</b>  | <b>146</b>  | 536         | 147         | 538        | 146        | 8      | <b>524</b>  | <b>150</b> | 523         | 151         | 525        | 150         |
| 470.lbm       | 8      | 954         | 115         | 953         | 115         | <b>953</b> | <b>115</b> | 8      | <b>587</b>  | <b>187</b> | 587         | 187         | 587        | 187         |
| 481.wrf       | 8      | 589         | 152         | <b>590</b>  | <b>151</b>  | 590        | 151        | 8      | 589         | 152        | <b>590</b>  | <b>151</b>  | 590        | 151         |
| 482.sphinx3   | 8      | <b>1173</b> | <b>133</b>  | 1172        | 133         | 1174       | 133        | 8      | <b>1141</b> | <b>137</b> | 1138        | 137         | 1142       | 137         |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages  
echo 7200 > /proc/sys/vm/nr\_hugepages  
export HUGETLB\_MORECORE=yes  
export LD\_PRELOAD=/usr/lib64/libhugetlbfs.so



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55

Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011

## Platform Notes

BIOS Settings:

Power Management = Maximum Performance (Default = Active Power Controller)

Data Reuse = Disabled (Default = Enabled)

## General Notes

The Dell PowerEdge R610 and the Bull NovaScale R440 F2 models are electronically equivalent. The results have been measured on a Dell PowerEdge R610 model.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55

Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55

Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011

## Peak Portability Flags (Continued)

470.lbm: -DSPEC\_CPU\_LP64

481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-ansi-alias -opt-prefetch -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

459.GemsFDTD: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 138

PowerEdge R610 (Intel Xeon E5607, 2.26 GHz)

SPECfp\_rate\_base2006 = 131

CPU2006 license: 55

Test date: Feb-2011

Test sponsor: Dell Inc.

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Jan-2011

## Peak Optimization Flags (Continued)

```
465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110308.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110308.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 16:35:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 March 2011.