# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY BX924 S2, Intel Xeon E5603, 1.60 GHz

SPECfp®2006 = 31.2

SPECfp_base2006 = 29.2

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Mar-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Apr-2011




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5603 |
| CPU Characteristics: | |
| CPU MHz: | 1600 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 (x86_64) with SP1, Kernel 2.6.32.12-0.7-default |
| Compiler: | Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3 |
| Auto Parallel: | Yes |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 64-bit |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY BX924 S2, Intel Xeon E5603, 1.60 GHz

SPECfp2006 = 31.2

SPECfp_base2006 = 29.2

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Mar-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Apr-2011

L3 Cache: 4 MB I+D on chip per chip
Other Cache: None
Memory: 96 GB (12 x 8 GB 2Rx4 PC3-10600R-9, ECC, running at 1067 MHz and CL7)
Disk Subsystem: 1 x SAS, 300 GB, 10000 RPM
Other Hardware: --

Peak Pointers: 32/64-bit
Other Software: None

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 108 | 126 | 108 | 126 | **108** | **126** | 108 | 126 | 108 | 126 | **108** | **126** |
| 416.gamess | 1651 | 11.9 | 1643 | 11.9 | **1646** | **11.9** | 1467 | 13.3 | **1467** | **13.3** | 1470 | 13.3 |
| 433.milc | 324 | 28.4 | **324** | **28.3** | 325 | 28.3 | 318 | 28.9 | 318 | 28.9 | **318** | **28.9** |
| 434.zeusmp | 163 | 55.9 | 163 | 56.0 | **163** | **56.0** | 163 | 55.9 | 163 | 56.0 | **163** | **56.0** |
| 435.gromacs | **674** | **10.6** | 672 | 10.6 | 677 | 10.5 | 629 | 11.4 | 629 | 11.3 | **629** | **11.4** |
| 436.cactusADM | **110** | **109** | 110 | 109 | 109 | 110 | **110** | **109** | 110 | 109 | 109 | 110 |
| 437.leslie3d | 130 | 72.2 | 136 | 69.2 | **135** | **69.5** | 130 | 72.2 | 136 | 69.2 | **135** | **69.5** |
| 444.namd | 858 | 9.35 | 859 | 9.34 | **858** | **9.35** | 843 | 9.51 | **843** | **9.52** | 842 | 9.52 |
| 447.dealII | **572** | **20.0** | 572 | 20.0 | 572 | 20.0 | **572** | **20.0** | 572 | 20.0 | 572 | 20.0 |
| 450.soplex | 508 | 16.4 | **508** | **16.4** | 508 | 16.4 | 508 | 16.4 | **508** | **16.4** | 508 | 16.4 |
| 453.povray | **358** | **14.9** | 358 | 14.8 | 358 | 14.9 | 283 | 18.8 | **283** | **18.8** | 283 | 18.8 |
| 454.calculix | 559 | 14.8 | **560** | **14.7** | 561 | 14.7 | 505 | 16.3 | 505 | 16.3 | **505** | **16.3** |
| 459.GemsFDTD | 233 | 45.5 | **232** | **45.7** | 202 | 52.5 | **179** | **59.2** | 179 | 59.2 | 212 | 50.1 |
| 465.tonto | 764 | 12.9 | **764** | **12.9** | 767 | 12.8 | 617 | 16.0 | 615 | 16.0 | **616** | **16.0** |
| 470.lbm | **81.2** | **169** | 81.0 | 170 | 81.6 | 168 | **81.2** | **169** | 81.0 | 170 | 81.6 | 168 |
| 481.wrf | **394** | **28.3** | 391 | 28.5 | 395 | 28.2 | **394** | **28.3** | 391 | 28.5 | 395 | 28.2 |
| 482.sphinx3 | 867 | 22.5 | **864** | **22.6** | 855 | 22.8 | 785 | 24.8 | **786** | **24.8** | 798 | 24.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'nodev /mnt/hugepages hugetlbfs defaults 0 0' was added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

```
BIOS configuration:
Data Reuse Optimization = Disable
Performance/Power Setting = Traditional
```

## General Notes

```
OMP_NUM_THREADS set to number of cores
For information about Fujitsu please visit: http://www.fujitsu.com
Binaries were compiled on RHEL5.5 with binutils-2.17.50.0.6-14.el5
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias
```

C++ benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias
```

Continued on next page

## Base Optimization Flags (Continued)

Fortran benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch -ansi-alias`

## Peak Compiler Invocation

C benchmarks:
`icc -m64`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

## Peak Portability Flags

`Same as Base Portability Flags`

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2) `-static -auto-ilp32 -ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `-xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias -parallel`

C++ benchmarks:

444.namd: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2) `-fno-alias -auto-ilp32`

Continued on next page

## Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel -static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -opt-prefetch -parallel -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc -opt-malloc-options=3 -auto -unroll4 -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32 -ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.html
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.xml
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 19:07:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 April 2011.