SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu
SPARC Enterprise M3000

SPECint®2006 = 16.3

SPECint_base2006 = 14.6

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jan-2011
Hardware Availability: Apr-2011
Software Availability: Sep-2010



Hardware

CPU Name:	SPARC64 VII+
CPU Characteristics:	
CPU MHz:	2860
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	5632 KB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	32 GB (8 x 4 GB, 2-way interleaved)
Disk Subsystem:	1 x 300 GB 10,000 RPM SAS
Other Hardware:	None

Software

Operating System:	Oracle Solaris 10 9/10
Compiler:	Oracle Solaris Studio 12.2
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu
SPARC Enterprise M3000

SPECint2006 = 16.3

SPECint_base2006 = 14.6

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jan-2011
Hardware Availability: Apr-2011
Software Availability: Sep-2010

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	823	11.9	**823**	**11.9**	824	11.9	597	16.4	598	16.3	**597**	**16.4**
401.bzip2	839	11.5	837	11.5	**837**	**11.5**	**724**	**13.3**	724	13.3	723	13.3
403.gcc	**720**	**11.2**	720	11.2	720	11.2	**670**	**12.0**	670	12.0	669	12.0
429.mcf	454	20.1	455	20.1	**454**	**20.1**	398	22.9	398	22.9	**398**	**22.9**
445.gobmk	**798**	**13.2**	798	13.2	797	13.2	709	14.8	**709**	**14.8**	709	14.8
456.hmmer	**877**	**10.6**	877	10.6	877	10.6	875	10.7	**875**	**10.7**	874	10.7
458.sjeng	**1270**	**9.53**	1270	9.53	1271	9.52	**1153**	**10.5**	1153	10.5	1152	10.5
462.libquantum	285	72.7	**285**	**72.7**	285	72.7	260	79.8	**260**	**79.7**	260	79.7
464.h264ref	**1065**	**20.8**	1066	20.8	1064	20.8	**959**	**23.1**	961	23.0	959	23.1
471.omnetpp	**748**	**8.36**	749	8.35	745	8.39	657	9.52	**657**	**9.51**	658	9.50
473.astar	649	10.8	**649**	**10.8**	648	10.8	610	11.5	**610**	**11.5**	612	11.5
483.xalancbmk	**428**	**16.1**	423	16.3	429	16.1	**403**	**17.1**	406	17.0	402	17.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
Oracle Solaris Studio 12.2 is distributed with mandatory OS patches
 118683-05  119963-20  120753-08
Oracle Solaris Studio 12.2 and patches are available at
 http://oracle.com/goto/solarisstudio
```

Submit Notes

```
Processes were assigned to specific processors using 'pbind'
commands.  The config file option 'submit' was used, along
with a list of processors in the 'BIND' variable, to generate
the pbind commands.  (For details, please see the config file.)
```

Operating System Notes

```
ulimit -s 131072 was used to limit the space
consumed by the stack (and therefore make more
space available to the heap).

System Tunables:
(/etc/system parameters)

    tune_t_fsflushr=10
       Controls how many seconds elapse between runs of the
       page flush daemon, fsflush.
```

Continued on next page

Operating System Notes (Continued)

```
      autoup=600
         Causes pages older than the listed number of seconds to
         be written by fsflush.
      bufhwm=3000
         Memory byte limit for caching I/O buffers.
      segmap_percent=1
         Set maximum percent memory for file system cache.

   Other System Settings:

       The "webconsole" service was turned off using
           svcadm disable webconsole
```

Platform Notes

```
    Memory is 2-way interleaved by filling all slots with
    the same capacity DIMMs.

   This result is measured on a SPARC Enterprise M3000 server from
   Fujitsu.  The SPARC Enterprise M3000 server from Oracle and from
   Fujitsu are electrically equivalent.
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-fast -fma=fused -xipo=2 -xpagesize=4M
-xprefetch_auto_type=indirect_array_access -xO4 -xalias_level=std
-xprefetch_level=2 -ll2amm

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-xdepend -library=stlport4 -M /usr/lib/ld/map.bssalign -fast
-fma=fused -xipo=2 -xpagesize=4M
-xprefetch_auto_type=indirect_array_access -xalias_level=compatible
-lfast

Base Other Flags

C benchmarks:
-xjobs=2 -V -#

C++ benchmarks:
-xjobs=2 -verbose=diags,version

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=2
-xchip=generic -xvector -xalias_level=std -xrestrict -Xc
-xprefetch=no%auto -lfast

401.bzip2: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xchip=generic -xalias_level=strong
-xprefetch_auto_type=indirect_array_access -lfast

Continued on next page

Peak Optimization Flags (Continued)

403.gcc: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=1 -xchip=generic -xalias_level=std
-xunroll=7 -ll2amm -lbsdmalloc

429.mcf: -fast -fma=fused -xpagesize=4M -M /usr/lib/ld/map.bssalign
-xipo=2 -xchip=generic -xlinkopt -xunroll=3
-W2,-Apf:llist=3 -W2,-Apf:noinnerllist -Wc,-Qlp-prt=1
-Wc,-Qlp-prwt=3 -xprefetch_auto_type=indirect_array_access
-xprefetch_level=2 -xprefetch=latx:0.5 -lfast

445.gobmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=std -xrestrict
-xprefetch=latx:0.5 -ll2amm -lbsdmalloc

456.hmmer: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=std -ll2amm

458.sjeng: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=2 -xO4
-xlinkopt -xunroll=2
-xprefetch_auto_type=indirect_array_access

462.libquantum: -fast -fma=fused -xpagesize=4M -xalias_level=std -xipo=2
-xO4 -xlinkopt -xunroll=8 -xprefetch=latx:0.5 -lmopt

464.h264ref: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=2 -xarch=sparcvis2 -xlinkopt
-xalias_level=std -xprefetch=latx:3 -ll2amm

C++ benchmarks:

471.omnetpp: -xdepend -library=stlport4
-xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -xipo=2
-Qoption cg -Qlp-av=0 -xunroll=2 -xprefetch=latx:6 -lfast
-lbsdmalloc

473.astar: -xdepend -library=stlport4
-xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -xunroll=6
-xprefetch_auto_type=indirect_array_access -lfast
-lbsdmalloc

Continued on next page

Peak Optimization Flags (Continued)

483.xalancbmk: `-xdepend -library=stlport4`
`-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused`
`-xpagesize=4M -xalias_level=compatible -xipo=1 -xvector`
`-xunroll=8 -xprefetch=no%auto -lfast`

Peak Other Flags

C benchmarks:
`-xjobs=2 -V -#`

C++ benchmarks:
`-xjobs=2 -verbose=diags,version`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 19:37:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 April 2011.