



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp®2006 = 47.1

SPECfp_base2006 = 45.5

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jun-2011

Hardware Availability: Jun-2011

Software Availability: Apr-2011



SPECfp_base2006 = 45.5

SPECfp2006 = 47.1

Hardware

CPU Name: Intel Core i3-2100
CPU Characteristics:
CPU MHz: 3100
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 11 (x86_64) SP1, Kernel 2.6.32.12-0.7-default
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3
Auto Parallel: Yes
File System: ext3
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp2006 = 47.1

SPECfp_base2006 = 45.5

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jun-2011

Hardware Availability: Jun-2011

Software Availability: Apr-2011

L3 Cache: 3 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600E-9, ECC)
 Disk Subsystem: 1 x SATA, 300 GB, 7200 RPM
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	141	96.6	140	97.4	<u>140</u>	<u>97.1</u>	<u>140</u>	<u>97.3</u>	140	97.4	140	97.0
416.gamess	704	27.8	704	27.8	700	28.0	614	31.9	615	31.9	614	31.9
433.milc	152	60.4	<u>152</u>	<u>60.4</u>	152	60.4	<u>152</u>	<u>60.4</u>	<u>152</u>	<u>60.4</u>	152	60.4
434.zeusmp	179	50.8	<u>179</u>	<u>50.8</u>	179	50.8	<u>179</u>	<u>50.8</u>	<u>179</u>	<u>50.8</u>	179	50.8
435.gromacs	302	23.6	<u>302</u>	<u>23.6</u>	303	23.6	302	23.6	<u>302</u>	<u>23.6</u>	303	23.6
436.cactusADM	156	76.6	<u>156</u>	<u>76.7</u>	155	77.0	<u>156</u>	<u>76.6</u>	<u>156</u>	<u>76.7</u>	155	77.0
437.leslie3d	172	54.6	<u>172</u>	<u>54.6</u>	172	54.6	<u>172</u>	<u>54.6</u>	<u>172</u>	<u>54.6</u>	172	54.6
444.namd	376	21.3	377	21.3	<u>377</u>	<u>21.3</u>	373	21.5	<u>373</u>	<u>21.5</u>	373	21.5
447.dealII	247	46.4	<u>246</u>	<u>46.5</u>	246	46.5	<u>247</u>	<u>46.4</u>	<u>246</u>	<u>46.5</u>	246	46.5
450.soplex	265	31.5	<u>265</u>	<u>31.5</u>	265	31.4	<u>265</u>	<u>31.5</u>	<u>265</u>	<u>31.5</u>	265	31.4
453.povray	<u>133</u>	<u>40.0</u>	133	39.9	133	40.0	110	48.3	111	48.1	<u>111</u>	<u>48.1</u>
454.calculix	234	35.2	<u>235</u>	<u>35.1</u>	235	35.1	<u>212</u>	<u>38.9</u>	<u>212</u>	<u>39.0</u>	212	39.0
459.GemsFDTD	225	47.2	<u>225</u>	<u>47.2</u>	225	47.2	204	52.0	<u>207</u>	<u>51.3</u>	207	51.3
465.tonto	<u>283</u>	<u>34.8</u>	283	34.8	284	34.7	<u>272</u>	<u>36.1</u>	272	36.1	271	36.3
470.lbm	125	110	125	110	<u>125</u>	<u>110</u>	125	110	125	110	<u>125</u>	<u>110</u>
481.wrf	<u>183</u>	<u>61.2</u>	183	61.2	183	61.1	<u>183</u>	<u>61.2</u>	183	61.2	183	61.1
482.sphinx3	<u>507</u>	<u>38.4</u>	510	38.2	507	38.5	<u>480</u>	<u>40.6</u>	<u>481</u>	<u>40.5</u>	<u>480</u>	<u>40.6</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'nodev /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

Platform Notes

BIOS configuration:
 Intel HT Technology = Disable



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp2006 = 47.1

SPECfp_base2006 = 45.5

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jun-2011

Hardware Availability: Jun-2011

Software Availability: Apr-2011

General Notes

OMP_NUM_THREADS set to number of cores

For information about Fujitsu please visit: <http://www.fujitsu.com>

Binaries were compiled on RHEL5.5

Base Compiler Invocation

C benchmarks:

 icc -m64

C++ benchmarks:

 icpc -m64

Fortran benchmarks:

 ifort -m64

Benchmarks using both Fortran and C:

 icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

 -xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
 -ansi-alias

C++ benchmarks:

 -xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp2006 =

47.1

SPECfp_base2006 =

45.5

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date:

Jun-2011

Hardware Availability: Jun-2011

Software Availability: Apr-2011

Base Optimization Flags (Continued)

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll12 -ansi-alias
-parallel

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp2006 =

47.1

SPECfp_base2006 =

45.5

CPU2006 license: 19

Test date: Jun-2011

Test sponsor: Fujitsu

Hardware Availability: Jun-2011

Tested by: Fujitsu

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

450.soplex: basepeak = yes

```
453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias
             -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

Fortran benchmarks:

```
410.bwaves: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -parallel
             -static
```

```
416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
             -inline-level=0 -scalar-rep- -static
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

```
459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
                -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
                -inline-level=0 -opt-prefetch -parallel
                -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

```
465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
             -opt-malloc-options=3 -auto -unroll14
             -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

```
454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias
               -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.html>
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20110705.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.xml>
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20110705.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S7, Intel Core i3-2100, 3.10 GHz

SPECfp2006 = 47.1

SPECfp_base2006 = 45.5

CPU2006 license: 19

Test date: Jun-2011

Test sponsor: Fujitsu

Hardware Availability: Jun-2011

Tested by: Fujitsu

Software Availability: Apr-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 22:04:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 5 July 2011.