SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH67BLB3 Motherboard (Intel Core i5-2500K)

SPECint®2006 = 45.0

SPECint_base2006 = 42.8

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jul-2011
Hardware Availability: Mar-2011
Software Availability: Apr-2011



Hardware

CPU Name:	Intel Core i5-2500K
CPU Characteristics:	Intel Turbo Boost Technology up to 3.7 GHz
CPU MHz:	3300
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)
Disk Subsystem:	Seagate 1 TB SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows 7 Ultimate (64-bit)
Compiler:	Intel C++ Compiler XE for IA32 and Intel 64 Version 12.0.3.176 Build 20110309 Microsoft Visual Studio 2008 Professional SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 9.01 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH67BLB3 Motherboard (Intel Core i5-2500K)

SPECint2006 = 45.0

SPECint_base2006 = 42.8

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jul-2011
Hardware Availability: Mar-2011
Software Availability: Apr-2011

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	333	29.4	332	29.4	**332**	**29.4**	263	37.1	**263**	**37.2**	263	37.2
401.bzip2	**401**	**24.1**	406	23.8	400	24.1	403	24.0	**400**	**24.1**	390	24.7
403.gcc	**282**	**28.6**	282	28.6	282	28.6	263	30.6	**263**	**30.6**	263	30.6
429.mcf	178	51.3	178	51.1	**178**	**51.3**	179	51.0	178	51.1	**179**	**51.1**
445.gobmk	400	26.2	400	26.3	**400**	**26.2**	372	28.2	372	28.2	**372**	**28.2**
456.hmmer	174	53.7	**174**	**53.7**	174	53.7	**173**	**53.9**	171	54.5	173	53.9
458.sjeng	419	28.9	419	28.9	**419**	**28.9**	419	28.9	419	28.9	**419**	**28.9**
462.libquantum	30.6	677	**30.6**	**677**	30.6	677	30.6	677	**30.6**	**677**	30.6	677
464.h264ref	389	56.9	389	56.8	**389**	**56.9**	336	66.0	335	66.1	**335**	**66.1**
471.omnetpp	250	25.1	**250**	**25.1**	250	25.0	229	27.3	229	27.3	**229**	**27.3**
473.astar	**252**	**27.9**	252	27.9	252	27.9	**252**	**27.9**	252	27.9	252	27.9
483.xalancbmk	210	32.8	**210**	**32.8**	210	32.8	210	32.8	**210**	**32.8**	210	32.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Base Portability Flags

400.perlbench: `-DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64 -DSPEC_CPU_NO_NEED_VA_COPY`
401.bzip2: `-DSPEC_CPU_P64`
403.gcc: `-DSPEC_CPU_P64 -DSPEC_CPU_WIN64`
429.mcf: `-DSPEC_CPU_P64`
445.gobmk: `-DSPEC_CPU_P64`
456.hmmer: `-DSPEC_CPU_P64`
458.sjeng: `-DSPEC_CPU_P64`

Continued on next page

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32 /F512000000

C++ benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

C++ benchmarks:
icl -Qvc9

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

Continued on next page

Peak Optimization Flags (Continued)

401.bzip2: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32
/F512000000

403.gcc: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qauto-ilp32 /F512000000

429.mcf: -QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F512000000

445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: -QxAVX -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qauto-ilp32 /F512000000

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32
/F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Thu Jul 24 00:22:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 August 2011.