# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 F2 (Intel Xeon E5620, 2.40 GHz)

SPECint®2006 = 34.1

SPECint_base2006 = 32.3

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** May-2011
**Hardware Availability:** Mar-2010
**Software Availability:** Jan-2011




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5620 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 2.66 GHz |
| CPU MHz: | 2400 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 12 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC, running at 1066 MHz) |
| Disk Subsystem: | 1 x 146 GB 15000 RPM SAS |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.12-0.7-default |
| Compiler: | Intel C++ Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116 |
| Auto Parallel: | Yes |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32/64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Microquill SmartHeap V9.01 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 F2 (Intel Xeon E5620, 2.40 GHz)

SPECint2006 = 34.1

SPECint_base2006 = 32.3

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** May-2011
**Hardware Availability:** Mar-2010
**Software Availability:** Jan-2011

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 460 | 21.2 | 459 | 21.3 | **460** | **21.3** | 407 | 24.0 | 407 | 24.0 | **407** | **24.0** |
| 401.bzip2 | **613** | **15.7** | 613 | 15.7 | 613 | 15.7 | **585** | **16.5** | 585 | 16.5 | 585 | 16.5 |
| 403.gcc | **363** | **22.2** | 364 | 22.1 | 362 | 22.2 | **340** | **23.7** | 341 | 23.6 | 340 | 23.7 |
| 429.mcf | 224 | 40.7 | 225 | 40.5 | **225** | **40.6** | 211 | 43.2 | 212 | 43.0 | **212** | **43.0** |
| 445.gobmk | **547** | **19.2** | 541 | 19.4 | 548 | 19.1 | 517 | 20.3 | 518 | 20.2 | **518** | **20.3** |
| 456.hmmer | **245** | **38.1** | 245 | 38.1 | 245 | 38.1 | 241 | 38.6 | 241 | 38.7 | **241** | **38.7** |
| 458.sjeng | **567** | **21.3** | 564 | 21.5 | 568 | 21.3 | **551** | **21.9** | 552 | 21.9 | 551 | 21.9 |
| 462.libquantum | 28.9 | 718 | 28.9 | 718 | **28.9** | **718** | 28.9 | 718 | 28.9 | 718 | **28.9** | **718** |
| 464.h264ref | 737 | 30.0 | 741 | 29.9 | **738** | **30.0** | 653 | 33.9 | 654 | 33.8 | **653** | **33.9** |
| 471.omnetpp | **305** | **20.5** | 305 | 20.5 | 303 | 20.6 | 270 | 23.1 | 271 | 23.1 | **270** | **23.1** |
| 473.astar | **356** | **19.7** | 356 | 19.7 | 356 | 19.7 | **356** | **19.7** | 356 | 19.7 | 356 | 19.7 |
| 483.xalancbmk | 219 | 31.4 | **217** | **31.9** | 216 | 31.9 | 219 | 31.4 | **217** | **31.9** | 216 | 31.9 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

```
BIOS Settings:
Power Management = Maximum Performance (Default = Active Power Controller)
Logical Processor = Disabled (Default = Enabled)
```

## General Notes

```
OMP_NUM_THREADS set to number of cores
The Dell PowerEdge R710 and
the Bull NovaScale R460 F2 models are electronically equivalent.
The results have been measured on a Dell PowerEdge R710 model
Binaries were compiled on RHEL5.5
```

## Base Compiler Invocation

C benchmarks:

```
icc  -m64
```

Continued on next page

## Base Compiler Invocation (Continued)

C++ benchmarks:
icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/smartheap -lsmartheap64
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

400.perlbench: icc -m32

Continued on next page

## Peak Compiler Invocation (Continued)

429.mcf: `icc -m32`

445.gobmk: `icc -m32`

464.h264ref: `icc -m32`

C++ benchmarks (except as noted below):
`icpc -m64`

471.omnetpp: `icpc -m32`

## Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
403.gcc: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
458.sjeng: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`
473.astar: `-DSPEC_CPU_LP64`
483.xalancbmk: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

400.perlbench: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2)
`-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2)
`-opt-prefetch -ansi-alias`
`-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT`

401.bzip2: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2)
`-O3`(pass 2) `-no-prec-div -prof-use`(pass 2) `-auto-ilp32`
`-opt-prefetch -ansi-alias`

403.gcc: `-xSSE4.2 -ipo -O3 -no-prec-div -inline-calloc`
`-opt-malloc-options=3 -auto-ilp32`
`-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT`

429.mcf: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2)
`-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2)
`-auto-ilp32 -ansi-alias`
`-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT`

445.gobmk: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-prof-use`(pass 2)
`-auto-ilp32 -ansi-alias`
`-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT`

Continued on next page

## Peak Optimization Flags (Continued)

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32
-ansi-alias
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll4

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll2 -ansi-alias
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-opt-ra-region-strategy=block -ansi-alias -Wl,-z,muldefs
-L/smartheap -lsmartheap
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html
http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml
http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 F2 (Intel Xeon E5620, 2.40 GHz)

SPECint2006 = 34.1

SPECint_base2006 = 32.3

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** May-2011
**Hardware Availability:** Mar-2010
**Software Availability:** Jan-2011

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 23:13:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 August 2011.