



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DX58SO2 motherboard (Intel Core i7-990X Extreme Edition)

SPECint_rate2006 = 203

SPECint_rate_base2006 = 188

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011



Hardware

CPU Name: Intel Core i7-990X Extreme Edition
 CPU Characteristics: Intel Turbo Boost Technology up to 3.73 GHz
 CPU MHz: 3466
 FPU: Integrated
 CPU(s) enabled: 6 cores, 1 chip, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 12 MB I+D on chip per chip
 Other Cache: None
 Memory: 12 GB (3 x 4 GB 2Rx8 PC3-8600U-7)
 Disk Subsystem: Intel 160 GB SSD
 Other Hardware: None

Software

Operating System: Windows 7 Ultimate SP1 (64-bit)
 Compiler: C/C++: Version 12.0.3.176 of Intel C++ Studio XE for Windows;
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DX58SO2 motherboard (Intel Core i7-990X Extreme Edition)

SPECint_rate2006 = 203

SPECint_rate_base2006 = 188

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	12	720	163	720	163	710	166	12	537	218	527	222	529	222
401.bzip2	12	999	116	998	116	1000	116	12	982	118	981	118	982	118
403.gcc	12	758	127	751	128	754	128	12	768	126	743	130	748	130
429.mcf	12	716	152	716	152	711	154	6	312	176	311	176	311	176
445.gobmk	12	635	198	646	194	637	198	12	571	221	569	222	568	222
456.hammer	12	449	250	448	250	448	250	12	394	284	395	283	394	284
458.sjeng	12	768	190	768	190	767	190	12	712	204	714	203	712	204
462.libquantum	12	236	1050	236	1050	236	1050	12	223	1110	223	1110	223	1110
464.h264ref	12	959	277	958	277	958	277	12	933	284	938	283	934	284
471.omnetpp	12	719	104	718	104	718	104	12	700	107	700	107	700	107
473.astar	12	743	113	744	113	743	113	12	747	113	746	113	746	113
483.xalancbmk	12	501	166	501	166	500	166	12	501	166	501	166	500	166

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

The start command with the /affinity switch was used to bind processes to cores

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
System was configured with an ATI HD 6990 discrete graphics card

Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DWIN32 -DSPEC_CPU_NO_INTTYPES

483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DX58SO2 motherboard (Intel Core i7-990X Extreme Edition)

SPECint_rate2006 = 203

SPECint_rate_base2006 = 188

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Base Optimization Flags

C benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000
```

C++ benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
/F512000000 shlw32M.lib -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icl -Qvc9 -Qstd=c99
```

```
456.hmmr: C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe
```

```
458.sjeng: C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe
```

```
462.libquantum: C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe  
-Qstd=c99
```

C++ benchmarks (except as noted below):

```
icl -Qvc9
```

```
473.astar: C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
```

```
456.hmmr: -DSPEC_CPU_P64
```

```
458.sjeng: -DSPEC_CPU_P64
```

```
462.libquantum: -DSPEC_CPU_P64
```

```
464.h264ref: -DWIN32 -DSPEC_CPU_NO_INTTYPES
```

```
473.astar: -DSPEC_CPU_P64
```

```
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DX58SO2 motherboard (Intel Core i7-990X Extreme Edition)

SPECint_rate2006 = 203

SPECint_rate_base2006 = 188

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
                -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
                /F512000000 shlw32M.lib           -link /FORCE:MULTIPLE

401.bzip2: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
            /F512000000

403.gcc: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
          -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
          /F512000000

445.gobmk: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qauto-ilp32 -QxSSE4.2(pass 2) -Qprof_gen(pass 1)
            -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch
            /F512000000

458.sjeng: -Qauto-ilp32 -QxSSE4.2(pass 2) -Qprof_gen(pass 1)
            -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll14
            /F512000000

462.libquantum: -Qauto-ilp32 -QxSSE4.2 -Qipo -O3 -Qprec-div-
                 -Qopt-prefetch /F512000000

464.h264ref: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
              -Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias /F512000000
```

C++ benchmarks:

```
471.omnetpp: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
              -Qipo -O3 -Qprec-div- -Qansi-alias
              -Qopt-ra-region-strategy=block /F512000000 shlw32M.lib
              -link /FORCE:MULTIPLE

473.astar: -Qauto-ilp32 -QxSSE4.2 -Qipo -O3 -Qprec-div-
            -Qopt-prefetch /F512000000 shlw64M.lib
            -link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DX58SO2 motherboard (Intel Core i7-990X Extreme Edition)

SPECint_rate2006 = 203

SPECint_rate_base2006 = 188

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

456.hmmer: -link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib
-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64

458.sjeng: -link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib
-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64

462.libquantum: -link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib
-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64

C++ benchmarks:

473.astar: -link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64
-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib
-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-win32-revC.20111012.html>
<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-win32-revC.20111012.xml>
<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings-revC.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Thu Jul 24 01:17:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 December 2011.