SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH77KC motherboard (Intel Core i7-3770S)

SPECint®2006 = 52.9

SPECint_base2006 = 49.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2012
Hardware Availability: Apr-2012
Software Availability: Apr-2011



Hardware

CPU Name:	Intel Core i7-3770S
CPU Characteristics:	Intel Turbo Boost Technology up to 3.90 GHz
CPU MHz:	3100
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	8 GB (2 x 4 GB 2Rx4 PC3-12800U-11)
Disk Subsystem:	1 TB Seagate SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows 7 Ultimate (64-bit) 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows; Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 9.01 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH77KC motherboard (Intel Core i7-3770S)

SPECint2006 = 52.9

SPECint_base2006 = 49.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2012
Hardware Availability: Apr-2012
Software Availability: Apr-2011

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	306	31.9	304	32.2	**304**	**32.2**	**231**	**42.4**	230	42.4	232	42.1
401.bzip2	**362**	**26.6**	362	26.6	362	26.7	351	27.5	351	27.5	**351**	**27.5**
403.gcc	258	31.2	258	31.2	**258**	**31.2**	244	33.0	244	33.1	**244**	**33.0**
429.mcf	120	76.3	119	76.6	**120**	**76.3**	120	76.3	119	76.6	**120**	**76.3**
445.gobmk	**384**	**27.3**	384	27.3	384	27.3	335	31.3	335	31.3	**335**	**31.3**
456.hmmer	**143**	**65.2**	143	65.3	143	65.2	**143**	**65.2**	143	65.3	143	65.2
458.sjeng	**397**	**30.5**	397	30.5	397	30.5	**397**	**30.5**	397	30.5	397	30.5
462.libquantum	22.2	933	**22.2**	**933**	22.2	933	22.2	933	**22.2**	**933**	22.2	933
464.h264ref	**361**	**61.4**	361	61.4	361	61.4	306	72.4	**306**	**72.4**	306	72.4
471.omnetpp	251	24.9	**249**	**25.1**	246	25.4	233	26.8	231	27.0	**231**	**27.0**
473.astar	218	32.2	**218**	**32.2**	218	32.1	218	32.2	**218**	**32.2**	218	32.1
483.xalancbmk	155	44.5	**155**	**44.5**	155	44.4	155	44.5	**155**	**44.5**	155	44.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler was set up to generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2008" (shortcut provided in the Intel(r) Parallel Studio XE 2011 program folder)
```

Platform Notes

```
Sysinfo program C:\CPU200~1.17A/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on CltE840F206A3A6 Fri May  4 20:45:17 2012

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model  : DH77KC__
Processor(s)  : 1 Processor(s) Installed.
     [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3101 Mhz
BIOS Version  : Intel Corp. KCH7710H.86A.0069.2012.0224.1825, 2/24/2012
Total Physical Memory: 8,090 MB

Trying 'wmic cpu get /value'
DeviceID      : CPU0
L2CacheSize   : 1024
L3CacheSize   : 8192
```

Continued on next page

Platform Notes (Continued)

```
MaxClockSpeed : 3101
Name          : Intel(R) Core(TM) i7-3770S CPU @ 3.10GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)
```

Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
```

General Notes

```
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64 -DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:
```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32
/F512000000
```

C++ benchmarks:
```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F512000000 shlW64M.lib            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc9
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE`

401.bzip2: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32 /F512000000`

403.gcc: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32 /F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 09:29:50 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 18 July 2012.