



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp[®]2006 = **40.7**

Express5800/GT110e-S (Intel Pentium G640)

SPECfp_base2006 = **39.9**

CPU2006 license: 9006


Test date: Aug-2012

Test sponsor: NEC Corporation

Hardware Availability: Jul-2012

Tested by: NEC Corporation

Software Availability: Feb-2012



Hardware

CPU Name: Intel Pentium G640
 CPU Characteristics:
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)
 Kernel 2.6.32-220.el6.x86_64
 Compiler: C/C++: Version 12.1.3.293 of Intel C++ Studio XE for Linux;
 Fortran: Version 12.1.3.293 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = **40.7**

Express5800/GT110e-S (Intel Pentium G640)

SPECfp_base2006 = **39.9**

CPU2006 license: 9006

Test date: Aug-2012

Test sponsor: NEC Corporation

Hardware Availability: Jul-2012

Tested by: NEC Corporation

Software Availability: Feb-2012

L3 Cache: 3 MB I+D on chip per chip
Other Cache: None
Memory: 16 GB (2 x 8 GB 2Rx8 PC3L-12800E-11, ECC, running at 1066 MHz and CL7)
Disk Subsystem: 1 x 250 GB SATA, 7200 RPM
Other Hardware: None

System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---------------|---------|-------|------------|-------------|------------|-------------|------------|-------------|------------|-------------|------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 177 | 76.7 | 176 | 77.1 | 177 | 76.9 | 177 | 76.7 | 176 | 77.1 | 177 | 76.9 |
| 416.gamess | 710 | 27.6 | 715 | 27.4 | 710 | 27.6 | 662 | 29.6 | 660 | 29.7 | 659 | 29.7 |
| 433.milc | 174 | 52.6 | 174 | 52.6 | 174 | 52.6 | 174 | 52.6 | 174 | 52.6 | 174 | 52.6 |
| 434.zeusmp | 166 | 54.7 | 167 | 54.5 | 167 | 54.6 | 166 | 54.7 | 167 | 54.5 | 167 | 54.6 |
| 435.gromacs | 293 | 24.3 | 295 | 24.2 | 294 | 24.3 | 293 | 24.3 | 295 | 24.2 | 294 | 24.3 |
| 436.cactusADM | 180 | 66.6 | 176 | 67.8 | 177 | 67.6 | 180 | 66.6 | 176 | 67.8 | 177 | 67.6 |
| 437.leslie3d | 205 | 45.9 | 204 | 46.0 | 204 | 46.1 | 205 | 45.9 | 204 | 46.0 | 204 | 46.1 |
| 444.namd | 426 | 18.8 | 426 | 18.8 | 426 | 18.8 | 420 | 19.1 | 420 | 19.1 | 420 | 19.1 |
| 447.dealII | 246 | 46.5 | 245 | 46.6 | 245 | 46.7 | 246 | 46.5 | 245 | 46.6 | 245 | 46.7 |
| 450.soplex | 289 | 28.9 | 289 | 28.9 | 289 | 28.9 | 289 | 28.9 | 289 | 28.9 | 289 | 28.9 |
| 453.povray | 150 | 35.5 | 150 | 35.6 | 149 | 35.8 | 128 | 41.7 | 126 | 42.3 | 128 | 41.6 |
| 454.calculix | 258 | 32.0 | 258 | 32.0 | 257 | 32.1 | 253 | 32.7 | 253 | 32.7 | 254 | 32.5 |
| 459.GemsFDTD | 260 | 40.8 | 260 | 40.9 | 259 | 40.9 | 259 | 41.0 | 259 | 41.0 | 259 | 41.0 |
| 465.tonto | 316 | 31.1 | 315 | 31.2 | 315 | 31.2 | 302 | 32.5 | 302 | 32.5 | 303 | 32.5 |
| 470.lbm | 258 | 53.3 | 256 | 53.7 | 256 | 53.6 | 258 | 53.3 | 256 | 53.7 | 256 | 53.6 |
| 481.wrf | 216 | 51.7 | 215 | 51.9 | 216 | 51.7 | 216 | 51.7 | 215 | 51.9 | 216 | 51.7 |
| 482.sphinx3 | 547 | 35.6 | 548 | 35.6 | 548 | 35.6 | 547 | 35.6 | 548 | 35.6 | 548 | 35.6 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Default BIOS settings were used.

General Notes

Environment variables set by runspec before the start of the run:
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64"
OMP_NUM_THREADS = "2"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 40.7

Express5800/GT110e-S (Intel Pentium G640)

SPECfp_base2006 = 39.9

CPU2006 license: 9006

Test date: Aug-2012

Test sponsor: NEC Corporation

Hardware Availability: Jul-2012

Tested by: NEC Corporation

Software Availability: Feb-2012

General Notes (Continued)

Added glibc-static-2.12-1.47.el6.x86_64.rpm
to enable static linking

Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

| | | |
|--|--------------------------|-------------|
| NEC Corporation | SPECfp2006 = | 40.7 |
| Express5800/GT110e-S (Intel Pentium G640) | SPECfp_base2006 = | 39.9 |

| | |
|--------------------------------------|--|
| CPU2006 license: 9006 | Test date: Aug-2012 |
| Test sponsor: NEC Corporation | Hardware Availability: Jul-2012 |
| Tested by: NEC Corporation | Software Availability: Feb-2012 |

Base Optimization Flags (Continued)

C++ benchmarks:
 -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:
 -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:
 -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
 -ansi-alias

Peak Compiler Invocation

C benchmarks:
 icc -m64

C++ benchmarks:
 icpc -m64

Fortran benchmarks:
 ifort -m64

Benchmarks using both Fortran and C:
 icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
 -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 40.7

Express5800/GT110e-S (Intel Pentium G640)

SPECfp_base2006 = 39.9

CPU2006 license: 9006

Test date: Aug-2012

Test sponsor: NEC Corporation

Hardware Availability: Jul-2012

Tested by: NEC Corporation

Software Availability: Feb-2012

Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120425.html>
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120425.xml>
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 40.7

Express5800/GT110e-S (Intel Pentium G640)

SPECfp_base2006 = 39.9

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Aug-2012

Hardware Availability: Jul-2012

Software Availability: Feb-2012

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 10:44:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 August 2012.