SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH77KC Motherboard (Intel Core i5-3470)

SPECfp®_rate2006 = 119

SPECfp_rate_base2006 = 117

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2012
Hardware Availability: Jun-2012
Software Availability: Apr-2011



Hardware

CPU Name:	Intel Core i5-3470
CPU Characteristics:	Intel Turbo Boost Technology up to 3.6 GHz
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software

Operating System:	Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows; Fortran: Version 12.1.0.229 of Intel Fortran Studio XE for Windows; Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
Auto Parallel:	No

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH77KC Motherboard (Intel Core i5-3470)

SPECfp_rate2006 = 119

SPECfp_rate_base2006 = 117

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2012
Hardware Availability: Jun-2012
Software Availability: Apr-2011

L3 Cache: 6 MB I+D on chip per chip
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx8 PC3-12800U-9)
Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
Other Hardware: None

File System: NTFS
System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 9.01 from http://www.microquill.com/

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	495	110	494	110	**494**	**110**	4	495	110	494	110	**494**	**110**
416.gamess	4	**557**	**141**	556	141	557	141	4	**557**	**141**	556	141	557	141
433.milc	4	326	113	**326**	**113**	326	113	4	326	113	**326**	**113**	326	113
434.zeusmp	4	256	142	258	141	**256**	**142**	4	256	142	258	141	**256**	**142**
435.gromacs	4	287	99.2	287	99.6	**287**	**99.6**	4	287	99.2	287	99.6	**287**	**99.6**
436.cactusADM	4	301	159	**303**	**158**	304	158	4	301	159	**303**	**158**	304	158
437.leslie3d	4	513	73.2	513	73.2	**513**	**73.2**	4	513	73.2	513	73.2	**513**	**73.2**
444.namd	4	338	94.8	**339**	**94.8**	339	94.8	4	330	97.2	330	97.2	**330**	**97.2**
447.dealII	4	**322**	**142**	323	142	320	143	4	**322**	**142**	323	142	320	143
450.soplex	4	435	76.8	435	76.8	**435**	**76.8**	4	434	76.8	**433**	**77.2**	433	77.2
453.povray	4	122	174	**123**	**173**	123	173	4	100	213	**100**	**213**	100	213
454.calculix	4	**206**	**160**	206	160	206	160	4	**206**	**160**	206	160	206	160
459.GemsFDTD	4	**650**	**65.2**	650	65.2	650	65.2	4	**650**	**65.2**	650	65.2	650	65.2
465.tonto	4	317	124	318	124	**318**	**124**	4	301	131	**301**	**131**	301	131
470.lbm	4	407	135	408	135	**407**	**135**	4	407	135	408	135	**407**	**135**
481.wrf	4	345	130	**345**	**130**	344	130	4	345	130	**345**	**130**	344	130
482.sphinx3	4	658	118	671	116	**659**	**118**	4	650	120	652	120	**652**	**120**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
ipsxe-comp-vars batch file invoked with intel64
```

Submit Notes

```
Processes were bound to specific processors using the start command with the /affinity switch.
The config file option 'submit' was used to generate the affinity mask for each process.
```

Platform Notes

```
Sysinfo program C:\CPU200~1.17A/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on CltE840F20AA525 Sat May 19 10:04:28 2012

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model  : DH77KC__
Processor(s)  : 1 Processor(s) Installed.
     [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3201 Mhz
BIOS Version  : Intel Corp. KCH7710H.86A.0069.2012.0224.1825, 2/24/2012
Total Physical Memory: 8,090 MB

Trying 'wmic cpu get /value'
DeviceID      : CPU0
L2CacheSize   : 1024
L3CacheSize   : 6144
MaxClockSpeed : 3201
Name          : Intel(R) Core(TM) i5-3470 CPU @ 3.20GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)
```

Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
```

General Notes

```
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F1000000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:
-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc9
```

Fortran benchmarks:
```
ifort
```

Benchmarks using both Fortran and C:
```
icl -Qvc9 -Qstd=c99 ifort
```

Peak Portability Flags

```
Same as Base Portability Flags
```

Peak Optimization Flags

C benchmarks:

433.milc: `basepeak = yes`

470.lbm: `basepeak = yes`

482.sphinx3: `-QxAVX -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE`

C++ benchmarks:

444.namd: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

447.dealII: `basepeak = yes`

450.soplex: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

453.povray: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

Fortran benchmarks:

Continued on next page

Peak Optimization Flags (Continued)

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 13:11:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 November 2012.