



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint®\_rate2006 = 892**

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate\_base2006 = 787**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Nov-2012

Hardware Availability: Dec-2012

Software Availability: Aug-2012



**SPECint\_rate\_base2006 = 787**

**SPECint\_rate2006 = 892**

## Hardware

CPU Name: AMD Opteron 6366 HE  
CPU Characteristics: AMD Turbo CORE technology up to 3.10 GHz  
CPU MHz: 1800  
FPU: Integrated  
CPU(s) enabled: 64 cores, 4 chips, 16 cores/chip  
CPU(s) orderable: 2,4 chips  
Primary Cache: 512 KB I on chip per chip,  
64 KB I shared / 2 cores;  
16 KB D on chip per core  
Secondary Cache: 16 MB I+D on chip per chip, 2 MB shared / 2 cores  
L3 Cache: 16 MB I+D on chip per chip, 8 MB shared / 8 cores  
Other Cache: None  
Memory: 256 GB (32 x 8 GB 2Rx4 PC3-12800R-11, ECC)  
Disk Subsystem: 1 x 300 GB 10000 RPM SAS  
Other Hardware: None

## Software

Operating System: Red Hat Enterprise Linux Server release 6.3,  
Kernel 2.6.32-279.el6.x86\_64  
Compiler: C/C++: Version 4.5.2 of x86 Open64 Compiler Suite  
(from AMD)  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (Full multiuser with network)  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap 10.0 32-bit Library for Linux



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECint\_rate2006 = 892**

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate\_base2006 = 787**

CPU2006 license: 55

Test date: Nov-2012

Test sponsor: Dell Inc.

Hardware Availability: Dec-2012

Tested by: Dell Inc.

Software Availability: Aug-2012

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	64	1106	565	1112	562	<b>1112</b>	<b>563</b>	64	942	664	<b>937</b>	<b>667</b>	937	668
401.bzip2	64	1286	480	1283	482	<b>1283</b>	<b>481</b>	64	1199	515	<b>1215</b>	<b>508</b>	1218	507
403.gcc	64	859	600	855	603	<b>855</b>	<b>602</b>	64	769	670	767	671	771	668
429.mcf	64	734	795	<b>730</b>	<b>800</b>	725	805	64	434	1340	437	1340	<b>435</b>	<b>1340</b>
445.gobmk	64	<b>1196</b>	<b>561</b>	1197	561	1196	561	64	<b>1096</b>	<b>613</b>	1092	615	1096	612
456.hammer	64	544	1100	<b>546</b>	<b>1090</b>	553	1080	64	<b>493</b>	<b>1210</b>	493	1210	482	1240
458.sjeng	64	<b>1401</b>	<b>553</b>	1404	552	1401	553	64	1340	578	<b>1340</b>	<b>578</b>	1346	576
462.libquantum	64	205	6470	<b>205</b>	<b>6470</b>	205	6470	64	205	6470	<b>205</b>	<b>6470</b>	205	6470
464.h264ref	64	2186	648	2310	613	<b>2190</b>	<b>647</b>	64	1838	771	1808	783	<b>1810</b>	<b>782</b>
471.omnetpp	64	582	688	585	683	<b>584</b>	<b>685</b>	64	628	637	<b>584</b>	<b>685</b>	583	686
473.astar	64	843	533	<b>842</b>	<b>534</b>	842	534	64	676	665	<b>675</b>	<b>666</b>	673	668
483.xalancbmk	64	530	833	529	835	<b>529</b>	<b>835</b>	64	522	846	<b>523</b>	<b>844</b>	524	843

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
'numactl' was used to bind copies to the cores.  
See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size  
'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set transparent\_hugepage=never as a boot parameter in /boot/grub/menu.lst

Set vm/nr\_hugepages=57344 in /etc/sysctl.conf  
mount -t hugetlbfs nodev /mnt/hugepages

## General Notes

Environment variables set by runspec before the start of the run:

HUGETLB\_LIMIT = "896"

LD\_LIBRARY\_PATH = "/root/cpu2006-1.2/amd1206-rate-libs-revA/32:/root/cpu2006-1.2/amd1206-rate-libs-revA/64"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at  
<http://developer.amd.com/cpu/open64>

Binaries were compiled on a system with 2x AMD Opteron 6386SE chips + 128GB Memory using RHEL 6.3



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate2006 = 892**

CPU2006 license: 55

**Test date:** Nov-2012

Test sponsor: Dell Inc.

**Hardware Availability:** Dec-2012

Tested by: Dell Inc.

**Software Availability:** Aug-2012

## Base Compiler Invocation

C benchmarks:  
opencc

C++ benchmarks:  
openCC

## Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64  
401.bzip2: -DSPEC_CPU_LP64  
403.gcc: -DSPEC_CPU_LP64  
429.mcf: -DSPEC_CPU_LP64  
445.gobmk: -DSPEC_CPU_LP64  
456.hmmr: -DSPEC_CPU_LP64  
458.sjeng: -DSPEC_CPU_LP64  
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX  
464.h264ref: -DSPEC_CPU_LP64  
483.xalancbmk: -DSPEC_CPU_LINUX
```

## Base Optimization Flags

C benchmarks:  
`-Ofast -CG:local_sched_alg=1 -INLINE:aggressive=ON -IPA:plimit=8000  
-IPA:small_pu=100 -HP:bd=2m:heap=2m -mso -LNO:prefetch=2  
-march=bdver1`

C++ benchmarks:  
`-Ofast -m32 -INLINE:aggressive=on -CG:cmp_peep=on -D__OPEN64_FAST_SET  
-march=bdver1 -L/root/work/libraries/SmartHeap-10/lib -lsmartheap`

## Peak Compiler Invocation

C benchmarks:  
opencc

C++ benchmarks:  
openCC

## Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate2006 = 892**

**SPECint\_rate\_base2006 = 787**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Nov-2012

**Hardware Availability:** Dec-2012

**Software Availability:** Aug-2012

## Peak Portability Flags (Continued)

```

401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

## Peak Optimization Flags

C benchmarks:

```

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
    -LNO:prefetch=2 -LNO:opt=0 -IPA:plimit=20000
    -OPT:unroll_times_max=8 -OPT:unroll_size=256
    -OPT:unroll_level=2 -OPT:keep_ext=on -WOPT:if_conv=0
    -WOPT:sib=on -CG:local_sched_alg=1 -CG:unroll_fb_req=on
    -CG:movext_icmp=off -HP:bd=2m:heap=2m -march=bdver1
    -GRA:aggr_loop_splitting=off -GRA:loop_splitting=off

401.bzip2: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
    -LNO:prefetch=2 -LNO:pf2=0 -OPT:alias=disjoint
    -OPT:goto=off -CG:local_sched_alg=1 -HP:bdt=2m:heap=2m
    -march=bdver2

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
    -LNO:trip_count=256 -CG:cmp_peep=on -CG:pre_minreg_level=2
    -m32 -HP:bdt=2m:heap=2m -GRA:unspill=on -IPA:small_pu=200
    -WOPT:sib=on -march=bdver2 -mno-fma4

429.mcf: -O3 -OPT:unroll_times_max=5 -ipa -INLINE:aggressive=on
    -CG:gcm=off -CG:dsched=on -GRA:prioritize_by_density=on
    -m32 -HP:bdt=2m:heap=2m -mso -march=bdver1

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
    -OPT:unroll_size=256 -OPT:unroll_times_max=8
    -OPT:keep_ext=on -IPA:plimit=750 -IPA:min_hotness=300
    -IPA:pu_reorder=1 -LNO:ignore_feedback=off -WOPT:if_conv=2
    -HP:bd=2m:heap=2m -march=bdver1

456.hmmer: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
    -LNO:prefetch=2 -OPT:alias=disjoint
    -OPT:unroll_times_max=16 -OPT:unroll_size=512
    -OPT:unroll_level=2 -OPT:keep_ext=on -CG:cflow=0
    -CG:cmp_peep=on -CG:pre_local_sched=off -HP:bdt=2m:heap=2m
    -CG:p2align=0 -CG:load_exe=3 -CG:dsched=on -march=bdver1

```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate2006 = 892**

CPU2006 license: 55

**Test date:** Nov-2012

Test sponsor: Dell Inc.

**Hardware Availability:** Dec-2012

Tested by: Dell Inc.

**Software Availability:** Aug-2012

## Peak Optimization Flags (Continued)

```
458.sjeng: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast  
-CG:ptr_load_use=0 -CG:divrem_opt=on -CG:movext_icmp=off  
-CG:locs_best=on -LNO:full_unroll=10 -IPA:pu_reorder=2  
-HP:heap=2m:bd=2m -WOPT:sib=on -march=bdver1
```

```
462.libquantum: basepeak = yes
```

```
464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3  
-OPT:unroll_size=256 -OPT:unroll_times_max=2  
-IPA:plimit=20000 -OPT:alias=disjoint -CG:ptr_load_use=0  
-CG:local_sched_alg=1 -HP:bdt=2m:heap=2m -march=bdver1
```

C++ benchmarks:

```
471.omnetpp: -Ofast -m32 -INLINE:aggressive=on -CG:cmp_peep=on  
-WOPT:sib=on -D__OPEN64_FAST_SET -march=bdver2 -mno-fma4  
-L/root/work/libraries/SmartHeap-10/lib -lsmartheap
```

```
473.astar: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast  
-WOPT:if_conv=0 -WOPT:sib=on -CG:divrem_opt=on  
-CG:p2align=1 -CG:dsched=on -GRA:optimize_boundary=on  
-OPT:alias=disjoint -INLINE:aggressive=on  
-IPA:small_pu=3000 -IPA:plimit=3000 -HP:bdt=2m:heap=2m  
-march=bdver1
```

```
483.xalancbmk: -Ofast -LNO:prefetch=2 -OPT:unroll_size=512  
-OPT:unroll_times_max=8 -D__OPEN64_FAST_SET  
-INLINE:aggressive=on -m32 -CG:cmp_peep=on  
-CG:local_sched=off -CG:p2align=1 -GRA:unspill=on  
-TENV:frame_pointer=off -fno-emit-exceptions -march=bdver2  
-mno-fma4  
-L/root/work/libraries/SmartHeap-10/lib -lsmartheap
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/x86-open64-452-flags-rate-revA-II.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/x86-open64-452-flags-rate-revA-II.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge M915 (AMD Opteron 6366 HE, 1.80 GHz)

**SPECint\_rate2006 = 892**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Nov-2012

**Hardware Availability:** Dec-2012

**Software Availability:** Aug-2012

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 15:16:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 26 February 2013.