



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp<sup>®</sup>2006 = **99.7**

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

SPECfp\_base2006 = **95.5**

CPU2006 license: 19


Test date: Sep-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013



### Hardware

CPU Name: Intel Xeon E5-2650 v2  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 2.6.32-358.11.1.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **99.7**

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

SPECfp\_base2006 = **95.5**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Sep-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013

L3 Cache: 20 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC3-14900R-13, ECC)  
 Disk Subsystem: 1 x SATA, 450 GB, 15000 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	28.6	475	27.6	492	<b><u>27.8</u></b>	<b><u>488</u></b>	28.6	475	27.6	492	<b><u>27.8</u></b>	<b><u>488</u></b>
416.gamess	623	31.5	<b><u>621</u></b>	<b><u>31.5</u></b>	620	31.6	532	36.8	<b><u>532</u></b>	<b><u>36.8</u></b>	533	36.7
433.milc	134	68.3	<b><u>135</u></b>	<b><u>68.0</u></b>	135	68.0	131	70.3	133	69.1	<b><u>133</u></b>	<b><u>69.2</u></b>
434.zeusmp	<b><u>55.0</u></b>	<b><u>165</u></b>	54.6	167	55.0	165	<b><u>55.0</u></b>	<b><u>165</u></b>	54.6	167	55.0	165
435.gromacs	171	41.9	<b><u>171</u></b>	<b><u>41.8</u></b>	171	41.8	171	41.9	<b><u>171</u></b>	<b><u>41.8</u></b>	171	41.8
436.cactusADM	<b><u>20.5</u></b>	<b><u>584</u></b>	20.7	578	20.5	584	<b><u>20.5</u></b>	<b><u>584</u></b>	20.7	578	20.5	584
437.leslie3d	38.6	243	31.8	295	<b><u>32.0</u></b>	<b><u>293</u></b>	38.6	243	31.8	295	<b><u>32.0</u></b>	<b><u>293</u></b>
444.namd	340	23.6	<b><u>342</u></b>	<b><u>23.4</u></b>	342	23.4	335	23.9	335	24.0	<b><u>335</u></b>	<b><u>24.0</u></b>
447.dealII	<b><u>210</u></b>	<b><u>54.4</u></b>	210	54.4	211	54.3	<b><u>210</u></b>	<b><u>54.4</u></b>	210	54.4	211	54.3
450.soplex	<b><u>184</u></b>	<b><u>45.4</u></b>	181	46.1	184	45.4	<b><u>184</u></b>	<b><u>45.4</u></b>	181	46.1	184	45.4
453.povray	<b><u>118</u></b>	<b><u>45.3</u></b>	118	45.2	116	46.1	<b><u>98.9</u></b>	<b><u>53.8</u></b>	98.9	53.8	98.5	54.0
454.calculix	<b><u>183</u></b>	<b><u>45.0</u></b>	181	45.5	184	44.9	170	48.6	<b><u>170</u></b>	<b><u>48.6</u></b>	166	49.7
459.GemsFDTD	52.6	202	<b><u>53.2</u></b>	<b><u>199</u></b>	53.2	199	49.1	216	<b><u>49.3</u></b>	<b><u>215</u></b>	49.5	214
465.tonto	265	37.1	<b><u>265</u></b>	<b><u>37.2</u></b>	264	37.3	213	46.1	214	45.9	<b><u>214</u></b>	<b><u>46.0</u></b>
470.lbm	24.2	567	24.8	554	<b><u>24.8</u></b>	<b><u>554</u></b>	24.2	567	24.8	554	<b><u>24.8</u></b>	<b><u>554</u></b>
481.wrf	<b><u>108</u></b>	<b><u>104</u></b>	107	104	108	103	<b><u>108</u></b>	<b><u>104</u></b>	107	104	108	103
482.sphinx3	267	73.0	264	73.7	<b><u>267</u></b>	<b><u>73.1</u></b>	<b><u>266</u></b>	<b><u>73.1</u></b>	266	73.2	267	72.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Energy Performance = Performance  
 Utilization Profile = Unbalanced

## General Notes

Environment variables set by runspec before the start of the run:  
 KMP\_AFFINITY = "granularity=fine,compact,1,0"  
 LD\_LIBRARY\_PATH = "/SPECcpu2006/libs/32:/SPECcpu2006/libs/64:/SPECcpu2006/sh"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = 99.7

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

SPECfp\_base2006 = 95.5

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Sep-2013  
Hardware Availability: Oct-2013  
Software Availability: Sep-2013

### General Notes (Continued)

OMP\_NUM\_THREADS = "16"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

This result was measured on the PRIMERGY RX350 S8. The PRIMERGY RX350 S8 and the PRIMERGY TX300 S8 are electronically equivalent.

For information about Fujitsu please visit: <http://www.fujitsu.com>

### Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 99.7**

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

**SPECfp\_base2006 = 95.5**

CPU2006 license: 19

Test date: Sep-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013

## Base Optimization Flags

C benchmarks:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias`

C++ benchmarks:

`-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: `-xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32  
-ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `-xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 99.7**

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

**SPECfp\_base2006 = 95.5**

**CPU2006 license:** 19

**Test date:** Sep-2013

**Test sponsor:** Fujitsu

**Hardware Availability:** Oct-2013

**Tested by:** Fujitsu

**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20130924.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20130924.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 99.7

PRIMERGY RX350 S8, Intel Xeon E5-2650 v2, 2.60 GHz

SPECfp\_base2006 = 95.5

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Sep-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 17:13:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 9 October 2013.