



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp<sup>®</sup>2006 = **92.4**

Express5800/R120e-2M (Intel Xeon E5-2660 v2)

SPECfp\_base2006 = **88.2**

CPU2006 license: 9006


Test date: Nov-2013

Test sponsor: NEC Corporation

Hardware Availability: Sep-2013

Tested by: NEC Corporation

Software Availability: Sep-2013



**Hardware**

CPU Name: Intel Xeon E5-2660 v2  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.00 GHz  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

**Software**

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 Kernel 2.6.32-358.18.1.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp2006 = **92.4**

Express5800/R120e-2M (Intel Xeon E5-2660 v2)

SPECfp\_base2006 = **88.2**

CPU2006 license: 9006

Test date: Nov-2013

Test sponsor: NEC Corporation

Hardware Availability: Sep-2013

Tested by: NEC Corporation

Software Availability: Sep-2013

L3 Cache: 25 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 128 GB (8 x 16 GB 2Rx4 PC3-14900R-13, ECC)  
 Disk Subsystem: 1 x 250 GB SATA, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	30.8	441	<b>30.4</b>	<b>447</b>	30.2	450	30.8	441	<b>30.4</b>	<b>447</b>	30.2	450
416.gamess	713	27.5	705	27.8	<b>713</b>	<b>27.5</b>	602	32.5	<b>602</b>	<b>32.5</b>	602	32.5
433.milc	152	60.5	151	60.9	<b>151</b>	<b>60.9</b>	148	61.9	149	61.8	<b>148</b>	<b>61.9</b>
434.zeusmp	59.6	153	<b>59.2</b>	<b>154</b>	58.8	155	59.6	153	<b>59.2</b>	<b>154</b>	58.8	155
435.gromacs	197	36.2	198	36.1	<b>198</b>	<b>36.1</b>	197	36.2	198	36.1	<b>198</b>	<b>36.1</b>
436.cactusADM	20.5	583	<b>20.3</b>	<b>589</b>	20.1	595	20.5	583	<b>20.3</b>	<b>589</b>	20.1	595
437.leslie3d	<b>29.8</b>	<b>315</b>	30.8	305	29.6	317	<b>29.8</b>	<b>315</b>	30.8	305	29.6	317
444.namd	387	20.7	<b>388</b>	<b>20.7</b>	388	20.7	380	21.1	380	21.1	<b>380</b>	<b>21.1</b>
447.dealII	213	53.6	<b>213</b>	<b>53.6</b>	214	53.6	213	53.6	<b>213</b>	<b>53.6</b>	214	53.6
450.soplex	<b>198</b>	<b>42.0</b>	199	42.0	198	42.1	<b>198</b>	<b>42.0</b>	199	42.0	198	42.1
453.povray	130	40.9	133	40.1	<b>131</b>	<b>40.7</b>	<b>112</b>	<b>47.7</b>	112	47.7	109	48.8
454.calculix	205	40.1	<b>208</b>	<b>39.7</b>	208	39.7	192	42.9	192	43.0	<b>192</b>	<b>43.0</b>
459.GemsFDTD	57.0	186	57.4	185	<b>57.1</b>	<b>186</b>	51.1	207	51.9	204	<b>51.4</b>	<b>207</b>
465.tonto	<b>306</b>	<b>32.1</b>	307	32.1	302	32.6	241	40.8	241	40.8	<b>241</b>	<b>40.8</b>
470.lbm	24.2	567	23.6	582	<b>23.8</b>	<b>577</b>	24.2	567	23.6	582	<b>23.8</b>	<b>577</b>
481.wrf	120	93.4	121	92.3	<b>121</b>	<b>92.4</b>	120	93.4	121	92.3	<b>121</b>	<b>92.4</b>
482.sphinx3	300	65.1	304	64.2	<b>302</b>	<b>64.6</b>	300	65.1	304	64.2	<b>302</b>	<b>64.6</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
Energy Performance: Performance

## General Notes

Environment variables set by runspec before the start of the run:  
 KMP\_AFFINITY = "granularity=fine,compact,1,0"  
 LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"  
 OMP\_NUM\_THREADS = "20"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 92.4

Express5800/R120e-2M (Intel Xeon E5-2660 v2)

SPECfp\_base2006 = 88.2

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

## General Notes (Continued)

Added glibc-static-2.12-1.107.el6.x86\_64.rpm  
to enable static linking

Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
The Express5800/R120e-1M and  
the Express5800/R120e-2M models are electronically equivalent.  
The results have been measured on the Express5800/R120e-2M model.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 92.4

Express5800/R120e-2M (Intel Xeon E5-2660 v2)

SPECfp\_base2006 = 88.2

CPU2006 license: 9006

Test date: Nov-2013

Test sponsor: NEC Corporation

Hardware Availability: Sep-2013

Tested by: NEC Corporation

Software Availability: Sep-2013

## Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

<b>NEC Corporation</b>	<b>SPECfp2006 =</b>	<b>92.4</b>
Express5800/R120e-2M (Intel Xeon E5-2660 v2)	<b>SPECfp_base2006 =</b>	<b>88.2</b>

<b>CPU2006 license:</b> 9006	<b>Test date:</b> Nov-2013
<b>Test sponsor:</b> NEC Corporation	<b>Hardware Availability:</b> Sep-2013
<b>Tested by:</b> NEC Corporation	<b>Software Availability:</b> Sep-2013

## Peak Optimization Flags (Continued)

### C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
 -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
 -inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
 -inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
 -opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 92.4

Express5800/R120e-2M (Intel Xeon E5-2660 v2)

SPECfp\_base2006 = 88.2

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Nov-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 17:59:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 3 December 2013.