



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sugon**

**SPECint®\_rate2006 = 812**

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate\_base2006 = 785**

CPU2006 license: 9046


**Test date:** Nov-2013

Test sponsor: Sugon

**Hardware Availability:** Nov-2013

Tested by: Sugon

**Software Availability:** Nov-2013



**SPECint\_rate\_base2006 = 785**

**SPECint\_rate2006 = 812**

## Hardware

CPU Name: Intel Xeon E5-2670 v2  
CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz  
CPU MHz: 2500  
FPU: Integrated  
CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 25 MB I+D on chip per chip  
Other Cache: None  
Memory: 256 GB (16 x 16 GB 2Rx4 PC3-14900R-13, ECC)  
Disk Subsystem: 4 x 450 GB SAS 10K RPM, RAID0  
Other Hardware: None

## Software

Operating System: SUSE Linux Enterprise Server 11 SP3 (x86\_64) 3.0.76-0.11-default  
Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (Full multiuser with network)  
Base Pointers: 32-bit  
Peak Pointers: 32/64-bit  
Other Software: Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sugon**

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate2006 = 812**

**SPECint\_rate\_base2006 = 785**

**CPU2006 license:** 9046

**Test date:** Nov-2013

**Test sponsor:** Sugon

**Hardware Availability:** Nov-2013

**Tested by:** Sugon

**Software Availability:** Nov-2013

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	40	<b>657</b>	<b>595</b>	657	595	658	594	40	<b>548</b>	<b>714</b>	545	717	548	713
401.bzip2	40	<b>911</b>	<b>424</b>	911	424	911	424	40	<b>895</b>	<b>431</b>	<b>894</b>	<b>432</b>	893	432
403.gcc	40	516	624	519	620	<b>517</b>	<b>623</b>	40	<b>520</b>	<b>620</b>	519	620	520	619
429.mcf	40	307	1190	307	1190	<b>307</b>	<b>1190</b>	40	307	1190	307	1190	<b>307</b>	<b>1190</b>
445.gobmk	40	719	583	720	583	<b>719</b>	<b>583</b>	40	704	596	702	597	<b>704</b>	<b>596</b>
456.hammer	40	349	1070	348	1070	<b>349</b>	<b>1070</b>	40	318	1170	319	1170	<b>319</b>	<b>1170</b>
458.sjeng	40	836	579	<b>837</b>	<b>579</b>	837	578	40	812	596	<b>808</b>	<b>599</b>	807	599
462.libquantum	40	158	5230	159	5230	<b>158</b>	<b>5230</b>	40	158	5230	159	5230	<b>158</b>	<b>5230</b>
464.h264ref	40	900	983	894	990	<b>898</b>	<b>986</b>	40	886	999	892	992	<b>890</b>	<b>995</b>
471.omnetpp	40	585	427	<b>585</b>	<b>427</b>	585	427	40	555	450	<b>557</b>	<b>449</b>	558	448
473.astar	40	636	441	<b>636</b>	<b>442</b>	634	443	40	636	441	<b>636</b>	<b>442</b>	634	443
483.xalancbmk	40	333	829	<b>331</b>	<b>834</b>	330	836	40	333	829	<b>331</b>	<b>834</b>	330	836

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Configuration:

Intel Virtualization technology set to disabled

Power Technology set to performance

Turbo boost set to enabled

DDR Speed set to force 1866

Sysinfo program /home/spec/config/sysinfo.rev6818

\$Rev: 6818 \$ \$Date::: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191

running on linux-tn7k Sat Nov 16 01:12:48 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2670 v2 @ 2.50GHz

2 "physical id"s (chips)

40 "processors"

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate2006 = 812**

CPU2006 license: 9046

**Test date:** Nov-2013

Test sponsor: Sugon

**Hardware Availability:** Nov-2013

Tested by: Sugon

**Software Availability:** Nov-2013

## Platform Notes (Continued)

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 10
siblings   : 20
physical 0: cores 0 1 2 3 4 8 9 10 11 12
physical 1: cores 0 1 2 3 4 8 9 10 11 12
cache size : 25600 KB
```

```
From /proc/meminfo
MemTotal:      264516912 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 11 (x86_64)
```

```
From /etc/*release* /etc/*version*
SuSE-release:
  SUSE Linux Enterprise Server 11 (x86_64)
  VERSION = 11
  PATCHLEVEL = 3
```

```
uname -a:
Linux linux-tn7k 3.0.76-0.11-default #1 SMP Fri Jun 14 08:21:43 UTC 2013
(ccab990) x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Nov 16 00:56 last=S
```

```
SPEC is set to: /home/spec
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/md126p1    ext3  784G  77G  668G  11% /home/spec
```

```
Additional information from dmidecode:
BIOS American Megatrends Inc. 3.0a 10/10/2013
Memory:
 16x 16 GB
 16x Hynix Semiconducto HMT42GR7AFR4C 16 GB 1866 MHz
```

(End of data from sysinfo program)

There is a error in sysinfo output. There are only 16 DIMMs in this system. The cause of this error is the sysinfo itself. The sysinfo of revision 6818 can't identify the correct memory information.

The memory information should be:

```
Memory:
 16x Hynix Semiconducto HMT42GR7AFR4C 16 GB 1866 MHz
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate2006 = 812**

CPU2006 license: 9046

Test date: Nov-2013

Test sponsor: Sugon

Hardware Availability: Nov-2013

Tested by: Sugon

Software Availability: Nov-2013

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/home/spec/libs/32:/home/spec/libs/64:/home/spec/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop\_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m32

C++ benchmarks:

icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/sh -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate2006 = 812**

**SPECint\_rate\_base2006 = 785**

**CPU2006 license:** 9046

**Test sponsor:** Sugon

**Tested by:** Sugon

**Test date:** Nov-2013

**Hardware Availability:** Nov-2013

**Software Availability:** Nov-2013

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

I620-G10 (Intel Xeon E5-2670 v2, 2.50 GHz)

**SPECint\_rate2006 = 812**

**SPECint\_rate\_base2006 = 785**

**CPU2006 license:** 9046

**Test sponsor:** Sugon

**Tested by:** Sugon

**Test date:** Nov-2013

**Hardware Availability:** Nov-2013

**Software Availability:** Nov-2013

## Peak Optimization Flags (Continued)

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-IVB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-IVB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 19:42:52 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 17 December 2013.