SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/A2040b (Intel Xeon E7-4830 v2)

SPECint®_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Mar-2014
Hardware Availability: Mar-2014
Software Availability: Oct-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Copies	
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483.xalancbmk	

Hardware

CPU Name:	Intel Xeon E7-4830 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 2.70 GHz
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	40 cores, 4 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable:	2,3,4 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	20 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Software

Operating System:	Red Hat Enterprise Linux Server release 6.4 (Santiago) Kernel 2.6.32-358.23.2.el6.x86_64
Compiler:	C/C++: Version 14.0.1.106 of Intel C++ Studio XE for Linux
Auto Parallel:	No
File System:	ext4
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit

Continued on next page

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/A2040b (Intel Xeon E7-4830 v2)

SPECint_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Mar-2014
Hardware Availability: Mar-2014
Software Availability: Oct-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Memory:	1 TB (64 x 16 GB 2Rx4 PC3L-12800R-11, ECC, running at 1333 MHz and CL9)
Disk Subsystem:	1 x 300 GB SAS, 10000 RPM
Other Hardware:	None

Other Software: Microquill SmartHeap Multi-Core V10.01

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
401.bzip2	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
403.gcc	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
429.mcf	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
445.gobmk	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
456.hmmer	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
458.sjeng	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
462.libquantum	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
464.h264ref	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
471.omnetpp	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
473.astar	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC
483.xalancbmk	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Zone reclaim mode enabled with:
echo 1 > /proc/sys/vm/zone_reclaim_mode
```

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/A2040b (Intel Xeon E7-4830 v2)

SPECint_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Mar-2014
Hardware Availability: Mar-2014
Software Availability: Oct-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Platform Notes

```
BIOS Settings:
 Memory RAS Mode: Independent mode
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/opt/SmartHeap_10mc/lib:/opt/SmartHeap_10mc/lib32:/opt/intel/composer_xe_2013_sp1.1.106/compiler/lib/ia32:/opt/intel/composer_xe_2013_sp1.1.106/compiler/lib/intel64"

 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
 Filesystem page cache cleared with:
 echo 1 > /proc/sys/vm/drop_caches
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
```

Base Compiler Invocation

C benchmarks:
```
icc  -m32
```

C++ benchmarks:
```
icpc -m32
```

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX
```

Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Base Optimization Flags (Continued)

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
-Wl,-z,muldefs -L/opt/SmartHeap_10mc/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:
icpc -m32

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -ansi-alias -opt-mem-layout-trans=3

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/opt/SmartHeap_10mc/lib -lsmartheap

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by NEC or Intel.

Non-Compliant

Peak Optimization Flags (Continued)

473.astar: `basepeak = yes`

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html`
`http://www.spec.org/cpu2006/flags/NEC-platform-Settings-V1.2-A2040b-RevA.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml`
`http://www.spec.org/cpu2006/flags/NEC-platform-Settings-V1.2-A2040b-RevA.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Sep 19 15:47:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 April 2014.