SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ87PG motherboard (Intel Core i5-4670)

SPECfp®2006 = 65.5

SPECfp_base2006 = 64.0

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2013
Hardware Availability: Jul-2013
Software Availability: Apr-2013



Hardware

CPU Name:	Intel Core i5-4670
CPU Characteristics:	Intel Turbo Boost Technology up to 3.80 GHz
CPU MHz:	3400
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software

Operating System:	Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows; Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows; Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
Auto Parallel:	Yes

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ87PG motherboard (Intel Core i5-4670)

SPECfp2006 = 65.5

SPECfp_base2006 = 64.0

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2013
Hardware Availability: Jul-2013
Software Availability: Apr-2013

L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)
Disk Subsystem:	250 GB Seagate SATA HDD, 7200 RPM
Other Hardware:	None

File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 10.0 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	134	102	128	107	**131**	**104**	134	102	128	107	**131**	**104**
416.gamess	486	40.3	489	40.1	**488**	**40.1**	450	43.5	**450**	**43.5**	450	43.5
433.milc	132	69.8	131	69.9	**132**	**69.8**	132	69.8	131	69.9	**132**	**69.8**
434.zeusmp	**86.4**	**105**	85.8	106	86.8	105	**86.4**	**105**	85.8	106	86.8	105
435.gromacs	**150**	**47.5**	151	47.2	150	47.6	**150**	**47.5**	151	47.2	150	47.6
436.cactusADM	57.7	207	**59.3**	**202**	61.0	196	57.7	207	**59.3**	**202**	61.0	196
437.leslie3d	137	68.5	**137**	**68.5**	137	68.5	137	68.5	**137**	**68.5**	137	68.5
444.namd	281	28.6	**281**	**28.5**	281	28.5	**279**	**28.7**	279	28.7	279	28.7
447.dealII	**191**	**59.9**	191	59.9	191	59.9	**191**	**59.9**	191	59.9	191	59.9
450.soplex	**224**	**37.2**	224	37.3	226	37.0	**224**	**37.2**	224	37.3	226	37.0
453.povray	99.9	53.3	**102**	**52.4**	103	51.7	79.1	67.3	**78.9**	**67.4**	78.8	67.5
454.calculix	**172**	**48.1**	171	48.1	172	48.1	**172**	**48.1**	171	48.1	172	48.1
459.GemsFDTD	196	54.0	195	54.3	**195**	**54.3**	196	54.0	195	54.3	**195**	**54.3**
465.tonto	**232**	**42.4**	232	42.4	233	42.3	216	45.6	219	44.9	**216**	**45.5**
470.lbm	**125**	**110**	125	110	124	111	**125**	**110**	125	110	124	111
481.wrf	127	88.1	**127**	**88.0**	128	87.5	127	88.1	**127**	**88.0**	128	87.5
482.sphinx3	280	69.7	280	69.6	**280**	**69.7**	280	69.7	280	69.6	**280**	**69.7**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 13.1 was set up to
generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r)
Parallel Studio XE 2013 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC13.1/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on Clt7C05070FB316 Fri Sep 27 20:31:25 2013

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
      http://www.spec.org/cpu2006/Docs/config.html#sysinfo

    Trying 'systeminfo'
    OS Name       : Microsoft Windows 7 Enterprise
    OS Version    : 6.1.7601 Service Pack 1 Build 7601
    System Manufacturer: INTEL_
    System Model  : DQ87PG__
    Processor(s)  : 1 Processor(s) Installed.
         [01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~3401 Mhz
    BIOS Version  : Intel(R) Corp. PGQ8710H.86A.0036.2013.0702.1908, 7/2/2013
    Total Physical Memory: 3,749 MB

    Trying 'wmic cpu get /value'
    DeviceID      : CPU0
    L2CacheSize   : 1024
    L3CacheSize   : 6144
    MaxClockSpeed : 3401
    Name          : Intel(R) Core(TM) i5-4670 CPU @ 3.40GHz
    NumberOfCores : 4
    NumberOfLogicalProcessors: 4

    (End of data from sysinfo program)
  BIOS: SATA mode set to RAID
  Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066
  Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027
```

Component Notes

```
  Tested systems can be used with Shin-G ATX case,
  PC Power and Cooling 1200W power supply
  Micron MT8JTF25664AZ-1G6 Series Memory DIMMs
```

General Notes

```
  OMP_NUM_THREADS set to number of processors cores
  KMP_AFFINITY set to granularity=fine,scatter
  Binaries compiled on a system with 1x Intel Core i7-860 CPU
  + 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
     icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
     icl -Qvc10
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000

C++ benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

Benchmarks using both Fortran and C:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Fortran benchmarks:
```
ifort
```

Benchmarks using both Fortran and C:
```
icl -Qvc10 -Qstd=c99 ifort
```

Peak Portability Flags

```
Same as Base Portability Flags
```

Peak Optimization Flags

C benchmarks:

433.milc: `basepeak = yes`

470.lbm: `basepeak = yes`

482.sphinx3: `basepeak = yes`

C++ benchmarks:

444.namd: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000`
`shlW64M.lib -link /FORCE:MULTIPLE`

447.dealII: `basepeak = yes`

450.soplex: `basepeak = yes`

453.povray: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32`
`/F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias`
`-Qscalar-rep- /F1000000000`

Continued on next page

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 9 10:56:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.