



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sugon

**SPECint®2006 = 50.6**

Sugon I620-G20 (Intel Xeon E5-2650 v3)

**SPECint\_base2006 = 48.3**

CPU2006 license: 9046


Test date: Oct-2014

Test sponsor: Sugon

Hardware Availability: Sep-2014

Tested by: Sugon

Software Availability: Sep-2013



### Hardware

CPU Name: Intel Xeon E5-2650 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.00 GHz  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 25 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)  
 Disk Subsystem: 1 x 2.0 TB SATA 7200 RPM  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 2.6.32-358.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sugon

SPECint2006 = **50.6**

Sugon I620-G20 (Intel Xeon E5-2650 v3)

SPECint\_base2006 = **48.3**

CPU2006 license: 9046  
Test sponsor: Sugon  
Tested by: Sugon

Test date: Oct-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2013

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	332	29.4	<b><u>332</u></b>	<b><u>29.4</u></b>	333	29.3	282	34.6	281	34.8	<b><u>281</u></b>	<b><u>34.7</u></b>
401.bzip2	515	18.7	<b><u>515</u></b>	<b><u>18.8</u></b>	513	18.8	510	18.9	510	18.9	<b><u>510</u></b>	<b><u>18.9</u></b>
403.gcc	<b><u>287</u></b>	<b><u>28.0</u></b>	287	28.1	287	28.0	282	28.5	<b><u>282</u></b>	<b><u>28.6</u></b>	281	28.6
429.mcf	<b><u>177</u></b>	<b><u>51.6</u></b>	177	51.7	179	51.0	179	50.9	<b><u>178</u></b>	<b><u>51.2</u></b>	178	51.3
445.gobmk	490	21.4	489	21.4	<b><u>489</u></b>	<b><u>21.4</u></b>	483	21.7	484	21.7	<b><u>483</u></b>	<b><u>21.7</u></b>
456.hammer	<b><u>181</u></b>	<b><u>51.6</u></b>	181	51.7	181	51.6	<b><u>181</u></b>	<b><u>51.6</u></b>	181	51.7	181	51.6
458.sjeng	479	25.3	<b><u>479</u></b>	<b><u>25.3</u></b>	478	25.3	473	25.6	472	25.6	<b><u>472</u></b>	<b><u>25.6</u></b>
462.libquantum	4.25	4870	<b><u>4.25</u></b>	<b><u>4870</u></b>	4.25	4870	4.25	4870	<b><u>4.25</u></b>	<b><u>4870</u></b>	4.25	4870
464.h264ref	<b><u>527</u></b>	<b><u>42.0</u></b>	528	41.9	526	42.0	<b><u>527</u></b>	<b><u>42.0</u></b>	528	41.9	526	42.0
471.omnetpp	222	28.2	225	27.7	<b><u>225</u></b>	<b><u>27.8</u></b>	<b><u>161</u></b>	<b><u>38.9</u></b>	163	38.4	159	39.2
473.astar	277	25.3	278	25.3	<b><u>277</u></b>	<b><u>25.3</u></b>	277	25.3	278	25.3	<b><u>277</u></b>	<b><u>25.3</u></b>
483.xalancbmk	137	50.5	136	50.6	<b><u>136</u></b>	<b><u>50.6</u></b>	137	50.5	136	50.6	<b><u>136</u></b>	<b><u>50.6</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Configuration:

Enforce POR set to disabled

DDR Speed set to 2133

Early Snoop set to disabled

COD set to disable

Power Technology set to performance

Sysinfo program /home/cpu2006/config/sysinfo.rev6874

\$Rev: 6874 \$ \$Date:: 2013-11-20 #\$ 654bd3fcf53b06faef0efe54ed011998

running on localhost Thu Oct 23 18:50:17 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz

2 "physical id"s (chips)

40 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org/>

Page 2



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sugon

SPECint2006 = 50.6

### Sugon I620-G20 (Intel Xeon E5-2650 v3)

SPECint\_base2006 = 48.3

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

## Platform Notes (Continued)

following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 10
siblings  : 20
physical 0: cores 0 1 2 3 4 8 9 10 11 12
physical 1: cores 0 1 2 3 4 8 9 10 11 12
cache size : 25600 KB
```

From /proc/meminfo

```
MemTotal:      264478484 kB
HugePages_Total:    0
Hugepagesize:    2048 kB
```

/usr/bin/lsb\_release -d

```
Red Hat Enterprise Linux Server release 6.4 (Santiago)
```

From /etc/\*release\* /etc/\*version\*

```
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

uname -a:

```
Linux localhost 2.6.32-358.el6.x86_64 #1 SMP Tue Jan 29 11:47:41 EST 2013
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Oct 23 18:46

SPEC is set to: /home/cpu2006

```
Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/sda3        ext4      1.8T  480G  1.3T  28% /
```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS American Megatrends Inc. 067 08/13/2014

Memory:

```
8x NO DIMM NO DIMM
16x Samsung M393A2G40DB0-CPB 16 GB 2 rank 2133 MHz
```

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,scatter"

LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"

OMP\_NUM\_THREADS = "20"

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sugon**

**SPECint2006 = 50.6**

**Sugon I620-G20 (Intel Xeon E5-2650 v3)**

**SPECint\_base2006 = 48.3**

**CPU2006 license:** 9046

**Test sponsor:** Sugon

**Tested by:** Sugon

**Test date:** Oct-2014

**Hardware Availability:** Sep-2014

**Software Availability:** Sep-2013

## General Notes (Continued)

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
runspec command invoked through numactl i.e.:  
numactl --interleave=all runspec <etc>

Submitted\_by: Tian Yuwan <tianyw@sugon.com>  
Submitted: Tue Nov 4 05:06:08 EST 2014  
Submission: cpu2006-20141104-32750.sub

Submitted\_by: Tian Yuwan <tianyw@sugon.com>  
Submitted: Sun Nov 23 21:26:15 EST 2014  
Submission: cpu2006-20141104-32750.sub

Submitted\_by: Tian Yuwan <tianyw@sugon.com>  
Submitted: Wed Nov 26 05:11:52 EST 2014  
Submission: cpu2006-20141104-32750.sub

Submitted\_by: Tian Yuwan <tianyw@sugon.com>  
Submitted: Thu Nov 27 00:57:34 EST 2014  
Submission: cpu2006-20141104-32750.sub

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.mcf: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
471.omnetpp: -DSPEC\_CPU\_LP64  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 50.6

Sugon I620-G20 (Intel Xeon E5-2650 v3)

SPECint\_base2006 = 48.3

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-Wl,-z,muldefs -L/sh -lsmartheap64

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

400.perlbench: icc -m32

445.gobmk: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

471.omnetpp: icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.mcf: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 50.6

Sugon I620-G20 (Intel Xeon E5-2650 v3)

SPECint\_base2006 = 48.3

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -ansi-alias

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div -prof-use(pass 2) -auto-ilp32  
-opt-prefetch -ansi-alias

403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc  
-opt-malloc-options=3 -auto-ilp32

429.mcf: -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel  
-opt-prefetch -auto-p32

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias

456.hmmcr: basepeak = yes

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-ra-region-strategy=block -ansi-alias  
-Wl,-z,muldefs -L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Sugon

**SPECint2006 = 50.6**

**Sugon I620-G20 (Intel Xeon E5-2650 v3)**

**SPECint\_base2006 = 48.3**

**CPU2006 license:** 9046

**Test sponsor:** Sugon

**Tested by:** Sugon

**Test date:** Oct-2014

**Hardware Availability:** Sep-2014

**Software Availability:** Sep-2013

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-HSW-revA.20141203.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-HSW-revA.20141203.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Wed Dec 3 10:28:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 December 2014.