



# SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp®\_rate2006 = 822**

**SPECfp\_rate\_base2006 = 789**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Apr-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014



**SPECfp\_rate\_base2006 = 789**

**SPECfp\_rate2006 = 822**

## Hardware

CPU Name: Intel Xeon E7-8893 v3  
CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz  
CPU MHz: 3200  
FPU: Integrated  
CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 2,4 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: SUSE Linux Enterprise Server 12 3.12.28-4-default  
Compiler: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;  
Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux  
Auto Parallel: No  
File System: ext4  
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp\_rate2006 = 822**

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate\_base2006 = 789**

CPU2006 license: 55

Test date: Apr-2015

Test sponsor: Dell Inc.

Hardware Availability: Jun-2015

Tested by: Dell Inc.

Software Availability: Oct-2014

L3 Cache: 45 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 512 GB (32 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)  
 Disk Subsystem: 2 x 200 GB SAS6 SSD, RAID0  
 Other Hardware: None

Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32	407	1070	<b>407</b>	<b>1070</b>	406	1070	32	407	1070	<b>407</b>	<b>1070</b>	406	1070
416.gamess	32	924	678	921	681	<b>921</b>	<b>680</b>	32	<b>875</b>	<b>716</b>	879	713	872	719
433.milc	32	289	1020	289	1020	<b>289</b>	<b>1020</b>	32	<b>289</b>	<b>1020</b>	289	1020	289	1020
434.zeusmp	32	362	805	<b>364</b>	<b>801</b>	367	794	32	362	805	<b>364</b>	<b>801</b>	367	794
435.gromacs	32	287	796	290	787	<b>290</b>	<b>788</b>	32	282	811	283	807	<b>283</b>	<b>807</b>
436.cactusADM	32	418	916	401	954	<b>411</b>	<b>931</b>	32	418	916	401	954	<b>411</b>	<b>931</b>
437.leslie3d	32	628	479	613	491	<b>624</b>	<b>482</b>	16	210	718	<b>209</b>	<b>719</b>	209	719
444.namd	32	460	557	<b>459</b>	<b>559</b>	457	561	32	<b>450</b>	<b>570</b>	448	572	452	567
447.dealII	32	345	1060	<b>345</b>	<b>1060</b>	346	1060	32	345	1060	<b>345</b>	<b>1060</b>	346	1060
450.soplex	32	461	579	462	578	<b>462</b>	<b>578</b>	32	461	579	462	578	<b>462</b>	<b>578</b>
453.povray	32	185	921	184	926	<b>185</b>	<b>922</b>	32	164	1040	169	1010	<b>165</b>	<b>1030</b>
454.calculix	32	261	1010	<b>261</b>	<b>1010</b>	261	1010	32	261	1010	<b>261</b>	<b>1010</b>	261	1010
459.GemsFDTD	32	818	415	<b>818</b>	<b>415</b>	818	415	32	818	415	<b>818</b>	<b>415</b>	818	415
465.tonto	32	381	827	<b>383</b>	<b>823</b>	383	822	32	364	864	<b>357</b>	<b>882</b>	354	891
470.lbm	32	586	751	<b>586</b>	<b>751</b>	586	751	32	586	751	<b>586</b>	<b>751</b>	586	751
481.wrf	32	345	1040	<b>343</b>	<b>1040</b>	342	1050	32	345	1040	<b>343</b>	<b>1040</b>	342	1050
482.sphinx3	32	<b>622</b>	<b>1000</b>	623	1000	619	1010	32	609	1020	620	1010	<b>610</b>	<b>1020</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:

Virtualization Technology disabled

System Profile set to Custom

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp\_rate2006 = 822**

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test date:** Apr-2015

**Test sponsor:** Dell Inc.

**Hardware Availability:** Jun-2015

**Tested by:** Dell Inc.

**Software Availability:** Oct-2014

## Platform Notes (Continued)

CPU Power Management set to Maximum Performance

Memory Frequency set to Maximum Performance

Turbo Boost enabled

Energy Efficient Turbo disabled

C1E disabled

C States disabled

Collaborative CPU Performance Control disabled

Memory Patrol Scrub disabled

Memory Refresh Rate set to 1x

Uncore Frequency set to Maximum

Energy Efficient Policy set to Performance

Monitor/MWait enabled

Sysinfo program

/root/Desktop/Performance/ic15.0\_Aug29\_2014/config/sysinfo.rev6914

\$Rev: 6914 \$ \$Date::: 2014-06-25 #\\$ e3fbb8667b5a285932ceab81e28219e1

running on linux-luzu Sat Apr 11 04:19:59 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-8893 v3 @ 3.20GHz
        4 "physical id"s (chips)
        32 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
        cpu cores : 4
        siblings : 8
        physical 0: cores 1 5 16 20
        physical 1: cores 1 5 16 20
        physical 2: cores 1 5 16 20
        physical 3: cores 1 5 16 20
cache size : 46080 KB
```

```
From /proc/meminfo
MemTotal:      529204236 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 12
```

```
From /etc/*release* /etc/*version*
SuSE-release:
        SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 0
# This file is deprecated and will be removed in a future service pack or
release.
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp\_rate2006 = 822**

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test date:** Apr-2015

**Test sponsor:** Dell Inc.

**Hardware Availability:** Jun-2015

**Tested by:** Dell Inc.

**Software Availability:** Oct-2014

## Platform Notes (Continued)

```
# Please check /etc/os-release for details about this release.
os-release:
  NAME="SLES"
  VERSION="12"
  VERSION_ID="12"
  PRETTY_NAME="SUSE Linux Enterprise Server 12"
  ID="sles"
  ANSI_COLOR="0;32"
  CPE_NAME="cpe:/o:suse:sles:12"

uname -a:
Linux linux-luzu 3.12.28-4-default #1 SMP Thu Sep 25 17:02:34 UTC 2014
(9879bd4) x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Apr 10 19:19 last=5

SPEC is set to: /root/Desktop/Performance/ic15.0_Aug29_2014
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdb3        ext4  325G  21G  304G   7% /home
Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program
reads system data which is "intended to allow hardware to be accurately
determined", but the intent may not be met, as there are frequent changes to
hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Dell Inc. 1.0.1 [MRC_096] 03/27/2015
Memory:
 32x 00AD00B300AD Not Specified 16 GB 2 rank 2133 MHz, configured at 1600 MHz
 64x Not Specified Not Specified

(End of data from sysinfo program)
```

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/root/Desktop/Performance/ic15.0\_Aug29\_2014/lib32:/root/Desktop/Performance/ic15.0\_Aug29\_2014/lib64:/root/Desktop/Performance/ic15.0\_Aug29\_2014/sh"

Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB  
memory using RedHat EL 7.0  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/transparent\_hugepage/enabled  
Filesystem page cache cleared with:  
echo 1> /proc/sys/vm/drop\_caches  
runspec command invoked through numactl i.e.:  
numactl --interleave=all runspec <etc>



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate2006 = 822**

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Oct-2014

## Base Compiler Invocation

C benchmarks:

  icc -m64

C++ benchmarks:

  icpc -m64

Fortran benchmarks:

  ifort -m64

Benchmarks using both Fortran and C:

  icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
  433.milc: -DSPEC\_CPU\_LP64  
  434.zeusmp: -DSPEC\_CPU\_LP64  
  435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
  437.leslie3d: -DSPEC\_CPU\_LP64  
  444.namd: -DSPEC\_CPU\_LP64  
  447.dealII: -DSPEC\_CPU\_LP64  
  450.soplex: -DSPEC\_CPU\_LP64  
  453.povray: -DSPEC\_CPU\_LP64  
  454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
  465.tonto: -DSPEC\_CPU\_LP64  
  470.lbm: -DSPEC\_CPU\_LP64  
  481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

  -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
  -ansi-alias -opt-mem-layout-trans=3

C++ benchmarks:

  -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
  -ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:

  -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate2006 = 822**

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Oct-2014

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-ilp32  
-ansi-alias -opt-mem-layout-trans=3
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2)  
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2)  
-auto-ilp32
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3  
-unroll2
```

C++ benchmarks:

```
444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2)  
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate2006 = 822**

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Oct-2014

## Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2)  
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -unroll14  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll14  
-auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2)  
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revE.20150421.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revE.20150421.xml>



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8893 v3, 3.20 GHz)

**SPECfp\_rate2006 = 822**

**SPECfp\_rate\_base2006 = 789**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Oct-2014

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue May 5 15:15:43 2015 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 5 May 2015.