SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS Z170MPLUS motherboard (Intel Core i5-6600K)

SPECfp®2006 = 90.8

SPECfp_base2006 = 88.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Oct-2015
Hardware Availability: Sep-2015
Software Availability: Aug-2015



Hardware

CPU Name:	Intel Core i5-6600K
CPU Characteristics:	Intel Turbo Boost Technology up to 3.90 GHz
CPU MHz:	3500
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software

Operating System:	Microsoft Windows 10 Pro 10.0.10240 N/A Build 10240
Compiler:	C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
Auto Parallel:	Yes

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS Z170MPLUS motherboard (Intel Core i5-6600K)

SPECfp2006 = 90.8

SPECfp_base2006 = 88.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Oct-2015
Hardware Availability: Sep-2015
Software Availability: Aug-2015

L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	8 GB (2 x 4 GB 2Rx4 PC4-2133P-U)
Disk Subsystem:	1 TB Seagate SATA HDD, 7200 RPM
Other Hardware:	None

File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 11.0 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	100	136	**100**	**136**	99.7	136	100	136	**100**	**136**	99.7	136
416.gamess	414	47.3	413	47.4	**413**	**47.4**	**371**	**52.7**	371	52.8	372	52.7
433.milc	99.9	91.9	**100**	**91.4**	100	91.4	99.9	91.9	**100**	**91.4**	100	91.4
434.zeusmp	47.9	190	**47.9**	**190**	47.9	190	47.9	190	**47.9**	**190**	47.9	190
435.gromacs	**105**	**68.3**	104	68.4	105	68.3	**105**	**68.3**	104	68.4	105	68.3
436.cactusADM	**35.3**	**339**	35.5	337	35.2	340	**35.3**	**339**	35.5	337	35.2	340
437.leslie3d	102	92.3	102	92.1	**102**	**92.2**	102	92.3	102	92.1	**102**	**92.2**
444.namd	213	37.6	**213**	**37.6**	213	37.6	209	38.3	209	38.3	**209**	**38.3**
447.dealII	155	73.9	154	74.1	**155**	**74.0**	155	73.9	154	74.1	**155**	**74.0**
450.soplex	**167**	**49.9**	167	50.1	168	49.8	**167**	**49.9**	167	50.1	168	49.8
453.povray	75.5	70.5	**75.5**	**70.5**	75.6	70.4	63.9	83.3	64.1	83.0	**64.0**	**83.1**
454.calculix	**110**	**75.2**	110	75.3	110	75.1	**110**	**75.2**	110	75.3	110	75.1
459.GemsFDTD	146	72.8	145	73.0	**146**	**72.9**	146	72.8	145	73.0	**146**	**72.9**
465.tonto	178	55.4	**176**	**55.9**	176	56.0	156	63.2	154	63.9	**154**	**63.8**
470.lbm	84.0	164	**84.1**	**163**	84.2	163	84.0	164	**84.1**	**163**	84.2	163
481.wrf	**93.7**	**119**	128	87.5	93.3	120	**93.7**	**119**	128	87.5	93.3	120
482.sphinx3	213	91.5	214	91.1	**214**	**91.2**	213	91.5	214	91.1	**214**	**91.2**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on DESKTOP-C8BQEO8 Wed Oct  7 20:12:05 2015

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
      http://www.spec.org/cpu2006/Docs/config.html#sysinfo

    Trying 'systeminfo'
    OS Name        : Microsoft Windows 10 Pro
    OS Version     : 10.0.10240 N/A Build 10240
    System Manufacturer: System manufacturer
    System Model   : System Product Name
    Processor(s)   : 1 Processor(s) Installed.
         [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3501 Mhz
    BIOS Version   : American Megatrends Inc. 0408, 8/28/2015
    Total Physical Memory: 8,084 MB

    Trying 'wmic cpu get /value'
    DeviceID       : CPU0
    L2CacheSize    : 1024
    L3CacheSize    : 6144
    MaxClockSpeed : 3501
    Name           : Intel(R) Core(TM) i5-6600K CPU @ 3.50GHz
    NumberOfCores : 4
    NumberOfLogicalProcessors: 4

    (End of data from sysinfo program)
```

Component Notes

```
    Tested systems can be used with Shin-G ATX case,
    PC Power and Cooling 1200W power supply
```

General Notes

```
  450.soplex (base): "getline_test" src.alt was used.

  447.dealII (base): "max_prototype" src.alt was used.
  447.dealII (base): "cxx11_make_pair" src.alt was used.

  450.soplex (base): "getline_test" src.alt was used.

  447.dealII (base): "max_prototype" src.alt was used.
  447.dealII (base): "cxx11_make_pair" src.alt was used.

   OMP_NUM_THREADS set to number of processors cores
   KMP_AFFINITY set to granularity=fine,scatter
   Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
   + 64GB memory using Windows 8.1 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
453.povray: -DSPEC_CPU_P64
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

C++ benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

Peak Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

453.povray: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Nov 17 19:18:09 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 November 2015.