SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei 5288 V3 (Intel Xeon E5-2683 v4)

SPECint®_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Aug-2015

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483.xalancbmk	

Non-Compliant

Hardware

CPU Name:	el Xeon E5-2683 v4
CPU Characteristics:	Intel Turbo Boost Technology up to 3.00 GHz
CPU MHz:	2100
FPU:	Integrated
CPU(s) enabled:	32 cores, 2 chips, 16 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	40 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2400T-R)
Disk Subsystem:	1 x 500GB SATA, 10000 RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 7.0 (Maipo) 3.10.0-123.el7.x86_64
Compiler:	C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux
Auto Parallel:	No
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.2

SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei 5288 V3 (Intel Xeon E5-2683 v4)

SPECint_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Aug-2015

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
401.bzip2	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
403.gcc	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
429.mcf	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
445.gobmk	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
456.hmmer	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
458.sjeng	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
462.libquantum	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
464.h264ref	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
471.omnetpp	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
473.astar	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
483.xalancbmk	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Platform Notes

```
BIOS Configuration:
Set Power Efficiency Mode to Performance
Set Snoop Mode to COD mode
Set Patrol Scrub to Disable
Sysinfo program /spec16/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Wed Mar 23 05:45:02 2016

This section contains SUT (System Under Test) info as seen by
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Platform Notes (Continued)

```
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2683 v4 @ 2.10GHz
      2 "physical id"s (chips)
      64 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 8
      siblings  : 16
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
   cache size : 20480 KB

From /proc/meminfo
   MemTotal:       263565104 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.0 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.0"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:
   Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
   EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Mar 23 05:40

SPEC is set to: /spec16
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda2      xfs   449G  9.1G  440G   3% /
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Platform Notes (Continued)

```
 Additional information from dmidecode:

    Warning: Use caution when you interpret this section. The 'dmidecode' program
    reads system data which is "intended to allow hardware to be accurately
    determined", but the intent may not be met, as there are frequent changes to
    hardware, firmware, and the "DMTF SMBIOS" standard.

   BIOS Insyde Corp. 3.09 02/17/2016
   Memory:
    8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz
    8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz

 (End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/spec16/libs/32:/spec16/libs/64:/spec16/sh"

 Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB
 memory using RedHat EL 7.1
 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
 Filesystem page cache cleared with:
 echo 1> /proc/sys/vm/drop_caches
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
```

Base Compiler Invocation

C benchmarks:

```
icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin
```

C++ benchmarks:

```
icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin
```

Non-Compliant

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Base Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LIN IA32
401.bzip2: -D_FILE_OFFSET_BITS=64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64
458.sjeng: -D_FILE_OFFSET_BITS=64
462.libquantum: -D_FILE_OFFSET_BITS=64 DSPEC CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSE _BITS=64 -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -n -prec-div -opt-prefetch
-opt-mem-layout-t ns=3

C++ benchmarks:
-xCORE-AVX2 -ip -O3 -n -prec-div -opt-prefetch
-opt-mem-layout-t ns=3 -Wl,-z,muldefs -L/sh -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

400.perlbench: icc -m64

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Peak Compiler Invocation (Continued)

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:
icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
458.sjeng: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch
-auto-ilp32 -ansi-alias

403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div

Continued on next page

Non-Compliant

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen:thr ad fe(pass 1)
-prof-use(pass 2) -par-num-threads=1(pa 1) -ansi-alias
-opt-mem-layout-trans=3

456.hmmer: -xCORE-AVX2 -ipo -O3 -no- -div unroll2 -auto-ilp32

458.sjeng: -xCORE-AVX2(pass 2) -prof gen:thr adsafe(pass 1)
-ipo(pass 2) -O3(pas 2) -no- rec-di (pass 2)
-par-num-threa s=1(pass 1) of use(pass 2) -unroll4
-auto-ilp32

462.libquantum: basepeak = ye

464.h264ref: -xCORE-AVX2(pass -prof gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) o-prec-div(pass 2)
-par-num-threa s=1(pass 1) -prof-use(pass 2) -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -xCO AVX2(pa s 2) -prof-gen:threadsafe(pass 1)
-ipo(pas 2) -O3(pass 2) -no-prec-div(pass 2)
-pe num- reads=1(pass 1) -prof-use(pass 2) -ansi-alias
-opt a-region-strategy=block -Wl,-z,muldefs
-L/sh lsmartheap

47 astar: b eak = yes

b basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Non-Compliant

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml

Non-Compliant

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 20:04:29 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 April 2016.