



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp<sup>®</sup>\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Sep-2015

Software Availability: Aug-2015



### Hardware

CPU Name: Intel Pentium G4500  
 CPU Characteristics:  
 CPU MHz: 3500  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Microsoft Windows 7 Professional 6.1.7601 Service Pack 1 Build 7601  
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;  
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013  
 Auto Parallel: No

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13

Test date: Mar-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

L3 Cache: 3 MB I+D on chip per chip  
Other Cache: None  
Memory: 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U)  
Disk Subsystem: 1 TB Seagate Barracuda HDD, 7200 RPM  
Other Hardware: None

File System: NTFS  
System State: Default  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	200	136	199	137	<b>200</b>	<b>136</b>	2	199	137	199	137	<b>199</b>	<b>137</b>
416.gamess	2	454	86.4	453	86.4	<b>453</b>	<b>86.4</b>	2	454	86.4	453	86.4	<b>453</b>	<b>86.4</b>
433.milc	2	151	122	<b>151</b>	<b>121</b>	151	121	2	151	122	<b>151</b>	<b>121</b>	151	121
434.zeusmp	2	148	123	<b>148</b>	<b>123</b>	148	123	2	148	123	<b>148</b>	<b>123</b>	148	123
435.gromacs	2	141	101	142	101	<b>141</b>	<b>101</b>	2	141	101	142	101	<b>141</b>	<b>101</b>
436.cactusADM	2	157	152	158	151	<b>157</b>	<b>152</b>	2	157	152	158	151	<b>157</b>	<b>152</b>
437.leslie3d	2	223	84.2	<b>223</b>	<b>84.4</b>	222	84.6	2	222	84.8	<b>221</b>	<b>85.0</b>	221	85.2
444.namd	2	<b>295</b>	<b>54.4</b>	297	54.0	295	54.4	2	286	56.0	286	56.2	<b>286</b>	<b>56.2</b>
447.dealII	2	179	128	<b>180</b>	<b>127</b>	180	127	2	179	128	<b>180</b>	<b>127</b>	180	127
450.soplex	2	<b>240</b>	<b>69.6</b>	238	70.0	240	69.4	2	244	68.4	245	68.2	<b>244</b>	<b>68.2</b>
453.povray	2	91.0	117	89.9	118	<b>89.9</b>	<b>118</b>	2	79.4	134	79.8	133	<b>79.6</b>	<b>134</b>
454.calculix	2	<b>161</b>	<b>103</b>	160	103	161	103	2	<b>161</b>	<b>103</b>	160	103	161	103
459.GemsFDTD	2	340	62.4	339	62.6	<b>340</b>	<b>62.6</b>	2	300	70.8	300	70.8	<b>300</b>	<b>70.8</b>
465.tonto	2	242	81.4	242	81.2	<b>242</b>	<b>81.4</b>	2	226	87.2	226	87.0	<b>226</b>	<b>87.0</b>
470.lbm	2	<b>159</b>	<b>173</b>	159	173	159	173	2	<b>158</b>	<b>174</b>	158	174	158	174
481.wrf	2	<b>181</b>	<b>124</b>	178	126	181	123	2	<b>181</b>	<b>124</b>	178	126	181	123
482.sphinx3	2	394	98.8	<b>396</b>	<b>98.4</b>	396	98.4	2	394	98.8	<b>396</b>	<b>98.4</b>	396	98.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:  
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

## Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on CltF832E4885654 Tue Mar 8 12:54:42 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Mar-2016  
Hardware Availability: Sep-2015  
Software Availability: Aug-2015

## Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 7 Professional
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3500 Mhz
BIOS Version  : American Megatrends Inc. 0704, 1/12/2016
Total Physical Memory: 8,070 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 512
L3CacheSize   : 3072
MaxClockSpeed : 3500
Name          : Intel(R) Pentium(R) CPU G4500 @ 3.50GHz
NumberOfCores : 2
NumberOfLogicalProcessors: 2
```

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

```
450.soplex (peak): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.
```

Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU  
+ 64GB memory using Windows 8.1 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:  
icl -Qvc12 -Qstd=c99

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Mar-2016  
Hardware Availability: Sep-2015  
Software Availability: Aug-2015

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icl -Qvc12  
  
Fortran benchmarks:  
ifort  
  
Benchmarks using both Fortran and C:  
icl -Qvc12 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64  
416.gamess: -DSPEC\_CPU\_P64  
433.milc: -DSPEC\_CPU\_P64  
434.zeusmp: -DSPEC\_CPU\_P64  
435.gromacs: -DSPEC\_CPU\_P64  
436.cactusADM: -DSPEC\_CPU\_P64 /names:lowercase /assume:underscore  
437.leslie3d: -DSPEC\_CPU\_P64  
444.namd: -DSPEC\_CPU\_P64 /TP  
447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
-DSPEC\_CPU\_BOOST\_CONFIG\_MSC\_VER -DSPEC\_NEED\_ALGORITHM  
450.soplex: -DSPEC\_CPU\_P64 -DSPEC\_GETLINE\_TEST  
453.povray: -DSPEC\_CPU\_P64  
454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER /names:lowercase  
459.GemsFDTD: -DSPEC\_CPU\_P64  
465.tonto: -DSPEC\_CPU\_P64  
470.lbm: -DSPEC\_CPU\_P64  
481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:  
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE  
  
C++ benchmarks:  
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE  
  
Fortran benchmarks:  
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F1000000000 -link /FORCE:MULTIPLE

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Mar-2016  
Hardware Availability: Sep-2015  
Software Availability: Aug-2015

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc12
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc12 -Qstd=c99 ifort
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: -QxSSE4.2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3
-Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE
```

```
447.dealIII: basepeak = yes
```

```
450.soplex: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp\_rate2006 = 104

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp\_rate\_base2006 = 102

CPU2006 license: 13

Test date: Mar-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

## Peak Optimization Flags (Continued)

```
453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
410.bwaves: -QxSSE4.2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3
-Qprec-div- -Qansi-alias -Qopt-prefetch /F1000000000
-link /FORCE:MULTIPLE
```

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: Same as 410.bwaves

459.GemsFDTD: Same as 410.bwaves

```
465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
-link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**  
(Test Sponsor: Intel Corporation)

**SPECfp\_rate2006 = 104**

**ASUS Q170M-C motherboard (Intel Pentium G4500)**

**SPECfp\_rate\_base2006 = 102**

**CPU2006 license:** 13  
**Test sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test date:** Mar-2016  
**Hardware Availability:** Sep-2015  
**Software Availability:** Aug-2015

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Jul 12 11:02:24 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 12 July 2016.