# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp®2006 = 70.6

SPECfp_base2006 = 69.6

**CPU2006 license:** 13
**Test sponsor:** Intel Corporation
**Tested by:** Intel Corporation

**Test date:** Mar-2016
**Hardware Availability:** Sep-2015
**Software Availability:** Aug-2015




## Hardware

| | |
|---|---|
| CPU Name: | Intel Pentium G4500 |
| CPU Characteristics: | |
| CPU MHz: | 3500 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | Microsoft Windows 7 Professional 6.1.7601 Service Pack 1 Build 7601 |
| Compiler: | C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013 |
| Auto Parallel: | Yes |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS Q170M-C motherboard (Intel Pentium G4500)

SPECfp2006 = 70.6

SPECfp_base2006 = 69.6

**CPU2006 license:** 13
**Test sponsor:** Intel Corporation
**Tested by:** Intel Corporation

**Test date:** Mar-2016
**Hardware Availability:** Sep-2015
**Software Availability:** Aug-2015

| | |
|---|---|
| L3 Cache: | 3 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U) |
| Disk Subsystem: | 1 TB Seagate Barracuda HDD, 7200 RPM |
| Other Hardware: | None |

| | |
|---|---|
| File System: | NTFS |
| System State: | Default |
| Base Pointers: | 32/64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | SmartHeap Library Version 11.0 from http://www.microquill.com/ |

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 102 | 134 | 100 | 136 | **100** | **136** | 102 | 134 | 100 | 136 | **100** | **136** |
| 416.gamess | 455 | 43.1 | **455** | **43.0** | 455 | 43.0 | 443 | 44.2 | **443** | **44.2** | 443 | 44.2 |
| 433.milc | 113 | 81.1 | **113** | **81.1** | 113 | 81.1 | 113 | 81.1 | **113** | **81.1** | 113 | 81.1 |
| 434.zeusmp | **82.3** | **111** | 82.2 | 111 | 82.3 | 111 | **82.3** | **111** | 82.2 | 111 | 82.3 | 111 |
| 435.gromacs | 131 | 54.6 | **131** | **54.7** | 130 | 54.8 | 131 | 54.6 | **131** | **54.7** | 130 | 54.8 |
| 436.cactusADM | 82.0 | 146 | 82.1 | 146 | **82.0** | **146** | 82.0 | 146 | 82.1 | 146 | **82.0** | **146** |
| 437.leslie3d | 129 | 72.7 | 129 | 72.9 | **129** | **72.8** | 129 | 72.7 | 129 | 72.9 | **129** | **72.8** |
| 444.namd | **294** | **27.3** | 294 | 27.3 | 293 | 27.3 | 286 | 28.0 | 286 | 28.1 | **286** | **28.1** |
| 447.dealII | **167** | **68.6** | 167 | 68.6 | 166 | 68.8 | **167** | **68.6** | 167 | 68.6 | 166 | 68.8 |
| 450.soplex | 190 | 44.0 | **190** | **44.0** | 190 | 44.0 | 190 | 44.0 | **190** | **44.0** | 190 | 44.0 |
| 453.povray | **89.8** | **59.2** | 89.7 | 59.3 | 90.2 | 59.0 | 78.8 | 67.5 | 78.3 | 67.9 | **78.3** | **67.9** |
| 454.calculix | **154** | **53.6** | 154 | 53.6 | 154 | 53.6 | **154** | **53.6** | 154 | 53.6 | 154 | 53.6 |
| 459.GemsFDTD | 175 | 60.5 | **175** | **60.5** | 175 | 60.5 | 175 | 60.5 | **175** | **60.5** | 175 | 60.5 |
| 465.tonto | 223 | 44.2 | 223 | 44.2 | **223** | **44.2** | 210 | 46.9 | **210** | **46.8** | 210 | 46.8 |
| 470.lbm | 81.0 | 170 | **81.0** | **170** | 81.0 | 170 | 81.0 | 170 | **81.0** | **170** | 81.0 | 170 |
| 481.wrf | 123 | 90.6 | 123 | 90.7 | **123** | **90.7** | 123 | 90.6 | 123 | 90.7 | **123** | **90.7** |
| 482.sphinx3 | **301** | **64.7** | 302 | 64.5 | 301 | 64.7 | **301** | **64.7** | 302 | 64.5 | 301 | 64.7 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

## Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on CltF832E4885654 Tue Mar  8 02:35:28 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

## Platform Notes (Continued)

```
      http://www.spec.org/cpu2006/Docs/config.html#sysinfo

    Trying 'systeminfo'
    OS Name        : Microsoft Windows 7 Professional
    OS Version     : 6.1.7601 Service Pack 1 Build 7601
    System Manufacturer: System manufacturer
    System Model   : System Product Name
    Processor(s)   : 1 Processor(s) Installed.
         [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3500 Mhz
    BIOS Version   : American Megatrends Inc. 0704, 1/12/2016
    Total Physical Memory: 8,070 MB

    Trying 'wmic cpu get /value'
    DeviceID       : CPU0
    L2CacheSize    : 512
    L3CacheSize    : 3072
    MaxClockSpeed  : 3500
    Name           : Intel(R) Pentium(R) CPU G4500 @ 3.50GHz
    NumberOfCores  : 2
    NumberOfLogicalProcessors: 2

    (End of data from sysinfo program)
```

## Component Notes

```
    Tested systems can be used with Shin-G ATX case,
    PC Power and Cooling 1200W power supply
```

## General Notes

```
  450.soplex (base): "getline_test" src.alt was used.

  447.dealII (base): "max_prototype" src.alt was used.
  447.dealII (base): "cxx11_make_pair" src.alt was used.

  450.soplex (base): "getline_test" src.alt was used.

  447.dealII (base): "max_prototype" src.alt was used.
  447.dealII (base): "cxx11_make_pair" src.alt was used.

   OMP_NUM_THREADS set to number of processors cores
   KMP_AFFINITY set to granularity=fine,scatter
   Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
   + 64GB memory using Windows 8.1 Enterprise 64-bit
```

## Base Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
453.povray: -DSPEC_CPU_P64
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

## Base Optimization Flags

C benchmarks:
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch /F1000000000

C++ benchmarks:
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch -Qcxx-features /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch /F1000000000

Continued on next page

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

## Peak Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

Continued on next page

## Peak Optimization Flags (Continued)

453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Jul 12 11:02:39 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 July 2016.