



SPEC[®] CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp[®]2006 = 70.6

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = 69.0

CPU2006 license: 13


Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015



Hardware

CPU Name: Intel Core i3-6100T
 CPU Characteristics:
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Microsoft Windows 7 Professional 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: Yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = **70.6**

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = **69.0**

CPU2006 license: 13

Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

L3 Cache: 3 MB I+D on chip per chip
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U)
Disk Subsystem: 1 TB Seagate Barracuda HDD, 7200 RPM
Other Hardware: None

File System: NTFS
System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	102	134	103	133	103	133	102	134	103	133	103	133
416.gamess	520	37.6	520	37.7	521	37.6	475	41.3	474	41.3	475	41.2
433.milc	115	80.0	115	80.0	115	79.9	115	80.0	115	80.0	115	79.9
434.zeusmp	76.2	119	76.3	119	76.1	120	76.2	119	76.3	119	76.1	120
435.gromacs	149	48.0	148	48.1	148	48.2	149	48.0	148	48.1	148	48.2
436.cactusADM	69.8	171	69.6	172	69.8	171	69.8	171	69.6	172	69.8	171
437.leslie3d	137	68.8	137	68.5	137	68.7	137	68.8	137	68.5	137	68.7
444.namd	264	30.4	264	30.4	264	30.4	259	31.0	259	31.0	259	31.0
447.dealII	179	63.9	180	63.7	179	63.8	179	63.9	180	63.7	179	63.8
450.soplex	204	40.8	205	40.8	205	40.8	204	40.8	205	40.8	205	40.8
453.povray	96.6	55.1	96.5	55.1	96.6	55.1	81.2	65.5	81.1	65.6	80.7	65.9
454.calculix	134	61.6	134	61.6	134	61.7	134	61.6	134	61.6	134	61.7
459.GemsFDTD	175	60.8	175	60.8	175	60.7	175	60.8	175	60.8	175	60.7
465.tonto	217	45.3	216	45.5	216	45.5	195	50.5	196	50.3	195	50.4
470.lbm	82.1	167	82.1	167	82.1	167	82.1	167	82.1	167	82.1	167
481.wrf	121	92.1	121	92.5	121	92.7	121	92.1	121	92.5	121	92.7
482.sphinx3	336	57.9	335	58.2	334	58.3	336	57.9	335	58.2	334	58.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on CltF832E48859C5 Tue Apr 26 04:09:31 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 70.6

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = 69.0

CPU2006 license: 13

Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 7 Professional
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)   : 1 Processor(s) Installed.
                [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3201 Mhz
BIOS Version   : American Megatrends Inc. 0704, 1/12/2016
Total Physical Memory: 8,070 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 512
L3CacheSize   : 3072
MaxClockSpeed : 3201
Name          : Intel(R) Core(TM) i3-6100T CPU @ 3.20GHz
NumberOfCores : 2
NumberOfLogicalProcessors: 4
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

```
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit
```



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 70.6

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = 69.0

CPU2006 license: 13

Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
 450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
 453.povray: -DSPEC_CPU_P64
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 70.6

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = 69.0

CPU2006 license: 13

Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

Peak Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 70.6

ASUS Q170M-C motherboard (Intel Core i3-6100T)

SPECfp_base2006 = 69.0

CPU2006 license: 13

Test date: Apr-2016

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

Peak Optimization Flags (Continued)

```
453.povray: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000
            shlW64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

410.bwaves: basepeak = yes

```
416.gamess: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
            -Qscalar-rep- /F1000000000
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-alloc
            /F1000000000
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Jul 12 11:02:36 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 July 2016.