SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A10-8750 with Radeon R7 Graphics)

SPECfp®2006 = 36.1

SPECfp_base2006 = 34.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Aug-2016
Hardware Availability: Dec-2015
Software Availability: Aug-2015



Hardware

CPU Name:	AMD A10-8750
CPU Characteristics:	AMD Turbo CORE technology up to 4.00 GHz
CPU MHz:	3600
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	192 KB I on chip per chip, 96 KB I shared / 2 cores; 16 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip, 2 MB shared / 2 cores

Continued on next page

Software

Operating System:	Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
Auto Parallel:	Yes

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A10-8750 with Radeon R7 Graphics)

SPECfp2006 = 36.1

SPECfp_base2006 = 34.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Aug-2016
Hardware Availability: Dec-2015
Software Availability: Aug-2015

L3 Cache:	None
Other Cache:	None
Memory:	8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
Disk Subsystem:	Seagate Barracuda 250 GB SATA, 7200 RPM
Other Hardware:	None

File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 11.0 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	**198**	**68.5**	193	70.4	202	67.4	**198**	**68.5**	193	70.4	202	67.4
416.gamess	787	24.9	783	25.0	**786**	**24.9**	639	30.6	637	30.8	**638**	**30.7**
433.milc	293	31.3	291	31.6	**293**	**31.4**	293	31.3	291	31.6	**293**	**31.4**
434.zeusmp	**177**	**51.5**	177	51.5	179	51.0	**177**	**51.5**	177	51.5	179	51.0
435.gromacs	289	24.7	**289**	**24.7**	289	24.7	289	24.7	**289**	**24.7**	289	24.7
436.cactusADM	**174**	**68.6**	176	68.1	173	69.0	**174**	**68.6**	176	68.1	173	69.0
437.leslie3d	**262**	**35.9**	261	36.0	264	35.6	**262**	**35.9**	261	36.0	264	35.6
444.namd	409	19.6	**409**	**19.6**	409	19.6	**402**	**19.9**	402	20.0	402	19.9
447.dealII	249	45.9	**248**	**46.1**	248	46.1	249	45.9	**248**	**46.1**	248	46.1
450.soplex	**425**	**19.6**	425	19.6	424	19.7	**425**	**19.6**	425	19.6	424	19.7
453.povray	**174**	**30.6**	174	30.7	176	30.2	153	34.7	**153**	**34.7**	154	34.6
454.calculix	243	34.0	244	33.9	**243**	**33.9**	243	34.0	244	33.9	**243**	**33.9**
459.GemsFDTD	347	30.5	352	30.2	**350**	**30.3**	347	30.5	352	30.2	**350**	**30.3**
465.tonto	**440**	**22.4**	441	22.3	439	22.4	350	28.1	**350**	**28.1**	351	28.1
470.lbm	158	86.9	160	85.9	**159**	**86.5**	158	86.9	160	85.9	**159**	**86.5**
481.wrf	287	38.9	**288**	**38.8**	289	38.7	287	38.9	**288**	**38.8**	289	38.7
482.sphinx3	795	24.5	**795**	**24.5**	797	24.5	795	24.5	**795**	**24.5**	797	24.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on Clt1C872C5DF572 Tue Aug  2 21:08:58 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
    http://www.spec.org/cpu2006/Docs/config.html#sysinfo

  Trying 'systeminfo'
  OS Name        : Microsoft Windows 7 Ultimate
  OS Version     : 6.1.7601 Service Pack 1 Build 7601
  System Manufacturer: System manufacturer
  System Model   : System Product Name
  Processor(s)   : 1 Processor(s) Installed.
       [01]: AMD64 Family 21 Model 56 Stepping 1 AuthenticAMD ~3600 Mhz
  BIOS Version   : American Megatrends Inc. 2502, 12/11/2015
  Total Physical Memory: 7,108 MB

  Trying 'wmic cpu get /value'
  DeviceID       : CPU0
  L2CacheSize    : 25359
  L3CacheSize    : 0
  MaxClockSpeed : 3600
  Name           : AMD A10-8750 Radeon R7, 12 Compute Cores 4C+8G
  NumberOfCores : 2
  NumberOfLogicalProcessors: 4

  (End of data from sysinfo program)
```

Component Notes

```
  Tested systems can be used with Shin-G ATX case,
  PC Power and Cooling 1200W power supply
```

General Notes

```
 450.soplex (base): "getline_test" src.alt was used.

 447.dealII (base): "max_prototype" src.alt was used.
 447.dealII (base): "cxx11_make_pair" src.alt was used.

 450.soplex (base): "getline_test" src.alt was used.

 447.dealII (base): "max_prototype" src.alt was used.
 447.dealII (base): "cxx11_make_pair" src.alt was used.

  OMP_NUM_THREADS set to number of processors cores
  KMP_AFFINITY set to granularity=fine,scatter
  Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
  + 64GB memory using Windows 8.1 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
453.povray: -DSPEC_CPU_P64
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch /F1000000000

C++ benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch -Qcxx-features /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch /F1000000000

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
`/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch /F1000000000`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc12 -Qstd=c99`

C++ benchmarks:
`icl -Qvc12`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icl -Qvc12 -Qstd=c99 ifort`

Peak Portability Flags

`Same as Base Portability Flags`

Peak Optimization Flags

C benchmarks:

433.milc: `basepeak = yes`

470.lbm: `basepeak = yes`

482.sphinx3: `basepeak = yes`

C++ benchmarks:

444.namd: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

447.dealII: `basepeak = yes`

450.soplex: `basepeak = yes`

Continued on next page

Peak Optimization Flags (Continued)

453.povray: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000`

434.zeusmp: `basepeak = yes`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `basepeak = yes`

465.tonto: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc /F1000000000`

Benchmarks using both Fortran and C:

435.gromacs: `basepeak = yes`

436.cactusADM: `basepeak = yes`

454.calculix: `basepeak = yes`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:56 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.