SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu
Fujitsu SPARC M12-2S

SPECint®_rate2006 = 956

SPECint_rate_base2006 = 819

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Feb-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017



Hardware

CPU Name:	SPARC64 XII
CPU Characteristics:	High Speed Mode up to 4.35 GHz
CPU MHz:	4250
FPU:	Integrated
CPU(s) enabled:	12 cores, 1 chip, 12 cores/chip, 8 threads/core
CPU(s) orderable:	1 to 16 BBs; each BB contains 1 or 2 CPU chips; the number of orderable total cores is 2, 3, 4, .. 384
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	32 MB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (16 x 32 GB 2Rx4 PC4-2400T-R)
Disk Subsystem:	1 x 600 GB 10K RPM SAS (for system disk)
Other Hardware:	None

Software

Operating System:	Oracle Solaris 11.3 (with June 2017 SRU)
Compiler:	C/C++: Version 12.6 of Oracle Developer Studio
Auto Parallel:	No
File System:	tmpfs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu
Fujitsu SPARC M12-2S

SPECint_rate2006 = 956

SPECint_rate_base2006 = 819

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Feb-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	96	1347	696	1348	696	**1348**	**696**	96	951	986	950	988	**951**	**987**
401.bzip2	96	**2296**	**403**	2295	404	2296	403	48	1075	431	**1074**	**431**	1072	432
403.gcc	96	1234	626	1200	644	**1211**	**638**	96	1144	676	1132	682	**1137**	**680**
429.mcf	96	**1257**	**697**	1248	701	1257	697	48	399	1100	399	1100	**399**	**1100**
445.gobmk	96	**1253**	**804**	1250	805	1256	802	96	**1106**	**910**	1106	910	1104	912
456.hmmer	96	**906**	**989**	908	986	905	990	48	**411**	**1090**	411	1090	412	1090
458.sjeng	96	1648	705	**1643**	**707**	1643	707	96	1437	808	**1436**	**809**	1436	809
462.libquantum	96	284	7010	**284**	**7010**	283	7020	24	49.5	10000	50.0	9950	**49.5**	**10000**
464.h264ref	96	2037	1040	**2037**	**1040**	2037	1040	48	937	1130	**938**	**1130**	941	1130
471.omnetpp	96	1464	410	1464	410	**1464**	**410**	96	1409	426	1408	426	**1408**	**426**
473.astar	96	**1337**	**504**	1338	504	1337	504	96	1306	516	1304	517	**1305**	**516**
483.xalancbmk	96	775	855	774	856	**774**	**855**	96	724	915	721	919	**723**	**917**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
Processes were assigned to specific processors using 'pbind' commands.
The config file option 'submit' was used, along with a list of
processors in the 'BIND' variable, to generate the pbind commands.
(For details, please see the config file.)
```

Operating System Notes

```
Shell Environments:
   ulimit -s 131072 was used to limit the space consumed by the stack
   (and therefore make more space available to the heap).

   The "Logical Domains Manager" service was turned off using the command "svcadm disable ldmd".

System Tunables:
(/etc/system parameters)
   autoup = 86400
      Causes pages older than the listed number of seconds to be written by fsflush.
   doiflush = 0
     Controls whether file system metadata syncs will be executed during fsflush invocations.
   dopageflush = 0
      Controls whether memory is examined for modified pages during fsflush invocations.
   zfs:zfs_arc_max=1073741824
      Determines the maximum size of the ZFS Adaptive Replacement Cache (ARC).
```

Platform Notes

```
Firmware Settings:
(XSCF operations)
   Set High Speed Mode via XSCF command "sethsmode -s on".

 Sysinfo program /export/cpu2006/config/sysinfo
 Revision 6993 of 2015-11-06 (c9426fd40261140bb4c02f7d35768596)
 running on H2S-253-D0 Tue Feb 28 12:28:01 2017

 This section contains SUT (System Under Test) info as seen by
 some common utilities.  To remove or add to this section, see:
   http://www.spec.org/cpu2006/Docs/config.html#sysinfo

 From /usr/sbin/psrinfo
    SPARC64-XII (chipid 0, clock 4250 MHz)
    1 chips
    96 threads
    4250 MHz

 From kstat:       12 cores

 From prtconf: 521728 Megabytes

 /etc/release:
      Oracle Solaris 11.3 SPARC
 uname -a:
    SunOS H2S-253-D0 5.11 11.3 sun4v sparc sun4v

 SPEC is set to: /export/cpu2006

 disk: df -h  /export/cpu2006
 Filesystem             Size   Used  Available Capacity  Mounted on
 rpool/export           547G   9.1G       265G     4%    /export

 (End of data from sysinfo program)
```

General Notes

```
The Building Block (BB) is just a Fujitsu SPARC M12-2S that is the basic
unit to be expanded as if stacking up children’s blocks.

File System:
 tmpfs: output_root was used to put run directories in /tmp/cpu2006
 zfs: operating system

SPEC CPU2006 benchmark:
 Updated with runspec --update
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-std=c99 -m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M
-xsegment_align=4M -xthroughput -xalias_level=std

C++ benchmarks:
-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M
-xsegment_align=4M -xthroughput -xalias_level=compatible
-library=stlport4 -lfast

Base Other Flags

C benchmarks:
-xjobs=8

C++ benchmarks:
-xjobs=8

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xtarget=sparc64xplus -xipo=1
-xalias_level=std -xrestrict -xprefetch=no%auto -xO4
-Wc,-Qiselect-funcalign=4 -xthroughput=no -lfast

401.bzip2: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xalias_level=strong -xprefetch=no%auto
-Wc,-Qiselect-funcalign=4 -Wc,-Qicache-chbab=1
-xinline_param=max_inst_hard:1000,max_inst_soft:500,max_growth:60
-lfast

403.gcc: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xO4 -xipo=2 -xprefetch=no%auto
-Wc,-Qiselect-funcalign=64
-xcache=32/128/4/4:256/128/8/4:8192/128/16/24
-xalias_level=layout

429.mcf: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=2 -xalias_level=std -xprefetch=latx:0.2
-W2,-Asac -Wc,-Qiselect-funcalign=64

445.gobmk: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xO4 -xalias_level=std -xrestrict
-xprefetch=no%auto -Wc,-Qiselect-funcalign=64
-Wc,-Qgsched-T=4

456.hmmer: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=1 -xunroll=8 -Wc,-Qms_pipe-pref

Continued on next page

Peak Optimization Flags (Continued)

456.hmmer (continued):
-Wc,-Qiselect-funcalign=4
-xcache=32/128/4/4:256/128/8/4:8192/128/16/48

458.sjeng: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xO4 -xipo=2 -xalias_level=std -xunroll=4
-Wc,-Qiselect-funcalign=4 -W2,-Afully_unroll:always=on
-xprefetch=latx:0.6 -xcheck=%none

462.libquantum: -std=c99 -m32 -fast -xtarget=sparc64xii -xpagesize=256M
-xsegment_align=256M -xthroughput -m64
-xtarget=sparc64xplus -xipo=2
-xcache=32/128/4/4:256/128/8/4:8192/128/16/24
-xinline_param=level:1 -Wc,-Qiselect-funcalign=4
-xalias_level=layout -xprefetch=latx:0.2

464.h264ref: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xtarget=sparc64xplus -xipo=1
-Wc,-Qiselect-funcalign=4 -xthroughput=no
-xalias_level=layout -xprefetch=latx:0.2 -xcheck=%none

C++ benchmarks:

471.omnetpp: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=1 -xalias_level=compatible -xunroll=2
-xprefetch_level=3 -W2,-Asac -xthroughput=no -lfast

473.astar: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xtarget=sparc64xplus -xalias_level=compatible
-xipo=2 -xunroll=6 -xrestrict=%source
-Wc,-Qiselect-funcalign=64 -Wc,-Qgsched-T=4
-xprefetch=latx:0.3 -lfast

483.xalancbmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=2 -xalias_level=compatible -xdepend
-xprefetch_level=3 -xprefetch=latx:0.4 -library=stlport4
-W2,-Asac -Wc,-Qiselect-funcalign=64 -features=no%except
-lfast

Peak Other Flags

C benchmarks:
`-xjobs=8`

C++ benchmarks:
`-xjobs=8`

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.html
http://www.spec.org/cpu2006/flags/Fujitsu-M12-2S.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.xml
http://www.spec.org/cpu2006/flags/Fujitsu-M12-2S.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Apr 20 09:42:32 2017 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 April 2017.