



SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECint®_rate2006 = Not Run

HPC S2600WF (Intel Xeon Silver 4112, 2.60 GHz)

SPECint_rate_base2006 = 418

CPU2006 license: 4204


Test sponsor: M Computers s.r.o.

Tested by: M Computers s.r.o.

Test date: Aug-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017



SPECint_rate_base2006 = 418

Hardware

CPU Name: Intel Xeon Silver 4112
 CPU Characteristics: Intel Turbo Boost Technology up to 3.00 GHz
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: 8.25 MB I+D on chip per chip
 Other Cache: None
 Memory: 384 GB (24 x 16 GB 2Rx8 PC4-2400V-R, running at 2400 MT/s)
 Disk Subsystem: 1 x 1600 GB SATA SSD
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 12 SP2 4.4.21-69-default
 Compiler: C/C++: Version 17.0.4.196 of Intel C/C++ Compiler for Linux
 Auto Parallel: No
 File System: xfs
 System State: Run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V11.2



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECint_rate2006 = Not Run

HPC S2600WF (Intel Xeon Silver 4112, 2.60 GHz)

SPECint_rate_base2006 = 418

CPU2006 license: 4204

Test date: Aug-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	517	302	<u>514</u>	<u>304</u>	513	305							
401.bzip2	16	827	187	820	188	<u>824</u>	<u>187</u>							
403.gcc	16	405	318	407	316	<u>406</u>	<u>317</u>							
429.mcf	16	236	618	<u>234</u>	<u>622</u>	234	623							
445.gobmk	16	646	260	646	260	<u>646</u>	<u>260</u>							
456.hammer	16	236	634	240	623	<u>239</u>	<u>624</u>							
458.sjeng	16	703	275	<u>704</u>	<u>275</u>	704	275							
462.libquantum	16	<u>77.8</u>	<u>4260</u>	77.8	4260	77.7	4270							
464.h264ref	16	738	480	<u>735</u>	<u>482</u>	709	500							
471.omnetpp	16	481	208	<u>479</u>	<u>209</u>	479	209							
473.astar	16	<u>461</u>	<u>244</u>	468	240	461	244							
483.xalancbmk	16	206	535	206	537	<u>206</u>	<u>536</u>							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS settings:
Patrol Scrub=Disabled
CPU and Power Performance Policy=Performance
Set Fan Profile=Performance
Sysinfo program /spec/config/sysinfo.rev6993
Revision 6993 of 2015-11-06 (300de342723409e6453f54e8c50448c3)
running on kvasir Fri Aug 18 11:56:28 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : Intel(R) Xeon(R) Silver 4112 CPU @ 2.60GHz
2 "physical id"s (chips)
16 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECint_rate2006 = Not Run

HPC S2600WF (Intel Xeon Silver 4112, 2.60 GHz)

SPECint_rate_base2006 = 418

CPU2006 license: 4204

Test date: Aug-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Platform Notes (Continued)

following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 4
siblings  : 8
physical 0: cores 1 2 4 5
physical 1: cores 1 2 4 5
cache size : 8448 KB
```

From /proc/meminfo

```
MemTotal:      394667276 kB
HugePages_Total:      0
Hugepagesize:    2048 kB
```

/usr/bin/lsb_release -d

```
SUSE Linux Enterprise Server 12 SP2
```

From /etc/*release* /etc/*version*

SuSE-release:

```
SUSE Linux Enterprise Server 12 (x86_64)
```

```
VERSION = 12
```

```
PATCHLEVEL = 2
```

```
# This file is deprecated and will be removed in a future service pack or release.
```

```
# Please check /etc/os-release for details about this release.
```

os-release:

```
NAME="SLES"
```

```
VERSION="12-SP2"
```

```
VERSION_ID="12.2"
```

```
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
```

```
ID="sles"
```

```
ANSI_COLOR="0;32"
```

```
CPE_NAME="cpe:/o:suse:sles:12:sp2"
```

uname -a:

```
Linux kvasir 4.4.21-69-default #1 SMP Tue Oct 25 10:58:20 UTC 2016 (9464f67)
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Aug 17 09:49

SPEC is set to: /spec

```
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdal        xfs   650G  67G  584G  11% /
```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Intel Corporation SE5C620.86B.0X.01.0007.060920171037 06/09/2017

Memory:

```
1x Hynix HMA42GR7AFR4N-UH 16 GB 2 rank 2400 MHz
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECint_rate2006 = Not Run

HPC S2600WF (Intel Xeon Silver 4112, 2.60 GHz)

SPECint_rate_base2006 = 418

CPU2006 license: 4204

Test date: Aug-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Platform Notes (Continued)

23x Samsung M393A2G40EB1-CRC 16 GB 2 rank 2400 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/spec/lib/ia32:/spec/lib/intel64:/spec/shl1.2"

Binaries compiled on a system with 2x Intel Xeon-SP 4112 CPU + 192GB RAM memory using Redhat Enterprise Linux 7.3

Transparent Huge Pages enabled by default.

Filesystem page cache cleared with:

```
echo 1 > /proc/sys/vm/drop_caches
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

Base Compiler Invocation

C benchmarks:

```
icc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32
```

C++ benchmarks:

```
icpc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32
```

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
```

```
-qopt-mem-layout-trans=3
```

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
```

```
-qopt-mem-layout-trans=3 -Wl,-z,muldefs -L/shl1.2 -lsmartheap
```



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECint_rate2006 = Not Run

HPC S2600WF (Intel Xeon Silver 4112, 2.60 GHz)

SPECint_rate_base2006 = 418

CPU2006 license: 4204

Test date: Aug-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64-revF.html>

<http://www.spec.org/cpu2006/flags/MComputers-Platform-Settings-V1.2-revB.20170920.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64-revF.xml>

<http://www.spec.org/cpu2006/flags/MComputers-Platform-Settings-V1.2-revB.20170920.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Sep 20 11:01:37 2017 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 September 2017.