SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8256, 3.80GHz

SPECrate®2017_int_base = 253

SPECrate®2017_int_peak = Not Run

CPU2017 License: 19
Test Sponsor: Fujitsu
Tested by: Fujitsu

Test Date: Jul-2019
Hardware Availability: Apr-2019
Software Availability: Feb-2019



Hardware

CPU Name:	Intel Xeon Platinum 8256
Max MHz:	3900
Nominal:	3800
Enabled:	32 cores, 8 chips, 2 threads/core
Orderable:	2,4,6,8 chips
Cache L1:	32 KB I + 32 KB D on chip per core
L2:	1 MB I+D on chip per core
L3:	16.5 MB I+D on chip per chip
Other:	None
Memory:	3 TB (96 x 32 GB 2Rx4 PC4-2933Y-R)
Storage:	1 x SAS HDD, 600GB, 10.5K RPM, SAS HDD
Other:	None

Software

OS:	SUSE Linux Enterprise Server 15 4.12.14-25.28-default
Compiler:	C/C++: Version 19.0.1.144 of Intel C/C++ Compiler for Linux; Fortran: Version 19.0.1.144 of Intel Fortran Compiler for Linux
Parallel:	No
Firmware:	PRIMEQUEST 3800E2 Unified Firmware Version PB19043, Released Jun-2019
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other:	None
Power Management:	--

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8256, 3.80GHz

SPECrate®2017_int_base = 253

SPECrate®2017_int_peak = Not Run

CPU2017 License: 19
Test Sponsor: Fujitsu
Tested by: Fujitsu

Test Date: Jul-2019
Hardware Availability: Apr-2019
Software Availability: Feb-2019

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	64	529	193	**530**	**192**	532	192							
502.gcc_r	64	436	208	**439**	**206**	441	205							
505.mcf_r	64	308	336	308	335	**308**	**335**							
520.omnetpp_r	64	**522**	**161**	521	161	524	160							
523.xalancbmk_r	64	206	327	**206**	**328**	205	329							
525.x264_r	64	213	527	**213**	**527**	212	528							
531.deepsjeng_r	64	355	207	354	207	**354**	**207**							
541.leela_r	64	543	195	561	189	**552**	**192**							
548.exchange2_r	64	377	445	**377**	**445**	377	445							
557.xz_r	64	421	164	**421**	**164**	421	164							

SPECrate®2017_int_base = 253

SPECrate®2017_int_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Kernel Boot Parameter set with : nohz_full=1-63
```

General Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/Benchmark/speccpu2017-int/lib/intel64"

 Binaries compiled on a system with 1x Intel Core i9-7900X CPU + 32GB RAM
 memory using Redhat Enterprise Linux 7.5
 Transparent Huge Pages enabled by default
 Prior to runcpu invocation
 Filesystem page cache synced and cleared with:
 sync; echo 3>       /proc/sys/vm/drop_caches
 runcpu command invoked through numactl i.e.:
 numactl --interleave=all runcpu <etc>
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
```

(Continued on next page)

General Notes (Continued)

```
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
```

Platform Notes

```
 BIOS configuration:
 DCU Streamer Prefetcher = Disabled
 DDR4 Write Data CRC Protection = Disabled
 HWPM Support = Native Mode with no legacy
 Stale AtoS = Enabled
 Sub Numa Clustering = Enabled
 Uncore Frequency Scaling = Disabled
 UPI Link L0p = Disabled
 XPT Prefetch = Enabled
 Fan Control = Full
 Sysinfo program /home/Benchmark/speccpu2017-int/bin/sysinfo
 Rev: r5974 of 2018-05-19 9bcde8f2999c33d61f64985e45859ea9
 running on linux-8r5c Mon Jul  8 20:06:14 2019

 SUT (System Under Test) info as seen by some common utilities.
 For more information on this section, see
    https://www.spec.org/cpu2017/Docs/config.html#sysinfo

 From /proc/cpuinfo
    model name : Intel(R) Xeon(R) Platinum 8256 CPU @ 3.80GHz
       8  "physical id"s (chips)
       64 "processors"
    cores, siblings (Caution: counting these is hw and system dependent. The following
    excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)
       cpu cores : 4
       siblings  : 8
       physical 0: cores 1 2 4 13
       physical 1: cores 4 8 9 13
       physical 2: cores 1 2 5 13
       physical 3: cores 1 2 5 13
       physical 4: cores 1 2 4 13
       physical 5: cores 2 9 12 13
       physical 6: cores 1 2 5 13
       physical 7: cores 3 8 9 13

 From lscpu:
      Architecture:        x86_64
      CPU op-mode(s):      32-bit, 64-bit
      Byte Order:          Little Endian
      CPU(s):              64
      On-line CPU(s) list: 0-63
```

(Continued on next page)

Platform Notes (Continued)

```
Thread(s) per core:  2
Core(s) per socket:  4
Socket(s):           8
NUMA node(s):        16
Vendor ID:           GenuineIntel
CPU family:          6
Model:               85
Model name:          Intel(R) Xeon(R) Platinum 8256 CPU @ 3.80GHz
Stepping:            6
CPU MHz:             3800.000
CPU max MHz:         3900.0000
CPU min MHz:         1200.0000
BogoMIPS:            7600.00
Virtualization:      VT-x
L1d cache:           32K
L1i cache:           32K
L2 cache:            1024K
L3 cache:            16896K
NUMA node0 CPU(s):   0,1,32,33
NUMA node1 CPU(s):   2,3,34,35
NUMA node2 CPU(s):   4,7,36,39
NUMA node3 CPU(s):   5,6,37,38
NUMA node4 CPU(s):   8,9,40,41
NUMA node5 CPU(s):   10,11,42,43
NUMA node6 CPU(s):   12,13,44,45
NUMA node7 CPU(s):   14,15,46,47
NUMA node8 CPU(s):   16,17,48,49
NUMA node9 CPU(s):   18,19,50,51
NUMA node10 CPU(s):  20,21,52,53
NUMA node11 CPU(s):  22,23,54,55
NUMA node12 CPU(s):  24,25,56,57
NUMA node13 CPU(s):  26,27,58,59
NUMA node14 CPU(s):  28,31,60,63
NUMA node15 CPU(s):  29,30,61,62
Flags:               fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc cpuid
aperfmperf pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16
xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave
avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb cat_l3 cdp_l3
invpcid_single intel_ppin ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow vnmi
flexpriority ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm
cqm mpx rdt_a avx512f avx512dq rdseed adx smap clflushopt clwb intel_pt avx512cd
avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
cqm_mbm_local dtherm ida arat pln pts hwp hwp_act_window hwp_epp hwp_pkg_req pku
ospke avx512_vnni flush_l1d arch_capabilities
```

(Continued on next page)

Platform Notes (Continued)

```
 /proc/cpuinfo cache data
    cache size : 16896 KB

 From numactl --hardware  WARNING: a numactl 'node' might or might not correspond to a
 physical chip.
   available: 16 nodes (0-15)
   node 0 cpus: 0 1 32 33
   node 0 size: 192271 MB
   node 0 free: 192073 MB
   node 1 cpus: 2 3 34 35
   node 1 size: 193532 MB
   node 1 free: 193392 MB
   node 2 cpus: 4 7 36 39
   node 2 size: 193532 MB
   node 2 free: 193394 MB
   node 3 cpus: 5 6 37 38
   node 3 size: 193503 MB
   node 3 free: 193350 MB
   node 4 cpus: 8 9 40 41
   node 4 size: 193532 MB
   node 4 free: 193394 MB
   node 5 cpus: 10 11 42 43
   node 5 size: 193532 MB
   node 5 free: 193397 MB
   node 6 cpus: 12 13 44 45
   node 6 size: 193532 MB
   node 6 free: 193403 MB
   node 7 cpus: 14 15 46 47
   node 7 size: 193532 MB
   node 7 free: 193407 MB
   node 8 cpus: 16 17 48 49
   node 8 size: 193532 MB
   node 8 free: 193386 MB
   node 9 cpus: 18 19 50 51
   node 9 size: 193532 MB
   node 9 free: 193136 MB
   node 10 cpus: 20 21 52 53
   node 10 size: 193532 MB
   node 10 free: 193390 MB
   node 11 cpus: 22 23 54 55
   node 11 size: 193532 MB
   node 11 free: 193404 MB
   node 12 cpus: 24 25 56 57
   node 12 size: 193532 MB
   node 12 free: 193284 MB
   node 13 cpus: 26 27 58 59
   node 13 size: 193532 MB
```

(Continued on next page)

Platform Notes (Continued)

```
   node 13 free: 193393 MB
   node 14 cpus: 28 31 60 63
   node 14 size: 193331 MB
   node 14 free: 193207 MB
   node 15 cpus: 29 30 61 62
   node 15 size: 193532 MB
   node 15 free: 193408 MB
   node distances:
   node   0   1   2   3   4   5   6   7   8   9  10  11  12  13  14  15
     0:  10  11  20  20  20  20  28  28  28  28  28  28  20  20  28  28
     1:  11  10  20  20  20  20  28  28  28  28  28  28  20  20  28  28
     2:  20  20  10  11  28  28  20  20  28  28  20  20  28  28  28  28
     3:  20  20  11  10  28  28  20  20  28  28  20  20  28  28  28  28
     4:  20  20  28  28  10  11  20  20  20  20  28  28  28  28  28  28
     5:  20  20  28  28  11  10  20  20  20  20  28  28  28  28  28  28
     6:  28  28  20  20  20  20  10  11  28  28  28  28  28  28  20  20
     7:  28  28  20  20  20  20  11  10  28  28  28  28  28  28  20  20
     8:  28  28  28  28  20  20  28  28  10  11  20  20  20  20  28  28
     9:  28  28  28  28  20  20  28  28  11  10  20  20  20  20  28  28
    10:  28  28  20  20  28  28  28  28  20  20  10  11  28  28  20  20
    11:  28  28  20  20  28  28  28  28  20  20  11  10  28  28  20  20
    12:  20  20  28  28  28  28  28  28  20  20  28  28  10  11  20  20
    13:  20  20  28  28  28  28  28  28  20  20  28  28  11  10  20  20
    14:  28  28  28  28  28  28  20  20  28  28  20  20  20  20  10  11
    15:  28  28  28  28  28  28  20  20  28  28  20  20  20  20  11  10

 From /proc/meminfo
    MemTotal:       3169312984 kB
    HugePages_Total:       0
    Hugepagesize:       2048 kB

 From /etc/*release* /etc/*version*
    os-release:
       NAME="SLES"
       VERSION="15"
       VERSION_ID="15"
       PRETTY_NAME="SUSE Linux Enterprise Server 15"
       ID="sles"
       ID_LIKE="suse"
       ANSI_COLOR="0;32"
       CPE_NAME="cpe:/o:suse:sles:15"

 uname -a:
    Linux linux-8r5c 4.12.14-25.28-default #1 SMP Wed Jan 16 20:00:47 UTC 2019 (dd6077c)
    x86_64 x86_64 x86_64 GNU/Linux

 Kernel self-reported vulnerability status:
```


(Continued on next page)

Platform Notes (Continued)

```
 CVE-2017-5754 (Meltdown):          Not affected
 CVE-2017-5753 (Spectre variant 1): Mitigation: __user pointer sanitization
 CVE-2017-5715 (Spectre variant 2): Mitigation: Enhanced IBRS, IBPB: conditional, RSB
 filling

 run-level 3 Jul 8 20:04

 SPEC is set to: /home/Benchmark/speccpu2017-int
    Filesystem     Type  Size  Used Avail Use% Mounted on
    /dev/sda3      xfs   142G   35G  107G  25% /home

 Additional information from dmidecode follows.  WARNING: Use caution when you interpret
 this section. The 'dmidecode' program reads system data which is "intended to allow
 hardware to be accurately determined", but the intent may not be met, as there are
 frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.
   BIOS FUJITSU V1.0.0.0 R1.16.0 for D3858-B1x            04/24/2019
   Memory:
    68x Micron 36ASF4G72PZ-2G9E2 32 GB 2 rank 2933
    28x Samsung M393A4K40CB2-CVF 32 GB 2 rank 2933

 (End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
C       | 500.perlbench_r(base) 502.gcc_r(base) 505.mcf_r(base)
        | 525.x264_r(base) 557.xz_r(base)
------------------------------------------------------------------------------
Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++     | 520.omnetpp_r(base) 523.xalancbmk_r(base) 531.deepsjeng_r(base)
        | 541.leela_r(base)
------------------------------------------------------------------------------
Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran | 548.exchange2_r(base)
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
  64, Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`icc -m64 -std=c11`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Base Portability Flags

500.perlbench_r: `-DSPEC_LP64 -DSPEC_LINUX_X64`
502.gcc_r: `-DSPEC_LP64`
505.mcf_r: `-DSPEC_LP64`
520.omnetpp_r: `-DSPEC_LP64`
523.xalancbmk_r: `-DSPEC_LP64 -DSPEC_LINUX`
525.x264_r: `-DSPEC_LP64`
531.deepsjeng_r: `-DSPEC_LP64`
541.leela_r: `-DSPEC_LP64`
548.exchange2_r: `-DSPEC_LP64`
557.xz_r: `-DSPEC_LP64`

Base Optimization Flags

C benchmarks:
`-Wl,-z,muldefs -xCORE-AVX512 -ipo -O3 -no-prec-div`
`-qopt-mem-layout-trans=4`
`-L/usr/local/IntelCompiler19/compilers_and_libraries_2019.1.144/linux/compiler/lib/intel64`
`-lqkmalloc`

C++ benchmarks:
`-Wl,-z,muldefs -xCORE-AVX512 -ipo -O3 -no-prec-div`
`-qopt-mem-layout-trans=4`
`-L/usr/local/IntelCompiler19/compilers_and_libraries_2019.1.144/linux/compiler/lib/intel64`

(Continued on next page)

Base Optimization Flags (Continued)

C++ benchmarks (continued):
`-lqkmalloc`

Fortran benchmarks:
`-Wl,-z,muldefs -xCORE-AVX512 -ipo -O3 -no-prec-div`
`-qopt-mem-layout-trans=4 -nostandard-realloc-lhs -align array32byte`
`-L/usr/local/IntelCompiler19/compilers_and_libraries_2019.1.144/linux/compiler/lib/intel64`
`-lqkmalloc`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2019-04-02.html`
`http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-CSL-RevE.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2019-04-02.xml`
`http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-CSL-RevE.xml`

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.0.5 on 2019-07-08 07:06:13-0400.
Report generated on 2019-10-15 14:44:39 by CPU2017 PS formatter v6255.
Originally published on 2019-10-15.