



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3


Test Sponsor: HPE

Tested by: HPE

**Test Date:** Jan-2023

**Hardware Availability:** Dec-2022

**Software Availability:** Nov-2022



## Hardware

CPU Name: AMD EPYC 9634  
 Max MHz: 3700  
 Nominal: 2250  
 Enabled: 168 cores, 2 chips, 2 threads/core  
 Orderable: 1,2 chips  
 Cache L1: 32 KB I + 32 KB D on chip per core  
 L2: 1 MB I+D on chip per core  
 L3: 384 MB I+D on chip per chip,  
 32 MB shared / 7 cores  
 Other: None  
 Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-4800B-R)  
 Storage: 1 x 480 GB SATA SSD  
 Other: None

## Software

OS: Ubuntu 22.04.1 LTS  
 Compiler: Kernel 5.15.0-56-generic  
 Parallel: C/C++/Fortran: Version 4.0.0 of AOCC  
 Firmware: No  
 File System: HPE BIOS Version v1.12 11/24/2022 released  
 System State: Nov-2022  
 Base Pointers: ext4  
 Peak Pointers: Run level 5 (multi-user)  
 Other: 64-bit  
 Power Management: Peak Pointers: 32/64-bit  
 Other: None  
 Power Management: BIOS and OS set to prefer performance at  
 the cost of additional power usage



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

Test Date: Jan-2023

Test Sponsor: HPE

Hardware Availability: Dec-2022

Tested by: HPE

Software Availability: Nov-2022

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	336	534	1000	535	1000	<b>534</b>	<b>1000</b>	336	534	1000	535	1000	<b>534</b>	<b>1000</b>		
502.gcc_r	336	462	1030	460	1030	<b>461</b>	<b>1030</b>	336	<b>357</b>	<b>1330</b>	358	1330	<b>357</b>	<b>1330</b>		
505.mcf_r	336	<b>284</b>	<b>1910</b>	283	1920	285	1910	336	284	1920	<b>284</b>	<b>1910</b>	284	1910		
520.omnetpp_r	336	618	713	628	702	<b>627</b>	<b>703</b>	336	618	713	628	702	<b>627</b>	<b>703</b>		
523.xalancbmk_r	336	234	1520	237	1500	<b>236</b>	<b>1510</b>	336	180	1970	<b>195</b>	<b>1820</b>	207	1710		
525.x264_r	336	181	3250	<b>182</b>	<b>3240</b>	182	3240	336	181	3250	<b>182</b>	<b>3240</b>	182	3240		
531.deepsjeng_r	336	<b>331</b>	<b>1160</b>	332	1160	331	1160	336	<b>331</b>	<b>1160</b>	332	1160	<b>331</b>	<b>1160</b>		
541.leela_r	336	481	1160	491	1130	<b>489</b>	<b>1140</b>	336	481	1160	491	1130	<b>489</b>	<b>1140</b>		
548.exchange2_r	336	282	3130	<b>282</b>	<b>3120</b>	282	3120	336	281	3130	<b>281</b>	<b>3130</b>	281	3130		
557.xz_r	336	501	725	<b>500</b>	<b>726</b>	497	730	336	497	731	<b>498</b>	<b>729</b>	498	728		

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Notes

The AMD64 AOCC Compiler Suite is available at  
<http://developer.amd.com/amd-aocc/>

## Submit Notes

The config file option 'submit' was used.  
 'numactl' was used to bind copies to the cores.  
 See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size limit  
 'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:  
 numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty\_ratio=8' run as root.  
 To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.  
 To free node-local memory and avoid remote memory usage,  
 'sysctl -w vm.zone\_reclaim\_mode=1' run as root.  
 To clear filesystem caches, 'sync; sysctl -w vm.drop\_caches=3' run as root.  
 To disable address space layout randomization (ASLR) to reduce run-to-run  
 variability, 'sysctl -w kernel.randomize\_va\_space=0' run as root.

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

**Test Date:** Jan-2023

**Hardware Availability:** Dec-2022

**Software Availability:** Nov-2022

## Operating System Notes (Continued)

To enable Transparent Hugepages (THP) only on request for base runs,  
'echo madvise > /sys/kernel/mm/transparent\_hugepage/enabled' run as root.  
To enable THP for all allocations for peak runs,  
'echo always > /sys/kernel/mm/transparent\_hugepage/enabled' and  
'echo always > /sys/kernel/mm/transparent\_hugepage/defrag' run as root.

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH =
    "/home/cpu2017/amd_rate_aocc400_genoa_B_lib/lib:/home/cpu2017/amd_rate_a
    occ400_genoa_B_lib/lib32:"
MALLOC_CONF = "retain:true"
```

Environment variables set by runcpu during the 523.xalancbmk\_r peak run:

```
MALLOC_CONF = "thp:never"
```

## General Notes

Binaries were compiled on a system with 2x AMD EPYC 9174F CPU + 1.5TiB Memory using RHEL 8.6

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

## Platform Notes

BIOS Configuration

Workload Profile set to General Throughput Compute

Determinism Control set to Manual

Performance Determinism set to Power Deterministic

Last-Level Cache (LLC) as NUMA Node set to Enabled

NUMA memory domains per socket set to Four memory domains per socket

ACPI CST C2 Latency set to 18 microseconds

Thermal Configuration set to Maximum Cooling

Workload Profile set to Custom

Power Regulator set to OS Control Mode

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

**Test Date:** Jan-2023

**Hardware Availability:** Dec-2022

**Software Availability:** Nov-2022

## Platform Notes (Continued)

The system ROM used for this result contains microcode version 0xa10110e for the AMD EPYC 9nn4X family of processors. The reference code/AGESA version used in this ROM is version GenoaPI 1.0.0.1-L6

```
Sysinfo program /home/cpu2017/bin/sysinfo
Rev: r6622 of 2021-04-07 982a61ec0915b55891ef0e16acafcc64d
running on admin1 Tue Jun 28 07:45:14 2022
```

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : AMD EPYC 9634 84-Core Processor
  2 "physical id"s (chips)
  336 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 84
  siblings   : 168
  physical 0: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
  28 29 30 32 33 34 35 36 37 38 40 41 42 43 44 45 46 48 49 50 51 52 53 54 56 57 58 59
  60 61 62 64 65 66 67 68 69 70 72 73 74 75 76 77 78 80 81 82 83 84 85 86 88 89 90 91
  92 93 94
  physical 1: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
  28 29 30 32 33 34 35 36 37 38 40 41 42 43 44 45 46 48 49 50 51 52 53 54 56 57 58 59
  60 61 62 64 65 66 67 68 69 70 72 73 74 75 76 77 78 80 81 82 83 84 85 86 88 89 90 91
  92 93 94
```

```
From lscpu from util-linux 2.37.2:
```

Architecture:	x86_64
CPU op-mode(s):	32-bit, 64-bit
Address sizes:	52 bits physical, 57 bits virtual
Byte Order:	Little Endian
CPU(s):	336
On-line CPU(s) list:	0-335
Vendor ID:	AuthenticAMD
Model name:	AMD EPYC 9634 84-Core Processor
CPU family:	25
Model:	17
Thread(s) per core:	2
Core(s) per socket:	84
Socket(s):	2
Stepping:	1
Frequency boost:	enabled
CPU max MHz:	3701.0000
CPU min MHz:	400.0000

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

**Test Date:** Jan-2023

Test Sponsor: HPE

**Hardware Availability:** Dec-2022

Tested by: HPE

**Software Availability:** Nov-2022

## Platform Notes (Continued)

BogoMIPS:

4493.48

Flags:

fpu vme de pse tsc msr pae mce cx8 apic sep mtrr  
pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr\_opt  
pdpe1gb rdtscp lm constant\_tsc rep\_good nopl nonstop\_tsc cpuid extd\_apicid  
aperfmpfperf rapl pni pclmulqdq monitor ssse3 fma cx16 pcid sse4\_1 sse4\_2 x2apic movbe  
popcnt aes xsave avx f16c rdrand lahf\_lm cmp\_legacy svm extapic cr8\_legacy abm sse4a  
misalignsse 3dnowprefetch osvw ibs skinit wdt tce topoext perfctr\_core perfctr\_nb  
bpext perfctr\_llc mwaitx cpb cat\_13 cdp\_13 invpcid\_single hw\_pstate ssbd mba ibrs  
ibpb stibp vmmcall fsgsbase bmi1 avx2 smep bmi2 erms invpcid cqmq rdt\_a avx512f  
avx512dq rdseed adx smap avx512ifma clflushopt clwb avx512cd sha\_ni avx512bw  
avx512vl xsaveopt xsavec xgetbv1 xsaves cqmq\_llc cqmq\_occup\_llc cqmq\_mbm\_total  
cqmq\_mbm\_local avx512\_bf16 clzero irperf xsaveerptr rdpru wbnoinvd amd\_ppin cppc arat  
npt lbrv svm\_lock nrip\_save tsc\_scale vmcb\_clean flushbyasid decodeassists  
pausefilter pfthreshold avic v\_vmsave\_vmload vgif v\_spec\_ctrl avx512vbmi umip pkru  
ospke avx512\_vbmi2 gfni vaes vpclmulqdq avx512\_vnni avx512\_bitalg avx512\_vpopcntdq  
la57 rdpid overflow\_recov succor smca fsrm flush\_ll1d

Virtualization:

AMD-V

L1d cache:

5.3 MiB (168 instances)

L1i cache:

5.3 MiB (168 instances)

L2 cache:

168 MiB (168 instances)

L3 cache:

768 MiB (24 instances)

NUMA node(s):

24

NUMA node0 CPU(s):

0-6,168-174

NUMA node1 CPU(s):

28-34,196-202

NUMA node2 CPU(s):

56-62,224-230

NUMA node3 CPU(s):

14-20,182-188

NUMA node4 CPU(s):

42-48,210-216

NUMA node5 CPU(s):

70-76,238-244

NUMA node6 CPU(s):

21-27,189-195

NUMA node7 CPU(s):

49-55,217-223

NUMA node8 CPU(s):

77-83,245-251

NUMA node9 CPU(s):

7-13,175-181

NUMA node10 CPU(s):

35-41,203-209

NUMA node11 CPU(s):

63-69,231-237

NUMA node12 CPU(s):

84-90,252-258

NUMA node13 CPU(s):

112-118,280-286

NUMA node14 CPU(s):

140-146,308-314

NUMA node15 CPU(s):

98-104,266-272

NUMA node16 CPU(s):

126-132,294-300

NUMA node17 CPU(s):

154-160,322-328

NUMA node18 CPU(s):

105-111,273-279

NUMA node19 CPU(s):

133-139,301-307

NUMA node20 CPU(s):

161-167,329-335

NUMA node21 CPU(s):

91-97,259-265

NUMA node22 CPU(s):

119-125,287-293

NUMA node23 CPU(s):

147-153,315-321

Vulnerability Itlb multihit:

Not affected

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

**Test Date:** Jan-2023

Test Sponsor: HPE

**Hardware Availability:** Dec-2022

Tested by: HPE

**Software Availability:** Nov-2022

## Platform Notes (Continued)

Vulnerability L1tf:	Not affected
Vulnerability Mds:	Not affected
Vulnerability Meltdown:	Not affected
Vulnerability Mmio stale data:	Not affected
Vulnerability Retbleed:	Not affected
Vulnerability Spec store bypass:	Mitigation; Speculative Store Bypass disabled via prctl and seccomp
Vulnerability Spectre v1:	Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Vulnerability Spectre v2:	Mitigation; Retpolines, IBPB conditional, IBRS_FW, STIBP always-on, RSB filling, PBRSB-eIBRS Not affected
Vulnerability Srbds:	Not affected
Vulnerability Tsx async abort:	Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	32K	5.3M	8	Data	1	64	1	64
L1i	32K	5.3M	8	Instruction	1	64	1	64
L2	1M	168M	8	Unified	2	2048	1	64
L3	32M	768M	16	Unified	3	32768	1	64

/proc/cpuinfo cache data  
cache size : 1024 KB

From numactl --hardware

WARNING: a numactl 'node' might or might not correspond to a physical chip.

```
available: 24 nodes (0-23)
node 0 cpus: 0 1 2 3 4 5 6 168 169 170 171 172 173 174
node 0 size: 64198 MB
node 0 free: 63878 MB
node 1 cpus: 28 29 30 31 32 33 34 196 197 198 199 200 201 202
node 1 size: 64508 MB
node 1 free: 64292 MB
node 2 cpus: 56 57 58 59 60 61 62 224 225 226 227 228 229 230
node 2 size: 64508 MB
node 2 free: 64267 MB
node 3 cpus: 14 15 16 17 18 19 20 182 183 184 185 186 187 188
node 3 size: 64508 MB
node 3 free: 64175 MB
node 4 cpus: 42 43 44 45 46 47 48 210 211 212 213 214 215 216
node 4 size: 64473 MB
node 4 free: 64167 MB
node 5 cpus: 70 71 72 73 74 75 76 238 239 240 241 242 243 244
node 5 size: 64508 MB
node 5 free: 64217 MB
node 6 cpus: 21 22 23 24 25 26 27 189 190 191 192 193 194 195
node 6 size: 64508 MB
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

**SPECrate®2017\_int\_base = 1350**

**SPECrate®2017\_int\_peak = 1410**

CPU2017 License: 3

**Test Date:** Jan-2023

Test Sponsor: HPE

**Hardware Availability:** Dec-2022

Tested by: HPE

**Software Availability:** Nov-2022

## Platform Notes (Continued)

```
node 6 free: 64182 MB
node 7 cpus: 49 50 51 52 53 54 55 217 218 219 220 221 222 223
node 7 size: 64508 MB
node 7 free: 64215 MB
node 8 cpus: 77 78 79 80 81 82 83 245 246 247 248 249 250 251
node 8 size: 64508 MB
node 8 free: 64236 MB
node 9 cpus: 7 8 9 10 11 12 13 175 176 177 178 179 180 181
node 9 size: 64508 MB
node 9 free: 64245 MB
node 10 cpus: 35 36 37 38 39 40 41 203 204 205 206 207 208 209
node 10 size: 64508 MB
node 10 free: 64293 MB
node 11 cpus: 63 64 65 66 67 68 69 231 232 233 234 235 236 237
node 11 size: 64508 MB
node 11 free: 64275 MB
node 12 cpus: 84 85 86 87 88 89 90 252 253 254 255 256 257 258
node 12 size: 64508 MB
node 12 free: 64293 MB
node 13 cpus: 112 113 114 115 116 117 118 280 281 282 283 284 285 286
node 13 size: 64508 MB
node 13 free: 64311 MB
node 14 cpus: 140 141 142 143 144 145 146 308 309 310 311 312 313 314
node 14 size: 64508 MB
node 14 free: 64322 MB
node 15 cpus: 98 99 100 101 102 103 104 266 267 268 269 270 271 272
node 15 size: 64508 MB
node 15 free: 64315 MB
node 16 cpus: 126 127 128 129 130 131 132 294 295 296 297 298 299 300
node 16 size: 64508 MB
node 16 free: 64330 MB
node 17 cpus: 154 155 156 157 158 159 160 322 323 324 325 326 327 328
node 17 size: 64508 MB
node 17 free: 64334 MB
node 18 cpus: 105 106 107 108 109 110 111 273 274 275 276 277 278 279
node 18 size: 64508 MB
node 18 free: 64295 MB
node 19 cpus: 133 134 135 136 137 138 139 301 302 303 304 305 306 307
node 19 size: 64508 MB
node 19 free: 64226 MB
node 20 cpus: 161 162 163 164 165 166 167 329 330 331 332 333 334 335
node 20 size: 64508 MB
node 20 free: 64269 MB
node 21 cpus: 91 92 93 94 95 96 97 259 260 261 262 263 264 265
node 21 size: 64508 MB
node 21 free: 64263 MB
node 22 cpus: 119 120 121 122 123 124 125 287 288 289 290 291 292 293
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Date: Jan-2023

Test Sponsor: HPE

Hardware Availability: Dec-2022

Tested by: HPE

Software Availability: Nov-2022

## Platform Notes (Continued)

```
node 22 size: 64508 MB
node 22 free: 64332 MB
node 23 cpus: 147 148 149 150 151 152 153 315 316 317 318 319 320 321
node 23 size: 64450 MB
node 23 free: 64270 MB
node distances:
node   0   1   2   3   4   5   6   7   8   9   10  11  12  13  14  15  16  17  18  19
20  21  22  23
  0: 10  11  11  12  12  12  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  1: 11  10  11  12  12  12  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  2: 11  11  10  12  12  12  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  3: 12  12  12  10  11  11  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  4: 12  12  12  11  10  11  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  5: 12  12  12  11  11  10  12  12  12  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  6: 12  12  12  12  12  12  10  11  11  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  7: 12  12  12  12  12  12  11  10  11  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  8: 12  12  12  12  12  12  11  11  10  12  12  12  32  32  32  32  32  32  32
  32  32  32  32
  9: 12  12  12  12  12  12  12  12  12  10  11  11  32  32  32  32  32  32  32
  32  32  32  32
 10: 12  12  12  12  12  12  12  12  12  11  10  11  32  32  32  32  32  32  32
 32  32  32  32
 11: 12  12  12  12  12  12  12  12  12  11  11  10  32  32  32  32  32  32  32
 32  32  32  32
 12: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  10  11  11  12
 12  12  12
 13: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  11  10  11  12
 12  12  12
 12: 12  12  12
 14: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  11  11  10  12
 12  12  12
 12: 12  12  12
 15: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  10
 11  11  12
 12: 12  12  12
 16: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  11
 10  11  12
 12: 12  12  12
 17: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  11
 11  11  10
 12: 12  12  12
 18: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  12
 10  11
 11: 12  12  12
 19: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  12
 11  10
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Date: Jan-2023

Test Sponsor: HPE

Hardware Availability: Dec-2022

Tested by: HPE

Software Availability: Nov-2022

## Platform Notes (Continued)

```
11 12 12 12
20: 32 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 12 12 11 11
10 12 12 12
21: 32 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 12 12 12 12
12 10 11 11
22: 32 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 12 12 12 12
12 11 10 11
23: 32 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 12 12 12 12
12 11 11 10
```

From /proc/meminfo

```
MemTotal: 1584947636 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

/sbin/tuned-adm active

```
Current active profile: throughput-performance
```

/sys/devices/system/cpu/cpu\*/cpufreq/scaling\_governor has  
performance

/usr/bin/lsb\_release -d  
Ubuntu 22.04.1 LTS

From /etc/\*release\* /etc/\*version\*

```
debian_version: bookworm/sid
os-release:
PRETTY_NAME="Ubuntu 22.04.1 LTS"
NAME="Ubuntu"
VERSION_ID="22.04"
VERSION="22.04.1 LTS (Jammy Jellyfish)"
VERSION_CODENAME=jammy
ID=ubuntu
ID_LIKE=debian
HOME_URL="https://www.ubuntu.com/"
```

uname -a:

```
Linux admin1 5.15.0-56-generic #62-Ubuntu SMP Tue Nov 22 19:54:14 UTC 2022 x86_64
x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

CVE-2018-12207 (iTLB Multihit):	Not affected
CVE-2018-3620 (L1 Terminal Fault):	Not affected
Microarchitectural Data Sampling:	Not affected
CVE-2017-5754 (Meltdown):	Not affected
mmio_stale_data:	Not affected

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Platform Notes (Continued)

retbleed:

CVE-2018-3639 (Speculative Store Bypass):

Not affected

Mitigation: Speculative Store Bypass disabled via prctl and seccomp

CVE-2017-5753 (Spectre variant 1):

Mitigation: usercopy/swapgs barriers and \_\_user pointer sanitization

CVE-2017-5715 (Spectre variant 2):

Mitigation: Retpolines, IBPB: conditional, IBRS\_FW, STIBP: always-on, RSB filling, PBRSB-eIBRS: Not affected

CVE-2020-0543 (Special Register Buffer Data Sampling): Not affected

CVE-2019-11135 (TSX Asynchronous Abort): Not affected

run-level 5 Jun 28 00:01

SPEC is set to: /home/cpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/ubuntu--vg-ubuntu--lv	ext4	437G	20G	399G	5%	/

From /sys/devices/virtual/dmi/id

Vendor:	HPE
Product:	ProLiant DL365 Gen11
Product Family:	ProLiant
Serial:	DL365G11-003

Additional information from dmidecode 3.3 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

24x Hynix HMCG94AEBRA103N 64 GB 2 rank 4800

BIOS:

BIOS Vendor:	HPE
BIOS Version:	1.12
BIOS Date:	11/24/2022
BIOS Revision:	1.12
Firmware Revision:	1.10

(End of data from sysinfo program)

## Compiler Version Notes

=====

C | 502.gcc\_r(peak)

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Compiler Version Notes (Continued)

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on LLVM Mirror.Version.14.0.6)  
Target: i386-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C	500.perlbench_r(base, peak) 502.gcc_r(base) 505.mcf_r(base, peak)
	525.x264_r(base, peak) 557.xz_r(base, peak)

=====

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on LLVM Mirror.Version.14.0.6)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C	502.gcc_r(peak)
---	-----------------

=====

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on LLVM Mirror.Version.14.0.6)  
Target: i386-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C	500.perlbench_r(base, peak) 502.gcc_r(base) 505.mcf_r(base, peak)
	525.x264_r(base, peak) 557.xz_r(base, peak)

=====

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on LLVM Mirror.Version.14.0.6)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C++	523.xalancbmk_r(peak)
-----	-----------------------

=====

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on LLVM Mirror.Version.14.0.6)  
Target: i386-unknown-linux-gnu  
Thread model: posix

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11  
(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Compiler Version Notes (Continued)

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C++ | 520.omnetpp\_r(base, peak) 523.xalancbmk\_r(base)  
| 531.deepsjeng\_r(base, peak) 541.leela\_r(base, peak)

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on  
LLVM Mirror.Version.14.0.6)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C++ | 523.xalancbmk\_r(peak)

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on  
LLVM Mirror.Version.14.0.6)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

C++ | 520.omnetpp\_r(base, peak) 523.xalancbmk\_r(base)  
| 531.deepsjeng\_r(base, peak) 541.leela\_r(base, peak)

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on  
LLVM Mirror.Version.14.0.6)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====

Fortran | 548.exchange2\_r(base, peak)

AMD clang version 14.0.6 (CLANG: AOCC\_4.0.0-Build#389 2022\_10\_07) (based on  
LLVM Mirror.Version.14.0.6)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11  
(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Base Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang

## Base Portability Flags

500.perlbench\_r: -DSPEC\_LINUX\_X64 -DSPEC\_LP64  
502.gcc\_r: -DSPEC\_LP64  
505.mcf\_r: -DSPEC\_LP64  
520.omnetpp\_r: -DSPEC\_LP64  
523.xalancbmk\_r: -DSPEC\_LINUX -DSPEC\_LP64  
525.x264\_r: -DSPEC\_LP64  
531.deepsjeng\_r: -DSPEC\_LP64  
541.leela\_r: -DSPEC\_LP64  
548.exchange2\_r: -DSPEC\_LP64  
557.xz\_r: -DSPEC\_LP64

## Base Optimization Flags

C benchmarks:

-m64 -fno -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-ldist-scalar-expand -fenable-aggressive-gather  
-z muldefs -O3 -march=znver4 -fveclib=AMDLIBM -ffast-math  
-fstruct-layout=7 -mllvm -unroll-threshold=50  
-mllvm -inline-threshold=1000 -fremap-arrays -fstrip-mining  
-mllvm -reduce-array-computations=3 -zopt -lamdlibm -lflang  
-lamdalloc

C++ benchmarks:

-m64 -fno -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -z muldefs -O3  
-march=znver4 -fveclib=AMDLIBM -ffast-math  
-mllvm -unroll-threshold=100 -finline-aggressive  
-mllvm -loop-unswitch-threshold=200000  
-mllvm -reduce-array-computations=3 -zopt  
-fvirtual-function-elimination -fvisibility=hidden -lamdlibm -lflang

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Base Optimization Flags (Continued)

C++ benchmarks (continued):

-lamdalloc-ext

Fortran benchmarks:

```
-m64 -fsto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-inline-recursion=4 -Wl,-mllvm -Wl,-lsr-in-nested-loop  
-Wl,-mllvm -Wl,-enable-iv-split -z muldefs -O3 -march=znver4  
-fveclib=AMDLIBM -ffast-math -fepilog-vectorization-of-inductions  
-mllvm -optimize-strided-mem-cost -floop-transform  
-mllvm -unroll-aggressive -mllvm -unroll-threshold=500 -lamdlibm  
-flang -lamdalloc
```

## Base Other Flags

C benchmarks:

-Wno-unused-command-line-argument

C++ benchmarks:

-Wno-unused-command-line-argument

Fortran benchmarks:

-Wno-unused-command-line-argument

## Peak Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang

## Peak Portability Flags

500.perlbench\_r: -DSPEC\_LINUX\_X64 -DSPEC\_LP64

502.gcc\_r: -D\_FILE\_OFFSET\_BITS=64

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11  
(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Peak Portability Flags (Continued)

505.mcf\_r: -DSPEC\_LP64  
520.omnetpp\_r: -DSPEC\_LP64  
523.xalancbmk\_r: -DSPEC\_LINUX -DSPEC\_LP64  
525.x264\_r: -DSPEC\_LP64  
531.deepsjeng\_r: -DSPEC\_LP64  
541.leela\_r: -DSPEC\_LP64  
548.exchange2\_r: -DSPEC\_LP64  
557.xz\_r: -DSPEC\_LP64

## Peak Optimization Flags

C benchmarks:

500.perlbench\_r: basepeak = yes  
  
502.gcc\_r: -m32 -flto -z muldefs -Ofast -march=znver4  
-fveclib=AMDLIBM -ffast-math -fstruct-layout=7  
-mllvm -unroll-threshold=50 -fremap-arrays -fstrip-mining  
-mllvm -inline-threshold=1000  
-mllvm -reduce-array-computations=3 -zopt -fgnu89-inline  
-lamdalloc  
  
505.mcf\_r: -m64 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver4 -fveclib=AMDLIBM -ffast-math  
-fstruct-layout=7 -mllvm -unroll-threshold=50  
-fremap-arrays -fstrip-mining  
-mllvm -inline-threshold=1000  
-mllvm -reduce-array-computations=3 -zopt -lamdlibm  
-lflang -lamdalloc

525.x264\_r: basepeak = yes

557.xz\_r: Same as 505.mcf\_r

C++ benchmarks:

520.omnetpp\_r: basepeak = yes  
  
523.xalancbmk\_r: -m32 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-do-block-reorder=aggressive  
-fno-loop-reroll -Ofast -march=znver4 -fveclib=AMDLIBM  
-ffast-math -finline-aggressive

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11

(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

## Peak Optimization Flags (Continued)

523.xalancbmk\_r (continued):

```
-mllvm -unroll-threshold=100  
-mllvm -reduce-array-computations=3 -zopt  
-mllvm -do-block-reorder=aggressive  
-fvirtual-function-elimination -fvisibility=hidden  
-lamdalloc-ext
```

531.deepsjeng\_r: basepeak = yes

541.leela\_r: basepeak = yes

Fortran benchmarks:

```
-m64 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-inline-recursion=4 -Wl,-mllvm -Wl,-lsr-in-nested-loop  
-Wl,-mllvm -Wl,-enable-iv-split -O3 -march=znver4 -fveclib=AMDLIBM  
-ffast-math -fepilog-vectorization-of-inductions  
-mllvm -optimize-strided-mem-cost -floop-transform  
-mllvm -unroll-aggressive -mllvm -unroll-threshold=500 -lamdlibm  
-lflang -lamdalloc
```

## Peak Other Flags

C benchmarks (except as noted below):

-Wno-unused-command-line-argument

502.gcc\_r: -L/usr/lib32 -Wno-unused-command-line-argument

-L/home/work/cpu2017/v118/aocc4/b1/rate/amd\_rate\_aocc400\_genoa\_B\_lib/lib32

C++ benchmarks (except as noted below):

-Wno-unused-command-line-argument

523.xalancbmk\_r: -L/usr/lib32 -Wno-unused-command-line-argument

-L/home/work/cpu2017/v118/aocc4/b1/rate/amd\_rate\_aocc400\_genoa\_B\_lib/lib32

Fortran benchmarks:

-Wno-unused-command-line-argument

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.html>

<http://www.spec.org/cpu2017/flags/aocc400-flags.html>



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL365 Gen11  
(2.25 GHz, AMD EPYC 9634)

SPECrate®2017\_int\_base = 1350

SPECrate®2017\_int\_peak = 1410

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2023

Hardware Availability: Dec-2022

Software Availability: Nov-2022

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.xml>

<http://www.spec.org/cpu2017/flags/aocc400-flags.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.8 on 2022-06-27 22:15:14-0400.

Report generated on 2023-03-02 11:21:00 by CPU2017 PDF formatter v6442.

Originally published on 2023-02-28.