



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro


SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

CPU2017 License: 001176  
Test Sponsor: Supermicro  
Tested by: Supermicro

Test Date: May-2026  
Hardware Availability: Jun-2026  
Software Availability: Apr-2026



### Hardware

CPU Name: Intel Xeon 6980E+  
Max MHz: 3200  
Nominal: 2100  
Enabled: 264 cores, 1 chip  
Orderable: 1 chip  
Cache L1: 64 KB I + 32 KB D on chip per core  
L2: 264 MB I+D on chip per chip, 4 MB shared / 4 cores  
L3: 528 MB I+D on chip per chip  
Other: None  
Memory: 1152 GB (12 x 96 GB 2Rx4 PC5-8000B-R)  
Storage: 1 x 480 GB NVMe SSD  
Other: CPU Cooling: Air

### Software

OS: Red Hat Enterprise Linux 9.7  
Kernel 5.14.0-611.5.1.el9\_7.x86\_64  
Compiler: C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux;  
Fortran: Version 2026.0 of Intel Fortran Compiler for Linux;  
C/C++: Version 2024.2 of Intel oneAPI DPC++/C++ Compiler for Linux;  
Parallel: No  
Firmware: Version 1.5b released May-2026  
File System: xfs  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other: jemalloc memory allocator V5.0.1  
Power Management: BIOS and OS set to prefer performance at the cost of additional power usage.



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP, Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

CPU2017 License: 001176  
Test Sponsor: Supermicro  
Tested by: Supermicro

Test Date: May-2026  
Hardware Availability: Jun-2026  
Software Availability: Apr-2026

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	264	<b>402</b>	<b>1040</b>	402	1040	404	1040	264	369	1140	368	1140	<b>369</b>	<b>1140</b>
502.gcc_r	264	468	798	<b>467</b>	<b>801</b>	466	802	264	373	1000	372	1010	<b>372</b>	<b>1010</b>
505.mcf_r	264	271	1570	<b>271</b>	<b>1570</b>	272	1570	264	271	1570	<b>271</b>	<b>1570</b>	272	1570
520.omnetpp_r	264	566	612	570	608	<b>567</b>	<b>611</b>	264	566	612	570	608	<b>567</b>	<b>611</b>
523.xalancbmk_r	264	<b>159</b>	<b>1750</b>	159	1750	159	1750	264	<b>159</b>	<b>1750</b>	159	1750	159	1750
525.x264_r	264	<b>145</b>	<b>3180</b>	145	3190	146	3180	264	140	3310	140	3310	<b>140</b>	<b>3310</b>
531.deepsjeng_r	264	264	1150	<b>264</b>	<b>1150</b>	264	1150	264	264	1150	<b>264</b>	<b>1150</b>	264	1150
541.leela_r	264	<b>443</b>	<b>986</b>	444	986	443	986	264	<b>443</b>	<b>986</b>	444	986	443	986
548.exchange2_r	264	163	4250	166	4160	<b>165</b>	<b>4190</b>	264	163	4250	166	4160	<b>165</b>	<b>4190</b>
557.xz_r	264	518	551	<b>517</b>	<b>551</b>	517	552	264	518	551	<b>517</b>	<b>551</b>	517	552

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:  
LD\_LIBRARY\_PATH = "/home/cpu2017/lib/intel64:/home/cpu2017/lib/ia32"  
MALLOC\_CONF = "retain:true"

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM memory using Red Hat Enterprise Linux 8.4  
Transparent Huge Pages enabled by default  
Prior to runcpu invocation  
Filesystem page cache synced and cleared with:  
sync; echo 3> /proc/sys/vm/drop\_caches  
runcpu command invoked through numactl i.e.:  
numactl --interleave=all runcpu <etc>

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

### General Notes (Continued)

is mitigated in the system as tested and documented.  
jemalloc, a general purpose malloc implementation  
built with the RedHat Enterprise 7.5, and the system compiler gcc 4.8.5  
sources available from jemalloc.net or <https://github.com/jemalloc/jemalloc/releases>

### Platform Notes

BIOS settings:  
Workload Profile = HPC  
KTI Prefetch = Enable  
Stale AtoS = Disable  
LLC Dead Line Alloc = Disable

Sysinfo program /home/cpu2017/bin/sysinfo  
Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197  
running on 135-179-165.engtw Mon May 25 15:43:01 2026

SUT (System Under Test) info as seen by some common utilities.

-----  
Table of contents  
-----

1. uname -a
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 252 (252-55.el9)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. tuned-adm active
16. sysctl
17. /sys/kernel/mm/transparent\_hugepage
18. /sys/kernel/mm/transparent\_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS

-----  
1. uname -a  
Linux 135-179-165.engtw 5.14.0-611.5.1.el9\_7.x86\_64 #1 SMP PREEMPT\_DYNAMIC Fri Oct 17 14:16:35 EDT 2025  
x86\_64 x86\_64 x86\_64 GNU/Linux  
-----

-----  
2. w  
15:43:02 up 1 min, 1 user, load average: 0.10, 0.06, 0.02  
USER TTY LOGIN@ IDLE JCPU PCPU WHAT  
root tty1 15:41 3.00s 1.11s 0.01s -bash  
-----

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP, Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

## Platform Notes (Continued)

### 3. Username

From environment variable \$USER: root

### 4. ulimit -a

```

real-time non-blocking time (microseconds, -R) unlimited
core file size (blocks, -c) 0
data seg size (kbytes, -d) unlimited
scheduling priority (-e) 0
file size (blocks, -f) unlimited
pending signals (-i) 4640021
max locked memory (kbytes, -l) 64
max memory size (kbytes, -m) unlimited
open files (-n) 1024
pipe size (512 bytes, -p) 8
POSIX message queues (bytes, -q) 819200
real-time priority (-r) 0
stack size (kbytes, -s) unlimited
cpu time (seconds, -t) unlimited
max user processes (-u) 4640021
virtual memory (kbytes, -v) unlimited
file locks (-x) unlimited

```

### 5. sysinfo process ancestry

```

/usr/lib/systemd/systemd rhgb --switched-root --system --deserialize 31
login -- root
-bash
-bash
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=264 -c
ic2026.0-lin-clearwaterforest-rate-20260429.cfg --define smt-on --define cores=264 --define physicalfirst
--define invoke_with_interleave --define drop_caches --reportable --tune base,peak -o all intrate
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=264 --configfile
ic2026.0-lin-clearwaterforest-rate-20260429.cfg --define smt-on --define cores=264 --define physicalfirst
--define invoke_with_interleave --define drop_caches --reportable --tune base,peak --output_format all
--nopower --runmode rate --tune base:peak --size refrate intrate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2017.001/templogs/preenv.intrate.001.0.log --lognum 001.0 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2017

```

### 6. /proc/cpuinfo

```

model name      : Intel(R) Xeon(R) 6980E+
vendor_id      : GenuineIntel
cpu family     : 6
model          : 221
stepping       : 1
microcode      : 0x1000120
bugs           : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi spectre_v2_user
cpu cores      : 264
siblings       : 264
1 physical ids (chips)
264 processors (hardware threads)
physical id 0: core ids 0-87,128-215,256-343
physical id 0: apicids
0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38,40,42,44,46,48,50,52,54,56,58,60,62,64,66,68,70,72
,74,76,78,80,82,84,86,88,90,92,94,96,98,100,102,104,106,108,110,112,114,116,118,120,122,124,126,128,130,1
32,134,136,138,140,142,144,146,148,150,152,154,156,158,160,162,164,166,168,170,172,174,256,258,260,262,26
4,266,268,270,272,274,276,278,280,282,284,286,288,290,292,294,296,298,300,302,304,306,308,310,312,314,316
,318,320,322,324,326,328,330,332,334,336,338,340,342,344,346,348,350,352,354,356,358,360,362,364,366,368,

```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

### Platform Notes (Continued)

370, 372, 374, 376, 378, 380, 382, 384, 386, 388, 390, 392, 394, 396, 398, 400, 402, 404, 406, 408, 410, 412, 414, 416, 418, 420, 422, 424, 426, 428, 430, 512, 514, 516, 518, 520, 522, 524, 526, 528, 530, 532, 534, 536, 538, 540, 542, 544, 546, 548, 550, 552, 554, 556, 558, 560, 562, 564, 566, 568, 570, 572, 574, 576, 578, 580, 582, 584, 586, 588, 590, 592, 594, 596, 598, 600, 602, 604, 606, 608, 610, 612, 614, 616, 618, 620, 622, 624, 626, 628, 630, 632, 634, 636, 638, 640, 642, 644, 646, 648, 650, 652, 654, 656, 658, 660, 662, 664, 666, 668, 670, 672, 674, 676, 678, 680, 682, 684, 686

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

#### 7. lscpu

From lscpu from util-linux 2.37.4:

```

Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:          52 bits physical, 48 bits virtual
Byte Order:             Little Endian
CPU(s):                 264
On-line CPU(s) list:   0-263
Vendor ID:              GenuineIntel
BIOS Vendor ID:        Intel(R) Corporation
Model name:             Intel(R) Xeon(R) 6980E+
BIOS Model name:       Intel(R) Xeon(R) 6980E+
CPU family:             6
Model:                  221
Thread(s) per core:    1
Core(s) per socket:    264
Socket(s):              1
Stepping:               1
BogoMIPS:               4200.00
Flags:                  fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                        pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                        pdpe1gb rdtscp lm constant_tsc art arch_perfmon bts rep_good nopl
                        xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                        pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma
                        cx16 xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt
                        tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
                        3dnowprefetch cpuid_fault epb cat_l3 cat_l2 cdp_l3 intel_ppin
                        cdp_l2 ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow
                        flexpriority ept vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep
                        bmi2 erms invpcid cqm rdt_a rdseed adx smap clflushopt clwb
                        intel_pt sha_ni xsaveopt xsavec xgetbv1 xsaves cqm_llc
                        cqm_occup_llc cqm_mbm_total cqm_mbm_local split_lock_detect
                        user_shstk avx_vnni lam wbnoinvd dtherm ida arat pln pts vmmi umip
                        pku ospke waitpkg gfni vaes vpclmulqdq tme rdpid bus_lock_detect
                        cldemote movdiri movdir64b enqcmd fsrm md_clear serialize pconfig
                        arch_lbr ibt flush_lld arch_capabilities
Virtualization:         VT-x
L1d cache:              8.3 MiB (264 instances)
L1i cache:              16.5 MiB (264 instances)
L2 cache:               264 MiB (66 instances)
L3 cache:               528 MiB (1 instance)
NUMA node(s):          3
NUMA node0 CPU(s):     0-87
NUMA node1 CPU(s):     88-175
NUMA node2 CPU(s):     176-263
Vulnerability Gather data sampling: Not affected
Vulnerability Indirect target selection: Not affected
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf:     Not affected
Vulnerability Mds:      Not affected

```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

### Platform Notes (Continued)

Vulnerability Meltdown:	Not affected
Vulnerability Mmio stale data:	Not affected
Vulnerability Reg file data sampling:	Not affected
Vulnerability Retbleed:	Not affected
Vulnerability Spec rstack overflow:	Not affected
Vulnerability Spec store bypass:	Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1:	Mitigation; usercopy/swaps barriers and __user pointer sanitization
Vulnerability Spectre v2:	Mitigation; Enhanced / Automatic IBRS; IBPB conditional; PBRBS-eIBRS Not affected; BHI BHI_DIS_S
Vulnerability Srbds:	Not affected
Vulnerability Tsa:	Not affected
Vulnerability Tsx async abort:	Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	32K	8.3M	8	Data	1	64	1	64
L1i	64K	16.5M	8	Instruction	1	128	1	64
L2	4M	264M	16	Unified	2	4096	1	64
L3	528M	528M	16	Unified	3	540672	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

```

available: 3 nodes (0-2)
node 0 cpus: 0-87
node 0 size: 386041 MB
node 0 free: 384464 MB
node 1 cpus: 88-175
node 1 size: 387003 MB
node 1 free: 384706 MB
node 2 cpus: 176-263
node 2 size: 387023 MB
node 2 free: 385842 MB
node distances:
node  0  1  2
0:  10 15 17
1:  15 10 15
2:  17 15 10

```

9. /proc/meminfo

MemTotal: 1187911072 kB

10. who -r

run-level 3 May 25 15:41

11. Systemd service manager version: systemd 252 (252-55.e19)

Default Target	Status
multi-user	running

12. Services, from systemctl list-unit-files

STATE	UNIT FILES
enabled	ModemManager NetworkManager NetworkManager-dispatcher NetworkManager-wait-online accounts-daemon atd auditd avahi-daemon bluetooth chronyd crond cups dbus-broker firewalld gdm getty@ insights-client-boot irqbalance iscsi-onboot iscsi-starter kdump libstoragemgmt low-memory-monitor lvm2-monitor mcelog mdmonitor microcode multipathd nis-domainname

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

### Platform Notes (Continued)

```

enabled-runtime  nvmeofc-boot-connections ostree-remount qemu-guest-agent rhsmcertd rsyslog rtkit-daemon
disabled         selinux-autorelabel-mark smartd sshd sssd switcheroo-control systemd-boot-update
                 systemd-network-generator systemd-pstore tuned udisks2 upower vgauthd vmtoolsd
                 systemd-remount-fs
indirect         arp-ethers blk-availability brltty canberra-system-bootup canberra-system-shutdown
                 canberra-system-shutdown-reboot chrony-wait chronyd-restricted cni-dhcp console-getty
                 cpupower cups-browsed dbus-daemon debug-shell dnf-system-upgrade dnsmasq iprdump iprinit
                 iprupdate iscsi-init iscsid iscsiuiio kpatch kvm_stat ledmon lvm-devices-import
                 man-db-restart-cache-update netavark-dhcp-proxy netavark-firewalld-reload nftables
                 nvmf-autoconnect ostree-readonly-sysroot-migration ostree-state-overlay@ podman
                 podman-auto-update podman-clean-transient podman-kube@ podman-restart psacct ras-mc-ctl
                 rasdaemon rdisc rhod rhsm rhsm-facts rpmdb-rebuild selinux-check-proper-disable
                 serial-getty@ speech-dispatcherd sshd-keygen@ systemd-boot-check-no-failures
                 systemd-sysexit tuned-ppd wpa_supplicant
                 indirect iscsi spice-vdagentd sssd-autofs sssd-kcm sssd-nss sssd-pac sssd-pam sssd-ssh sssd-sudo
                 systemd-sysupdate systemd-sysupdate-reboot

```

```

-----
13. Linux kernel boot-time arguments, from /proc/cmdline
BOOT_IMAGE=(hd0,gpt2)/vmlinuz-5.14.0-611.5.1.el9_7.x86_64
root=/dev/mapper/rhel_135--180--133-root
ro
resume=/dev/mapper/rhel_135--180--133-swap
rd.lvm.lv=rhel_135-180-133/root
rd.lvm.lv=rhel_135-180-133/swap
rhgb
quiet
crashkernel=1G-2G:192M,2G-64G:256M,64G-:512M

```

```

-----
14. cpupower frequency-info
analyzing CPU 226:
  Unable to determine current policy
  boost state support:
    Supported: yes
    Active: yes

```

```

-----
15. tuned-adm active
Current active profile: throughput-performance

```

```

-----
16. sysctl
kernel.numa_balancing          1
kernel.randomize_va_space      2
vm.compaction_proactiveness    20
vm.dirty_background_bytes      0
vm.dirty_background_ratio     10
vm.dirty_bytes                 0
vm.dirty_expire_centisecs     3000
vm.dirty_ratio                 40
vm.dirty_writeback_centisecs   500
vm.dirtytime_expire_seconds   43200
vm.extfrag_threshold           500
vm.min_unmapped_ratio         1
vm.nr_hugepages                0
vm.nr_hugepages_mempolicy     0
vm.nr_overcommit_hugepages    0
vm.swappiness                  10
vm.watermark_boost_factor     15000

```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

### Platform Notes (Continued)

```
vm.watermark_scale_factor      10
vm.zone_reclaim_mode           0
```

```
-----
17. /sys/kernel/mm/transparent_hugepage
defrag          always defer defer+madvise [madvise] never
enabled         [always] madvise never
hpage_pmd_size 2097152
shmem_enabled   always within_size advise [never] deny force
-----
```

```
-----
18. /sys/kernel/mm/transparent_hugepage/khugepaged
alloc_sleep_millisecs  60000
defrag                  1
max_ptes_none          511
max_ptes_shared        256
max_ptes_swap          64
pages_to_scan          4096
scan_sleep_millisecs  10000
-----
```

```
-----
19. OS release
From /etc/*-release /etc/*-version
os-release      Red Hat Enterprise Linux 9.7 (Plow)
redhat-release Red Hat Enterprise Linux release 9.7 (Plow)
system-release Red Hat Enterprise Linux release 9.7 (Plow)
-----
```

```
-----
20. Disk information
SPEC is set to: /home/cpu2017
Filesystem                                Type  Size  Used Avail Use% Mounted on
/dev/mapper/rhel_135--180--133-home xfs   372G  37G  336G  10% /home
-----
```

```
-----
21. /sys/devices/virtual/dmi/id
Vendor:      Supermicro
Product:     Super Server
Product Family: Family
Serial:      0123456789
-----
```

```
-----
22. dmidecode
Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
"DMTF SMBIOS" standard.
Memory:
  12x SK Hynix HMCGM4AMBRB970N 96 GB 2 rank 8000
-----
```

```
-----
23. BIOS
(This section combines info from /sys/devices and dmidecode.)
BIOS Vendor:      American Megatrends International, LLC.
BIOS Version:     1.5b
BIOS Date:        05/04/2026
BIOS Revision:    5.35
-----
```



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP, Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

## Compiler Version Notes

=====  
C | 502.gcc\_r(peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on IA-32, Version 2024.2.1 Build 20240711  
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.  
=====

=====  
C | 500.perlbench\_r(base, peak) 502.gcc\_r(base) 505.mcf\_r(base, peak) 525.x264\_r(base, peak)  
| 557.xz\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2026.0.0 Build 20260331  
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.  
=====

=====  
C | 502.gcc\_r(peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on IA-32, Version 2024.2.1 Build 20240711  
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.  
=====

=====  
C | 500.perlbench\_r(base, peak) 502.gcc\_r(base) 505.mcf\_r(base, peak) 525.x264\_r(base, peak)  
| 557.xz\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2026.0.0 Build 20260331  
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.  
=====

=====  
C++ | 520.omnetpp\_r(base, peak) 523.xalancbmk\_r(base, peak) 531.deepsjeng\_r(base, peak)  
| 541.leela\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2026.0.0 Build 20260331  
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.  
=====

=====  
Fortran | 548.exchange2\_r(base, peak)  
=====

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2026.0.0 Build 20260331  
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.  
=====

## Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

## Base Portability Flags

500.perlbench\_r: -DSPEC\_LP64 -DSPEC\_LINUX\_X64  
502.gcc\_r: -DSPEC\_LP64  
505.mcf\_r: -DSPEC\_LP64  
520.omnetpp\_r: -DSPEC\_LP64  
523.xalancbmk\_r: -DSPEC\_LP64 -DSPEC\_LINUX  
525.x264\_r: -DSPEC\_LP64  
531.deepsjeng\_r: -DSPEC\_LP64  
541.leela\_r: -DSPEC\_LP64  
548.exchange2\_r: -DSPEC\_LP64  
557.xz\_r: -DSPEC\_LP64

## Base Optimization Flags

### C benchmarks:

-w -std=c11 -m64 -Wl,-z,muldefs -xclearwaterforest -O3 -ffast-math  
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4  
-L/home/specdev/intel-compilers/compiler/latest/lib -lqkmallo

### C++ benchmarks:

-w -std=c++14 -m64 -Wl,-z,muldefs -xclearwaterforest -O3  
-ffast-math -flto -mfpmath=sse -funroll-loops  
-qopt-mem-layout-trans=4 -fdelayed-template-parsing  
-L/home/specdev/intel-compilers/compiler/latest/lib -lqkmallo

### Fortran benchmarks:

-w -m64 -Wl,-z,muldefs -xclearwaterforest -O3 -ffast-math -flto  
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4  
-nostandard-realloc-lhs -align array32byte -auto  
-L/home/specdev/intel-compilers/compiler/latest/lib -lqkmallo

## Peak Compiler Invocation

### C benchmarks (except as noted below):

icx

502.gcc\_r: icx

### C++ benchmarks:

icpx

### Fortran benchmarks:

ifx



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP, Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

## Peak Portability Flags

```
500.perlbench_r: -DSPEC_LP64 -DSPEC_LINUX_X64
502.gcc_r: -D_FILE_OFFSET_BITS=64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LP64 -DSPEC_LINUX
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64
```

## Peak Optimization Flags

C benchmarks:

```
500.perlbench_r: -w -std=c11 -m64 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profddata(pass 2) -xCORE-AVX2 -flto
-Ofast -ffast-math -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-strict-overflow
-fno-strict-aliasing
-L/home/specdev/intel-compilers/compiler/latest/lib
-lqkmalloc

502.gcc_r: -m32 -L/home/specdev/intel-compilers/compiler/2024.2/lib32
-std=gnu89 -Wl,-z,muldefs -fprofile-generate(pass 1)
-fprofile-use=default.profddata(pass 2) -xCORE-AVX2 -flto
-Ofast -ffast-math -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -L/usr/local/jemalloc32-5.0.1/lib
-ljemalloc

505.mcf_r: basepeak = yes

525.x264_r: -w -std=c11 -m64 -Wl,-z,muldefs -xclearwaterforest
-Ofast -ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-alias
-L/home/specdev/intel-compilers/compiler/latest/lib
-lqkmalloc

557.xz_r: basepeak = yes
```

C++ benchmarks:

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Supermicro

SuperServer SYS-112HA-TN  
(X14SBH-AP , Intel Xeon 6980E+)

SPECrate®2017\_int\_base = 1280

SPECrate®2017\_int\_peak = 1320

**CPU2017 License:** 001176  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** May-2026  
**Hardware Availability:** Jun-2026  
**Software Availability:** Apr-2026

## Peak Optimization Flags (Continued)

520.omnetpp\_r: basepeak = yes

523.xalancbmk\_r: basepeak = yes

531.deepsjeng\_r: basepeak = yes

541.leela\_r: basepeak = yes

Fortran benchmarks:

548.exchange2\_r: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic2026-official-linux64.html>

<http://www.spec.org/cpu2017/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic2026-official-linux64.xml>

<http://www.spec.org/cpu2017/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.9 on 2026-05-25 03:43:01-0400.

Report generated on 2026-06-16 17:50:16 by CPU2017 PDF formatter v6716.

Originally published on 2026-06-16.