SPEC CPU®2026 Floating Point Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Lenovo Global Technology

(Test Sponsor: Ampere Computing, Inc.)

ThinkSystem HR330A
(3.00 GHz Ampere eMAG 8180)

SPECspeed®2026_fp_base =	1.00
SPECspeed®2026_fp_energy_base =	1.00
SPECspeed®2026_fp_peak =	1.04
SPECspeed®2026_fp_energy_peak =	1.02

CPU2026 License: 6412
Test Sponsor: Ampere Computing, Inc.
Tested by: Ampere Computing, Inc.

Test Date: Feb-2026
Hardware Availability: Apr-2019
Software Availability: Aug-2025



Hardware

CPU Name: Ampere eMAG 8180
Max MHz: 3300
Nominal: 3000
Enabled: 32 cores, 1 chip
Orderable: 1 chips

(Continued on next page)

Software

OS: Ubuntu 24.04.1 LTS kernel 6.8.0 (64KB pages)
Compiler: C/C++/Fortran: Version 15.2.0 of GCC
Compiler Category: Community
Firmware: Version 1.12 released Nov-2019
File System: ext4

(Continued on next page)

SPEC CPU®2026 Floating Point Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Lenovo Global Technology

(Test Sponsor: Ampere Computing, Inc.)

ThinkSystem HR330A (3.00 GHz Ampere eMAG 8180)

SPECspeed®2026_fp_base =	1.00
SPECspeed®2026_fp_energy_base =	1.00
SPECspeed®2026_fp_peak =	1.04
SPECspeed®2026_fp_energy_peak =	1.02

CPU2026 License: 6412
Test Sponsor: Ampere Computing, Inc.
Tested by: Ampere Computing, Inc.

Test Date: Feb-2026
Hardware Availability: Apr-2019
Software Availability: Aug-2025

Hardware (Continued)

Cache L1:	32 KB I + 32 KB D on chip per core
L2:	4 MB I+D on chip per chip (256 KB shared / 2 cores)
L3:	32 MB I+D on chip per chip
Other:	None
Memory:	128 GB (8 x 16 GB 2Rx4 PC4-2666V-R)
Storage:	1 x 480 GB SATA SSD
Cooling:	Air
Other:	None

Software (Continued)

System State:	Run level 5 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	jemalloc v5.3+, commit hash 1972241
Power Management:	OS CPU governor set to "performance"

Power

Max. Power (W):	299.15
Idle Power (W):	76.7
Min. Temperature (C):	20.81
Elevation (m):	60
Line Standard:	120 V / 60 Hz / 1 phase / 2 wire
Provisioning:	Line powered

Power Settings

Management FW:	Version 11.05.111 of Falcon BMC
Memory Mode:	Normal

Power-Relevant Hardware

Power Supply:	1 x 550 W (non-redundant)
Details:	Lenovo 03LD785 550 Watt High Efficiency Platinum AC Power Supply
Backplane:	N/A
Other Storage:	N/A
Storage Model #s:	1 x Lenovo 01PE965 (480GB SATA SSD) connected to on-board HBA
NICs Installed:	1 x Lenovo 01PE857 @ 10 GbE (2 ports ethernet)
NICs Enabled (FW/OS):	2 / 1
NICs Connected/Speed:	1 @ 1 Gbps
Other HW Model #s:	--

Power Analyzer

Power Analyzer:	cpu-reference-ptd:8000
Hardware Vendor:	Yokogawa
Model:	WT-310
Serial Number:	T11733285
Input Connection:	Serial over USB
Metrology Institute:	NIST
Calibration By:	Yokogawa USA
Calibration Label:	T126622
Calibration Date:	13-Aug-2025
PTDaemon® Version:	1.11.3 (0c074d7d; 2025-10-15)
Setup Description:	Directly connected
Current Ranges Used:	5A
Voltage Range Used:	150V

Temperature Meter

Temperature Meter:	cpu-reference-ptd:9000
Hardware Vendor:	PCSensor
Model:	USB9097+DS18B20
Serial Number:	--
Input Connection:	USB
PTDaemon Version:	1.11.3 (0c074d7d; 2025-10-15)
Setup Description:	In front of SUT front panel primary air inlet

SPEC CPU®2026 Floating Point Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Lenovo Global Technology

(Test Sponsor: Ampere Computing, Inc.)

ThinkSystem HR330A (3.00 GHz Ampere eMAG 8180)

SPECspeed®2026_fp_base = 1.00

SPECspeed®2026_fp_energy_base = 1.00

SPECspeed®2026_fp_peak = 1.04

SPECspeed®2026_fp_energy_peak = 1.02

CPU2026 License: 6412
Test Sponsor: Ampere Computing, Inc.
Tested by: Ampere Computing, Inc.

Test Date: Feb-2026
Hardware Availability: Apr-2019
Software Availability: Aug-2025

Base Results Table

Benchmark	Threads	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power
800.pot3d_s	32	**673**	**1.00**	**126**	**1.00**	**187**	**196**	673	1.00	126	1.00	187	193	672	1.00	126	1.00	187	195
803.sph_exa_s	32	**1238**	**1.00**	**209**	**1.00**	**169**	**212**	1240	0.998	209	1.00	169	212	1234	1.00	208	1.00	169	213
809.cactus_s	32	1123	0.999	203	0.999	181	213	**1121**	**1.00**	**202**	**1.00**	**181**	**213**	1119	1.00	202	1.00	181	214
811.tealeaf_s	32	**557**	**1.00**	**140**	**1.00**	**251**	**299**	563	0.989	144	0.968	256	297	557	1.00	142	0.987	254	299
816.nab_s	32	**1126**	**1.00**	**193**	**1.00**	**171**	**183**	1127	0.999	193	0.999	172	183	1125	1.00	193	1.00	171	182
820.cloverleaf_s	32	**857**	**1.00**	**166**	**1.00**	**194**	**230**	855	1.00	166	1.00	194	227	857	1.00	166	1.00	194	230
822.palm_s	32	1229	0.999	207	1.00	168	221	1228	1.00	207	1.00	168	225	**1228**	**1.00**	**207**	**1.00**	**169**	**221**
849.fotonik3d_s	32	659	1.00	123	1.00	186	203	**659**	**1.00**	**123**	**1.00**	**187**	**204**	656	1.01	123	1.00	187	204
857.namd_s	32	1451	1.00	265	1.00	183	220	**1451**	**1.00**	**266**	**1.00**	**183**	**224**	1451	1.00	266	1.00	183	219
865.roms_s	32	1089	1.00	232	0.998	213	246	**1090**	**1.00**	**231**	**1.00**	**212**	**249**	1091	0.999	232	0.999	212	235
867.nest_s	32	**2159**	**1.00**	**386**	**1.00**	**179**	**280**	2138	1.01	385	1.00	180	285	2164	0.998	388	0.996	179	268
872.marian_s	32	1081	1.00	160	1.01	148	221	**1082**	**1.00**	**161**	**1.00**	**149**	**233**	1084	0.998	161	1.00	148	222
881.neutron_s	32	814	1.00	132	1.00	162	238	**814**	**1.00**	**131**	**1.00**	**161**	**221**	813	1.00	132	1.00	162	224

SPECspeed®2026_fp_base = 1.00

SPECspeed®2026_fp_energy_base = 1.00

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Peak Results Table

Benchmark	Threads	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power	Seconds	Ratio	Energy (kJ)	Energy Ratio	Average Power	Maximum Power
800.pot3d_s	32	**673**	**1.00**	**126**	**1.00**	**187**	**196**	673	1.00	126	1.00	187	193	672	1.00	126	1.00	187	195
803.sph_exa_s	32	1153	1.07	196	1.07	170	215	1159	1.07	197	1.06	170	215	**1157**	**1.07**	**196**	**1.07**	**170**	**215**
809.cactus_s	32	**1082**	**1.04**	**202**	**1.00**	**187**	**222**	1081	1.04	201	1.01	186	222	1083	1.04	202	1.00	186	218
811.tealeaf_s	32	**557**	**1.00**	**140**	**1.00**	**251**	**299**	563	0.989	144	0.968	256	297	557	1.00	142	0.987	254	299
816.nab_s	32	**1095**	**1.03**	**183**	**1.05**	**167**	**182**	1096	1.03	183	1.05	167	184	1095	1.03	183	1.06	167	178
820.cloverleaf_s	32	**857**	**1.00**	**166**	**1.00**	**194**	**230**	855	1.00	166	1.00	194	227	857	1.00	166	1.00	194	230
822.palm_s	32	**1120**	**1.10**	**196**	**1.06**	**175**	**224**	1118	1.10	196	1.06	175	220	1120	1.10	196	1.06	175	220
849.fotonik3d_s	32	**659**	**1.00**	**120**	**1.03**	**183**	**201**	656	1.01	120	1.03	183	201	659	1.00	120	1.03	182	201
857.namd_s	32	1433	1.01	265	1.00	185	228	**1434**	**1.01**	**265**	**1.00**	**185**	**235**	1434	1.01	264	1.00	184	218
865.roms_s	32	**1077**	**1.01**	**232**	**0.998**	**215**	**260**	1077	1.01	231	1.00	215	248	1076	1.01	231	1.00	215	258
867.nest_s	32	2117	1.02	386	1.00	182	279	2119	1.02	385	1.00	182	267	**2118**	**1.02**	**387**	**1.00**	**183**	**272**
872.marian_s	32	929	1.16	152	1.06	164	261	**921**	**1.17**	**152**	**1.06**	**164**	**272**	919	1.18	150	1.07	163	242
881.neutron_s	32	786	1.04	127	1.04	161	230	**785**	**1.04**	**126**	**1.04**	**161**	**230**	785	1.04	126	1.04	161	230

SPECspeed®2026_fp_peak = 1.04

SPECspeed®2026_fp_energy_peak = 1.02

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/usr/lib64/:/usr/lib/:/lib64:/home/mjm/jemalloc/lib"
OMP_STACKSIZE = "120M"
```

General Notes

```
jemalloc is a general purpose malloc(3) implementation that emphasizes
fragmentation avoidance and scalable concurrency support.
```

(Continued on next page)

General Notes (Continued)

```
sources available from https://github.com/jemalloc/jemalloc/tree/1972241
and built via "./configure --with-lg-quantum=3" which used system gcc-14 -O3

This benchmark result is intended to provide perspective on
past power and/or performance using the historical hardware
and/or software described on this result page.

The system as described on this result page was formerly
generally available. At the time of this publication, it may
not be shipping, and/or may not be supported, and/or may fail
to meet other tests of General Availability described in the
SPEC OSG Policy document, http://www.spec.org/osg/policy.html

This measured result may not be representative of the result
that would be measured were this benchmark run with hardware
and software available as of the publication date.
```

Platform Notes

```
 Sysinfo program /home/mjm/RC2/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on emag Sat Feb 21 05:13:15 2026

 SUT (System Under Test) info as seen by some common utilities.

 ------------------------------------------------------------
 Table of contents
 ------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 255 (255.4-1ubuntu8.8)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. sysctl
```

(Continued on next page)

Platform Notes (Continued)

```
 15. /sys/kernel/mm/transparent_hugepage
 16. /sys/kernel/mm/transparent_hugepage/khugepaged
 17. OS release
 18. Disk information
 19. /sys/devices/virtual/dmi/id
 20. dmidecode
 21. BIOS
------------------------------------------------------------

------------------------------------------------------------
 1. uname -srvm
   Linux 6.8.0 #1 SMP PREEMPT_DYNAMIC Fri Feb 28 00:25:30 UTC 2025 aarch64

------------------------------------------------------------
 2. w
    05:13:15 up 64 days,  5:38,  2 users,  load average: 1.45, 14.34, 24.62
   USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT
   mjm              10.13.114.186    28Jan26 23:10m  0.00s  0.02s sshd: mjm [priv]

------------------------------------------------------------
 3. Username
   From environment variable $USER:  mjm

------------------------------------------------------------
 4. ulimit -a
   time(seconds)        unlimited
   file(blocks)         unlimited
   data(kbytes)         unlimited
   stack(kbytes)        unlimited
   coredump(blocks)     0
   memory(kbytes)       unlimited
   locked memory(kbytes) 16691648
   process              128681
   nofiles              1024
   vmemory(kbytes)      unlimited
   locks                unlimited
   rtprio               0

------------------------------------------------------------
 5. sysinfo process ancestry
  /usr/lib/systemd/systemd --system --deserialize=66
  SCREEN
  -bin/tcsh
 runcpu --flagsurl=$SPEC/config/flags/gcc.xml -c emag-golden --reportable -n 3 --tune=base,peak --power
    fpspeed
```

(Continued on next page)

Platform Notes (Continued)

```
 runcpu --flagsurl $SPEC/config/flags/gcc.xml --configfile emag-golden --reportable --iterations 3 --tune
   base,peak --power --runmode speed --tune base:peak --size refspeed fpspeed --nopreenv --note-preenv
   --logfile $SPEC/tmp/CPU2026.067/templogs/preenv.fpspeed.067.0.log --lognum 067.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo -f
$SPEC = /home/mjm/RC2

------------------------------------------------------------
6. /proc/cpuinfo
    CPU implementer : 0x50
    CPU architecture: 8
    CPU variant     : 0x3
    CPU part        : 0x000
    CPU revision    : 2
    Features        : fp asimd evtstrm aes pmull sha1 sha2 crc32 cpuid

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.39.3:
  Architecture:                         aarch64
  CPU op-mode(s):                       32-bit, 64-bit
  Byte Order:                           Little Endian
  CPU(s):                               32
  On-line CPU(s) list:                  0-31
  Vendor ID:                            APM
  Model name:                           -
  Model:                                2
  Thread(s) per core:                   1
  Core(s) per socket:                   32
  Socket(s):                            1
  Stepping:                             0x3
  Frequency boost:                      disabled
  CPU(s) scaling MHz:                   100%
  CPU max MHz:                          2911.7639
  CPU min MHz:                          363.9700
  BogoMIPS:                             80.00
  Flags:                                fp asimd evtstrm aes pmull sha1 sha2 crc32 cpuid
  L1d cache:                            1 MiB (32 instances)
  L1i cache:                            1 MiB (32 instances)
  L2 cache:                             4 MiB (16 instances)
  NUMA node(s):                         1
  NUMA node0 CPU(s):                    0-31
  Vulnerability Gather data sampling:   Not affected
  Vulnerability Itlb multihit:          Not affected
  Vulnerability L1tf:                   Not affected
```

(Continued on next page)

Platform Notes (Continued)

```
  Vulnerability Mds:                 Not affected
  Vulnerability Meltdown:            Mitigation; PTI
  Vulnerability Mmio stale data:     Not affected
  Vulnerability Retbleed:            Not affected
  Vulnerability Spec rstack overflow: Not affected
  Vulnerability Spec store bypass:   Vulnerable
  Vulnerability Spectre v1:          Mitigation; __user pointer sanitization
  Vulnerability Spectre v2:          Vulnerable
  Vulnerability Srbds:               Not affected
  Vulnerability Tsx async abort:     Not affected

From lscpu --cache:
     NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL SETS PHY-LINE COHERENCY-SIZE
     L1d       32K       1M    8 Data            1
     L1i       32K       1M    8 Instruction     1
     L2       256K       4M   32 Unified         2

------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 1 nodes (0)
  node 0 cpus: 0-31
  node 0 size: 130403 MB
  node 0 free: 104553 MB
  node distances:
  node   0
    0:  10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       133533376 kB

------------------------------------------------------------
10. who -r
  run-level 5 Dec 18 23:35

------------------------------------------------------------
11. Systemd service manager version: systemd 255 (255.4-1ubuntu8.8)
  Default Target  Status
  graphical       running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled         ModemManager apparmor apport blk-availability cloud-config cloud-final cloud-init
```

(Continued on next page)

Platform Notes (Continued)

```
                cloud-init-local console-setup cron dmesg e2scrub_reap finalrd getty@ grub-common
               grub-initrd-fallback keyboard-setup lvm2-monitor multipathd networkd-dispatcher open-iscsi
               open-vm-tools pollinate power-profiles-daemon rsyslog secureboot-db setvtrgb snapd sysstat
                 systemd-networkd systemd-networkd-wait-online systemd-pstore systemd-resolved
               systemd-timesyncd ua-reboot-cmds ubuntu-advantage udisks2 ufw unattended-upgrades vgauth
  enabled-runtime  netplan-ovs-cleanup systemd-fsck-root systemd-remount-fs
 disabled        console-getty debug-shell ipmievd iscsid nftables rsync ssh systemd-boot-check-no-failures
                   systemd-confext systemd-network-generator systemd-networkd-wait-online@
               systemd-pcrlock-file-system systemd-pcrlock-firmware-code systemd-pcrlock-firmware-config
                    systemd-pcrlock-machine-id systemd-pcrlock-make-policy
                systemd-pcrlock-secureboot-authority systemd-pcrlock-secureboot-policy systemd-sysext
                    systemd-time-wait-sync
  generated         openipmi perlbal
  indirect          serial-getty@ systemd-sysupdate systemd-sysupdate-reboot uuidd
 masked          cryptdisks cryptdisks-early hwclock multipath-tools-boot screen-cleanup sudo x11-common

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.8.0
  root=UUID=16268541-06d0-4374-97ca-2d512d4db26f
  ro
  cma=1024M
  iommu.passthrough=1

------------------------------------------------------------
14. sysctl
  kernel.numa_balancing               0
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                     20
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                      60
  vm.watermark_boost_factor       15000
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                0
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
15. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         always [madvise] never
  hpage_pmd_size  536870912
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
16. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none            8191
  max_ptes_shared          4096
  max_ptes_swap            1024
  pages_to_scan           65536
  scan_sleep_millisecs    10000

------------------------------------------------------------
17. OS release
  From /etc/*-release /etc/*-version
  os-release Ubuntu 24.04.1 LTS

------------------------------------------------------------
18. Disk information
SPEC is set to: /home/mjm/RC2
  Filesystem     Type  Size  Used Avail Use% Mounted on
  /dev/sda2      ext4  439G  184G  232G  45% /

------------------------------------------------------------
19. /sys/devices/virtual/dmi/id
    Vendor:         Lenovo
    Product:        HR330A            7X33CTO1WW
    Product Family: Lenovo ThinkSystem HR330A/HR350A

------------------------------------------------------------
20. dmidecode
  Additional information from dmidecode 3.5 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
  "DMTF SMBIOS" standard.
  Memory:
    8x Samsung M393A2K43CB2-CTD 16 GB 2 rank 2667
```

(Continued on next page)

Platform Notes (Continued)

```
 ------------------------------------------------------------
 21. BIOS
 (This section combines info from /sys/devices and dmidecode.)
    BIOS Vendor:       LENOVO
    BIOS Version:      HVE104N-1.12
    BIOS Date:         11/29/2019
    BIOS Revision:     1.12
    Firmware Revision: 1.7
```

Power Settings Notes

```
OS CPU governor was set using the command:
echo performance | tee /sys/devices/system/cpu/cpu*/cpufreq/scaling_governor
```

Compiler Version Notes

```
==============================================================================
C       | 811.tealeaf_s(base, peak) 816.nab_s(base, peak) 881.neutron_s(base,
        | peak)
------------------------------------------------------------------------------
gcc (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------

==============================================================================
C++     | 803.sph_exa_s(base, peak) 857.namd_s(base, peak) 867.nest_s(base,
        | peak) 872.marian_s(base, peak)
------------------------------------------------------------------------------
g++ (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base pass 0, peak pass 1, peak pass 2)
------------------------------------------------------------------------------
g++ (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
```

(Continued on next page)

Compiler Version Notes (Continued)

```
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base pass 0, peak pass 1, peak pass 2)
------------------------------------------------------------------------------
gcc (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base pass 0, peak pass 1, peak pass 2)
------------------------------------------------------------------------------
g++ (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base pass 0, peak pass 1, peak pass 2)
------------------------------------------------------------------------------
gcc (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------

==============================================================================
Fortran | 800.pot3d_s(base, peak) 820.cloverleaf_s(base, peak)
        | 822.palm_s(base, peak) 849.fotonik3d_s(base, peak) 865.roms_s(base,
        | peak)
------------------------------------------------------------------------------
GNU Fortran (GCC) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions.  There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
gcc

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

Benchmarks using both C and C++:
g++ gcc

Base Portability Flags

800.pot3d_s: -DSPEC_SUPPRESS_LOCAL_AND_REDUCE -DSPEC_LP64
803.sph_exa_s: -DSPEC_LP64
809.cactus_s: -DSPEC_LP64
811.tealeaf_s: -DSPEC_LP64
816.nab_s: -DSPEC_LP64
820.cloverleaf_s: -DSPEC_LP64
822.palm_s: -DSPEC_LP64
849.fotonik3d_s: -DSPEC_LP64
857.namd_s: -DSPEC_LP64
865.roms_s: -DSPEC_LP64
867.nest_s: -fno-finite-math-only -DSPEC_LP64
872.marian_s: -DSPEC_LP64
881.neutron_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:
-mabi=lp64 -std=c18 -g -O3 -ffast-math -mcpu=native -flto=16
-fopenmp -DSPEC_OPENMP -L/home/mjm/jemalloc/lib -ljemalloc

C++ benchmarks:

803.sph_exa_s: -mabi=lp64 -std=c++17 -g -O3 -ffast-math -mcpu=native
-flto=16 -fopenmp -DSPEC_OPENMP -L/home/mjm/jemalloc/lib
-ljemalloc

(Continued on next page)

Base Optimization Flags (Continued)

857.namd_s: Same as 803.sph_exa_s

867.nest_s: Same as 803.sph_exa_s

872.marian_s: -mabi=lp64 -std=c++17 -g -O3 -ffast-math -mcpu=native
-flto=16 -pthread -L/home/mjm/jemalloc/lib -ljemalloc

Fortran benchmarks:

800.pot3d_s: -mabi=lp64 -std=f2018 -g -O3 -ffast-math -mcpu=native
-flto=16 -fallow-argument-mismatch
-ftree-parallelize-loops=32 -L/home/mjm/jemalloc/lib
-ljemalloc

820.cloverleaf_s: -mabi=lp64 -std=f2018 -g -O3 -ffast-math -mcpu=native
-flto=16 -fallow-argument-mismatch -DSPEC_OPENMP
-fopenmp -L/home/mjm/jemalloc/lib -ljemalloc

822.palm_s: Same as 820.cloverleaf_s

849.fotonik3d_s: Same as 820.cloverleaf_s

865.roms_s: Same as 820.cloverleaf_s

Benchmarks using both C and C++:
-mabi=lp64 -std=c++17 -std=c18 -g -O3 -ffast-math -mcpu=native
-flto=16 -fopenmp -DSPEC_OPENMP -L/home/mjm/jemalloc/lib -ljemalloc

Peak Compiler Invocation

C benchmarks:
gcc

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

(Continued on next page)

Peak Compiler Invocation (Continued)

Benchmarks using both C and C++:
g++ gcc

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

811.tealeaf_s: basepeak = yes

816.nab_s: -mabi=lp64 -std=c18 -fprofile-generate -fprofile-use -g
-Ofast -mcpu=native -flto=16 -fopenmp -DSPEC_OPENMP
-L/home/mjm/jemalloc/lib -ljemalloc

881.neutron_s: Same as 816.nab_s

C++ benchmarks:

803.sph_exa_s: -mabi=lp64 -std=c++17 -fprofile-generate -fprofile-use
-g -Ofast -mcpu=native -flto=16 -fopenmp -DSPEC_OPENMP
-L/home/mjm/jemalloc/lib -ljemalloc

857.namd_s: Same as 803.sph_exa_s

867.nest_s: Same as 803.sph_exa_s

872.marian_s: -mabi=lp64 -std=c++17 -fprofile-generate -fprofile-use
-g -Ofast -mcpu=native -flto=16 -pthread
-L/home/mjm/jemalloc/lib -ljemalloc

Fortran benchmarks:

800.pot3d_s: basepeak = yes

820.cloverleaf_s: basepeak = yes

(Continued on next page)

Peak Optimization Flags (Continued)

822.palm_s: `-mabi=lp64 -std=f2018 -fprofile-generate -fprofile-use -g -Ofast -mcpu=native -flto=16 -fallow-argument-mismatch -DSPEC_OPENMP -fopenmp -L/home/mjm/jemalloc/lib -ljemalloc`

849.fotonik3d_s: `Same as 822.palm_s`

865.roms_s: `Same as 822.palm_s`

Benchmarks using both C and C++:
`-mabi=lp64 -std=c++17 -std=c18 -fprofile-generate -fprofile-use -g -Ofast -mcpu=native -flto=16 -fopenmp -DSPEC_OPENMP -L/home/mjm/jemalloc/lib -ljemalloc`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2026/results/flags/gcc-rev-A2.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2026/results/flags/gcc-rev-A2.xml`

PTDaemon, SPEC CPU, and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v0.903.0 on 2026-02-21 00:13:13-0500.
Report generated on 2026-05-04 23:26:13 by CPU2026 PS formatter (86729d3b).
Originally published on 2026-05-05.