SPEC CPU®2026 Integer Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R7715 (AMD EPYC 9845 160-Core Processor)

SPECspeed®2026_int_base = 6.41

SPECspeed®2026_int_peak = 6.41

CPU2026 License: 6573
Test Sponsor: Dell Inc.
Tested by: Dell Inc.

Test Date: Feb-2026
Hardware Availability: Mar-2025
Software Availability: Jan-2026



Hardware

CPU Name:	AMD EPYC 9845
Max MHz:	3700
Nominal:	2100
Enabled:	160 cores, 1 chip
Orderable:	1 chip
Cache L1:	32 KB I + 48 KB D on chip per core
L2:	1 MB I+D on chip per core
L3:	320 MB I+D on chip per chip, 32 MB shared / 16 cores
Other:	None
Memory:	768 GB (12 x 64 GB 2Rx4 PC5-6400B-R, running at 5200)
Storage:	120 GB on tmpfs
Cooling:	Air
Other:	None

Software

OS:	Ubuntu 24.04.2 LTS 6.8.0-85-generic
Compiler:	C/C++: Version 5.1.0 of AOCC Fortran: Flang v22
Compiler Category:	Vendor
Firmware:	Version 1.5.3 released Oct-2025
File System:	tmpfs
System State:	Run level 5 (graphical multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	None
Power Management:	BIOS set to prefer performance at the cost of additional power usage.

SPEC CPU®2026 Integer Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R7715 (AMD EPYC 9845 160-Core Processor)

SPECspeed®2026_int_base = 6.41

SPECspeed®2026_int_peak = 6.41

CPU2026 License: 6573
Test Sponsor: Dell Inc.
Tested by: Dell Inc.

Test Date: Feb-2026
Hardware Availability: Mar-2025
Software Availability: Jan-2026

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
801.xz_s	160	217	2.73	**217**	**2.72**			160	217	2.73	**217**	**2.72**		
807.ntest_s	160	65.8	17.3	**66.0**	**17.3**			160	65.8	17.3	**66.0**	**17.3**		
817.flac_s	160	430	4.04	**431**	**4.03**			160	430	4.04	**431**	**4.03**		
821.gcc_s	160	**109**	**18.9**	109	18.9			160	**109**	**18.9**	109	18.9		
823.llvm_s	160	77.8	18.1	**78.0**	**18.1**			160	77.8	18.1	**78.0**	**18.1**		
827.cppcheck_s	160	99.1	11.3	**100**	**11.1**			160	99.1	11.3	**100**	**11.1**		
829.abc_s	160	351	2.36	**354**	**2.35**			160	351	2.36	**354**	**2.35**		
834.vpr_s	160	**252**	**3.79**	250	3.82			160	**252**	**3.79**	250	3.82		
835.gem5_s	160	262	4.35	**264**	**4.32**			160	262	4.35	**264**	**4.32**		
838.diamond_s	160	127	7.89	**127**	**7.89**			160	127	7.89	**127**	**7.89**		
846.minizinc_s	160	**294**	**2.28**	293	2.29			160	**294**	**2.28**	293	2.29		
853.ns3_s	160	**168**	**6.84**	168	6.85			160	**168**	**6.84**	168	6.85		
854.graph500_s	160	**67.1**	**9.10**	66.8	9.14			160	**67.1**	**9.10**	66.8	9.14		

SPECspeed®2026_int_base = 6.41

SPECspeed®2026_int_peak = 6.41

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

```
The AMD64 AOCC Compiler Suite is available at
http://developer.amd.com/amd-aocc/
Flang v22 is available at
https://flang.llvm.org/
```

Submit Notes

```
The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.
```

Operating System Notes

```
'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.
To free node-local memory and avoid remote memory usage,
```

(Continued on next page)

Operating System Notes (Continued)

```
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.
To disable address space layout randomization (ASLR) to reduce run-to-run
variability, 'sysctl -w kernel.randomize_va_space=0' run as root.
To enable Transparent Hugepages (THP) for all allocations,
'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
GOMP_CPU_AFFINITY = "0-159"
LD_LIBRARY_PATH =
     "/mnt/ramdisk/cpu2026rc2/amd_speed_aocc510_flang22_znver5_A_lib/lib:/mnt
     /ramdisk/cpu2026rc2/amd_speed_aocc510_flang22_znver5_A_lib/lib32:"
MALLOC_CONF = "retain:true"
```

General Notes

```
Binaries were compiled on a system with an AMD EPYC 9754 CPU + 768 GiB Memory using Ubuntu 24.04
 Benchmark run from a 120 GB ramdisk created with the cmd: "mount -t tmpfs -o size=120G tmpfs /mnt/ramdisk"
```

Platform Notes

```
 BIOS Settings:
                    Logical Processor : Disabled
             Virtualization Technology : Disabled
                 NUMA Nodes Per Socket : 2

                        System Profile : Custom
                               C-States : Disabled
                   Memory Patrol Scrub : Disabled
    PCI ASPM L1 Link Power Management : Disabled
      Periodic Directory Rinse Tuning : Blended
                   Determinism Control : Manual
                    Determinism Slider : Power Determinism
                        Optimizer Mode : Enabled
  Algorithm Performance Boost Disable : Enabled
              ApbDis Fixed DF P-State : P0
                   Adaptive Allocation : Enabled
                    Dram Refresh Delay : Performance
                   DIMM Self Healing -
        on Uncorrectable Memory Error : Disabled
```

(Continued on next page)

Platform Notes (Continued)

```
Sysinfo program /mnt/ramdisk/cpu2026rc2/bin/sysinfo
Rev: 069f95da7e7f5d81b2ce48a82150e54f
running on SLR7719-R7715 Fri Feb  6 06:30:17 2026

SUT (System Under Test) info as seen by some common utilities.

------------------------------------------------------------
Table of contents
------------------------------------------------------------
 1. uname -srvm
 2. w
 3. Username
 4. ulimit -a
 5. sysinfo process ancestry
 6. /proc/cpuinfo
 7. lscpu
 8. numactl --hardware
 9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 255 (255.4-1ubuntu8.8)
12. Failed units, from systemctl list-units --state=failed
13. Services, from systemctl list-unit-files
14. Linux kernel boot-time arguments, from /proc/cmdline
15. cpupower frequency-info
16. sysctl
17. /sys/kernel/mm/transparent_hugepage
18. /sys/kernel/mm/transparent_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 6.8.0-85-generic #85-Ubuntu SMP PREEMPT_DYNAMIC Thu Sep 18 15:26:59 UTC 2025 x86_64

------------------------------------------------------------
2. w
   06:30:17 up 5 min,  1 user,  load average: 0.40, 0.13, 0.04
  USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU  WHAT
  root     tty1     -                06:25   33.00s  2.28s  1.05s /bin/bash
  ./amd_speed_aocc510_flang22_znver5_A1.sh

------------------------------------------------------------
```

(Continued on next page)

Platform Notes (Continued)

```
 3. Username
   From environment variable $USER:  root

 ------------------------------------------------------------
 4. ulimit -a
   time(seconds)        unlimited
   file(blocks)         unlimited
   data(kbytes)         unlimited
   stack(kbytes)        unlimited
   coredump(blocks)     0
   memory(kbytes)       unlimited
   locked memory(kbytes) 2097152
   process              3091233
   nofiles              1024
   vmemory(kbytes)      unlimited
   locks                unlimited
   rtprio               0

 ------------------------------------------------------------
 5. sysinfo process ancestry
  /sbin/init splash
  /bin/login -p --
  -bash
  /bin/bash /home/DellFiles/bin/DELL_speed.sh
  /bin/bash /home/DellFiles/bin/dell-run-main.sh speed
  /bin/bash /home/DellFiles/bin/dell-run-main.sh speed
  /bin/bash /home/DellFiles/bin/AMD/dell-run-speccpu.sh speed --define DL-VERS=7.0_T01 --output_format
    html,pdf,txt
  python3 ./run_amd_speed_aocc510_flang22_znver5_A1.py
  /bin/bash ./amd_speed_aocc510_flang22_znver5_A1.sh
  runcpu --config amd_speed_aocc510_flang22_znver5_A1.cfg --tune base --reportable --iterations 2 --define
    DL-VERS=7.0_T01 --output_format html,pdf,txt intspeed
  runcpu --configfile amd_speed_aocc510_flang22_znver5_A1.cfg --tune base --reportable --iterations 2 --define
    DL-VERS=7.0_T01 --output_format html,pdf,txt --nopower --runmode speed --tune base --size
    test:train:refspeed intspeed --nopreenv --note-preenv --logfile
    $SPEC/tmp/CPU2026.001/templogs/preenv.intspeed.001.0.log --lognum 001.0 --from_runcpu 2
  specperl $SPEC/bin/sysinfo
 $SPEC = /mnt/ramdisk/cpu2026rc2

 ------------------------------------------------------------
 6. /proc/cpuinfo
     model name      : AMD EPYC 9845 160-Core Processor
     vendor_id       : AuthenticAMD
     cpu family      : 26
     model           : 17
     stepping        : 0
     microcode       : 0xb101054
```

(Continued on next page)

Platform Notes (Continued)

```
     bugs            : sysret_ss_attrs spectre_v1 spectre_v2 spec_store_bypass
     TLB size        : 192 4K pages
     cpu cores       : 160
     siblings        : 160
     1 physical ids (chips)
     160 processors (hardware threads)
     physical id 0: core ids 0-159
     physical id 0: apicids 0-159
   Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
    virtualized systems.  Use the above data carefully.

 ------------------------------------------------------------
 7. lscpu

 From lscpu from util-linux 2.39.3:
   Architecture:                         x86_64
   CPU op-mode(s):                       32-bit, 64-bit
   Address sizes:                        52 bits physical, 57 bits virtual
   Byte Order:                           Little Endian
   CPU(s):                               160
   On-line CPU(s) list:                  0-159
   Vendor ID:                            AuthenticAMD
   BIOS Vendor ID:                       AMD
   Model name:                           AMD EPYC 9845 160-Core Processor
   BIOS Model name:                    AMD EPYC 9845 160-Core Processor                CPU @ 2.1GHz
   BIOS CPU family:                      107
   CPU family:                           26
   Model:                                17
   Thread(s) per core:                   1
   Core(s) per socket:                   160
   Socket(s):                            1
   Stepping:                             0
   Frequency boost:                      enabled
   CPU(s) scaling MHz:                   177%
   CPU max MHz:                          2100.0000
   CPU min MHz:                          1500.0000
   BogoMIPS:                             4193.88
   Flags:                              fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
  pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt pdpe1gb
   rdtscp lm constant_tsc rep_good amd_lbr_v2 nopl nonstop_tsc cpuid
  extd_apicid aperfmperf rapl pni pclmulqdq monitor ssse3 fma cx16 pcid
   sse4_1 sse4_2 x2apic movbe popcnt aes xsave avx f16c rdrand lahf_lm
   cmp_legacy extapic cr8_legacy abm sse4a misalignsse 3dnowprefetch
     osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb bpext
   perfctr_llc mwaitx cpb cat_l3 cdp_l3 hw_pstate ssbd mba perfmon_v2
  ibrs ibpb stibp ibrs_enhanced vmmcall fsgsbase tsc_adjust bmi1 avx2
     smep bmi2 invpcid cqm rdt_a avx512f avx512dq rdseed adx smap
```

(Continued on next page)

Platform Notes (Continued)

```
                                avx512ifma clflushopt clwb avx512cd sha_ni avx512bw avx512vl xsaveopt
                                     xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
                                    cqm_mbm_local user_shstk avx_vnni avx512_bf16 clzero irperf
                                  xsaveerptr rdpru wbnoinvd amd_ppin cppc amd_ibpb_ret arat npt lbrv
                                  svm_lock nrip_save tsc_scale vmcb_clean flushbyasid decodeassists
                                 pausefilter pfthreshold avic v_vmsave_vmload vgif x2avic v_spec_ctrl
                                   vnmi avx512vbmi umip pku ospke avx512_vbmi2 gfni vaes vpclmulqdq
                                avx512_vnni avx512_bitalg avx512_vpopcntdq la57 rdpid bus_lock_detect
                                  movdiri movdir64b overflow_recov succor smca avx512_vp2intersect
                                          flush_l1d debug_swap
  L1d cache:                              7.5 MiB (160 instances)
  L1i cache:                              5 MiB (160 instances)
  L2 cache:                               160 MiB (160 instances)
  L3 cache:                               320 MiB (10 instances)
  NUMA node(s):                           1
  NUMA node0 CPU(s):                      0-159
  Vulnerability Gather data sampling:   Not affected
  Vulnerability Itlb multihit:          Not affected
  Vulnerability L1tf:                   Not affected
  Vulnerability Mds:                    Not affected
  Vulnerability Meltdown:               Not affected
  Vulnerability Mmio stale data:        Not affected
  Vulnerability Reg file data sampling: Not affected
  Vulnerability Retbleed:               Not affected
  Vulnerability Spec rstack overflow:   Not affected
  Vulnerability Spec store bypass:      Mitigation; Speculative Store Bypass disabled via prctl
  Vulnerability Spectre v1:           Mitigation; usercopy/swapgs barriers and __user pointer sanitization
  Vulnerability Spectre v2:             Mitigation; Enhanced / Automatic IBRS; IBPB conditional; STIBP
                                      disabled; RSB filling; PBRSB-eIBRS Not affected; BHI Not affected
  Vulnerability Srbds:                  Not affected
  Vulnerability Tsx async abort:        Not affected

From lscpu --cache:
     NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL  SETS PHY-LINE COHERENCY-SIZE
     L1d       48K     7.5M   12 Data            1    64        1             64
     L1i       32K       5M    8 Instruction     1    64        1             64
     L2         1M     160M   16 Unified         2  1024        1             64
     L3        32M     320M   16 Unified         3 32768        1             64

------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 1 nodes (0)
  node 0 cpus: 0-159
  node 0 size: 772886 MB
  node 0 free: 756576 MB
  node distances:
```

(Continued on next page)

Platform Notes (Continued)

```
  node   0
    0:  10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       791435560 kB

------------------------------------------------------------
10. who -r
  run-level 5 Feb 6 06:24

------------------------------------------------------------
11. Systemd service manager version: systemd 255 (255.4-1ubuntu8.8)
  Default Target  Status
  graphical       degraded

------------------------------------------------------------
12. Failed units, from systemctl list-units --state=failed
    UNIT                         LOAD   ACTIVE SUB    DESCRIPTION
  * nvidia-persistenced.service loaded failed failed NVIDIA Persistence Daemon
  Legend: LOAD   -> Reflects whether the unit definition was properly loaded.
          ACTIVE -> The high-level unit activation state, i.e. generalization of SUB.
          SUB    -> The low-level unit activation state, values depend on unit type.
  1 loaded units listed.

------------------------------------------------------------
13. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled          ModemManager apparmor apport blk-availability cloud-config cloud-final cloud-init
                   cloud-init-local console-setup containerd cron dmesg docker e2scrub_reap finalrd getty@
                   gpu-manager grub-common grub-initrd-fallback keyboard-setup lm-sensors lvm2-monitor
                   multipathd munge mysql networkd-dispatcher nvidia-persistenced nvmefc-boot-connections
                   nvmf-autoconnect open-iscsi open-vm-tools pollinate rsyslog secureboot-db setvtrgb ssh
                   switcheroo-control sysstat systemd-networkd systemd-networkd-wait-online systemd-pstore
                   systemd-resolved systemd-timesyncd thermald ua-reboot-cmds ubuntu-advantage udisks2 ufw
                   vgauth
  enabled-runtime  netplan-ovs-cleanup systemd-fsck-root systemd-remount-fs
  disabled         console-getty debug-shell iscsid nftables nvidia-cdi-refresh nvidia-hibernate
                   nvidia-powerd nvidia-resume nvidia-suspend nvidia-suspend-then-hibernate rsync
                   serial-getty@ slurmctld slurmd systemd-boot-check-no-failures systemd-confext
                   systemd-network-generator systemd-networkd-wait-online@ systemd-pcrlock-file-system
                   systemd-pcrlock-firmware-code systemd-pcrlock-firmware-config systemd-pcrlock-machine-id
                   systemd-pcrlock-make-policy systemd-pcrlock-secureboot-authority
                   systemd-pcrlock-secureboot-policy systemd-sysext systemd-time-wait-sync upower
  generated        gdrdrv
  indirect         systemd-sysupdate systemd-sysupdate-reboot uuidd
  masked           cryptdisks cryptdisks-early hwclock multipath-tools-boot screen-cleanup sudo x11-common
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
14. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.8.0-85-generic
  root=UUID=fa6e327f-d7c6-4a1a-a00f-34f4bd279a0c
  ro
  quiet
  splash
  modprobe.blacklist=nouveau
  iommu=pt
  pci=realloc=off
  pcie_aspm=off
  nohz=off
  vt.handoff=7

------------------------------------------------------------
15. cpupower frequency-info
  analyzing CPU 21:
    current policy: frequency should be within 1.50 GHz and 2.10 GHz.
                    The governor "schedutil" may decide which speed to use
                    within this range.
    boost state support:
      Supported: yes
      Active: yes
      Boost States: 0
      Total States: 3
      Pstate-P0:  2100MHz

------------------------------------------------------------
16. sysctl
  kernel.numa_balancing               0
  kernel.randomize_va_space           0
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                      8
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                       1
  vm.watermark_boost_factor       15000
```

(Continued on next page)

Platform Notes (Continued)

```
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                1

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage
  defrag          [always] defer defer+madvise madvise never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
18. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
19. OS release
  From /etc/*-release /etc/*-version
  os-release Ubuntu 24.04.2 LTS

------------------------------------------------------------
20. Disk information
SPEC is set to: /mnt/ramdisk/cpu2026rc2
  Filesystem     Type   Size  Used Avail Use% Mounted on
  tmpfs          tmpfs  120G   11G  110G   9% /mnt/ramdisk

------------------------------------------------------------
21. /sys/devices/virtual/dmi/id
    Vendor:         Dell Inc.
    Product:        PowerEdge R7715
    Product Family: PowerEdge
    Serial:         SLR7719

------------------------------------------------------------
22. dmidecode
  Additional information from dmidecode 3.5 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
  "DMTF SMBIOS" standard.
  Memory:
    12x 80AD000080AD HMCG94AHBRA283N 64 GB 2 rank 6400, configured at 5200
```

(Continued on next page)

Platform Notes (Continued)

```
 ------------------------------------------------------------
 23. BIOS
 (This section combines info from /sys/devices and dmidecode.)
    BIOS Vendor:       Dell Inc.
    BIOS Version:      1.5.3
    BIOS Date:         10/29/2025
    BIOS Revision:     1.5
```

Compiler Version Notes

```
==============================================================================
C      | 854.graph500_s(base)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.1.0-Build#1994 2025_12_23)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-5.1.0/bin
------------------------------------------------------------------------------

==============================================================================
C++    | 807.ntest_s(base) 827.cppcheck_s(base) 853.ns3_s(base)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.1.0-Build#1994 2025_12_23)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-5.1.0/bin
------------------------------------------------------------------------------

==============================================================================
C++, C | 801.xz_s(base) 817.flac_s(base) 821.gcc_s(base) 823.llvm_s(base)
       | 829.abc_s(base) 834.vpr_s(base) 835.gem5_s(base) 838.diamond_s(base)
       | 846.minizinc_s(base)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.1.0-Build#1994 2025_12_23)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-5.1.0/bin
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
clang

(Continued on next page)

Base Compiler Invocation (Continued)

C++ benchmarks:
clang++

Benchmarks using both C and C++:
clang++ clang

Base Portability Flags

801.xz_s: -DSPEC_LP64
807.ntest_s: -DSPEC_LP64
817.flac_s: -DSPEC_LP64
821.gcc_s: -DSPEC_LP64
823.llvm_s: -DSPEC_LP64
827.cppcheck_s: -DSPEC_LP64
829.abc_s: -DSPEC_LP64
834.vpr_s: -fno-finite-math-only -DSPEC_LP64
835.gem5_s: -fno-finite-math-only -DSPEC_LP64
838.diamond_s: -DSPEC_LP64
846.minizinc_s: -DSPEC_LP64
853.ns3_s: -fno-finite-math-only -DSPEC_LP64
854.graph500_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:
-m64 -std=c18 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-allow-multiple-definition -Wl,-mllvm -Wl,-extra-inliner -O3 -flto
-march=znver5 -fveclib=AMDLIBM -ffast-math -zopt -fremap-arrays
-fstrip-mining -fstruct-layout=7 -mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -mllvm -unroll-threshold=50
-fopenmp -DSPEC_OPENMP -lamdalloc -lamdlibm -fopenmp=libomp -lomp

C++ benchmarks:
-m64 -std=c++17 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-x86-use-vzeroupper=false -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -zopt -mllvm -unroll-threshold=100
-mllvm -loop-unswitch-threshold=200000
-mllvm -reduce-array-computations=3 -fopenmp -DSPEC_OPENMP
-fvirtual-function-elimination -fvisibility=hidden -lamdalloc
-lamdlibm -fopenmp=libomp -lomp

(Continued on next page)

Base Optimization Flags (Continued)

Benchmarks using both C and C++:
-m64 -std=c++17 -std=c18 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-x86-use-vzeroupper=false -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -zopt -fremap-arrays -fstrip-mining
-fstruct-layout=7 -mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -mllvm -unroll-threshold=50
-mllvm -unroll-threshold=100 -mllvm -loop-unswitch-threshold=200000
-fopenmp -DSPEC_OPENMP -fvirtual-function-elimination
-fvisibility=hidden -lamdalloc -lamdlibm -fopenmp=libomp -lomp

Base Other Flags

C benchmarks:
-Wno-return-type

Benchmarks using both C and C++:
-Wno-return-type

Peak Optimization Flags

C benchmarks:

854.graph500_s: basepeak = yes

C++ benchmarks:

807.ntest_s: basepeak = yes

827.cppcheck_s: basepeak = yes

853.ns3_s: basepeak = yes

Benchmarks using both C and C++:

801.xz_s: basepeak = yes

817.flac_s: basepeak = yes

(Continued on next page)

Peak Optimization Flags (Continued)

821.gcc_s: `basepeak = yes`

823.llvm_s: `basepeak = yes`

829.abc_s: `basepeak = yes`

834.vpr_s: `basepeak = yes`

835.gem5_s: `basepeak = yes`

838.diamond_s: `basepeak = yes`

846.minizinc_s: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2026/results/flags/aocc-flags.html`
`http://www.spec.org/cpu2026/results/flags/Dell-Platform-Flags-PowerEdge-AMD-EPYC-v1.8.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2026/results/flags/aocc-flags.xml`
`http://www.spec.org/cpu2026/results/flags/Dell-Platform-Flags-PowerEdge-AMD-EPYC-v1.8.xml`

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v0.902.0 on 2026-02-06 01:30:17-0500.
Report generated on 2026-08-11 15:13:10 by CPU2026 PDF formatter (unknown).
Originally published on 2026-05-05.