



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19


Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026



Hardware

CPU Name: Xeon 6353P
Max MHz: 5400
Nominal: 2700
Enabled: 8 cores, 1 chip, 2 threads/core
Orderable: 1 chip
Cache L1: 32 KB I + 48 KB D on chip per core
L2: 2 MB I+D on chip per core
L3: 24 MB I+D on chip per chip
Other: None
Memory: 64 GB (2 x 32 GB 2Rx8 PC5-4800B-E, running at 4400)
Storage: 1 x SATA M.2 SSD, 960 GB
Cooling: Air
Other: None

Software

OS: SUSE Linux Enterprise Server 15 SP6 6.4.0-150600.21-default
Compiler: C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux;
Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category: Vendor
Firmware: Fujitsu BIOS Version V5.0.0.32 R2.6.0 for D4133-A1x. Released Jun-2026
File System: xfs
System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other: None
Power Management: BIOS set to prefer performance at the cost of additional power usage



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
706.stockfish_r	16	309	65.3	319	63.2	318	63.5							
707.ntest_r	16	284	33.3	284	33.3	284	33.4							
708.sqlite_r	16	296	28.5	296	28.5	297	28.5							
710.omnetpp_r	16	238	32.7	237	32.8	238	32.7							
714.cpython_r	16	227	33.7	228	33.6	228	33.6							
721.gcc_r	16	350	31.3	349	31.4	351	31.3							
723.llvm_r	16	236	34.4	238	34.1	238	34.1							
727.cppcheck_r	16	174	33.1	173	33.1	173	33.1							
729.abc_r	16	264	27.8	263	28.0	262	28.0							
734.vpr_r	16	215	34.3	215	34.3	215	34.3							
735.gem5_r	16	207	37.7	208	37.6	207	37.6							
750.sealcrypto_r	16	153	56.2	153	56.2	153	56.2							
753.ns3_r	16	200	49.0	200	49.1	200	49.0							
777.zstd_r	16	412	25.0	411	25.0	412	25.0							

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The taskset mechanism was used to bind copies to processors. The config file option 'submit' was used to generate taskset commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
tuned-adm was set to balanced using "tuned-adm profile balanced"

Environment Variables Notes

Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/benchmark/cpu2026/lib"
MALLOC_CONF = "retain:true"

General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
memory using CentOS Stream 9.

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

General Notes (Continued)

Transparent Huge Pages enabled by default
Prior to runcpu invocation
Filesystem page cache synced and cleared with:
sync; echo 3> /proc/sys/vm/drop_caches

Platform Notes

BIOS Settings:

Fan Control = Full

Total Memory Encryption = Disabled

Sysinfo program /home/benchmark/cpu2026/bin/sysinfo

Rev: 779ab21020787073335a329f3a45e2cd

running on localhost Fri Jun 12 14:38:46 2026

SUT (System Under Test) info as seen by some common utilities.

Table of contents

1. uname -srvm
 2. w
 3. Username
 4. ulimit -a
 5. sysinfo process ancestry
 6. /proc/cpuinfo
 7. lscpu
 8. numactl --hardware
 9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. tuned-adm active
 16. sysctl
 17. /sys/kernel/mm/transparent_hugepage
 18. /sys/kernel/mm/transparent_hugepage/khugepaged
 19. OS release
 20. Disk information
 21. /sys/devices/virtual/dmi/id
 22. dmidecode
 23. BIOS
- -----

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

1. uname -srvnm

Linux 6.4.0-150600.21-default #1 SMP PREEMPT_DYNAMIC Thu May 16 11:09:22 UTC 2024 (36c1e09) x86_64

2. w

14:38:46 up 1 day, 41 min, 1 user, load average: 3.81, 11.84, 14.42

USER	TTY	FROM	LOGIN@	IDLE	JCPU	PCPU	WHAT
root	tty1	-	Thu13	6:12m	1.53s	0.13s	-bash

3. Username

From environment variable \$USER: root

4. ulimit -a

core file size	(blocks, -c)	unlimited
data seg size	(kbytes, -d)	unlimited
scheduling priority	(-e)	0
file size	(blocks, -f)	unlimited
pending signals	(-i)	254378
max locked memory	(kbytes, -l)	8192
max memory size	(kbytes, -m)	unlimited
open files	(-n)	1024
pipe size	(512 bytes, -p)	8
POSIX message queues	(bytes, -q)	819200
real-time priority	(-r)	0
stack size	(kbytes, -s)	unlimited
cpu time	(seconds, -t)	unlimited
max user processes	(-u)	254378
virtual memory	(kbytes, -v)	unlimited
file locks	(-x)	unlimited

5. sysinfo process ancestry

/usr/lib/systemd/systemd --switched-root --system --deserialize=42

login -- root

-bash

-bash

runcpu --nobuild --action validate --define default-platform-flags --copies 16 -c

ic2026.0-core-avx2-cpu2026-1.0.1-rate-20260429.cfg --define smt-on --define cores=8 --define physicallogical --define no-numa --tune base -o all --define drop_caches -n 3 intrate

runcpu --nobuild --action validate --define default-platform-flags --copies 16 --configfile ic2026.0-core-avx2-cpu2026-1.0.1-rate-20260429.cfg --define smt-on --define cores=8 --define physicallogical --define no-numa --tune base --output_format all --define drop_caches --iterations 3 --nopower --runmode rate --tune base --size refrate intrate --nopreenv --note-preenv --logfile \$SPEC/tmp/CPU2026.001/templots/preenv.intrate.001.0.log --lognum 001.0 --from_runcpu 2 specperl \$SPEC/bin/sysinfo

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

\$SPEC = /home/benchmark/cpu2026

6. /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) 6353P
vendor_id       : GenuineIntel
cpu family      : 6
model           : 183
stepping        : 1
microcode       : 0x133
bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_pbrsb bhi
cpu cores       : 8
siblings        : 16
1 physical ids (chips)
16 processors (hardware threads)
physical id 0: core ids 0-7
physical id 0: apicids 0-15
```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

7. lscpu

From lscpu from util-linux 2.39.3:

```
Architecture:      x86_64
CPU op-mode(s):    32-bit, 64-bit
Address sizes:      46 bits physical, 48 bits virtual
Byte Order:        Little Endian
CPU(s):            16
On-line CPU(s) list: 0-15
Vendor ID:         GenuineIntel
BIOS Vendor ID:    Intel(R) Corporation
Model name:        Intel(R) Xeon(R) 6353P
BIOS Model name:   Intel(R) Xeon(R) 6353P   CPU @ 4.5GHz
BIOS CPU family:   179
CPU family:        6
Model:             183
Thread(s) per core: 2
Core(s) per socket: 8
Socket(s):         1
Stepping:          1
CPU(s) scaling MHz: 22%
CPU max MHz:       5400.0000
CPU min MHz:       800.0000
BogoMIPS:          5376.00
```

Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

**PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz**

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16
xtpr pdcm sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes
xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb ssbd
ibrs ibpb stibp ibrs_enhanced tpr_shadow flexpriority ept vpid ept_ad
fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid rdseed adx smap
clflushopt clwb intel_pt sha_ni xsaveopt xsavec xgetbv1 xsaves
split_lock_detect user_shstk avx_vnni dtherm ida arat pln pts hwp
hwp_notify hwp_act_window hwp_epp hwp_pkg_req hfi vnmi umip pku ospke
waitpkg gfni vaes vpclmulqdq tme rdpid movdiri movdir64b fsrm
md_clear serialize pconfig arch_lbr ibt flush_l1d arch_capabilities

Virtualization:

VT-x

L1d cache:

384 KiB (8 instances)

L1i cache:

256 KiB (8 instances)

L2 cache:

16 MiB (8 instances)

L3 cache:

24 MiB (1 instance)

NUMA node(s):

1

NUMA node0 CPU(s):

0-15

Vulnerability Gather data sampling:

Not affected

Vulnerability Itlb multihit:

Not affected

Vulnerability L1tf:

Not affected

Vulnerability Mds:

Not affected

Vulnerability Meltdown:

Not affected

Vulnerability Mmio stale data:

Not affected

Vulnerability Reg file data sampling:

Not affected

Vulnerability Retbleed:

Not affected

Vulnerability Spec rstack overflow:

Not affected

Vulnerability Spec store bypass:

Mitigation; Speculative Store Bypass disabled via prctl

Vulnerability Spectre v1:

Mitigation; usercopy/swaps barriers and __user pointer sanitization

Vulnerability Spectre v2:

Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling;

PBRSB-eIBRS SW sequence; BHI BHI_DIS_S

Vulnerability Srbds:

Not affected

Vulnerability Tsx async abort:

Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	384K	12	Data	1	64	1	64
L1i	32K	256K	8	Instruction	1	64	1	64
L2	2M	16M	16	Unified	2	2048	1	64
L3	24M	24M	12	Unified	3	32768	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

available: 1 nodes (0)

node 0 cpus: 0-15

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

node 0 size: 63620 MB

node 0 free: 62798 MB

node distances:

node 0

0: 10

9. /proc/meminfo

MemTotal: 65147472 kB

10. who -r

run-level 3 Jun 11 13:57

11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)

Default Target Status

multi-user running

12. Services, from systemctl list-unit-files

STATE UNIT FILES

enabled apparmor auditd cron getty@ irqbalance issue-generator kbdsettings lvm2-monitor postfix
purge-kernels rollback sep5 sshd systemd-pstore wicked wickedd-auto4 wickedd-dhcp4
wickedd-dhcp6 wickedd-nanny

enabled-runtime systemd-remount-fs

disabled YaST2-Firstboot YaST2-Second-Stage autofs autoyast-initscripts blk-availability
boot-sysctl ca-certificates chrony-wait chronyd console-getty cups cups-browsed
debug-shell display-manager ebttables exchange-bmc-os-info firewallld fsidd gpm grub2-once
haveged ipmi ipmievdd issue-add-ssh-keys kdump kdump-early kdump-notify kexec-load klog
lunmask man-db-create multipathd nfs nfs-blkmap nsd rpcbind rpmconfigcheck rsyncd rsyslog
serial-getty@ smartd smartd-generate_opts snmpd snmptrapd systemd-boot-check-no-failures
systemd-confext systemd-network-generator systemd-sysextd systemd-time-wait-sync
systemd-timesyncd tuned vncserver@

indirect systemd-userdbd wickedd

13. Linux kernel boot-time arguments, from /proc/cmdline

BOOT_IMAGE=/boot/vmlinuz-6.4.0-150600.21-default

root=UUID=69cd5337-d082-4cee-8e02-ec4054c30a5a

splash=silent

resume=/dev/disk/by-uuid/a5855c9d-a4a0-4b74-baec-bd075bde416b

quiet

security=apparmor

crashkernel=347M,high

crashkernel=72M,low

mitigations=auto

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

14. cpupower frequency-info

analyzing CPU 6:

current policy: frequency should be within 800 MHz and 5.30 GHz.

The governor "powersave" may decide which speed to use
within this range.

boost state support:

Supported: yes

Active: yes

15. tuned-adm active

Current active profile: balanced

16. sysctl

kernel.numa_balancing 0

kernel.randomize_va_space 2

vm.compaction_proactiveness 20

vm.dirty_background_bytes 0

vm.dirty_background_ratio 10

vm.dirty_bytes 0

vm.dirty_expire_centisecs 3000

vm.dirty_ratio 20

vm.dirty_writeback_centisecs 500

vm.dirtytime_expire_seconds 43200

vm.extfrag_threshold 500

vm.min_unmapped_ratio 1

vm.nr_hugepages 0

vm.nr_hugepages_mempolicy 0

vm.nr_overcommit_hugepages 0

vm.swappiness 60

vm.watermark_boost_factor 15000

vm.watermark_scale_factor 10

vm.zone_reclaim_mode 0

17. /sys/kernel/mm/transparent_hugepage

defrag always defer defer+madvice [madvice] never

enabled [always] madvice never

hpage_pmd_size 2097152

shmem_enabled always within_size advise [never] deny force

18. /sys/kernel/mm/transparent_hugepage/khugepaged

alloc_sleep_millisecs 60000

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Platform Notes (Continued)

```
defrag 1
max_ptes_none 511
max_ptes_shared 256
max_ptes_swap 64
pages_to_scan 4096
scan_sleep_millisecs 10000
```

19. OS release

```
From /etc/*-release /etc/*-version
os-release SUSE Linux Enterprise Server 15 SP6
```

20. Disk information

SPEC is set to: /home/benchmark/cpu2026

```
Filesystem Type Size Used Avail Use% Mounted on
/dev/sda5 xfs 751G 71G 681G 10% /home
```

21. /sys/devices/virtual/dmi/id

```
Vendor: FUJITSU
Product: PRIMERGY RX1330 M6
Product Family: SERVER
Serial: xxxxxxxxxx
```

22. dmidecode

Additional information from dmidecode 3.4 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

2x Samsung M324R4GA3BB0-CQK0L 32 GB 2 rank 4800, configured at 4400

23. BIOS

(This section combines info from /sys/devices and dmidecode.)

```
BIOS Vendor: FUJITSU // American Megatrends International, LLC.
BIOS Version: V5.0.0.32 R2.6.0 for D4133-A1x
BIOS Date: 04/23/2026
BIOS Revision: 2.6
```



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Compiler Version Notes

=====
C | 708.sqlite_r(base) 714.cpython_r(base) 777.zstd_r(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
=====

=====
C++ | 706.stockfish_r(base) 707.ntest_r(base) 727.cppcheck_r(base)
| 753.ns3_r(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
=====

=====
C++, C | 710.omnetpp_r(base) 721.gcc_r(base) 723.llvm_r(base) 729.abc_r(base)
| 734.vpr_r(base) 735.gem5_r(base) 750.sealcrypto_r(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
=====

Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Benchmarks using both C and C++:

icpx icx

Base Optimization Flags

C benchmarks:

-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xCORE-AVX2 -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-strict-aliasing
-L/opt/intel/oneapi/compiler/2026.0/lib -lqkmallo

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMERGY RX1330 M6,
Intel Xeon 6353P, 2.7 GHz

SPECrate®2026_int_base = 35.9

SPECrate®2026_int_peak = Not Run

CPU2026 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jun-2026

Hardware Availability: Apr-2025

Software Availability: Apr-2026

Base Optimization Flags (Continued)

C++ benchmarks:

```
-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500  
-xCORE-AVX2 -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops  
-qopt-mem-layout-trans=4 -L/opt/intel/oneapi/compiler/2026.0/lib  
-lqkmalloc
```

Benchmarks using both C and C++:

```
-m64 -std=c++17 -std=c18 -Wl,-z,muldefs  
-Wl,-plugin-opt=-inline-threshold=1500 -xCORE-AVX2 -O3 -ffp-model=fast  
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4  
-fno-strict-aliasing -L/opt/intel/oneapi/compiler/2026.0/lib -lqkmalloc
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html>

<http://www.spec.org/cpu2026/results/flags/Fsas-Platform-Settings-V1.0-RPL-R-RevB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml>

<http://www.spec.org/cpu2026/results/flags/Fsas-Platform-Settings-V1.0-RPL-R-RevB.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-06-12 01:38:46-0400.

Report generated on 2026-08-11 15:33:19 by CPU2026 PDF formatter (unknown).

Originally published on 2026-07-14.