SPEC CPU®2026 Floating Point Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant MicroServer Gen11
(3.10 GHz, Intel Xeon 6377P)

SPECspeed®2026_fp_base = 1.87

SPECspeed®2026_fp_peak = 1.88

CPU2026 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Jul-2026
Hardware Availability: Sep-2026
Software Availability: Apr-2026



Hardware

CPU Name:	Intel Xeon 6377P
Max MHz:	5700
Nominal:	3100
Enabled:	12 cores, 1 chip
Orderable:	1 Chip
Cache L1:	32 KB I + 48 KB D on chip per core
L2:	2 MB I+D on chip per core
L3:	36 MB I+D on chip per chip
Other:	None
Memory:	64 GB (2 x 32 GB 2Rx8 PC5-5600B-E, running at 4400)
Storage:	1 x 960 GB NVMe SSD
Cooling:	Air
Other:	None

Software

OS:	SUSE Linux Enterprise Server 15 SP7 Kernel 6.4.0-150700.53.6-default
Compiler:	C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category:	Vendor
Firmware:	HPE BIOS Version v2.50 06/25/2026 released Jun-2026
File System:	btrfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	jemalloc memory allocator v5.3
Power Management:	BIOS set to prefer performance at the cost of additional power usage

SPEC CPU®2026 Floating Point Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)
ProLiant MicroServer Gen11
(3.10 GHz, Intel Xeon 6377P)

SPECspeed®2026_fp_base = 1.87

SPECspeed®2026_fp_peak = 1.88

CPU2026 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Jul-2026
Hardware Availability: Sep-2026
Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
800.pot3d_s	12	625	1.08	628	1.07	**627**	**1.07**	12	625	1.08	628	1.07	**627**	**1.07**
803.sph_exa_s	12	**343**	**3.61**	338	3.67	344	3.60	12	**343**	**3.61**	338	3.67	344	3.60
809.cactus_s	12	229	4.91	228	4.92	**229**	**4.91**	12	229	4.91	228	4.92	**229**	**4.91**
811.tealeaf_s	12	774	0.719	**776**	**0.718**	777	0.717	12	774	0.719	**776**	**0.718**	777	0.717
816.nab_s	12	**388**	**2.90**	388	2.90	388	2.90	12	**385**	**2.93**	385	2.93	387	2.91
820.cloverleaf_s	12	834	1.03	833	1.03	**833**	**1.03**	12	**833**	**1.03**	833	1.03	833	1.03
822.palm_s	12	429	2.86	428	2.87	**429**	**2.86**	12	429	2.86	428	2.87	**429**	**2.86**
849.fotonik3d_s	12	644	1.02	**644**	**1.02**	644	1.03	12	644	1.02	**644**	**1.02**	644	1.03
857.namd_s	12	**787**	**1.85**	785	1.85	787	1.84	12	780	1.86	**781**	**1.86**	788	1.84
865.roms_s	12	711	1.53	**710**	**1.54**	709	1.54	12	711	1.53	**710**	**1.54**	709	1.54
867.nest_s	12	**1341**	**1.61**	1345	1.61	1340	1.61	12	**1341**	**1.61**	1345	1.61	1340	1.61
872.marian_s	12	297	3.65	306	3.54	**300**	**3.60**	12	297	3.65	306	3.54	**300**	**3.60**
881.neutron_s	12	**456**	**1.79**	456	1.79	456	1.79	12	**456**	**1.79**	456	1.79	456	1.79

SPECspeed®2026_fp_base = 1.87

SPECspeed®2026_fp_peak = 1.88

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled by default
Prior to runcpu invocation
Filesystem page cache synced and cleared with:
sync; echo 3>       /proc/sys/vm/drop_caches
tuned-adm profile was set to balanced using 'tuned-adm profile balanced'
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/home/cpu2026/lib"
MALLOC_CONF = "retain:true"
OMP_STACKSIZE = "192M"
```

General Notes

```
 Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
 memory using CentOS Stream 9.
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
```

(Continued on next page)

General Notes (Continued)

```
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
 jemalloc, a general purpose malloc implementation
 built with the CentOS Stream 9, and the system compiler gcc 11.5.0
 sources available from jemalloc.net or https://github.com/jemalloc/jemalloc/releases
```

Platform Notes

```
BIOS Configurations : Parameters are selected in the order shown below
Workload Profile set to General Peak Frequency Compute
Thermal Configuration set to Maximum Cooling
Intel Hyper-Threading set to Disabled
Workload Profile set to Custom
 Power Regulator set to Dynamic Power Savings Mode

 Sysinfo program /home/cpu2026/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on localhost Mon Jul 13 03:39:37 2026

 SUT (System Under Test) info as seen by some common utilities.

 ------------------------------------------------------------
 Table of contents
 ------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 254 (254.27+suse.167.g130293e510)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. tuned-adm active
 16. sysctl
 17. /sys/kernel/mm/transparent_hugepage
 18. /sys/kernel/mm/transparent_hugepage/khugepaged
 19. OS release
 20. Disk information
 21. /sys/devices/virtual/dmi/id
```

(Continued on next page)

Platform Notes (Continued)

```
 22. dmidecode
 23. BIOS
------------------------------------------------------------

------------------------------------------------------------
 1. uname -srvm
   Linux 6.4.0-150700.53.6-default #1 SMP PREEMPT_DYNAMIC Tue Jul  1 14:54:47 UTC 2025 (8ab7501) x86_64

------------------------------------------------------------
 2. w
    03:39:37 up 1 min,  3 users,  load average: 0.52, 0.34, 0.13
   USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT

------------------------------------------------------------
 3. Username
   From environment variable $USER:  root

------------------------------------------------------------
 4. ulimit -a
   core file size          (blocks, -c) unlimited
   data seg size           (kbytes, -d) unlimited
   scheduling priority             (-e) 0
   file size               (blocks, -f) unlimited
   pending signals                 (-i) 256695
   max locked memory       (kbytes, -l) 8192
   max memory size         (kbytes, -m) unlimited
   open files                      (-n) 1024
   pipe size            (512 bytes, -p) 8
   POSIX message queues     (bytes, -q) 819200
   real-time priority              (-r) 0
   stack size              (kbytes, -s) unlimited
   cpu time               (seconds, -t) unlimited
   max user processes              (-u) 256695
   virtual memory          (kbytes, -v) unlimited
   file locks                      (-x) unlimited

------------------------------------------------------------
 5. sysinfo process ancestry
  /usr/lib/systemd/systemd --switched-root --system --deserialize=42
  sshd: /usr/sbin/sshd -D [listener] 1 of 10-100 startups
  sshd: root [priv]
  sshd: root@notty
  bash -c cd $SPEC/ && $SPEC/fpspeed-avx512.sh
  runcpu --nobuild --reportable --action validate --define default-platform-flags -c
    ic2026.0-core-avx2-cpu2026-1.0.1-speed-20260429.cfg --iterations=3 --threads 12 --define cores=12 --tune
     base,peak -o all --define drop_caches fpspeed
  runcpu --nobuild --reportable --action validate --define default-platform-flags --configfile
```

(Continued on next page)

Platform Notes (Continued)

```
   ic2026.0-core-avx2-cpu2026-1.0.1-speed-20260429.cfg --iterations 3 --threads 12 --define cores=12 --tune
   base,peak --output_format all --define drop_caches --nopower --runmode speed --tune base:peak --size
    refspeed fpspeed --nopreenv --note-preenv --logfile
   $SPEC/tmp/CPU2026.001/templogs/preenv.fpspeed.001.0.log --lognum 001.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : Intel(R) Xeon(R) 6377P
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 183
    stepping        : 1
    microcode       : 0x137
    bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_pbrsb bhi
    cpu cores       : 12
    siblings        : 12
    1 physical ids (chips)
    12 processors (hardware threads)
    physical id 0: core ids 0-11
    physical id 0: apicids 0,2,4,6,8,10,12,14,16,18,20,22
  Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
   virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.40.4:
  Architecture:                            x86_64
  CPU op-mode(s):                          32-bit, 64-bit
  Address sizes:                           46 bits physical, 48 bits virtual
  Byte Order:                              Little Endian
  CPU(s):                                  12
  On-line CPU(s) list:                     0-11
  Vendor ID:                               GenuineIntel
  Model name:                              Intel(R) Xeon(R) 6377P
  CPU family:                              6
  Model:                                   183
  Thread(s) per core:                      1
  Core(s) per socket:                      12
  Socket(s):                               1
  Stepping:                                1
  CPU(s) scaling MHz:                      14%
  CPU max MHz:                             5700.0000
  CPU min MHz:                             800.0000
  BogoMIPS:                                6220.80
```

(Continued on next page)

Platform Notes (Continued)

```
  Flags:                               fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                       pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                       pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
                                       nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                                       pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma
                                       cx16 xtpr pdcm sse4_1 sse4_2 x2apic movbe popcnt
                                       tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
                                       3dnowprefetch cpuid_fault epb ssbd ibrs ibpb stibp ibrs_enhanced
                                       tpr_shadow flexpriority ept vpid ept_ad fsgsbase tsc_adjust bmi1
                                       avx2 smep bmi2 erms invpcid rdseed adx smap clflushopt clwb
                                       intel_pt sha_ni xsaveopt xsavec xgetbv1 xsaves split_lock_detect
                                       user_shstk avx_vnni dtherm ida arat pln pts hwp hwp_notify
                                       hwp_act_window hwp_epp hwp_pkg_req hfi vnmi umip pku ospke waitpkg
                                       gfni vaes vpclmulqdq tme rdpid movdiri movdir64b fsrm md_clear
                                       serialize pconfig arch_lbr ibt flush_l1d arch_capabilities
   Virtualization:                     VT-x
   L1d cache:                          576 KiB (12 instances)
   L1i cache:                          384 KiB (12 instances)
   L2 cache:                           24 MiB (12 instances)
   L3 cache:                           36 MiB (1 instance)
   NUMA node(s):                       1
   NUMA node0 CPU(s):                  0-11
   Vulnerability Gather data sampling: Not affected
   Vulnerability Indirect target selection: Not affected
   Vulnerability Itlb multihit:        Not affected
   Vulnerability L1tf:                 Not affected
   Vulnerability Mds:                  Not affected
   Vulnerability Meltdown:             Not affected
   Vulnerability Mmio stale data:      Not affected
   Vulnerability Reg file data sampling: Not affected
   Vulnerability Retbleed:             Not affected
   Vulnerability Spec rstack overflow: Not affected
  Vulnerability Spec store bypass:     Mitigation; Speculative Store Bypass disabled via prctl
  Vulnerability Spectre v1:            Mitigation; usercopy/swapgs barriers and __user pointer
                                       sanitization
  Vulnerability Spectre v2:            Mitigation; Enhanced / Automatic IBRS; IBPB conditional;
                                       PBRSB-eIBRS SW sequence; BHI BHI_DIS_S
   Vulnerability Srbds:                Not affected
   Vulnerability Tsx async abort:      Not affected

 From lscpu --cache:
      NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL  SETS PHY-LINE COHERENCY-SIZE
      L1d       48K     576K   12 Data            1    64        1             64
      L1i       32K     384K    8 Instruction     1    64        1             64
      L2         2M      24M   16 Unified         2  2048        1             64
      L3        36M      36M   12 Unified         3 49152        1             64
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 1 nodes (0)
  node 0 cpus: 0-11
  node 0 size: 64203 MB
  node 0 free: 63467 MB
  node distances:
  node   0
    0:  10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       65744224 kB

------------------------------------------------------------
10. who -r
  run-level 3 Jul 13 03:38

------------------------------------------------------------
11. Systemd service manager version: systemd 254 (254.27+suse.167.g130293e510)
  Default Target  Status
  multi-user      running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled          ModemManager YaST2-Firstboot YaST2-Second-Stage apparmor appstream-sync-cache auditd
                   bluetooth cron display-manager getty@ irqbalance issue-generator kbdsettings klog
                   lvm2-monitor nscd postfix purge-kernels rollback rsyslog smartd sshd systemd-pstore tuned
                   wicked wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny wpa_supplicant
  enabled-runtime  systemd-remount-fs
  disabled         NetworkManager NetworkManager-dispatcher NetworkManager-wait-online accounts-daemon autofs
                   autoyast-initscripts blk-availability bluetooth-mesh boot-sysctl ca-certificates
                   chrony-wait chronyd console-getty cups cups-browsed debug-shell dnsmasq ebtables
                   exchange-bmc-os-info firewalld fsidd gnome-remote-desktop gpm grub2-once haveged
                   hwloc-dump-hwdata ipmi ipmievd issue-add-ssh-keys kexec-load lunmask man-db-create
                   multipathd nfs nfs-blkmap nmb openvpn@ ostree-remount ostree-state-overlay@ rpcbind
                   rpmconfigcheck rsyncd rtkit-daemon samba-bgqd serial-getty@ smartd_generate_opts smb snmpd
                   snmptrapd speech-dispatcherd systemd-boot-check-no-failures systemd-confext
                   systemd-network-generator systemd-sysext systemd-time-wait-sync systemd-timesyncd udisks2
                   update-system-flatpaks upower vncserver@ wpa_supplicant@
  indirect         pcscd saned@ systemd-userdbd wickedd

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.53.6-default
```

(Continued on next page)

Platform Notes (Continued)

```
  root=UUID=16b66c39-3265-46a8-be7f-7591e5d8731a
  splash=silent
  mitigations=auto
  quiet
  security=apparmor

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 2:
    current policy: frequency should be within 800 MHz and 5.70 GHz.
                    The governor "powersave" may decide which speed to use
                    within this range.
    boost state support:
      Supported: yes
      Active: yes

------------------------------------------------------------
15. tuned-adm active
  Current active profile: balanced

------------------------------------------------------------
16. sysctl
  kernel.numa_balancing               0
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                     20
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                      60
  vm.watermark_boost_factor       15000
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                0

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
```

(Continued on next page)

Platform Notes (Continued)

```
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
18. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
19. OS release
  From /etc/*-release /etc/*-version
  os-release SUSE Linux Enterprise Server 15 SP7

------------------------------------------------------------
20. Disk information
SPEC is set to: /home/cpu2026
  Filesystem     Type   Size  Used Avail Use% Mounted on
  /dev/sda2      btrfs  931G  213G  716G  23% /home

------------------------------------------------------------
21. /sys/devices/virtual/dmi/id
    Vendor:         HPE
    Product:        ProLiant MicroServer Gen11
    Product Family: ProLiant
    Serial:         JRT31JQXTD

------------------------------------------------------------
22. dmidecode
  Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
   "DMTF SMBIOS" standard.
   Memory:
     2x Hynix HMCG88AGBEA084N 32 GB 2 rank 5600, configured at 4400


------------------------------------------------------------
23. BIOS
(This section combines info from /sys/devices and dmidecode.)
   BIOS Vendor:       HPE
   BIOS Version:      2.50
   BIOS Date:         06/25/2026
   BIOS Revision:     2.50
```

(Continued on next page)

Platform Notes (Continued)

```
    Firmware Revision: 1.62
```

Compiler Version Notes

```
==============================================================================
C       | 811.tealeaf_s(base, peak) 816.nab_s(base, peak) 881.neutron_s(base,
        | peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++     | 803.sph_exa_s(base, peak) 857.namd_s(base, peak) 867.nest_s(base,
        | peak) 872.marian_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran | 800.pot3d_s(base, peak) 820.cloverleaf_s(base, peak)
        | 822.palm_s(base, peak) 849.fotonik3d_s(base, peak) 865.roms_s(base,
        | peak)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
icx

(Continued on next page)

Base Compiler Invocation (Continued)

C++ benchmarks:
icpx

Fortran benchmarks:
ifx

Benchmarks using both C and C++:
icpx icx

Base Optimization Flags

C benchmarks:
-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xCORE-AVX2 -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fiopenmp -DSPEC_OPENMP
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

C++ benchmarks:
-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xCORE-AVX2 -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -pthread -fiopenmp -DSPEC_OPENMP
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Fortran benchmarks:
-m64 -stand f18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xCORE-AVX2 -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -DSPEC_OPENMP -fiopenmp
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Benchmarks using both C and C++:
-m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500 -xCORE-AVX2 -O3 -ffp-model=fast
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -fiopenmp
-DSPEC_OPENMP -pthread -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Peak Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

(Continued on next page)

Peak Compiler Invocation (Continued)

Fortran benchmarks:
ifx

Benchmarks using both C and C++:
icpx icx

Peak Optimization Flags

C benchmarks:

811.tealeaf_s: basepeak = yes

816.nab_s: -m64 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2
-ffp-model=fast -flto -qopt-mem-layout-trans=4 -O3
-mfpmath=sse -funroll-loops -fiopenmp -DSPEC_OPENMP
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

881.neutron_s: basepeak = yes

C++ benchmarks:

803.sph_exa_s: basepeak = yes

857.namd_s: -m64 -std=c++17 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2
-ffp-model=fast -flto -qopt-mem-layout-trans=4 -O3
-mfpmath=sse -funroll-loops -pthread -fiopenmp
-DSPEC_OPENMP -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

867.nest_s: basepeak = yes

872.marian_s: basepeak = yes

Fortran benchmarks:

800.pot3d_s: basepeak = yes

(Continued on next page)

Peak Optimization Flags (Continued)

820.cloverleaf_s: `-m64 -stand f18 -Wl,-z,muldefs`
`-Wl,-plugin-opt=-inline-threshold=1500`
`-fprofile-generate`(pass 1)
`-fprofile-use=default.profdata`(pass 2) `-xCORE-AVX2`
`-ffp-model=fast -flto -qopt-mem-layout-trans=4 -O3`
`-mfpmath=sse -funroll-loops -nostandard-realloc-lhs`
`-align array32byte -auto -DSPEC_OPENMP -fiopenmp`
`-L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

822.palm_s: `basepeak = yes`

849.fotonik3d_s: `basepeak = yes`

865.roms_s: `basepeak = yes`

Benchmarks using both C and C++:

809.cactus_s: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html`
`http://www.spec.org/cpu2026/results/flags/HPE-Platform-Flags-Intel-CatlowRefresh-rev1.0.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml`
`http://www.spec.org/cpu2026/results/flags/HPE-Platform-Flags-Intel-CatlowRefresh-rev1.0.xml`

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-07-12 18:09:37-0400.
Report generated on 2026-09-08 18:10:54 by CPU2026 PS formatter (86729d3b).
Originally published on 2026-09-08.