SPEC CPU®2026 Integer Speed Result

Cisco Systems

Cisco UCS XE130c M8 (Intel Xeon 6503P-B processor)

SPECspeed®2026_int_base = 1.83

SPECspeed®2026_int_peak = 1.85

CPU2026 License:	9019	**Test Date:**	Aug-2026
Test Sponsor:	Cisco Systems	**Hardware Availability:**	Feb-2025
Tested by:	Cisco Systems	**Software Availability:**	Apr-2026



Hardware

CPU Name:	Intel Xeon 6503P-B
Max MHz:	3500
Nominal:	2000
Enabled:	12 cores, 1 chip
Orderable:	1 Chips
Cache L1:	64 KB I + 48 KB D on chip per core
L2:	2 MB I+D on chip per core
L3:	48 MB I+D on chip per chip
Other:	None
Memory:	512 GB (8 x 64 GB 2Rx4 PC5-6400B-R, running at 4800)
Storage:	1 x 2.4 TB NVME SSD
Cooling:	Air
Other:	None

Software

OS:	SUSE Linux Enterprise Server 15 SP7 6.4.0-150700.51-default
Compiler:	C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category:	Vendor
Firmware:	Version 6.0.2c released May-2026
File System:	xfs
System State:	Run Level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	jemalloc memory allocator v5.3
Power Management:	BIOS set to prefer performance at the cost of additional power usage

Cisco Systems

Cisco UCS XE130c M8 (Intel Xeon 6503P-B processor)

SPECspeed®2026_int_base = 1.83

SPECspeed®2026_int_peak = 1.85

CPU2026 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: Aug-2026
Hardware Availability: Feb-2025
Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
801.xz_s	12	**695**	**0.850**	695	0.850			12	702	0.841	**704**	**0.840**		
807.ntest_s	12	**1044**	**1.09**	1044	1.09			12	**1044**	**1.09**	1044	1.09		
817.flac_s	12	**500**	**3.47**	500	3.47			12	513	3.38	**513**	**3.38**		
821.gcc_s	12	1526	1.36	**1526**	**1.36**			12	1388	1.49	**1388**	**1.49**		
823.llvm_s	12	**1013**	**1.39**	1013	1.39			12	1031	1.37	**1031**	**1.37**		
827.cppcheck_s	12	**859**	**1.30**	857	1.31			12	**859**	**1.30**	857	1.31		
829.abc_s	12	**394**	**2.11**	393	2.12			12	**394**	**2.11**	393	2.12		
834.vpr_s	12	**269**	**3.54**	267	3.58			12	**269**	**3.54**	267	3.58		
835.gem5_s	12	219	5.19	**220**	**5.18**			12	215	5.30	**217**	**5.25**		
838.diamond_s	12	1211	0.827	**1211**	**0.827**			12	1193	0.839	**1193**	**0.839**		
846.minizinc_s	12	**422**	**1.59**	408	1.64			12	**410**	**1.63**	406	1.65		
853.ns3_s	12	215	5.36	**215**	**5.35**			12	200	5.76	**200**	**5.76**		
854.graph500_s	12	**522**	**1.17**	521	1.17			12	**522**	**1.17**	521	1.17		

SPECspeed®2026_int_base = **1.83**

SPECspeed®2026_int_peak = **1.85**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/home/cpu2026/lib"
MALLOC_CONF = "retain:true"
OMP_STACKSIZE = "192M"
```

General Notes

```
 Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
 memory using CentOS Stream 9.
 Transparent Huge Pages enabled by default
 Prior to runcpu invocation
 Filesystem page cache synced and cleared with:
 sync; echo 3>       /proc/sys/vm/drop_caches

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
```

(Continued on next page)

General Notes (Continued)

```
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
 jemalloc, a general purpose malloc implementation
 built with the RedHat Enterprise 7.5, and the system compiler gcc 4.8.5
 sources available from jemalloc.net or https://github.com/jemalloc/jemalloc/releases
```

Platform Notes

```
BIOS settings:
Adjacent cache line prefetcher set to Enabled
DCU Streamer Prefetch set to Disabled
UPI Power Management set to Enabled
XPT prefetch set to Disabled
Patrol scrub set to Disabled
Hyper-Threading set to Disabled

 Sysinfo program /home/cpu2026/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on localhost Wed Aug 12 12:32:36 2026

 SUT (System Under Test) info as seen by some common utilities.

 ------------------------------------------------------------
 Table of contents
 ------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. sysctl
 16. /sys/kernel/mm/transparent_hugepage
 17. /sys/kernel/mm/transparent_hugepage/khugepaged
 18. OS release
 19. Disk information
```

(Continued on next page)

Platform Notes (Continued)

```
20. /sys/devices/virtual/dmi/id
21. dmidecode
22. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 6.4.0-150700.51-default #1 SMP PREEMPT_DYNAMIC Wed Apr 30 21:35:43 UTC 2025 (6930611) x86_64

------------------------------------------------------------
2. w
   12:32:36 up 1 day, 11:31,  5 users,  load average: 0.00, 2.44, 6.76
  USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT
  root     tty1     -                Tue01    3.00s  1.56s  0.01s -bash

------------------------------------------------------------
3. Username
  From environment variable $USER:  root

------------------------------------------------------------
4. ulimit -a
  core file size          (blocks, -c) unlimited
  data seg size           (kbytes, -d) unlimited
  scheduling priority             (-e) 0
  file size               (blocks, -f) unlimited
  pending signals                 (-i) 2061697
  max locked memory       (kbytes, -l) 8192
  max memory size         (kbytes, -m) unlimited
  open files                      (-n) 1024
  pipe size            (512 bytes, -p) 8
  POSIX message queues     (bytes, -q) 819200
  real-time priority              (-r) 0
  stack size              (kbytes, -s) unlimited
  cpu time               (seconds, -t) unlimited
  max user processes              (-u) 2061697
  virtual memory          (kbytes, -v) unlimited
  file locks                      (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd --switched-root --system --deserialize=42
 login -- root
 -bash
 -bash
 runcpu --nobuild --reportable --action validate --define default-platform-flags -c
   ic2026.0-graniterapids-cpu2026-1.0.1-speed-20260429.cfg --threads 12 --define cores=6 --tune base,peak -o
   all --define intspeedaffinity --define smt-on --define drop_caches intspeed
```

(Continued on next page)

Platform Notes (Continued)

```
 runcpu --nobuild --reportable --action validate --define default-platform-flags --configfile
   ic2026.0-graniterapids-cpu2026-1.0.1-speed-20260429.cfg --threads 12 --define cores=6 --tune base,peak
   --output_format all --define intspeedaffinity --define smt-on --define drop_caches --nopower --runmode
   speed --tune base:peak --size refspeed intspeed --nopreenv --note-preenv --logfile
   $SPEC/tmp/CPU2026.004/templogs/preenv.intspeed.004.0.log --lognum 004.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : INTEL(R) XEON(R) 6503P-B
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 174
    stepping        : 1
    microcode       : 0x10002b3
    bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi
    cpu cores       : 12
    siblings        : 12
    1 physical ids (chips)
    12 processors (hardware threads)
    physical id 0: core ids 0-11
    physical id 0: apicids 0,2,4,6,8,10,12,14,16,18,20,22
  Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
  virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.40.4:
  Architecture:                       x86_64
  CPU op-mode(s):                     32-bit, 64-bit
  Address sizes:                      46 bits physical, 57 bits virtual
  Byte Order:                         Little Endian
  CPU(s):                             12
  On-line CPU(s) list:                0-11
  Vendor ID:                          GenuineIntel
  Model name:                         INTEL(R) XEON(R) 6503P-B
  CPU family:                         6
  Model:                              174
  Thread(s) per core:                 1
  Core(s) per socket:                 12
  Socket(s):                          1
  Stepping:                           1
  CPU(s) scaling MHz:                 35%
  CPU max MHz:                        3500.0000
  CPU min MHz:                        800.0000
```

(Continued on next page)

Cisco Systems

Cisco UCS XE130c M8 (Intel Xeon 6503P-B processor)

SPECspeed®2026_int_base = 1.83

SPECspeed®2026_int_peak = 1.85

CPU2026 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: Aug-2026
Hardware Availability: Feb-2025
Software Availability: Apr-2026

Platform Notes (Continued)

```
BogoMIPS:                              4000.00
Flags:                                 fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                       pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                       pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
                                       nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                                       pclmulqdq dtes64 monitor ds_cpl smx est tm2 ssse3 sdbg fma cx16 xtpr
                                       pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer
                                       aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb
                                       cat_l3 cat_l2 cdp_l3 intel_ppin cdp_l2 ssbd mba ibrs ibpb stibp
                                       ibrs_enhanced fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid
                                       cqm rdt_a avx512f avx512dq rdseed adx smap avx512ifma clflushopt clwb
                                       intel_pt avx512cd sha_ni avx512bw avx512vl xsaveopt xsavec xgetbv1
                                       xsaves cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local
                                       split_lock_detect user_shstk avx_vnni avx512_bf16 wbnoinvd dtherm ida
                                       arat pln pts hwp hwp_act_window hwp_epp hwp_pkg_req avx512vbmi umip
                                       pku ospke waitpkg avx512_vbmi2 gfni vaes vpclmulqdq avx512_vnni
                                       avx512_bitalg tme avx512_vpopcntdq la57 rdpid bus_lock_detect
                                       cldemote movdiri movdir64b enqcmd fsrm md_clear serialize tsxldtrk
                                       pconfig arch_lbr ibt amx_bf16 avx512_fp16 amx_tile amx_int8 flush_l1d
                                       arch_capabilities
L1d cache:                             576 KiB (12 instances)
L1i cache:                             768 KiB (12 instances)
L2 cache:                              24 MiB (12 instances)
L3 cache:                              48 MiB (1 instance)
NUMA node(s):                          1
NUMA node0 CPU(s):                     0-11
Vulnerability Gather data sampling:    Not affected
Vulnerability Itlb multihit:           Not affected
Vulnerability L1tf:                    Not affected
Vulnerability Mds:                     Not affected
Vulnerability Meltdown:                Not affected
Vulnerability Mmio stale data:         Not affected
Vulnerability Reg file data sampling:  Not affected
Vulnerability Retbleed:                Not affected
Vulnerability Spec rstack overflow:    Not affected
Vulnerability Spec store bypass:       Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1:              Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Vulnerability Spectre v2:              Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling;
                                       PBRSB-eIBRS Not affected; BHI BHI_DIS_S
Vulnerability Srbds:                   Not affected
Vulnerability Tsx async abort:         Not affected

From lscpu --cache:
    NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL  SETS PHY-LINE COHERENCY-SIZE
    L1d       48K     576K   12 Data            1    64        1             64
    L1i       64K     768K   16 Instruction     1    64        1             64
    L2         2M      24M   16 Unified         2  2048        1             64
```

(Continued on next page)

Platform Notes (Continued)

```
     L3        48M      48M   16 Unified         3 49152        1             64

 ------------------------------------------------------------
 8. numactl --hardware
 NOTE: a numactl 'node' might or might not correspond to a physical chip.
   available: 1 nodes (0)
   node 0 cpus: 0-11
   node 0 size: 515451 MB
   node 0 free: 508842 MB
   node distances:
   node   0
     0:  10

 ------------------------------------------------------------
 9. /proc/meminfo
    MemTotal:       527822604 kB

 ------------------------------------------------------------
 10. who -r
   run-level 3 Aug 11 01:00

 ------------------------------------------------------------
 11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)
   Default Target  Status
   multi-user      running

 ------------------------------------------------------------
 12. Services, from systemctl list-unit-files
   STATE            UNIT FILES
   enabled          YaST2-Firstboot YaST2-Second-Stage apparmor auditd cron getty@ irqbalance iscsi
                    issue-generator kbdsettings klog lvm2-monitor nscd nvmefc-boot-connections
                    nvmf-autoconnect postfix purge-kernels rollback rsyslog smartd sshd systemd-pstore
                    virtqemud wicked wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
   enabled-runtime  systemd-remount-fs
   disabled         autofs autoyast-initscripts blk-availability boot-sysctl ca-certificates chrony-wait
                    chronyd console-getty cups cups-browsed debug-shell dnsmasq ebtables exchange-bmc-os-info
                    firewalld fsidd gpm grub2-once haveged hv_fcopy_daemon hv_fcopy_uio_daemon hv_kvp_daemon
                    hv_vss_daemon ipmi ipmievd iscsi-init iscsid issue-add-ssh-keys kexec-load ksm kvm_stat
                    libvirt-guests lunmask man-db-create multipathd nfs nfs-blkmap nfs-server nfsserver
                    rpcbind rpmconfigcheck rsyncd rtkit-daemon serial-getty@ smartd_generate_opts snmpd
                    snmptrapd strongswan strongswan-starter svnserve systemd-boot-check-no-failures
                    systemd-confext systemd-network-generator systemd-nspawn@ systemd-sysext
                    systemd-time-wait-sync systemd-timesyncd udisks2 virtinterfaced virtlockd virtlogd
                    virtnetworkd virtnodedevd virtnwfilterd virtsecretd virtstoraged
   indirect         pcscd systemd-userdbd tftp wickedd

 ------------------------------------------------------------
```

(Continued on next page)

Platform Notes (Continued)

```
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.51-default
  root=UUID=3b4ce6e1-b593-4070-a649-689a9dc5aeea
  splash=silent
  resume=/dev/disk/by-uuid/af9e348b-357a-48ea-9411-a8ab3cd0fb15
  mitigations=auto
  quiet
  security=apparmor

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 6:
    current policy: frequency should be within 800 MHz and 3.50 GHz.
                    The governor "powersave" may decide which speed to use
                    within this range.
    boost state support:
      Supported: yes
      Active: yes

------------------------------------------------------------
15. sysctl
  kernel.numa_balancing              0
  kernel.randomize_va_space          2
  vm.compaction_proactiveness       20
  vm.dirty_background_bytes          0
  vm.dirty_background_ratio         10
  vm.dirty_bytes                     0
  vm.dirty_expire_centisecs       3000
  vm.dirty_ratio                    20
  vm.dirty_writeback_centisecs     500
  vm.dirtytime_expire_seconds    43200
  vm.extfrag_threshold             500
  vm.min_unmapped_ratio              1
  vm.nr_hugepages                    0
  vm.nr_hugepages_mempolicy          0
  vm.nr_overcommit_hugepages         0
  vm.swappiness                     60
  vm.watermark_boost_factor      15000
  vm.watermark_scale_factor         10
  vm.zone_reclaim_mode               0

------------------------------------------------------------
16. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
18. OS release
  From /etc/*-release /etc/*-version
  os-release SUSE Linux Enterprise Server 15 SP7

------------------------------------------------------------
19. Disk information
SPEC is set to: /home/cpu2026
  Filesystem     Type  Size  Used Avail Use% Mounted on
  /dev/nvme1n1p3 xfs   2.4T  113G  2.3T   5% /home

------------------------------------------------------------
20. /sys/devices/virtual/dmi/id
    Vendor:         Cisco Systems Inc
    Product:        UCSXE-130C-M8-12
    Product Family: Cisco Edge Server
    Serial:         WZP294093N6

------------------------------------------------------------
21. dmidecode
  Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
  "DMTF SMBIOS" standard.
  Memory:
    8x 0xCE00 M321R8GA0PB2-CCPKC 64 GB 2 rank 6400, configured at 4800


------------------------------------------------------------
22. BIOS
(This section combines info from /sys/devices and dmidecode.)
   BIOS Vendor:       Cisco Systems, Inc.
   BIOS Version:      XE1X0M8.6.0.2c.0.0526261754
   BIOS Date:         05/26/2026
   BIOS Revision:     5.35
```

Compiler Version Notes

```
==============================================================================
C       | 854.graph500_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++     | 807.ntest_s(base, peak) 827.cppcheck_s(base, peak) 853.ns3_s(base,
        | peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++, C | 801.xz_s(base, peak) 817.flac_s(base, peak) 821.gcc_s(base, peak)
        | 823.llvm_s(base, peak) 829.abc_s(base, peak) 834.vpr_s(base, peak)
        | 835.gem5_s(base, peak) 838.diamond_s(base, peak)
        | 846.minizinc_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`icx`

C++ benchmarks:
`icpx`

Benchmarks using both C and C++:
`icpx icx`

Base Portability Flags

834.vpr_s: `-fno-fast-math`

Base Optimization Flags

C benchmarks:
-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xgraniterapids -mprefer-vector-width=512 -O3 -ffp-model=fast -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-fno-strict-aliasing -fiopenmp -DSPEC_OPENMP
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

C++ benchmarks:
-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xgraniterapids -mprefer-vector-width=512 -O3 -ffp-model=fast -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -pthread
-fiopenmp -DSPEC_OPENMP -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Benchmarks using both C and C++:
-m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500 -xgraniterapids
-mprefer-vector-width=512 -O3 -ffp-model=fast -flto -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4 -fno-strict-aliasing -fiopenmp
-DSPEC_OPENMP -pthread -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Peak Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

Benchmarks using both C and C++:
icpx icx

Peak Portability Flags

834.vpr_s: -fno-fast-math

Peak Optimization Flags

C benchmarks:

(Continued on next page)

Peak Optimization Flags (Continued)

854.graph500_s: `basepeak = yes`

C++ benchmarks:

807.ntest_s: `basepeak = yes`

827.cppcheck_s: `basepeak = yes`

853.ns3_s: `-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -fprofile-generate`(pass 1) `-fprofile-use=default.profdata`(pass 2) `-xHost`(pass 1) `-ffp-model=fast -xgraniterapids`(pass 2) `-flto -mprefer-vector-width=512 -qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops -pthread -fiopenmp -DSPEC_OPENMP -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

Benchmarks using both C and C++:

801.xz_s: `-m64 -std=c++17 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -fprofile-generate`(pass 1) `-fprofile-use=default.profdata`(pass 2) `-xHost`(pass 1) `-ffp-model=fast -xgraniterapids`(pass 2) `-flto -mprefer-vector-width=512 -qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops -fno-strict-aliasing -fiopenmp -DSPEC_OPENMP -pthread -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

817.flac_s: `Same as 801.xz_s`

821.gcc_s: `-m64 -std=c++17 -std=c18 -Wl,-z,muldefs -fprofile-generate`(pass 1) `-fprofile-use=default.profdata`(pass 2) `-xHost`(pass 1) `-ffp-model=fast -xgraniterapids`(pass 2) `-flto -mprefer-vector-width=512 -qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops -fno-strict-aliasing -fiopenmp -DSPEC_OPENMP -pthread -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

823.llvm_s: `Same as 821.gcc_s`

829.abc_s: `basepeak = yes`

834.vpr_s: `basepeak = yes`

(Continued on next page)

Peak Optimization Flags (Continued)

835.gem5_s: `Same as 801.xz_s`

838.diamond_s: `Same as 801.xz_s`

846.minizinc_s: `Same as 801.xz_s`

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html
http://www.spec.org/cpu2026/results/flags/Cisco-Platform-Settings-V2.0-GNR-revP.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml
http://www.spec.org/cpu2026/results/flags/Cisco-Platform-Settings-V2.0-GNR-revP.xml

Tested with SPEC CPU®2026 v1.0.1 on 2026-08-12 12:32:35-0400.
Report generated on 2026-09-22 12:59:37 by CPU2026 PS formatter (86729d3b).
Originally published on 2026-09-22.