SPEC CPU®2026 Floating Point Speed Result

xFusion

FusionServer 2158H V8
AMD EPYC 9115

SPECspeed®2026_fp_base = 4.66

SPECspeed®2026_fp_peak = 4.67

CPU2026 License:	6488	**Test Date:**	Oct-2026
Test Sponsor:	xFusion	**Hardware Availability:**	Oct-2024
Tested by:	xFusion	**Software Availability:**	May-2026



Hardware

CPU Name:	AMD EPYC 9115
Max MHz:	4100
Nominal:	2600
Enabled:	16 cores, 1 chip, 2 threads/core
Orderable:	1 chip
Cache L1:	32 KB I + 48 KB D on chip per core
L2:	1 MB I+D on chip per core
L3:	64 MB I+D on chip per chip, 32 MB shared / 8 cores
Other:	None
Memory:	384 GB (12 x 32 GB 2Rx8 PC5-6400B-R)
Storage:	1 x 480 GB SATA SSD
Cooling:	Air
Other:	None

Software

OS:	SUSE Linux Enterprise Server 15 SP6 kernel version 6.4.0-150600.21-default
Compiler:	C/C++: Version 5.2.0 of AOCC Fortran: Flang v22
Compiler Category:	Vendor
Firmware:	Version 01.13.06.48 released Aug-2026
File System:	btrfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	None
Power Management:	BIOS and OS set to prefer performance at the cost of additional power usage

SPEC CPU®2026 Floating Point Speed Result

xFusion

FusionServer 2158H V8
AMD EPYC 9115

SPECspeed®2026_fp_base = 4.66

SPECspeed®2026_fp_peak = 4.67

CPU2026 License:	6488	**Test Date:**	Oct-2026
Test Sponsor:	xFusion	**Hardware Availability:**	Oct-2024
Tested by:	xFusion	**Software Availability:**	May-2026

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
800.pot3d_s	16	152	4.43	**152**	**4.43**	152	4.44	16	152	4.43	152	4.44	**152**	**4.44**
803.sph_exa_s	16	200	6.20	**193**	**6.40**	193	6.41	16	191	6.50	**190**	**6.51**	188	6.59
809.cactus_s	16	126	8.88	126	8.90	**126**	**8.88**	16	124	9.03	125	8.99	**124**	**9.01**
811.tealeaf_s	16	**218**	**2.55**	220	2.54	218	2.56	16	220	2.53	218	2.55	**218**	**2.55**
816.nab_s	16	**238**	**4.73**	238	4.72	238	4.73	16	**238**	**4.73**	238	4.72	238	4.73
820.cloverleaf_s	16	208	4.13	208	4.13	**208**	**4.13**	16	**207**	**4.13**	207	4.13	208	4.13
822.palm_s	16	183	6.70	**184**	**6.66**	184	6.66	16	183	6.70	**184**	**6.66**	184	6.66
849.fotonik3d_s	16	149	4.42	149	4.43	**149**	**4.43**	16	149	4.42	149	4.43	**149**	**4.43**
857.namd_s	16	483	3.00	484	3.00	**484**	**3.00**	16	**483**	**3.00**	484	3.00	483	3.01
865.roms_s	16	**169**	**6.46**	169	6.47	169	6.44	16	**169**	**6.46**	169	6.47	169	6.44
867.nest_s	16	642	3.36	**638**	**3.38**	638	3.39	16	642	3.36	**638**	**3.38**	638	3.39
872.marian_s	16	134	8.09	**134**	**8.10**	133	8.11	16	134	8.09	**134**	**8.10**	133	8.11
881.neutron_s	16	332	2.46	**332**	**2.46**	332	2.46	16	332	2.46	**332**	**2.46**	332	2.46

SPECspeed®2026_fp_base = 4.66

SPECspeed®2026_fp_peak = 4.67

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

```
The AMD64 AOCC Compiler Suite is available at
http://developer.amd.com/amd-aocc/
Flang v22 is available at
https://flang.llvm.org/
```

Submit Notes

```
The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.
```

Operating System Notes

```
'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
    numactl --physcpubind=0-15 runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.
To free node-local memory and avoid remote memory usage,
```

(Continued on next page)

Operating System Notes (Continued)

```
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.
To disable address space layout randomization (ASLR) to reduce run-to-run
variability, 'sysctl -w kernel.randomize_va_space=0' run as root.

To enable Transparent Hugepages (THP) for all allocations,
'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

To disable Transparent Hugepages (THP) for 816.nab_s,865.roms_s=peak:
'echo never > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo never > /sys/kernel/mm/transparent_hugepage/defrag' run as root.
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
GOMP_CPU_AFFINITY = "0-31"
LD_LIBRARY_PATH =
     "/home/cpu2026/amd_speed_aocc520_znver5_A_lib/lib:/home/cpu2026/amd_spee
     d_aocc520_znver5_A_lib/lib32:"
MALLOC_CONF = "retain:true"
OMP_THREAD_LIMIT = "32"
```

General Notes

```
Binaries were compiled on a system with an AMD EPYC 9754 CPU + 768 GiB Memory using Ubuntu 24.04
 NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
 is mitigated in the system as tested and documented.
 Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
 is mitigated in the system as tested and documented.
 Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
 is mitigated in the system as tested and documented.
```

Platform Notes

```
BIOS settings:
 Determinism Control = Manual
 Determinism Enable = Power
 TDP Control = Manual
 TDP = 155
 PPT Control = Manual
 PPT = 155
 NUMA Nodes Per Socket = NPS2
```

(Continued on next page)

Platform Notes (Continued)

```
Sysinfo program /home/cpu2026/bin/sysinfo
Rev: 779ab21020787073335a329f3a45e2cd
running on localhost Wed Oct 14 05:29:11 2026

SUT (System Under Test) info as seen by some common utilities.

------------------------------------------------------------
Table of contents
------------------------------------------------------------
 1. uname -srvm
 2. w
 3. Username
 4. ulimit -a
 5. sysinfo process ancestry
 6. /proc/cpuinfo
 7. lscpu
 8. numactl --hardware
 9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. sysctl
16. /sys/kernel/mm/transparent_hugepage
17. /sys/kernel/mm/transparent_hugepage/khugepaged
18. OS release
19. Disk information
20. /sys/devices/virtual/dmi/id
21. dmidecode
22. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 6.4.0-150600.21-default #1 SMP PREEMPT_DYNAMIC Thu May 16 11:09:22 UTC 2024 (36c1e09) x86_64

------------------------------------------------------------
2. w
   05:29:11 up 1 day,  6:27,  1 user,  load average: 13.05, 16.80, 16.35
  USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT
  root     tty1     -                Mon23    7:57m  6.33s  5.11s python3
  ./run_amd_speed_aocc520_znver5_A1.py

------------------------------------------------------------
3. Username
  From environment variable $USER:  root
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
4. ulimit -a
  core file size          (blocks, -c) unlimited
  data seg size           (kbytes, -d) unlimited
  scheduling priority             (-e) 0
  file size               (blocks, -f) unlimited
  pending signals                 (-i) 1544364
  max locked memory       (kbytes, -l) 2048
  max memory size         (kbytes, -m) unlimited
  open files                      (-n) 1024
  pipe size            (512 bytes, -p) 8
  POSIX message queues     (bytes, -q) 819200
  real-time priority              (-r) 0
  stack size              (kbytes, -s) unlimited
  cpu time               (seconds, -t) unlimited
  max user processes              (-u) 1544364
  virtual memory          (kbytes, -v) unlimited
  file locks                      (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd --switched-root --system --deserialize=42
 login -- root
 -bash
 python3 ./run_amd_speed_aocc520_znver5_A1.py
 runcpu --config amd_speed_aocc520_znver5_A1.cfg --tune all --reportable --iterations 3 fpspeed
 runcpu --configfile amd_speed_aocc520_znver5_A1.cfg --tune all --reportable --iterations 3 --nopower
   --runmode speed --tune base:peak --size test:train:refspeed fpspeed --nopreenv --note-preenv --logfile
   $SPEC/tmp/CPU2026.039/templogs/preenv.fpspeed.039.0.log --lognum 039.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : AMD EPYC 9115 16-Core Processor
    vendor_id       : AuthenticAMD
    cpu family      : 26
    model           : 2
    stepping        : 1
    microcode       : 0xb002162
    bugs            : sysret_ss_attrs spectre_v1 spectre_v2 spec_store_bypass
    TLB size        : 192 4K pages
    cpu cores       : 16
    siblings        : 32
    1 physical ids (chips)
    32 processors (hardware threads)
```

(Continued on next page)

xFusion
FusionServer 2158H V8
AMD EPYC 9115

SPECspeed®2026_fp_base = 4.66
SPECspeed®2026_fp_peak = 4.67

CPU2026 License: 6488
Test Sponsor: xFusion
Tested by: xFusion
Test Date: Oct-2026
Hardware Availability: Oct-2024
Software Availability: May-2026

Platform Notes (Continued)

```
    physical id 0: core ids 0-15
    physical id 0: apicids 0-31
  Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
  virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.39.3:
  Architecture:                      x86_64
  CPU op-mode(s):                    32-bit, 64-bit
  Address sizes:                     52 bits physical, 57 bits virtual
  Byte Order:                        Little Endian
  CPU(s):                            32
  On-line CPU(s) list:               0-31
  Vendor ID:                         AuthenticAMD
  BIOS Vendor ID:                    Advanced Micro Devices, Inc.
  Model name:                        AMD EPYC 9115 16-Core Processor
  BIOS Model name:                   AMD EPYC 9115 16-Core Processor Unknown CPU @ 2.6GHz
  BIOS CPU family:                   107
  CPU family:                        26
  Model:                             2
  Thread(s) per core:                2
  Core(s) per socket:                16
  Socket(s):                         1
  Stepping:                          1
  Frequency boost:                   enabled
  CPU(s) scaling MHz:                84%
  CPU max MHz:                       4115.8198
  CPU min MHz:                       1500.0000
  BogoMIPS:                          5192.24
  Flags:                             fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                     pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt pdpe1gb
                                     rdtscp lm constant_tsc rep_good amd_lbr_v2 nopl nonstop_tsc cpuid
                                     extd_apicid aperfmperf rapl pni pclmulqdq monitor ssse3 fma cx16 pcid
                                     sse4_1 sse4_2 x2apic movbe popcnt aes xsave avx f16c rdrand lahf_lm
                                     cmp_legacy svm extapic cr8_legacy abm sse4a misalignsse 3dnowprefetch
                                     osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb bpext
                                     perfctr_llc mwaitx cpb cat_l3 cdp_l3 hw_pstate ssbd mba perfmon_v2
                                     ibrs ibpb stibp ibrs_enhanced vmmcall fsgsbase tsc_adjust bmi1 avx2
                                     smep bmi2 erms invpcid cqm rdt_a avx512f avx512dq rdseed adx smap
                                     avx512ifma clflushopt clwb avx512cd sha_ni avx512bw avx512vl xsaveopt
                                     xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
                                     cqm_mbm_local user_shstk avx_vnni avx512_bf16 clzero irperf
                                     xsaveerptr rdpru wbnoinvd amd_ppin cppc arat npt lbrv svm_lock
                                     nrip_save tsc_scale vmcb_clean flushbyasid decodeassists pausefilter
                                     pfthreshold avic v_vmsave_vmload vgif x2avic v_spec_ctrl vnmi
```

(Continued on next page)

Platform Notes (Continued)

```
                                     avx512vbmi umip pku ospke avx512_vbmi2 gfni vaes vpclmulqdq
                                     avx512_vnni avx512_bitalg avx512_vpopcntdq la57 rdpid bus_lock_detect
                                     movdiri movdir64b overflow_recov succor smca fsrm avx512_vp2intersect
                                     flush_l1d debug_swap
  Virtualization:                      AMD-V
  L1d cache:                           768 KiB (16 instances)
  L1i cache:                           512 KiB (16 instances)
  L2 cache:                            16 MiB (16 instances)
  L3 cache:                            64 MiB (2 instances)
  NUMA node(s):                        2
  NUMA node0 CPU(s):                   0-7,16-23
  NUMA node1 CPU(s):                   8-15,24-31
  Vulnerability Gather data sampling:  Not affected
  Vulnerability Itlb multihit:         Not affected
  Vulnerability L1tf:                  Not affected
  Vulnerability Mds:                   Not affected
  Vulnerability Meltdown:              Not affected
  Vulnerability Mmio stale data:       Not affected
  Vulnerability Reg file data sampling: Not affected
  Vulnerability Retbleed:              Not affected
  Vulnerability Spec rstack overflow:  Not affected
  Vulnerability Spec store bypass:     Mitigation; Speculative Store Bypass disabled via prctl
  Vulnerability Spectre v1:            Mitigation; usercopy/swapgs barriers and __user pointer sanitization
  Vulnerability Spectre v2:            Mitigation; Enhanced / Automatic IBRS; IBPB conditional; STIBP
                                       always-on; RSB filling; PBRSB-eIBRS Not affected; BHI Not affected
  Vulnerability Srbds:                 Not affected
  Vulnerability Tsx async abort:       Not affected

From lscpu --cache:
     NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL  SETS PHY-LINE COHERENCY-SIZE
     L1d       48K     768K   12 Data            1    64        1             64
     L1i       32K     512K    8 Instruction     1    64        1             64
     L2         1M      16M   16 Unified         2  1024        1             64
     L3        32M      64M   16 Unified         3 32768        1             64

------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 2 nodes (0-1)
  node 0 cpus: 0-7,16-23
  node 0 size: 193030 MB
  node 0 free: 192449 MB
  node 1 cpus: 8-15,24-31
  node 1 size: 193086 MB
  node 1 free: 192343 MB
  node distances:
  node   0   1
```

(Continued on next page)

Platform Notes (Continued)

```
    0:  10  12
    1:  12  10

 ------------------------------------------------------------
 9. /proc/meminfo
    MemTotal:       395383808 kB

 ------------------------------------------------------------
 10. who -r
   run-level 3 Oct 12 23:01

 ------------------------------------------------------------
 11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)
   Default Target  Status
   multi-user      running

 ------------------------------------------------------------
 12. Services, from systemctl list-unit-files
   STATE            UNIT FILES
   enabled          YaST2-Firstboot YaST2-Second-Stage apparmor auditd cron display-manager firewalld getty@
                    irqbalance issue-generator kbdsettings kdump kdump-early kdump-notify klog lvm2-monitor
                    nscd postfix purge-kernels rollback rsyslog smartd sshd systemd-pstore wicked
                    wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
   enabled-runtime  systemd-remount-fs
   disabled         autofs autoyast-initscripts blk-availability boot-sysctl ca-certificates chrony-wait
                    chronyd console-getty cups cups-browsed debug-shell ebtables exchange-bmc-os-info fsidd
                    gpm grub2-once haveged ipmi ipmievd issue-add-ssh-keys kexec-load lunmask man-db-create
                    multipathd nfs nfs-blkmap rpcbind rpmconfigcheck rsyncd serial-getty@ smartd_generate_opts
                    snmpd snmptrapd systemd-boot-check-no-failures systemd-confext systemd-network-generator
                    systemd-sysext systemd-time-wait-sync systemd-timesyncd vncserver@
   indirect         systemd-userdbd wickedd

 ------------------------------------------------------------
 13. Linux kernel boot-time arguments, from /proc/cmdline
   BOOT_IMAGE=/boot/vmlinuz-6.4.0-150600.21-default
   root=UUID=9287dffd-6361-492c-aaa8-19b8fa03cc61
   splash=silent
   mitigations=auto
   quiet
   security=apparmor
   crashkernel=350M,high
   crashkernel=72M,low

 ------------------------------------------------------------
 14. cpupower frequency-info
   analyzing CPU 29:
     current policy: frequency should be within 1.50 GHz and 2.60 GHz.
```

(Continued on next page)

Platform Notes (Continued)

```
                The governor "performance" may decide which speed to use
                within this range.
     boost state support:
       Supported: yes
       Active: yes

 ------------------------------------------------------------
 15. sysctl
   kernel.numa_balancing                1
   kernel.randomize_va_space            0
   vm.compaction_proactiveness         20
   vm.dirty_background_bytes            0
   vm.dirty_background_ratio           10
   vm.dirty_bytes                       0
   vm.dirty_expire_centisecs         3000
   vm.dirty_ratio                       8
   vm.dirty_writeback_centisecs       500
   vm.dirtytime_expire_seconds      43200
   vm.extfrag_threshold               500
   vm.min_unmapped_ratio                1
   vm.nr_hugepages                      0
   vm.nr_hugepages_mempolicy            0
   vm.nr_overcommit_hugepages           0
   vm.swappiness                        1
   vm.watermark_boost_factor        15000
   vm.watermark_scale_factor           10
   vm.zone_reclaim_mode                 1

 ------------------------------------------------------------
 16. /sys/kernel/mm/transparent_hugepage
   defrag          [always] defer defer+madvise madvise never
   enabled         [always] madvise never
   hpage_pmd_size  2097152
   shmem_enabled   always within_size advise [never] deny force

 ------------------------------------------------------------
 17. /sys/kernel/mm/transparent_hugepage/khugepaged
   alloc_sleep_millisecs   60000
   defrag                      1
   max_ptes_none             511
   max_ptes_shared           256
   max_ptes_swap              64
   pages_to_scan            4096
   scan_sleep_millisecs    10000

 ------------------------------------------------------------
 18. OS release
```

(Continued on next page)

Platform Notes (Continued)

```
  From /etc/*-release /etc/*-version
  os-release SUSE Linux Enterprise Server 15 SP6

------------------------------------------------------------
19. Disk information
SPEC is set to: /home/cpu2026
  Filesystem     Type   Size  Used Avail Use% Mounted on
  /dev/sda2      btrfs  200G   15G  183G   8% /home

------------------------------------------------------------
20. /sys/devices/virtual/dmi/id
    Vendor:         XFUSION
    Product:        2158H V8
    Product Family: Turin

------------------------------------------------------------
21. dmidecode
  Additional information from dmidecode 3.4 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
  "DMTF SMBIOS" standard.
  Memory:
    3x Samsung M321R4GA3EB2-CCPEC 32 GB 2 rank 6400
    9x Samsung M321R4GA3EB2-CCPWC 32 GB 2 rank 6400


------------------------------------------------------------
22. BIOS
(This section combines info from /sys/devices and dmidecode.)
   BIOS Vendor:       XFUSION
   BIOS Version:      01.13.06.48
   BIOS Date:         08/06/2026
   BIOS Revision:     6.48
```

Compiler Version Notes

```
==============================================================================
C       | 811.tealeaf_s(base, peak) 816.nab_s(base, peak) 881.neutron_s(base,
        | peak)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
==============================================================================
C++     | 803.sph_exa_s(base, peak) 857.namd_s(base, peak) 867.nest_s(base,
        | peak) 872.marian_s(base, peak)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin
------------------------------------------------------------------------------

==============================================================================
C++, C  | 809.cactus_s(base, peak)
------------------------------------------------------------------------------
AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin
------------------------------------------------------------------------------

==============================================================================
Fortran | 800.pot3d_s(base, peak) 820.cloverleaf_s(base, peak)
        | 822.palm_s(base, peak) 849.fotonik3d_s(base, peak) 865.roms_s(base,
        | peak)
------------------------------------------------------------------------------
flang version 22.1.0-rc2 (https://github.com/llvm/llvm-project
  a47b42eb9f9b302167b4fc413e6c92798d65dd0b)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/llvm/llvm-22.1.0-rc2/install/bin
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`clang`

C++ benchmarks:
`clang++`

Fortran benchmarks:
`flang-22`

Benchmarks using both C and C++:
`clang++ clang`

Base Portability Flags

800.pot3d_s: -DSPEC_LP64
803.sph_exa_s: -DSPEC_LP64
809.cactus_s: -DSPEC_LP64
811.tealeaf_s: -DSPEC_LP64
816.nab_s: -DSPEC_LP64
820.cloverleaf_s: -DSPEC_LP64
822.palm_s: -DSPEC_LP64
849.fotonik3d_s: -DSPEC_LP64
857.namd_s: -DSPEC_LP64
865.roms_s: -DSPEC_LP64
867.nest_s: -fno-finite-math-only -DSPEC_LP64
872.marian_s: -DSPEC_LP64
881.neutron_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:
-m64 -std=c18 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -fremap-arrays -fstrip-mining
-fstruct-layout=7 -mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -mllvm -unroll-threshold=50 -zopt
-mrecip=none -fopenmp -DSPEC_OPENMP -lamdalloc -lamdlibm
-fopenmp=libomp -lomp

C++ benchmarks:
-m64 -std=c++17 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -mllvm -unroll-threshold=100
-mllvm -loop-unswitch-threshold=200000
-mllvm -reduce-array-computations=3 -zopt -fopenmp -DSPEC_OPENMP
-pthread -lamdalloc -lamdlibm -fopenmp=libomp -lomp

Fortran benchmarks:
-m64 -std=f2018 -O3 -flto -march=znver5 -fveclib=AMDLIBM
-ffast-math -funroll-loops -DSPEC_OPENMP -fopenmp
-fdo-concurrent-to-openmp=host -lamdalloc -lamdlibm -fopenmp=libomp
-lomp

Benchmarks using both C and C++:
-m64 -std=c++17 -std=c18 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -fremap-arrays -fstrip-mining
-fstruct-layout=7 -mllvm -inline-threshold=1000

(Continued on next page)

Base Optimization Flags (Continued)

Benchmarks using both C and C++ (continued):
```
-mllvm -reduce-array-computations=3 -mllvm -unroll-threshold=50 -zopt
-mllvm -unroll-threshold=100 -mllvm -loop-unswitch-threshold=200000
-mrecip=none -fopenmp -DSPEC_OPENMP -pthread -lamdalloc -lamdlibm
-fopenmp=libomp -lomp
```

Base Other Flags

C benchmarks:
`-Wno-return-type -Wno-unused-command-line-argument`

Benchmarks using both C and C++:
`-Wno-return-type -Wno-unused-command-line-argument`

Peak Compiler Invocation

C benchmarks:
`clang`

C++ benchmarks:
`clang++`

Fortran benchmarks:
`flang-22`

Benchmarks using both C and C++:
`clang++ clang`

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

(Continued on next page)

Peak Optimization Flags (Continued)

811.tealeaf_s: -m64 -std=c18
-Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -flto
-march=znver5 -fveclib=AMDLIBM -ffast-math
-fremap-arrays -fstrip-mining -fstruct-layout=7
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3
-mllvm -unroll-threshold=50 -fopenmp -DSPEC_OPENMP
-lamdalloc -lamdlibm -fopenmp=libomp -lomp

816.nab_s: basepeak = yes

881.neutron_s: basepeak = yes

C++ benchmarks:

803.sph_exa_s: -m64 -std=c++17
-Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-fprofile-instr-generate(pass 1)
-fprofile-instr-use(pass 2) -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math
-mllvm -reduce-array-computations=3
-mllvm -unroll-threshold=100 -fopenmp -DSPEC_OPENMP
-pthread -lamdalloc -lamdlibm -fopenmp=libomp -lomp

857.namd_s: Same as 803.sph_exa_s

867.nest_s: basepeak = yes

872.marian_s: basepeak = yes

Fortran benchmarks:

800.pot3d_s: -m64 -std=f2018 -O3 -flto -march=znver5
-fveclib=AMDLIBM -ffast-math -funroll-loops
-DSPEC_OPENMP -fopenmp -fdo-concurrent-to-openmp=host
-lamdalloc -lamdlibm -fopenmp=libomp -lomp

820.cloverleaf_s: Same as 800.pot3d_s

822.palm_s: basepeak = yes

849.fotonik3d_s: Same as 800.pot3d_s

(Continued on next page)

xFusion
FusionServer 2158H V8
AMD EPYC 9115

SPECspeed®2026_fp_base = 4.66
SPECspeed®2026_fp_peak = 4.67

CPU2026 License: 6488
Test Sponsor: xFusion
Tested by: xFusion
Test Date: Oct-2026
Hardware Availability: Oct-2024
Software Availability: May-2026

Peak Optimization Flags (Continued)

865.roms_s: `basepeak = yes`

Benchmarks using both C and C++:
`-m64 -std=c++17 -std=c18 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6 -Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -flto -march=znver5 -fveclib=AMDLIBM -ffast-math -fremap-arrays -fstrip-mining -fstruct-layout=7 -mllvm -inline-threshold=1000 -mllvm -reduce-array-computations=3 -mllvm -unroll-threshold=50 -mllvm -unroll-threshold=100 -fopenmp -DSPEC_OPENMP -pthread -lamdalloc -lamdlibm -fopenmp=libomp -lomp`

Peak Other Flags

C benchmarks (except as noted below):
`-Wno-return-type -Wno-unused-command-line-argument`

811.tealeaf_s: `-Wno-return-type`

Benchmarks using both C and C++:
`-Wno-return-type`

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2026/results/flags/aocc-flags.2026-08-11.00.html
http://www.spec.org/cpu2026/results/flags/xFusion-Platform-CPU2026-Settings-AMD-V1.0-revB.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2026/results/flags/aocc-flags.2026-08-11.00.xml
http://www.spec.org/cpu2026/results/flags/xFusion-Platform-CPU2026-Settings-AMD-V1.0-revB.xml

Tested with SPEC CPU®2026 v1.0.1 on 2026-10-14 05:29:10-0400.
Report generated on 2026-11-04 10:50:06 by CPU2026 PS formatter (86729d3b).
Originally published on 2026-11-03.