SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Hitachi Ltd.
3500/555RM

SPECint95 = 5.75

SPECint_base95 = 5.28

SPEC license # 35	Tested By: Kanagawa Pref.Japan	Test Date: Jan-97	Hardware Avail: Mar-97	Software Avail: Apr-97



Hardware/Software Configuration for:
3500/555RM

Hardware

Model Name:	3500/555RM
CPU:	120MHz PA-RISC 7200
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	256KBI+256KBD off-chip
Secondary Cache:	None
Other Cache:	None
Memory:	512MB
Disk Subsystem:	SCSI Hitachi HT-F3305-731S (2.1GB)
Other Hardware:	Ethernet

Software

Operating System:	HI-UX/WE2/BASE 07-02
Compiler:	Hitachi C 05-03
File System:	Berkeley FFS
System State:	Multi-user

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	624	7.37	609	7.55
124.m88ksim	1900	409	4.65	346	5.50
126.gcc	1700	326	5.22	325	5.24
129.compress	1800	387	4.65	304	5.92
130.li	1900	350	5.43	307	6.20
132.ijpeg	2400	541	4.44	497	4.82
134.perl	1900	356	5.34	342	5.56
147.vortex	2700	479	5.64	482	5.60
SPECint_base95 (G. Mean)			5.28		
		SPECint95 (G. Mean)			5.75

Notes/Tuning Information

```
Portability Flags (base & peak): All: -Ae

Base Flags:
All:/opt/langtools/lib/fastmem.o +Oall +I/+P
Linker Flag: All:  -Wl,-aarchive
Peak Flags:
099.go      :+ESfic +ESlit +O4 +I/+P +Oentrysched +Olibcalls +Onofastaccess
.            +Onolimit +Onoloop_unroll +Optrs_strongly_typed +Ostaticprediction
124.m88ksim :+ESfic +ESlit +O4 +I/+P +Oaggressive +Onoparmsoverlap +Optrs_strongly_typed +Ostaticprediction
126.gcc     :+ESfic +ESlit +O4 +I/+P -DSPEC +Olibcalls +Onolimit +0staticprediction
129.compress:+ESfic +ESlit +O4 +I/+P +Olibcalls +Onofltacc +Onolimit +Optrs_strongly_typed +Owhole_program_mode
130.li      :+ESfic +ESlit +O4 +I/+P -lm +ESsfc +Oentrysched +Olibcalls
.            +Onolimit +Onoloop_unroll +Onoptrs_to_globals +Owhole_program_mode
132.ijpeg   :+ESfic +ESlit +O4 +I/+P +ESsfc +Olibcalls +Onolimit +Optrs_strongly_typed +Owhole_program_mode
134.perl    :+ESfic +ESlit +O4 +I/+P /opt/langtools/lib/fastmem.o -lm +Olibcalls +Onolimit +Owhole_program_mode
147.vortex  :+ESfic +ESlit +O4 +I/+P /opt/langtools/lib/fastmem.o -lm
.            +Oentryshed +Olibcalls +Onolimit +Onoloop_unroll +Optrs_strongly_type +Ostaticprediction
Linker Flag: All:  -Wl,-aarchive

note: The +I/+P indicates the use of profile based optimization.
```


For More Information Contact:

SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109

(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --