



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro


SPEChpc 2021\_sml\_base = 1.03

SPEChpc 2021\_sml\_peak = Not Run

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

hpc2021 License: 6569  
Test Sponsor: Supermicro  
Tested by: Supermicro

Test Date: Dec-2022  
Hardware Availability: Jan-2023  
Software Availability: Dec-2022



## Results Table

Benchmark	Base										Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	
605.lbm_s	OMP	8	30	<b>1338</b>	<b>1.16</b>	1341	1.16	1338	1.16										
613.soma_s	OMP	8	30	<b>636</b>	<b>2.52</b>	692	2.31	636	2.52										
618.tealeaf_s	OMP	8	30	4599	0.446	4610	0.445	<b>4602</b>	<b>0.445</b>										
619.clvleaf_s	OMP	8	30	<b>3584</b>	<b>0.460</b>	3584	0.460	3583	0.460										
621.miniswp_s	OMP	8	30	387	2.84	386	2.85	<b>387</b>	<b>2.84</b>										
628.pot3d_s	OMP	8	30	3833	0.437	3827	0.438	<b>3831</b>	<b>0.437</b>										
632.sph_exa_s	OMP	8	30	836	2.75	<b>835</b>	<b>2.75</b>	835	2.76										
634.hpgmgfv_s	OMP	8	30	1808	0.539	<b>1806</b>	<b>0.540</b>	1806	0.540										
635.weather_s	OMP	8	30	<b>2166</b>	<b>1.20</b>	2168	1.20	2162	1.20										

SPEChpc 2021\_sml\_base = 1.03

SPEChpc 2021\_sml\_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro

SPEChpc 2021\_sml\_base = 1.03

SPEChpc 2021\_sml\_peak = Not Run

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

**hpc2021 License:** 6569  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** Dec-2022  
**Hardware Availability:** Jan-2023  
**Software Availability:** Dec-2022

### Hardware Summary

Type of System: Homogenous  
Compute Node: SuperServer SYS-741GE-TNRT  
Interconnect: N/A  
Compute Nodes Used: 1  
Total Chips: 2  
Total Cores: 120  
Total Threads: 240  
Total Memory: 512 GB  
Max. Peak Threads: --

### Software Summary

Compiler: C/C++/Fortran: Version 2023.0.0 of Intel oneAPI Compiler  
MPI Library: Intel MPI Library for Linux\* OS, Version 2021.8.0 Build 20221129  
Other MPI Info: None  
Other Software: None  
Base Parallel Model: OMP  
Base Ranks Run: 8  
Base Threads Run: 30  
Peak Parallel Models: Not Run  
Minimum Peak Ranks: --  
Maximum Peak Ranks: --  
Max. Peak Threads: --  
Min. Peak Threads: --

### Node Description: SuperServer SYS-741GE-TNRT

#### Hardware

Number of nodes: 1  
Uses of the node: Compute  
Vendor: Supermicro  
Model: SuperServer SYS-741GE-TNRT  
CPU Name: Intel Xeon Platinum 8490H  
CPU(s) orderable: 1, 2 chips  
Chips enabled: 2  
Cores enabled: 120  
Cores per chip: 60  
Threads per core: 2  
CPU Characteristics: Intel Turbo Boost Technology up to 3.5 GHz  
CPU MHz: 1900  
Primary Cache: 32 KB I + 48 KB D on chip per core  
Secondary Cache: 2 MB I+D on chip per core  
L3 Cache: 112.5 MB I+D on chip per chip  
Other Cache: None  
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B-R)  
Disk Subsystem: 1 x 256 GB Apacer M.2 NVMe SSD  
Other Hardware: None  
Accel Count: --  
Accel Model: --  
Accel Vendor: --  
Accel Type: --  
Accel Connection: --  
Accel ECC enabled: --  
Accel Description: --  
Adapter: None  
Number of Adapters: 0  
Slot Type: None  
Data Rate: None

(Continued on next page)

#### Software

Accelerator Driver: --  
Adapter: None  
Adapter Driver: None  
Adapter Firmware: None  
Operating System: SUSE Linux Enterprise Server 15 SP4 Kernel 5.14.21-150400.22-default  
Local File System: xfs  
Shared File System: None  
System State: Multi-user, run level 3  
Other Software: None



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro

SPEChpc 2021\_sml\_base = 1.03

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6569  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** Dec-2022  
**Hardware Availability:** Jan-2023  
**Software Availability:** Dec-2022

### Node Description: SuperServer SYS-741GE-TNRT

#### Hardware (Continued)

Ports Used: 0  
Interconnect Type: None

### Interconnect Description: N/A

#### Hardware

Vendor: N/A  
Model: N/A  
Switch Model: None  
Number of Switches: 0  
Number of Ports: 0  
Data Rate: N/A  
Firmware: N/A  
Topology: N/A  
Primary Use: N/A

#### Software

: --

### Submit Notes

The config file option 'submit' was used.

### General Notes

MPI startup command:  
mpirun command (mpiexec.hydra) was used to start MPI jobs.

### Compiler Version Notes

=====  
CXXC 632.sph\_exa\_s(base)  
-----

Intel(R) oneAPI DPC++/C++ Compiler 2023.0.0 (2023.0.0.20221201)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /opt/intel/oneapi/compiler/2023.0.0/linux/bin-llvm  
Configuration file:  
/opt/intel/oneapi/compiler/2023.0.0/linux/bin-llvm/./bin/icpx.cfg  
-----

=====  
CC 605.lbm\_s(base) 613.soma\_s(base) 618.tealeaf\_s(base) 621.miniswp\_s(base)  
634.hpgmgfv\_s(base)  
-----

(Continued on next page)



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro

SPEChpc 2021\_sml\_base = 1.03

SPEChpc 2021\_sml\_peak = Not Run

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

**hpc2021 License:** 6569  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** Dec-2022  
**Hardware Availability:** Jan-2023  
**Software Availability:** Dec-2022

### Compiler Version Notes (Continued)

```
Intel(R) oneAPI DPC++/C++ Compiler 2023.0.0 (2023.0.0.20221201)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/intel/oneapi/compiler/2023.0.0/linux/bin-llvm
Configuration file:
/opt/intel/oneapi/compiler/2023.0.0/linux/bin-llvm/./bin/icx.cfg
```

```
=====
FC 619.clvleaf_s(base) 635.weather_s(base)
-----
```

```
ifx (IFORT) 2023.0.0 20221201
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
-----
```

```
=====
FC 628.pot3d_s(base)
-----
```

```
ifx: command line warning #10157: ignoring option '-W'; argument is of wrong
type
ifx (IFORT) 2023.0.0 20221201
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
-----
```

### Base Compiler Invocation

C benchmarks:  
mpiicc -cc=icx

C++ benchmarks:  
mpicpc -cxx=icpx

Fortran benchmarks:  
mpiifort -fc=ifx

### Base Portability Flags

```
605.lbm_s: -lstdc++
613.soma_s: -lstdc++
618.tealeaf_s: -lstdc++
619.clvleaf_s: -lstdc++
621.miniswp_s: -lstdc++
628.pot3d_s: -lstdc++
```

(Continued on next page)



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro

SPEChpc 2021\_sml\_base = 1.03

SPEChpc 2021\_sml\_peak = Not Run

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

**hpc2021 License:** 6569  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** Dec-2022  
**Hardware Availability:** Jan-2023  
**Software Availability:** Dec-2022

## Base Portability Flags (Continued)

632.sph\_exa\_s: -lstdc++  
634.hpgmgfv\_s: -lstdc++  
635.weather\_s: -lstdc++

## Base Optimization Flags

C benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-ansi-alias

C++ benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-ansi-alias

Fortran benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-nonstandard-realloc-lhs -align array64byte

## Base Other Flags

C benchmarks:

-Ispecmpitime

C++ benchmarks:

-Ispecmpitime

Fortran benchmarks:

619.clvleaf\_s: -Ispecmpitime

628.pot3d\_s: -Wno-incompatible-function-pointer-types

635.weather\_s: No flags used

The flags file that was used to format this result can be browsed at

[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2023-02-09.html](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-02-09.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2023-02-09.xml](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-02-09.xml)



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Supermicro

SPEChpc 2021\_sml\_base = 1.03

SuperServer SYS-741GE-TNRT (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6569  
**Test Sponsor:** Supermicro  
**Tested by:** Supermicro

**Test Date:** Dec-2022  
**Hardware Availability:** Jan-2023  
**Software Availability:** Dec-2022

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEChpc2021 v1.1.7 on 2022-12-30 04:52:37-0500.  
Report generated on 2023-02-09 20:17:14 by hpc2021 PDF formatter v1.0.3.  
Originally published on 2023-02-09.