



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz, DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13


Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	240	52.8	29.6	50.0	31.3	50.0	31.3							
107.leslie3d	240	211	24.7	212	24.7	212	24.7							
113.GemsFDTD	240	273	23.1	275	22.9	273	23.1							
115.fds4	240	32.2	60.6	32.1	60.9	32.3	60.5							
121.pop2	240	290	14.2	299	13.8	299	13.8							
122.tachyon	240	66.1	42.3	66.1	42.3	65.9	42.4							
126.lammps	240	133	21.9	133	21.9	133	21.9							
127.wrf2	240	145	53.9	119	65.7	120	64.8							
128.GAPgeofem	240	41.3	50.0	41.3	49.9	41.3	50.1							
129.tera_tf	240	83.3	33.2	81.6	33.9	81.4	34.0							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz, DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	240	93.2	41.0	92.9	41.1	92.9	41.1							
132.zeusmp2	240	56.6	54.9	57.1	54.3	56.5	54.9							
137.lu	240	54.6	67.3	54.7	67.2	54.4	67.6							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogeneous
 Compute Node: Endeavor Node
 Interconnects: IB Switch
 Gigabit Ethernet
 File Server Node: NFS
 Total Compute Nodes: 4
 Total Chips: 16
 Total Cores: 240
 Total Threads: 480
 Total Memory: 2 TB
 Base Ranks Run: 240
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

C Compiler: Intel C++ Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728
 C++ Compiler: Intel C++ Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728
 Fortran Compiler: Intel Fortran Composer XE 2013 for Linux, Version 14.0.0.080 Build 20130728
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 MPI Library: Intel MPI Library 4.1.3.045 for Linux
 Other MPI Info: None
 Pre-processors: No
 Other Software: None

Node Description: Endeavor Node

Hardware

Number of nodes: 4
 Uses of the node: compute
 Vendor: Intel
 Model: S4TR1SY4Q
 CPU Name: Intel Xeon E7-4890 v2
 CPU(s) orderable: 1-4 chips
 Chips enabled: 4
 Cores enabled: 60
 Cores per chip: 15
 Threads per core: 2
 CPU Characteristics: Intel Turbo Boost Technology disabled, 8.0 GT/s QPI, Hyper-Threading enabled
 CPU MHz: 2800
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 38400 KB I+D on chip per chip, 38400 KB shared / 15 cores
 Other Cache: None
 Memory: 512 GB (32 x 16 GB 2Rx4 PC3-12800R-11, ECC)
 Disk Subsystem: 2 x 300 GB SAS HDDs
 Other Hardware: None
 Adapter: Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
 Number of Adapters: 1

Software

Adapter: Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
 Adapter Driver: e1000
 Adapter Firmware: None
 Adapter: Mellanox MCX353A-FCAT ConnectX-3
 Adapter Driver: OFED 1.5.3.1
 Adapter Firmware: 2.10.0
 Operating System: Red Hat EL 6.4, kernel 2.6.32-358
 Local File System: Linux/ext2
 Shared File System: NFS
 System State: Multi-User
 Other Software: Platform LSF 9.1.1.1

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz, DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013

Node Description: Endeavor Node

Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MCX353A-FCAT ConnectX-3
Number of Adapters:	1
Slot Type:	PCIe x8 Gen3
Data Rate:	InfiniBand 4x FDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: NFS

Hardware	
Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	S7000FC4UR
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	16
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	--
CPU MHz:	2926
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	64 GB
Disk Subsystem:	8 disks, 500GB/disk, 2.7TB total
Other Hardware:	None
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software	
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000e
Adapter Firmware:	N/A
Operating System:	RedHat EL 5 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz, DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013

Interconnect Description: IB Switch

Hardware	Software
Vendor: Mellanox Model: Mellanox MSX6025F-1BFR Switch Model: Mellanox MSX6025F-1BFR Number of Switches: 46 Number of Ports: 36 Data Rate: InfiniBand 4x FDR Firmware: 7.2.0 Topology: Fat tree Primary Use: MPI traffic	

Interconnect Description: Gigabit Ethernet

Hardware	Software
Vendor: Force10 Networks Model: Force10 S50, Force10 C300 Switch Model: Force10 S50, Force10 C300 Number of Switches: 15 Number of Ports: 48 Data Rate: 1Gbps Ethernet, 10Gbps Ethernet Firmware: 8.2.1.0 Topology: Fat tree Primary Use: Cluster File System	

Submit Notes

The config file option 'submit' was used.

General Notes

130.socorro (base): "nullify_ptrs" src.alt was used.

MPI startup command:

mpiexec.hydra command was used to start MPI jobs.

BIOS settings:

Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)

Intel Turbo Boost Technology (Turbo) : Disabled (default is Enabled)

RAM configuration:

Compute nodes have 4x16-GB RDIMM on each memory channel.

Network:

Forty six 36-port switches: 18 core switches and 28 leaf switches.

Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs are used for compute nodes. On the remaining 3 leafs the ports are used

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz,
DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013

General Notes (Continued)

for FS nodes and other peripherals.

Job placement:

Each MPI job was assigned to a topologically compact set of nodes, i.e. the minimal needed number of leaf switches was used for each job: 1 switch for 60/120/240/480 ranks.

Platform LSF was used for job submission. It has no impact on performance. Information can be found at: <http://www.platform.com>

Base Compiler Invocation

C benchmarks:

mpiicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:

mpiifort

Benchmarks using both Fortran and C:

mpiicc mpiifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX
130.socorro: -assume nostd_intent_in

Base Optimization Flags

C benchmarks:

-O3 -xCORE-AVX-I -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xCORE-AVX-I -no-prec-div

Fortran benchmarks:

-O3 -xCORE-AVX-I -no-prec-div

Benchmarks using both Fortran and C:

-O3 -xCORE-AVX-I -no-prec-div



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E7-4890 v2, 2.80 GHz, DDR3-1600 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 36.8

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepugin

Test date: Feb-2014

Hardware Availability: Feb-2014

Software Availability: Dec-2013

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Jul 22 13:47:49 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 5 March 2014.