



# SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

SPECmpiL\_peak2007 = Not Run

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, 2.40 GHz)

SPECmpiL\_base2007 = 4.65

MPI2007 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Sep-2017



## Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	80	<b>842</b>	<b>4.62</b>	845	4.61	841	4.63							
122.tachyon	80	742	2.62	<b>745</b>	<b>2.61</b>	754	2.58							
125.RAxML	80	707	4.13	<b>707</b>	<b>4.13</b>	708	4.12							
126.lammps	80	757	3.25	753	3.26	<b>755</b>	<b>3.26</b>							
128.GAPgeofem	80	<b>869</b>	<b>6.83</b>	871	6.81	863	6.87							
129.tera_tf	80	361	3.04	<b>362</b>	<b>3.03</b>	363	3.02							
132.zeusmp2	80	462	4.59	<b>463</b>	<b>4.58</b>	464	4.57							
137.lu	80	<b>794</b>	<b>5.29</b>	800	5.25	786	5.34							
142.dmilc	80	533	6.91	532	6.93	<b>533</b>	<b>6.91</b>							
143.dleslie	80	495	6.26	<b>495</b>	<b>6.26</b>	497	6.24							
145.lGemsFDTD	80	860	5.13	859	5.14	<b>859</b>	<b>5.14</b>							
147.l2wrf2	80	1451	5.65	<b>1461</b>	<b>5.62</b>	1461	5.62							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

SPECmpiL\_peak2007 = Not Run

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, 2.40 GHz)

SPECmpiL\_base2007 = 4.65

**MPI2007 license:** 13

**Test date:** Jul-2017

**Test sponsor:** Intel Corporation

**Hardware Availability:** Jul-2017

**Tested by:** Intel Corporation

**Software Availability:** Sep-2017

### Hardware Summary

Type of System: Homogeneous  
 Compute Node: Endeavor Node  
 Interconnects: Intel Omni-Path  
 Intel Omni-Path  
 File Server Node: Lustre FS  
 Total Compute Nodes: 2  
 Total Chips: 4  
 Total Cores: 80  
 Total Threads: 160  
 Total Memory: 384 GB  
 Base Ranks Run: 80  
 Minimum Peak Ranks: --  
 Maximum Peak Ranks: --

### Software Summary

C Compiler: Intel C++ Composer XE 2017 for Linux  
 Version 17.0.4.196 Build 20170411  
 C++ Compiler: Intel C++ Composer XE 2017 for Linux  
 Version 17.0.4.196 Build 20170411  
 Fortran Compiler: Intel Fortran Composer XE 2017 for Linux  
 Version 17.0.4.196 Build 20170411  
 Base Pointers: 64-bit  
 Peak Pointers: Not Applicable  
 MPI Library: Intel MPI Library 17u4 for Linux  
 Other MPI Info: None  
 Pre-processors: No  
 Other Software: None

## Node Description: Endeavor Node

### Hardware

Number of nodes: 2  
 Uses of the node: compute  
 Vendor: Intel  
 Model: Intel Server System R2208WFTZS  
 (Intel Xeon Gold 6148, 2.4 GHz)  
 CPU Name: Intel Xeon Gold 6148  
 CPU(s) orderable: 1-2 chips  
 Chips enabled: 2  
 Cores enabled: 40  
 Cores per chip: 20  
 Threads per core: 2  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.7 GHz  
 CPU MHz: 2400  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 27.5 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 192 GB (12 x 16 GB 2Rx4 DDR4-2666 ECC Registered)  
 Disk Subsystem: 1 x 800 GB SSD (INTEL SSDSC2BA80)  
 Other Hardware: None  
 Adapter: Intel Omni-Path Fabric Adapter 100 series  
 Number of Adapters: 1  
 Slot Type: PCI-Express x16  
 Data Rate: 12.5 GB/s  
 Ports Used: 1  
 Interconnect Type: Intel Omni-Path Fabric Adapter 100 series  
 Adapter: Intel Omni-Path Edge Switch 100 series  
 Number of Adapters: 1  
 Slot Type: PCI-Express x16  
 Data Rate: 12.5 GB/s  
 Ports Used: 1  
 Interconnect Type: Intel Omni-Path Fabric Adapter 100 series

### Software

Adapter: Intel Omni-Path Fabric Adapter 100 series  
 Adapter Driver: IFS 10.4  
 Adapter Firmware: 0.9-46  
 Adapter: Intel Omni-Path Edge Switch 100 series  
 Adapter Driver: IFS 10.4  
 Adapter Firmware: 0.9-46  
 Operating System: Oracle Linux Server release 7.3, Kernel  
 3.10.0-514.6.2.0.1.el7.x86\_64.knl1  
 Local File System: Linux/xfst  
 Shared File System: LFS  
 System State: Multi-User  
 Other Software: IBM Platform LSF Standard 9.1.1.1



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

SPECmpiL\_peak2007 = Not Run

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, 2.40 GHz)

SPECmpiL\_base2007 = 4.65

**MPI2007 license:** 13

**Test date:** Jul-2017

**Test sponsor:** Intel Corporation

**Hardware Availability:** Jul-2017

**Tested by:** Intel Corporation

**Software Availability:** Sep-2017

### Node Description: Lustre FS

Hardware		Software	
Number of nodes:	11	Adapter:	Intel Omni-Path Fabric Adapter 100 series
Uses of the node:	fileserver	Adapter Driver:	IFS 10.4
Vendor:	Intel	Adapter Firmware:	0.9-46
Model:	Intel Server System R2224GZ4GC4	Operating System:	Redhat* Enterprise Linux* Server Release 7.2, Kernel 3.10.0-514.6.2.0.1.el7.x86_64.knl1
CPU Name:	Intel Xeon E5-2680	Local File System:	None
CPU(s) orderable:	1-2 chips	Shared File System:	Lustre FS
Chips enabled:	2	System State:	Multi-User
Cores enabled:	16	Other Software:	None
Cores per chip:	8		
Threads per core:	2		
CPU Characteristics:	Intel Turbo Boost Technology disabled		
CPU MHz:	2700		
Primary Cache:	32 KB I + 32 KB D on chip per core		
Secondary Cache:	2 MB I+D on chip per chip		
L3 Cache:	20 MB I+D on chip per chip		
Other Cache:	None		
Memory:	64 GB (8 x 8GB 1600MHz Reg ECC DDR3)		
Disk Subsystem:	2.1 TB		
Other Hardware:	None		
Adapter:	Intel Omni-Path Fabric Adapter 100 series		
Number of Adapters:	1		
Slot Type:	PCI-Express x16		
Data Rate:	12.5 GB/s		
Ports Used:	1		
Interconnect Type:	Intel Omni-Path Fabric Adapter 100 series		

### Interconnect Description: Intel Omni-Path

Hardware		Software	
Vendor:	Intel		
Model:	Intel Omni-Path 100 series		
Switch Model:	Intel Omni-Path Edge Switch 100 series		
Number of Switches:	24		
Number of Ports:	48		
Data Rate:	12.5 GB/s		
Firmware:	0.9-46		
Topology:	Fat tree		
Primary Use:	MPI traffic		



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Intel Corporation

SPECmpiL\_peak2007 = Not Run

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, 2.40 GHz)

SPECmpiL\_base2007 = 4.65

**MPI2007 license:** 13

**Test date:** Jul-2017

**Test sponsor:** Intel Corporation

**Hardware Availability:** Jul-2017

**Tested by:** Intel Corporation

**Software Availability:** Sep-2017

## Interconnect Description: Intel Omni-Path

	Hardware	Software
Vendor:	Intel Corporation	
Model:	Intel Omni-Path 100 series	
Switch Model:	Intel Omni-Path Edge Switch 100 series	
Number of Switches:	1	
Number of Ports:	48	
Data Rate:	12.5 GB/s	
Firmware:	0.9-46	
Topology:	Fat tree	
Primary Use:	Cluster File System	

## Submit Notes

The config file option 'submit' was used.

## General Notes

MPI startup command:

mpiexec.hydra command was used to start MPI jobs.

Software environment:

```
export I_MPI_COMPATIBILITY=3
export I_MPI_FABRICS=shm:tmi
export I_MPI_HYDRA_PMI_CONNECT=alltoall
```

Network:

Endeavour Omni-Path fabric consists of 48-port switches = 24 core switches connected to each leaf of the rack switch.

Job placement:

Each MPI job was assigned to a topologically compact set of nodes, i.e. the minimal needed number of leaf switches was used for each job = 1 switch for 40/80/160/320/640 ranks, 2 switches for 1280 and 1980 ranks.

IBM Platform LSF was used for job submission. It has no impact on performance.

Information can be found at: <http://www.ibm.com>

## Base Compiler Invocation

C benchmarks:

mpiicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:

mpiifort

Continued on next page

Standard Performance Evaluation Corporation

[info@spec.org](mailto:info@spec.org)

<http://www.spec.org/>

Page 4



# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

SPECmpiL\_peak2007 = Not Run

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, 2.40 GHz)

SPECmpiL\_base2007 = 4.65

MPI2007 license: 13

Test date: Jul-2017

Test sponsor: Intel Corporation

Hardware Availability: Jul-2017

Tested by: Intel Corporation

Software Availability: Sep-2017

## Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:  
mpiicc mpiifort

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG  
126.lammps: -DMPICH\_IGNORE\_CXX\_SEEK

## Base Optimization Flags

C benchmarks:

-O3 -xCORE-AVX512 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xCORE-AVX512 -no-prec-div

Fortran benchmarks:

-O3 -xCORE-AVX512 -no-prec-div

Benchmarks using both Fortran and C:

-O3 -xCORE-AVX512 -no-prec-div

The flags file that was used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel140\\_flags.20170822.html](http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20170822.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel140\\_flags.20170822.xml](http://www.spec.org/mpi2007/flags/EM64T_Intel140_flags.20170822.xml)

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v2.0.1.

Report generated on Tue Aug 22 18:38:18 2017 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 22 August 2017.