SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS22 Express (4 GHz, 4x4 core)

SPECmpiM_peak2007 = 2.79

SPECmpiM_base2007 = 2.44

MPI2007 license: 0005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2008
Hardware Availability: Nov-2008
Software Availability: Nov-2008



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	32	860	1.82	871	1.80	**869**	**1.80**	32	860	1.82	871	1.80	**869**	**1.80**
107.leslie3d	32	1681	3.11	**1719**	**3.04**	1728	3.02	32	**1692**	**3.08**	1694	3.08	1686	3.10
113.GemsFDTD	32	**1447**	**4.36**	1445	4.36	1451	4.35	32	**1447**	**4.36**	1445	4.36	1451	4.35
115.fds4	32	**873**	**2.23**	898	2.17	873	2.24	32	863	2.26	859	2.27	**863**	**2.26**
121.pop2	32	**1440**	**2.87**	1436	2.88	1441	2.86	32	**1440**	**2.87**	1436	2.88	1441	2.86
122.tachyon	32	**2056**	**1.36**	2059	1.36	2055	1.36	32	2015	1.39	2022	1.38	**2016**	**1.39**
126.lammps	32	1183	2.46	1209	2.41	**1194**	**2.44**	32	1183	2.46	1209	2.41	**1194**	**2.44**
127.wrf2	32	**2675**	**2.91**	2670	2.92	2677	2.91	32	**1774**	**4.39**	1786	4.36	1771	4.40
128.GAPgeofem	32	**667**	**3.10**	668	3.09	667	3.10	32	**667**	**3.10**	668	3.09	667	3.10
129.tera_tf	32	2077	1.33	**2077**	**1.33**	2076	1.33	32	**1510**	**1.83**	1511	1.83	1501	1.84

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS22 Express (4 GHz, 4x4 core)

SPECmpiM_peak2007 = 2.79

SPECmpiM_base2007 = 2.44

MPI2007 license: 0005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2008
Hardware Availability: Nov-2008
Software Availability: Nov-2008

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	32	1165	3.28	1166	3.27	**1166**	**3.27**	32	**451**	**8.46**	447	8.53	456	8.37
132.zeusmp2	32	1273	2.44	1325	2.34	**1288**	**2.41**	32	1273	2.44	1325	2.34	**1288**	**2.41**
137.lu	32	1607	2.29	1600	2.30	**1604**	**2.29**	32	1607	2.29	1600	2.30	**1604**	**2.29**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Heterogeneous
Compute Nodes:	IBM System JS22 IBM System JS22
Interconnects:	InfiniBand Ethernet
File Server Node:	IBM System JS22
Head Node:	IBM System JS22
Total Compute Nodes:	4
Total Chips:	8
Total Cores:	16
Total Threads:	32
Total Memory:	80 GB
Base Ranks Run:	32
Minimum Peak Ranks:	32
Maximum Peak Ranks:	32

Software Summary

C Compiler:	IBM XL C/C++ Enterprise Edition V9 for AIX Updated with the September 2008 Fix level
C++ Compiler:	IBM XL C/C++ Enterprise Edition V9 for AIX Updated with the September 2008 Fix level
Fortran Compiler:	IBM XL Fortran Enterprise Edition V11.1 for AIX Updated with the September 2008 Fix level
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
MPI Library:	IBM Parallel Environment for AIX, Version 5 Release 1
Other MPI Info:	None
Pre-processors:	None
Other Software:	IBM Engineering and Scientific Subroutine Library (ESSL) for AIX Version 4 Release 3 Updated with PTF Set 3

Node Description: IBM System JS22

Hardware

Number of nodes:	1
Uses of the node:	compute, head, fileserver
Vendor:	IBM Corporation
Model:	IBM System JS22
CPU Name:	POWER6
CPU(s) orderable:	4 cores per blade
Chips enabled:	2
Cores enabled:	4
Cores per chip:	2
Threads per core:	2
CPU Characteristics:	
CPU MHz:	4000
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	32 GB (4x8 GB) DDR2 500 MHz
Disk Subsystem:	1x146 GB SAS 15K RPM
Other Hardware:	BladeCenter-H chassis Voltaire 4X InfiniBand Pass-thru Module (P/N 43W4419)

Continued on next page

Software

Adapter:	4X InfiniBand DDR Expansion Card (CFFh) for IBM BladeCenter (P/N 43W4423)
Adapter Driver:	devices.pciex.b3157862.rte 6.1.2.0
Adapter Firmware:	2.3.0
Operating System:	IBM AIX V6.1 with the 6100-02 Technology Level
Local File System:	AIX/JFS2
Shared File System:	NFSv3
System State:	Multi-user
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS22 Express (4 GHz, 4x4 core)

SPECmpiM_peak2007 = 2.79

SPECmpiM_base2007 = 2.44

MPI2007 license: 0005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2008
Hardware Availability: Nov-2008
Software Availability: Nov-2008

Node Description: IBM System JS22

Adapter:	4X InfiniBand DDR Expansion Card (CFFh) for IBM BladeCenter (P/N 43W4423)
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	4x DDR 20Gbps
Ports Used:	1
Interconnect Type:	InfiniBand

General Notes

```
Blade[1] runs the following commands to compose the cluster:
     mkdev -c management -s infiniband -t icm
   /usr/sbin/mkiba -a 192.1.10.1 -m 255.255.255.0 -i ib0 -A iba0 -p 1 -P 0xFFFF -M 65532 -q 4000 -k off -Q 0x1E -S up
     startsrc -s ctcas
     preprpnode mpiblade1
     mkrpdomain mpiblades mpiblade1 mpiblade2 mpiblade3 mpiblade4
     startrpdomain mpiblades
     cd /usr/lpp/ppe.poe/samples/nrt
     make
     chmod 4755 nrt_api
     shutdown -rF
     su spec
     cd mpiblades.64ranks.load
     ../nrt_api -l
```

Node Description: IBM System JS22

Hardware

Number of nodes:	3
Uses of the node:	compute
Vendor:	IBM Corporation
Model:	IBM System JS22
CPU Name:	POWER6
CPU(s) orderable:	4 cores per blade
Chips enabled:	2
Cores enabled:	4
Cores per chip:	2
Threads per core:	2
CPU Characteristics:	
CPU MHz:	4000
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (4x4 GB) DDR2 667 MHz
Disk Subsystem:	1x146 GB SAS 15K RPM

Continued on next page

Software

Adapter:	4X InfiniBand DDR Expansion Card (CFFh) for IBM BladeCenter (P/N 43W4423)
Adapter Driver:	devices.pciex.b3157862.rte 6.1.2.0
Adapter Firmware:	2.3.0
Operating System:	IBM AIX V6.1 with the 6100-02 Technology Level
Local File System:	AIX/JFS2
Shared File System:	NFSv3
System State:	Multi-user
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS22 Express (4 GHz, 4x4 core)

SPECmpiM_peak2007 = 2.79

SPECmpiM_base2007 = 2.44

MPI2007 license: 0005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2008
Hardware Availability: Nov-2008
Software Availability: Nov-2008

Node Description: IBM System JS22

Other Hardware:	BladeCenter-H chassis Voltaire 4X InfiniBand Pass-thru Module (P/N 43W4419)
Adapter:	4X InfiniBand DDR Expansion Card (CFFh) for IBM BladeCenter (P/N 43W4423)
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	4x DDR 20Gbps
Ports Used:	1
Interconnect Type:	InfiniBand

General Notes

Each blade runs the following commands to compose the cluster, where $CLUSTER_INDEX is 2-4 for Blade[2]-Blade[4]:

```
mkdev -c management -s infiniband -t icm
/usr/sbin/mkiba -a 192.1.10.$CLUSTER_INDEX -m 255.255.255.0 -i ib0 -A iba0 -p 1 -P 0xFFFF -M 65532 -q 4000 -k off -Q 0x1E -S up
startsrc -s ctcas
preprpnode mpiblade1
cd /usr/lpp/ppe.poe/samples/nrt
make
chmod 4755 nrt_api
shutdown -rF
su spec
cd mpiblades.64ranks.load
../nrt_api -l
```

Interconnect Description: InfiniBand

Hardware	
Vendor:	IBM Corporation
Model:	4x DDR InfiniBand
Switch Model:	QLogic SilverStorm 9024
Number of Switches:	1
Number of Ports:	24
Data Rate:	4x DDR 20Gbps
Firmware:	4.2.1.1.1
Topology:	single switch
Primary Use:	MPI Communication

Software

Interconnect Description: Ethernet

Hardware	
Vendor:	IBM Corporation
Model:	4-port Gigabit Ethernet

Software

Continued on next page

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter JS22 Express (4 GHz, 4x4 core)

SPECmpiM_peak2007 = 2.79

SPECmpiM_base2007 = 2.44

MPI2007 license: 0005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2008
Hardware Availability: Nov-2008
Software Availability: Nov-2008

Interconnect Description: Ethernet

Switch Model:	IBM BladeCenter 4-port Gigabit Ethernet switch module (P/N 26K6483)
Number of Switches:	1
Number of Ports:	18
Data Rate:	1Gbps
Firmware:	1.08
Topology:	single switch
Primary Use:	File system

Compiler Invocation Notes

Blade[1], with 32GB of memory and 32GB of paging space, was used to compile the benchmarks.

Submit Notes

The config file option 'submit' was used.

```
submit = poe task_stride.2level.32+64rank 4 2 8 $ranks $command -procs $ranks -hostfile /spec/MapFiles/ib0hosts.8x.1-8
```

General Notes

```
Environment settings:
    All ulimits set to unlimited
    ranks                 = 32
    CWD                   = /spec/mpi2007
    MEMORY_AFFINITY       = MCM
    XLFRTEOPTS            = intrinthds=1
    MP_PGMMODEL           = spmd
    MP_MSG_API            = mpi
    MP_DEVTYPE            = ib
    MP_CLOCK_SOURCE       = AIX
    MP_STDINMODE          = none
    MP_SHARED_MEMORY      = yes
    MP_SINGLE_THREAD      = yes
    MP_EUILIB             = us
    NRT_WINDOW_COUNT      = 1
    MP_RESD               = no
    MP_PULSE              = 0
    ADAPTER_USE           = shared
    EUIDEVICE             = sn_single
    MP_CSS_INTERRUPT      = no
    MP_BUFFER_MEM         = 67108864
    MP_USE_BULK_XFER      = yes
    MP_BULK_MIN_MSG_SIZE  = 8192
    MP_EAGER_LIMIT        = 65536
    MP_WAIT_MODE          = yield
    MP_INFOLEVEL          = 0
    MP_LABELIO            = no
```

Continued on next page

General Notes (Continued)

```
MP_STDOUTMODE        = unordered
MP_PMDLOG            = no
NRT_JOB_KEY          = 64
```

Compiler Invocation

C benchmarks:
`/usr/bin/mpcc_r`

C++ benchmarks:

126.lammps: `/usr/bin/mpCC_r`

Fortran benchmarks:
`/usr/bin/mpxlf95_r`

Benchmarks using both Fortran and C:
`/usr/bin/mpcc_r /usr/bin/mpxlf95_r`

Portability Flags

107.leslie3d: `-qfixed`
115.fds4: `-DSPEC_MPI_LC_NO_TRAILING_UNDERSCORE -qfixed`
121.pop2: `-DSPEC_MPI_AIX`
127.wrf2: `-DNOUNDERSCORE -DSPEC_MPI_AIX`
130.socorro: `-DSPEC_NO_UNDERSCORE -qcpluscmt`
132.zeusmp2: `-qfixed -DSPEC_SINGLE_UNDERSCORE`
137.lu: `-qfixed`

Base Optimization Flags

C benchmarks:
`-bmaxdata:0x80000000 -O5 -D_ILS_MACROS -bdatapsize:64K -bstackpsize:64K -btextpsize:64K`

C++ benchmarks:

126.lammps: `-bmaxdata:0x80000000 -O5`

Fortran benchmarks:
`-bmaxdata:0x80000000 -O4 -qstrict -qalias=nostd -qhot=level=0 -qsave -bdatapsize:64K -bstackpsize:64K -btextpsize:64K`

Benchmarks using both Fortran and C:
`-bmaxdata:0x80000000 -O5 -D_ILS_MACROS -bdatapsize:64K -bstackpsize:64K -btextpsize:64K -O4 -qstrict -qalias=nostd`

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C (continued):
`-qhot=level=0 -qsave`

Peak Optimization Flags

C benchmarks:

104.milc: `basepeak = yes`

122.tachyon: `-O5 -lessl -D_ILS_MACROS -bdatapsize:64K -bstackpsize:64K -btextpsize:64K -q64`

C++ benchmarks:

126.lammps: `basepeak = yes`

Fortran benchmarks:

107.leslie3d: `-O5 -bdatapsize:64K -bstackpsize:64K -btextpsize:64K -bmaxdata:0x70000000`

113.GemsFDTD: `basepeak = yes`

129.tera_tf: `-O5 -qessl -lessl -bdatapsize:64K -bstackpsize:64K -btextpsize:64K`

137.lu: `basepeak = yes`

Benchmarks using both Fortran and C:

115.fds4: `-O5 -lessl -D_ILS_MACROS -bdatapsize:64K -bstackpsize:64K -btextpsize:64K -qstrict -qalias=nostd -qhot=level=0 -qsave -q64`

121.pop2: `basepeak = yes`

127.wrf2: `-O5 -bmaxdata:0x80000000`

128.GAPgeofem: `basepeak = yes`

130.socorro: `-O5 -lessl -D_ILS_MACROS -bdatapsize:64K -bstackpsize:64K -btextpsize:64K -qessl -bmaxdata:0x80000000`

132.zeusmp2: `basepeak = yes`

Other Flags

C benchmarks:
```
-w -qsuppress=1500-036 -qipa=noobject -qipa=threads
```

C++ benchmarks:

126.lammps: `-w -qsuppress=1500-036 -qipa=noobject -qipa=threads`

Fortran benchmarks:
```
-w -qsuppress=1500-036 -qsuppress=cmpmsg -qspillsize=32648
```

Benchmarks using both Fortran and C:
```
-w -qsuppress=1500-036 -qipa=noobject -qipa=threads -qsuppress=cmpmsg
-qspillsize=32648
```

The flags files that were used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/MPI2007_flags.20081105.html
http://www.spec.org/mpi2007/flags/IBM-XL.html
http://www.spec.org/mpi2007/flags/IBM-AIX.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/mpi2007/flags/MPI2007_flags.20081105.xml
http://www.spec.org/mpi2007/flags/IBM-XL.xml
http://www.spec.org/mpi2007/flags/IBM-AIX.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.
Report generated on Tue Jul 22 13:34:50 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 5 November 2008.