OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Supermicro Corporation
Supermicro H8DMU

SPECompMpeak2001 = 16707

SPECompMbase2001 = 16397

SPEC license #HPG0017 | Tested by: Advanced Micro Devices | Test site: Austin TX | Test date: May-2008 | Hardware Avail: Jun-2008 | Software Avail: Nov-2007

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	291	20602	254	23665
312.swim_m	6000	463	12963	399	15043
314.mgrid_m	7300	451	16174	451	16174
316.applu_m	4000	326	12285	326	12285
318.galgel_m	5100	299	17055	299	17055
320.equake_m	2600	152	17102	156	16699
324.apsi_m	3400	171	19893	183	18629
326.gafort_m	8700	520	16717	520	16717
328.fma3d_m	4600	449	10239	449	10239
330.art_m	6400	137	46626	137	46626
332.ammp_m	7000	747	9372	741	9452



Hardware

CPU:	Quad-Core AMD Opteron(tm) Processor 2347 HE
CPU MHz:	1900
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1-2
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	16GB (8x2GB, PC2-5300, CL5 dual-rank)
Disk Subsystem:	300GB 7200 RPM SATA
Other Hardware:	None

Software

OpenMP Threads:	8
Parallel:	OpenMP
Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1 2.6.16.46-0.12-smp
Compiler:	PathScale Compiler Suite ver. 3.1
File System:	Linux/reiserfs
System State:	Multi-User

Notes/Tuning Information

```
Extra art Base Flags
  330.art_m (extra): -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

Alternate Sources:
  314.mgrid_m (base and peak): intel
Base tuning:
  C       : pathcc  -gnu3 -mp -Ofast -mcmodel=medium
  Fortran : pathf90 -mp -Ofast -OPT:early_mp=on -mcmodel=medium
  ONESTEP=yes
Peak tuning:
   310.wupwise_m: -mp -Ofast -msse3 -LNO:prefetch_ahead=5:prefetch=3
                  -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3
                  -IPA:linear=on:plimit=50000:callee_limit=5000
   312.swim_m: -mp -O3 -OPT:Ofast -m3dnow -mcmodel=medium -LNO:simd=0
   314.mgrid_m: basepeak=yes
   316.applu_m: basepeak=yes
   318.galgel_m: basepeak=yes
   320.equake_m: -gnu3 -Ofast -mp -OPT:alias=disjoint
   324.apsi_m: -mp -O3 -OPT:Ofast -TENV:x=4 -LNO:fusion=2:prefetch=0
   326.gafort_m: basepeak=yes
   328.fma3d_m: basepeak=yes
   330.art_m: basepeak=yes
   332.ammp_m: -gnu3 -mp -Ofast -mcpu=barcelona -mcmodel=medium
```

Copyright 1999-2008, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                export PSC_OMP_GUIDED_CHUNK_MAX=700
   ONESTEP=yes for all peak tests.

Portablility flags:
 318.galgel_m    : -fixedform -col80

Base and Peak User Environment (bash):
  export OMP_NUM_THREADS=8
  export OMP_DYNAMIC=FALSE
  export PSC_OMP_AFFINITY=TRUE
  export PSC_OMP_STATIC_FAIR=TRUE
  export PSC_OMP_THREAD_SPIN=1000000000
  ulimit -s unlimited

For flag descriptions, see file AMD-Jul2008-psc31_flags.txt
Default BIOS settings used, except PowerNow! disabled in Bios
```