OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

IBM
IBM System x iDP dx360 M2

SPECompMpeak2001 = --

SPECompMbase2001 = 39551

SPEC license #: HPG3440A | Tested by: Indiana University | Test site: Indiana University | Test date: Jan-2011 | Hardware Avail: Dec-2009 | Software Avail: Jan-2010

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	83.1	72194		
312.swim_m	6000	160	37573		
314.mgrid_m	7300	229	31944		
316.applu_m	4000	131	30510		
318.galgel_m	5100	129	39628		
320.equake_m	2600	54.9	47340		
324.apsi_m	3400	94.3	36037		
326.gafort_m	8700	211	41301		
328.fma3d_m	4600	182	25314		
330.art_m	6400	65.9	97104		
332.ammp_m	7000	343	20416		



Hardware

CPU:	Intel Xeon E5570
CPU MHz:	2934
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip (HT off)
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	24 GB (6*4GB DDR3-1333 RDIMMs)
Disk Subsystem:	Single 500GB SATA
Other Hardware:	None

Software

OpenMP Threads:	8
Parallel:	--
Operating System:	RHEL5.5 (x86_64) Kernel 2.6.18-194.26.1.el5 Kernel 2.6.18-194.26.1.el5
Compiler:	Intel C/C++ Compiler 11.1.072 Intel Fortran Compiler 11.1.072
File System:	ext3
System State:	Multi-user, run level 3

Notes/Tuning Information

```
Intel Turbo Boost Technology (Turbo)  : Disabled
ulimit -s unlimited
    Removes limits on the maximum size of the automatically-
    extended stack region of the current process and each
    process it creates.
Compiler flags for base level optimization
    COPTIMIZE : -O3 -xSSE3 -ipo -no-prec-div -unroll-loops0 -openmp
    FOPTIMIZE : -O3 -xSSE3 -ipo -no-prec-div -unroll-loops0 -openmp
    F77OPTIMIZE : -O3 -xSSE3 -ipo -no-prec-div -unroll-loops0 -openmp
Environment:
    KMP_AFFINITY=enabled
     controls the binding of OpenMP threads to the physical processing units
    KMP_SCHEDULE=static,balanced
     used to fine tune the load balancing of parallel loops that are
     statically scheduled under OpenMP with no chunk size specification
    KMP_BLOCKTIME=infinite
     Sets the time, in milliseconds, that a thread should wait,
     after completing the execution of a parallel region, before sleeping.
    KMP_LIBRARY=throughput
     Selects the OpenMP run-time library
    KMP_STACKSIZE=31m
     Sets the number of bytes to allocate for each parallel thread to use as
     to use as its provate stack
```

Copyright 1999-2008, Standard Performance Evaluation Corporation

IBM
IBM System x iDP dx360 M2

SPECompMpeak2001 = --

SPECompMbase2001 = 39551

SPEC license #: HPG3440A | Tested by: Indiana University | Test site: Indiana University | Test date: Jan-2011 | Hardware Avail: Dec-2009 | Software Avail: Jan-2010

Notes/Tuning Information (Continued)

```
OMP_NESTED=TRUE
 Enables (TRUE) or  disables  (FALSE)  nested  parallelism.
OMP_DYNAMIC=FALSE
 Enables (true) or disables (false) the dynamic adjustment of the number of threads.
OMP_NUM_THREADS=8
 Sets  the maximum number of threads to use for OpenMP* parallel
 regions if no other value is specified in the  program  itself.
```