SPEC® OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Intel

Intel R2308WTTYS (Endeavour Node, Intel Xeon E5-2697 v4, 2.3GHz, DDR4-2400 MHz,SMT ON Turbo OFF)

SPECompG_peak2012 = 10.3

SPECompG_base2012 = 9.40

OMP2012 license: 13
Test sponsor: Intel
Tested by: Intel

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Feb-2016



Hardware

CPU Name:	Intel Xeon E5-2697 v4
CPU Characteristics:	Intel Turbo Boost Technology Disabled
CPU MHz:	2300
CPU MHz Maximum:	3600
FPU:	Integrated
CPU(s) enabled:	36 cores, 2 chips, 18 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 Chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	45 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (8 x 16 GB 2Rx4 PC4-2400U-R)
Disk Subsystem:	Panasas ActiveStor 14
Other Hardware:	--
Base Threads Run:	72
Minimum Peak Threads:	36

Continued on next page

Software

Operating System:	Oracle Linux Server release 6.7, Kernel 3.10.0-229.20.1.el6.x86_64.knl2
Compiler:	C/C++/Fortran: Version 14.0.4.211 of Intel Composer XE for Linux Build 20140805 C/C++/Fortran: Version 16.0.2.181 of Intel Composer XE for Linux Build 20160204
Auto Parallel:	No
File System:	Linux ext3
System State:	Default
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Intel

Intel R2308WTTYS (Endeavour Node, Intel Xeon E5-2697 v4, 2.3GHz, DDR4-2400 MHz,SMT ON Turbo OFF)

SPECompG_peak2012 = 10.3

SPECompG_base2012 = 9.40

OMP2012 license:13
Test sponsor: Intel
Tested by: Intel

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Feb-2016

Maximum Peak Threads: 72

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	72	438	10.6	442	10.5	**440**	**10.5**	72	325	14.2	325	14.2	**325**	**14.2**
351.bwaves	72	380	11.9	**380**	**11.9**	382	11.9	36	365	12.4	**365**	**12.4**	363	12.5
352.nab	72	442	8.80	449	8.67	**442**	**8.80**	72	377	10.3	**377**	**10.3**	376	10.3
357.bt331	72	346	13.7	348	13.6	**347**	**13.6**	72	**349**	**13.6**	348	13.6	351	13.5
358.botsalgn	72	**572**	**7.61**	572	7.61	572	7.61	72	**532**	**8.18**	532	8.18	532	8.18
359.botsspar	72	809	6.49	811	6.47	**811**	**6.47**	36	797	6.59	797	6.59	**797**	**6.59**
360.ilbdc	72	458	7.78	457	7.78	**457**	**7.78**	72	**456**	**7.80**	458	7.77	455	7.82
362.fma3d	72	**481**	**7.90**	478	7.95	490	7.76	72	478	7.95	502	7.58	**489**	**7.77**
363.swim	72	497	9.12	**497**	**9.11**	498	9.11	36	**472**	**9.60**	472	9.59	472	9.60
367.imagick	72	792	8.87	790	8.90	**792**	**8.87**	72	724	9.71	**724**	**9.70**	725	9.70
370.mgrid331	72	552	8.00	553	7.99	**553**	**8.00**	36	539	8.20	540	8.19	**539**	**8.20**
371.applu331	72	**329**	**18.4**	334	18.2	326	18.6	72	335	18.1	**331**	**18.3**	327	18.5
372.smithwa	72	572	9.37	565	9.49	**569**	**9.42**	36	**349**	**15.4**	350	15.3	342	15.7
376.kdtree	72	546	8.24	**545**	**8.25**	545	8.25	72	545	8.25	546	8.24	**546**	**8.24**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

Platform Notes

```
Sysinfo program /panfs/projects/innl/aknyaze1/OMP2012/1.0/Docs/sysinfo
$Rev: 395 $ $Date:: 2012-07-25 #$ 8f8c0fe9e19c658963a1e67685e50647
running on ewb264 Sun Mar 13 01:50:41 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2697 v4 @ 2.30GHz
      2 "physical id"s (chips)
      72 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 18
      siblings  : 36
      physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
```

Continued on next page

Platform Notes (Continued)

```
        physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
     cache size : 46080 KB

  From /proc/meminfo
     MemTotal:       131920288 kB
     HugePages_Total:       0
     Hugepagesize:       2048 kB

  /usr/bin/lsb_release -d
     Oracle Linux Server release 6.7

  From /etc/*release* /etc/*version*
     oracle-release: Oracle Linux Server release 6.7
     os-release:
        NAME="Oracle Linux Server"
        VERSION="6.7"
        ID="ol"
        VERSION_ID="6.7"
        PRETTY_NAME="Oracle Linux Server 6.7"
        ANSI_COLOR="0;31"
        CPE_NAME="cpe:/o:oracle:linux:6:7:server"
        HOME_URL="https://linux.oracle.com/"
     redhat-release: Red Hat Enterprise Linux Server release 6.7 (Santiago)
     system-release: Oracle Linux Server release 6.7
     system-release-cpe: cpe:/o:oracle:linux:6:7:server

  uname -a:
     Linux ewb264 3.10.0-229.20.1.el6.x86_64.knl2 #2 SMP Tue Dec 8 22:27:38 MST
     2015 x86_64 x86_64 x86_64 GNU/Linux

  run-level 3 Mar 10 14:11

  SPEC is set to: /panfs/projects/innl/aknyaze1/OMP2012/1.0
     Filesystem           Type   Size  Used Avail Use% Mounted on
     panfs://36.101.211.31/projects
                          panfs   78T   63T   16T  81% /panfs/projects

  Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

  (End of data from sysinfo program)
```

General Notes

```
  ------------------------------------------------------------------------
  General base OMP Library Settings
    ENV_KMP_AFFINITY=compact,0

  ------------------------------------------------------------------------
  General peak OMP Library Settings
    ENV_KMP_AFFINITY=compact,0
```

Continued on next page

General Notes (Continued)

```
================================================================================
General OMP Library Settings
  KMP_LIBRARY=turnaround
  KMP_STACKSIZE=256M
  KMP_BLOCKTIME=infinite
  OMP_DYNAMIC=FALSE
  OMP_NESTED=FALSE
  OMP_SCHEDULE=static
================================================================================
Compiler selection proxy script spec{icc/ifort/icpc/run} was used:
#!/bin/sh
COMPBIN=${BASH_SOURCE[0]:-$0}
COMPBIN=${COMPBIN##*/spec}
version=$1
shift

COMPILER_ROOT_PATHS="/opt/intel/compiler"

for COMPILER_ROOT_PATH in $COMPILER_ROOT_PATHS ; do
if [ -e "$COMPILER_ROOT_PATH/${version}/bin/compilervars.sh" ] ; then
. $COMPILER_ROOT_PATH/${version}/bin/compilervars.sh intel64
break
fi
done

exec $COMPBIN "$@"
for specrun last line is
exec "$@"
Compiler for base and most peak: C/C++/Fortran: Version 14.0.4.211 of Intel Composer XE for Linux Build 20140805
Compiler for some peak components (where 2016u2 is specified): C/C++/Fortran: Version 16.0.2.181 of Intel Composer XE for Linux Build 20160204
================================================================================
351.bwaves:peak:
  ENV_KMP_AFFINITY=compact,1
  ENV_OMP_SCHEDULE=static,1

================================================================================
359.botsspar:peak:
  ENV_KMP_AFFINITY=compact,1
  ENV_OMP_SCHEDULE=guided

================================================================================
363.swim:peak:
  ENV_KMP_AFFINITY=compact,1

================================================================================
370.mgrid331:peak:
  ENV_KMP_AFFINITY=compact,1

================================================================================
372.smithwa:peak:
  ENV_OMP_SCHEDULE=static,1
```

Base Compiler Invocation

C benchmarks:
```
specicc 2013_sp1.4.211
```

C++ benchmarks:
```
specicpc 2013_sp1.4.211
```

Fortran benchmarks:
```
specifort 2013_sp1.4.211
```

Base Portability Flags

350.md: `-FR`
357.bt331: `-mcmodel=medium`
363.swim: `-mcmodel=medium`
367.imagick: `-std=c99`

Base Optimization Flags

C benchmarks:
```
-O3 -openmp -ipo  -xCORE-AVX2 -ansi-alias
```

C++ benchmarks:
```
-O3 -openmp -ipo  -xCORE-AVX2 -ansi-alias
```

Fortran benchmarks:
```
-O3 -openmp -ipo  -xCORE-AVX2 -align array64byte
```

Peak Compiler Invocation

C benchmarks (except as noted below):
```
specicc 2016u2
```

359.botsspar: `specicc 2013_sp1.4.211`

372.smithwa: `specicc 2013_sp1.4.211`

C++ benchmarks:
```
specicpc 2013_sp1.4.211
```

Fortran benchmarks (except as noted below):
```
specifort 2013_sp1.4.211
```

350.md: `specifort 2016u2`

Continued on next page

Peak Compiler Invocation (Continued)

371.applu331: specifort 2016u2

Peak Portability Flags

350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Peak Optimization Flags

C benchmarks:

352.nab: -O3 -qopenmp -ipo -xCORE-AVX2 -fno-alias -opt-malloc-options=1 -opt-calloc -fp-model fast=2 -no-prec-div -no-prec-sqrt -ansi-alias

358.botsalgn: -O3 -qopenmp -ipo -xCORE-AVX2 -fno-alias -ansi-alias

359.botsspar: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -ansi-alias

367.imagick: -O3 -qopenmp -ipo -xCORE-AVX2 -ansi-alias

372.smithwa: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -opt-streaming-stores always -opt-malloc-options=1 -ansi-alias

C++ benchmarks:
-O3 -openmp -ipo -xCORE-AVX2 -fno-alias -ansi-alias

Fortran benchmarks:

350.md: -O3 -qopenmp -ipo -xCORE-AVX2 -fno-alias -opt-malloc-options=1 -fp-model fast=2 -no-prec-div -no-prec-sqrt -align array64byte

351.bwaves: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -fp-model fast=2 -no-prec-div -no-prec-sqrt -align array64byte

357.bt331: Same as 351.bwaves

360.ilbdc: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -align array64byte

362.fma3d: Same as 360.ilbdc

Continued on next page

Peak Optimization Flags (Continued)

363.swim: `-O3 -openmp -ipo -xCORE-AVX2 -fno-alias -opt-streaming-stores always -opt-malloc-options=3 -align array64byte`

370.mgrid331: `-O3 -openmp -ipo -xCORE-AVX2 -fno-alias -opt-malloc-options=3 -align array64byte`

371.applu331: `-O3 -qopenmp -ipo -xCORE-AVX2 -align array64byte`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20160331.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20160331.xml`

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.0.
Report generated on Thu Mar 31 11:10:17 2016 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 31 March 2016.