SPEC® OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

IBM
(Test Sponsor: Indiana University)

IBM S822LC for HPC
(Power8 with NVLink, 2.860 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 5.63

OMP2012 license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Apr-2018
Hardware Availability: Sep-2017
Software Availability: Dec-2017



Hardware

CPU Name:	POWER8 with NVLink
CPU Characteristics:	IBM Intelligent Energy Optimization enabled, up to 3.492 GHz
CPU MHz:	2860
CPU MHz Maximum:	3492
FPU:	Integrated
CPU(s) enabled:	20 cores, 2 chips, 10 cores/chip, 8 threads/core
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per core
Other Cache:	16 MB I+D off chip per 4 DIMMs
Memory:	256 GB (32 x 8 GB DIMMs DDR4 1600 MHz)
Disk Subsystem:	609TB GPFS
Other Hardware:	None
Base Threads Run:	160

Continued on next page

Software

Operating System:	CentOS Linux release 7.4.1708 (AltArch) 3.10.0-693.11.1.el7.ppc64le
Compiler:	C/C++: Version 4.0.1 of Clang Fortran: Version 4.0.1 of Flang
Auto Parallel:	No
File System:	GPFS 4.2.3.6
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

IBM
(Test Sponsor: Indiana University)

IBM S822LC for HPC
(Power8 with NVLink, 2.860 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 5.63

OMP2012 license:3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Apr-2018
Hardware Availability: Sep-2017
Software Availability: Dec-2017

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	160	946	4.90	941	4.92	**941**	**4.92**							
351.bwaves	160	1775	2.55	**1782**	**2.54**	1818	2.49							
352.nab	160	**823**	**4.73**	822	4.73	823	4.72							
357.bt331	160	650	7.30	**633**	**7.48**	633	7.49							
358.botsalgn	160	1058	4.11	1059	4.11	**1059**	**4.11**							
359.botsspar	160	**1659**	**3.16**	1662	3.16	1659	3.17							
360.ilbdc	160	**467**	**7.62**	479	7.44	466	7.63							
362.fma3d	160	904	4.20	891	4.26	**894**	**4.25**							
363.swim	160	452	10.0	451	10.0	**452**	**10.0**							
367.imagick	160	1328	5.29	**1329**	**5.29**	1330	5.29							
370.mgrid331	160	611	7.23	627	7.05	**627**	**7.05**							
371.applu331	160	634	9.56	**634**	**9.55**	638	9.50							
372.smithwa	160	501	10.7	**501**	**10.7**	501	10.7							
376.kdtree	160	993	4.53	993	4.53	**993**	**4.53**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /gpfs/homeb/padc/padc021/spec/omp2012-1.1-run/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on juronc13.juron.dns.zone Mon Apr 23 17:18:49 2018

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   clock : 4023.000000MHz
   machine : PowerNV 8335-GTB
   model : 8335-GTB
   platform : PowerNV
   revision : 1.0 (pvr 004c 0100)
   cpu : POWER8NVL (raw), altivec supported
*
* 0 "physical id" tags found.  Perhaps this is an older system,
* or a virtualized system.  Not attempting to guess how to
* count chips/cores for this system.
*
      160 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
```

Continued on next page

Platform Notes (Continued)

```
      following excerpts from /proc/cpuinfo might not be reliable.  Use with
      caution.)

   From /proc/meminfo
      MemTotal:       267801664 kB
      HugePages_Total:       0
      Hugepagesize:      16384 kB

   From /etc/*release* /etc/*version*
      centos-release: CentOS Linux release 7.4.1708 (AltArch)
      centos-release-upstream: Derived from Red Hat Enterprise Linux 7.4 (Source)
      os-release:
         NAME="CentOS Linux"
         VERSION="7 (AltArch)"
         ID="centos"
         ID_LIKE="rhel fedora"
         VERSION_ID="7"
         PRETTY_NAME="CentOS Linux 7 (AltArch)"
         ANSI_COLOR="0;31"
         CPE_NAME="cpe:/o:centos:centos:7"
      redhat-release: CentOS Linux release 7.4.1708 (AltArch)
      system-release: CentOS Linux release 7.4.1708 (AltArch)
      system-release-cpe: cpe:/o:centos:centos:7

   uname -a:
      Linux juronc13.juron.dns.zone 3.10.0-693.11.1.el7.ppc64le #1 SMP Mon Dec 4
      15:48:14 GMT 2017 ppc64le ppc64le ppc64le GNU/Linux

   run-level 3 Apr 10 19:42

   SPEC is set to: /gpfs/homeb/padc/padc021/spec/omp2012-1.1-run
      Filesystem     Type  Size  Used Avail Use% Mounted on
      homeb          gpfs  609T  498T  111T  82% /gpfs/homeb

   (End of data from sysinfo program)
```

General Notes

```
Environment Variables:
    OMP_STACKSIZE=1G
    ulimit -s unlimited
```

Base Compiler Invocation

C benchmarks:
clang

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
clang++

Fortran benchmarks:
flang

Base Portability Flags

350.md: -Mfreeform
357.bt331: -mcmodel=medium

Base Optimization Flags

C benchmarks:
-Ofast -fopenmp -fsigned-char

C++ benchmarks:
-Ofast -fopenmp

Fortran benchmarks:
-Ofast -fopenmp

The flags file that was used to format this result can be browsed at
http://www.spec.org/omp2012/flags/llvm40.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/omp2012/flags/llvm40.xml

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Jun 20 15:26:21 2018 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 20 June 2018.