SPEC® OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Dell

(Test Sponsor: University of Delaware)

Dell M630 Blade (Intel Xeon E5-2680 v3)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.77

OMP2012 license: 056A
Test sponsor: University of Delaware
Tested by: University of Delaware

Test date: Sep-2018
Hardware Availability: Jun-2018
Software Availability: Jun-2018



Hardware

CPU Name:	Dual Intel Xeon E5-2680 v3
CPU Characteristics:	Intel Turbo Boost Technology off, Hyper-Threading on
CPU MHz:	2500
CPU MHz Maximum:	3300
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip, 2 threads/core
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (16 x 8 GB 2Rx4 PC4-2133P-R)
Disk Subsystem:	400GB (SATA Mix Use MLC 6Gbps 2.5in Hot-plug Drive,13G (400-AEIX) dual SSDs, RAID-1)
Other Hardware:	None

Continued on next page

Software

Operating System:	CentOS Linux release 7.5.1804 (Core) 3.10.0-862.3.3.el7.x86_64
Compiler:	C/C++/Fortran: Version 18.0.3.222 of Intel Parallel Studio XE for Linux Build 20180410
Auto Parallel:	No
File System:	XFS
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other Software:	None

SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Dell
(Test Sponsor: University of Delaware)

Dell M630 Blade (Intel Xeon E5-2680 v3)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.77

OMP2012 license:056A
Test sponsor: University of Delaware
Tested by: University of Delaware

Test date: Sep-2018
Hardware Availability: Jun-2018
Software Availability: Jun-2018

Base Threads Run: 44
Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	44	**438**	**10.6**	435	10.6	439	10.6							
351.bwaves	44	441	10.3	445	10.2	**443**	**10.2**							
352.nab	44	**528**	**7.36**	530	7.33	528	7.37							
357.bt331	44	452	10.5	**452**	**10.5**	451	10.5							
358.botsalgn	44	862	5.05	862	5.05	**862**	**5.05**							
359.botsspar	44	1003	5.23	**1004**	**5.23**	1004	5.23							
360.ilbdc	44	587	6.07	616	5.78	**593**	**6.00**							
362.fma3d	44	598	6.36	**585**	**6.49**	577	6.59							
363.swim	44	556	8.14	547	8.28	**549**	**8.25**							
367.imagick	44	**712**	**9.87**	712	9.87	712	9.88							
370.mgrid331	44	635	6.96	**632**	**6.99**	629	7.03							
371.applu331	44	775	7.81	796	7.61	**779**	**7.78**							
372.smithwa	44	**451**	**11.9**	449	11.9	452	11.9							
376.kdtree	44	694	6.48	**695**	**6.47**	696	6.46							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /home/huberth/SPEC_OMP2012v1.1/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on r01c2b04 Thu Jul  5 12:31:11 2018

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/omp2012/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2680 v3 @ 2.50GHz
      2 "physical id"s (chips)
      48 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 12
      siblings  : 24
      physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13
      physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13
   cache size : 30720 KB
```

Continued on next page

Platform Notes (Continued)

```
From /proc/meminfo
   MemTotal:       131612412 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   CentOS Linux release 7.5.1804 (Core)

From /etc/*release* /etc/*version*
   centos-release: CentOS Linux release 7.5.1804 (Core)
   centos-release-upstream: Derived from Red Hat Enterprise Linux 7.5 (Source)
   os-release:
      NAME="CentOS Linux"
      VERSION="7 (Core)"
      ID="centos"
      ID_LIKE="rhel fedora"
      VERSION_ID="7"
      PRETTY_NAME="CentOS Linux 7 (Core)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:centos:centos:7"
   redhat-release: CentOS Linux release 7.5.1804 (Core)
   system-release: CentOS Linux release 7.5.1804 (Core)
   system-release-cpe: cpe:/o:centos:centos:7

uname -a:
   Linux r01c2b04 3.10.0-862.3.3.el7.x86_64 #1 SMP Fri Jun 15 04:15:27 UTC 2018
   x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Jul 5 11:28

SPEC is set to: /home/huberth/SPEC_OMP2012v1.1
   Filesystem                     Type  Size  Used Avail Use% Mounted on
   /dev/mapper/centos_r01c2b04-root xfs   926G   43G  884G   5% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.


(End of data from sysinfo program)
```

General Notes

```
Environment Variables:
    KMP_STACKSIZE=1G
    ulimit -s unlimited

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
```

Continued on next page

General Notes (Continued)

```
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Base Portability Flags

350.md: -free
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Base Optimization Flags

C benchmarks:
-ansi-alias -qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt
-fp-model fast=2 -xHost

C++ benchmarks:
-ansi-alias -qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt
-fp-model fast=2 -xHost

Fortran benchmarks:
-qopenmp -ipo -O3 -no-prec-div -no-prec-sqrt -fp-model fast=2
-xHost

The flags file that was used to format this result can be browsed at
http://www.spec.org/omp2012/flags/Intel-ic17-linux64.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/omp2012/flags/Intel-ic17-linux64.xml

Copyright 2012-2018 Standard Performance Evaluation Corporation

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Dec 19 12:52:22 2018 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 19 December 2018.