CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER800/1000/2000 (563MHz)

SPECint_rate2000 = 70.4

SPECint_rate_base2000 = 61.9

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Feb-2001 | Hardware Avail: May-2001 | Software Avail: Apr-2001



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	418	62.2	16	418	62.1
175.vpr	16	515	50.5	16	423	61.4
176.gcc	16	400	51.0	16	315	64.8
181.mcf	16	628	53.2	16	418	80.0
186.crafty	16	264	70.2	16	237	78.4
197.parser	16	511	65.4	16	499	66.9
252.eon	16	328	73.6	16	305	79.2
253.perlbmk	16	446	74.8	16	451	74.1
254.gap	16	520	39.3	16	520	39.3
255.vortex	16	380	92.7	16	327	108
256.bzip2	16	452	61.6	16	416	66.8
300.twolf	16	849	65.6	16	643	86.6

Hardware

CPU:	SPARC64 GP
CPU MHz:	563
FPU:	Integrated
CPU(s) enabled:	16 cores, 16 chips, 1 core/chip
CPU(s) orderable:	4 to 16/4 to 32/8 to 128
Parallel:	None
Primary Cache:	128KBI+128KBD on chip
Secondary Cache:	8MB(I+D) off chip, per CPU
L3 Cache:	None
Other Cache:	None
Memory:	16384MB
Disk Subsystem:	2 x 18.2GB SCSI (10025rpm)
Other Hardware:	Ethernet

Software

Operating System:	Solaris 8
Compiler:	Fujitsu Parallelnavi 1.0.1 Sun Forte Developer 6 update 1
File System:	ufs
System State:	single user

Notes/Tuning Information

```
Baseline (except 252.eon, for Parallelnavi 1.0.1): -Kfast_GP=3
 fdo_pre0=rm -rf ‘pwd‘/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=$(EXEBASE).fbk
(252.eon, for Forte Developer 6 update 1): -fast -xcrossfile -xarch=v8plus
 fdo_pre0=rm -rf ‘pwd‘/../feedback.profile ‘pwd‘/SunWS_cache
 PASS1=-xprofile=collect:‘pwd‘/../feedback
 PASS2=-xprofile=use:‘pwd‘/../feedback

Peak (for Parallelnavi 1.0.1):
 fdo_pre0=rm -rf ‘pwd‘/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=$(EXEBASE).fbk
 164.gzip: -Kfast_GP=3
 175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLD=3,xi=30
 181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=4,largepage -x-
 186.crafty: -Kfast_GP=3,switchopt,cond,noiopt,staticclump,xi=6,memalias
 197.parser: -Kfast_GP=3,switchopt,cond,staticclump,use_rodata,largepage,funcalign=128
 253.perlbmk: -Kfast_GP=3,memalias,switchopt,bcopy
 254.gap: -Kfast_GP=3
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 300.twolf: -Kfast_GP=5,GREG,popt,cfunc,staticclump,use_rodata,xi=10,nounroll,bcopy
(for Forte Developer 6 update 1)
 fdo_pre0=rm -rf ‘pwd‘/../feedback.profile ‘pwd‘/SunWS_cache
 PASS1=-xprofile=collect:‘pwd‘/../feedback
 PASS2=-xprofile=use:‘pwd‘/../feedback
 176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
           -xarch=v8plus -xprefetch
 252.eon: -fast -xcrossfile -xregs=syst -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
          -Qoption cg -Qgsched-trace_late=1,-Qgsched-trace_spec_load=1,-Qgsched-T4 -xarch=v8plus
           -lmopt
 255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
             -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
              -xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus
 256.bzip2: -fast -xarch=v8plus -W2,-Abopt -xcrossfile -xalias_level=strong
            -Wc,-Qiselect-funcalign=32 -xdepend -xregs=syst

Portability:
 176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSUN
 252.eon: -library=iostream,no%Cstd
 253.perlbmk: -DSPEC_CPU2000_SOLARIS -lnsl -lsocket
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
          -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Note:
 System Tunables: (for /etc/system)
  consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
  shmsys:shminfo_shmmax=268435456, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024
 (for /etc/opt/FJSVpnrm/lpg.conf)
  TSS=8192M, SHMSEGSIZE=256M
 ONESTEP=yes was set for all baseline and peak benchmarks.
 Feedback directed optimization was used for all baseline and peak benchmarks.
```