



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS160 Model 16 68/1001

SPECint_rate2000 = 111
SPECint_rate_base2000 = 98.9

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	16	301	86.3	16	297	87.4
175.vpr	16	299	86.9	16	292	88.9
176.gcc	16	196	104	16	155	132
181.mcf	16	504	66.3	16	369	90.6
186.crafty	16	130	143	16	130	143
197.parser	16	439	76.2	16	346	96.6
252.eon	16	194	124	16	165	146
253.perlbnk	16	328	102	16	300	111
254.gap	16	373	54.8	16	311	65.7
255.vortex	16	263	134	16	245	144
256.bzip2	16	250	112	16	230	121
300.twolf	16	369	151	16	364	153

Hardware	Software
CPU: Alpha 21264C	Operating System: Tru64 UNIX V5.1
CPU MHz: 1001	+Patch Kit 2
FPU: Integrated	Compiler: Compaq C V6.4-214-46B59
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip	Program Analysis Tools V2.0
CPU(s) orderable: 1 to 16	Spike V5.2 DTK (1.461 46B5P)
Parallel: No	Compaq C++ V6.3-010-46B2F
Primary Cache: 64KB(I)+64KB(D) on chip	File System: mfs
Secondary Cache: 8MB off chip per CPU	System State: Single-user
L3 Cache: None	
Other Cache: None	
Memory: 128GB	
Disk Subsystem: mfs (Memory File System)	
Other Hardware: None	

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
C++: cxx -arch ev6 -O2 ONESTEP

Peak:

```

All but 252.eon: cc -g3 -arch ev6 ONESTEP
164.zip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbnk: -fast -non_shared +CFB +IFB
254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
256.bzip2: -fast -O4 -non_shared +CFB
300.twolf: -fast -O4 -assume restricted_pointers -all
-ldensemalloc -none +CFB +IFB

```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS160 Model 16 68/1001

SPECint_rate2000 = 111
SPECint_rate_base2000 = 98.9

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbmk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

Information on UNIX V5.1 Patches can be found at
<http://ftpl1.service.digital.com/public/unix/v5.1/>

```
submit = runon <cpu #> $command
sysconfigtab settings:
    max_proc_per_user = 4096
    max_threads_per_user = 4096
    per_proc_data_size = 21474836480
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS160 Model 16 68/1001

SPECint_rate2000 = 111
SPECint_rate_base2000 = 98.9

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

```
max_per_proc_data_size = 21474836480
per_proc_address_space = 21474836480
max_per_proc_address_space = 21474836480
```

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a beta kit in August, 2001, and as a production release in October, 2001. The C compiler for this SPEC submission has been available at the same location, as a production release, since May, 2001.