



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER650 (810MHz)

SPECfp2000 = 644
SPECfp_base2000 = 483

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Jun-2002 Hardware Avail: Aug-2002 Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	473	338	257	624
171.swim	3100	578	536	578	536
172.mgrid	1800	461	390	412	437
173.applu	2100	788	266	384	546
177.mesa	1400	466	301	297	471
178.galgel	2900	258	1126	190	1528
179.art	2600	112	2316	73.2	3554
183.earthquake	1300	267	487	143	910
187.facerec	1900	288	660	264	719
188.amp	2200	525	419	390	564
189.lucas	2000	440	454	440	454
191.fma3d	2100	599	351	583	360
200.sixtrack	1100	400	275	291	378
301.apsi	2600	597	436	578	450

Hardware

CPU: SPARC64 GP
 CPU MHz: 810
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 2 to 8
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 8MB(I+D) off chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 8192MB
 Disk Subsystem: 36GB SCSI
 Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
 Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01, Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01 Sun Performance Library 7
 File System: ufs
 System State: single user

Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
  fdo_pre0=rm -rf `pwd`/*.*.d
  PASS1=-Kpg PASS2=-Kpu
FDO: (Sun ONE Studio 7)
  fdo_pre0=rm -rf `pwd`/../feedback.profile
  PASS1=-xprofile=collect:`pwd`/../feedback
  PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Sun ONE Studio 7)
-fast -xtarget=ultra3 -lprism32 FDO

(using C compiler of Sun ONE Studio 7)
-fast -xipo=2 -xdepend FDO

Peak:

(using Fortran compiler of Parallelnavi 1.0.2)
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER650 (810MHz)

SPECfp2000 = 644
SPECfp_base2000 = 483

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```

168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=`pwd`/../../src
             -fs -lssl2mtfma FDO ONESTEP=yes
172.mgrid:   -Kfast_GP=2,preex,GREG,commonpad=144,unroll=3,largepage,prefetch=3
             -O4 -fs
178.galgel:  -Kfast_GP=2,GREG,largepage,preex,unroll=3,prefetch_iteration=2,commonpad=24
             -O4 -lssl2mtfma -fs FDO
             RM_SOURCES=lapak.f90
200.sixtrack: -Kfast_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs
301.apsi:    -Kfast_GP=2,GREG,preex,ilfunc,largepage,unroll=2 -O4 -fs

```

(using FORTRAN77 compiler of Sun ONE Studio 7)

```

171.swim: basepeak=yes
173.applu: -fast -xtarget=ultra3 -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
           -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg
           -Qlp=1-av=192-fa=1 -Qoption f90comp -O3 -stackvar ONESTEP=yes

```

(using FORTRAN90 compiler of Sun ONE Studio 7)

```

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes
189.lucas:  basepeak=1

```

```

191.fma3d: -fast -xarch=v8plusb -xcrossfile -stackvar -xdepend
           -xprefetch -Qoption cg -Qlp=1-av=256-t=3-fa=1 FDO ONESTEP=yes

```

(using C compiler of Sun ONE Studio 7)

```

177.mesa: -fast -xtarget=ultra2 -xcrossfile -xrestrict -xalias_level=strong
          -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-trace_spec_load=1
          -xarch=v8plus -W2,-Amemopt -xsafe=mem -dn
          FDO ONESTEP=yes
179.art:  -fast -xtarget=ultra3 -xipo=2 -xalias_level=strong -xregs=syst -dn
          FDO ONESTEP=yes
183.quake: -fast -xtarget=ultra3 -xalias_level=std -xdepend
           -W2,-whole,-Amemopt:arrayloc,-crit -xprefetch -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -lm
           FDO ONESTEP=yes
188.ammp: -fast -xtarget=ultra3 -xcrossfile -xrestrict
          -xalias_level=strong -xdepend -xprefetch
          -Wc,-Qiselect-funcalign=64 -lprism32 FDO ONESTEP=yes

```

Portability:

```

(for Sun ONE Studio 7)
178.galgel: -e -fixed
(for Parallelnavi 1.0.2)
178.galgel: -Am -Fixed

```

Note:

```

System Tunables: (for /etc/system)
consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmnni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1
(for /etc/opt/FJSVpnm/lpg.conf)
TSS=512M, SHMSEGSIZE=256M

```

Shell Environments:

```

LD_LIBRARY_PATH="/usr/lib:/opt/FD7/SUNWspro/lib/v8plusb:/opt/FD7/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"
LD_LIBRARY_PATH_64="/usr/lib/64:/opt/FD7/SUNWspro/lib/v9:/opt/FD7/SUNWspro/prod/lib/v9"
PRISM_HEAP=268435456
PRISM_MODE=2

```

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 200.sixtrack.



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER650 (810MHz)

SPECfp2000 = 644

SPECfp_base2000 = 483

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

Small configuration memory system mode used ("4cpu mode", enabled via front panel).
System board used with only one CPU present.