



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 2000 (1.2GHz)

SPECint_rate2000 = 8.38
SPECint_rate_base2000 = 7.44

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	1	293	5.54	1	238	6.81
175.vpr	1	254	6.39	1	236	6.87
176.gcc	1	162	7.89	1	151	8.43
181.mcf	1	263	7.93	1	213	9.82
186.crafty	1	150	7.72	1	128	9.03
197.parser	1	315	6.63	1	272	7.69
252.eon	1	169	8.93	1	162	9.31
253.perlbnk	1	282	7.42	1	257	8.12
254.gap	1	236	5.40	1	205	6.23
255.vortex	1	191	11.6	1	168	13.1
256.bzip2	1	215	8.08	1	200	8.71
300.twolf	1	456	7.64	1	422	8.24

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-2
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 2GB 4-way interleaved
Disk Subsystem: 1 x 73GB 10K RPM FC-AL Disk, Sun Option X6805A
Other Hardware: None

Software

Operating System: Solaris 9 12/02
Compiler: Sun ONE Studio 8 (pre-FCS build 3/09)
Sun Performance Library 8 (pre-FCS build 3/09)
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

```
C: cc
CXX: CC
F90: f90
F77: f90
```

Integer base flags:

```
-fast -xipo=2 with ONESTEP=yes and feedback
```

Integer peak flags:

```
ONESTEP=yes and feedback for all benchmarks
```

```
164.zip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
175.vpr: -fast -xalias_level=std -xipo=2
-Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
Feedback adds -xlinkopt in PASS2
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 2000 (1.2GHz)

SPECint_rate2000 = 8.38
SPECint_rate_base2000 = 7.44

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Notes/Tuning Information (Continued)

```

197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

System Settings:

2nd cpu physically removed from system